

Determinants (Part 3)

Sarang S. Sane

Recall :

- ▶ For a 1×1 matrix $[a]$, the determinant is defined by $\det([a]) = a$.

Recall :

- ▶ For a 1×1 matrix $[a]$, the determinant is defined by $\det([a]) = a$.
- ▶ For an $n \times n$ matrix, the determinant is defined inductively via the minors M_{1j} or cofactors C_{1j} corresponding to the first row.

Recall :

- ▶ For a 1×1 matrix $[a]$, the determinant is defined by $\det([a]) = a$.
- ▶ For an $n \times n$ matrix, the determinant is defined inductively via the minors M_{1j} or cofactors C_{1j} corresponding to the first row.
- ▶ The (i, j) -th minor is the determinant of the submatrix formed by deleting the i -th row and j -th column.

Recall :

- ▶ For a 1×1 matrix $[a]$, the determinant is defined by $\det([a]) = a$.
- ▶ For an $n \times n$ matrix, the determinant is defined inductively via the minors M_{1j} or cofactors C_{1j} corresponding to the first row.
- ▶ The (i, j) -th minor is the determinant of the submatrix formed by deleting the i -th row and j -th column.
- ▶ The (i, j) -th cofactor $C_{ij} = (-1)^{i+j} M_{ij}$.

Recall :

- ▶ For a 1×1 matrix $[a]$, the determinant is defined by $\det([a]) = a$.
- ▶ For an $n \times n$ matrix, the determinant is defined inductively via the minors M_{1j} or cofactors C_{1j} corresponding to the first row.
- ▶ The (i, j) -th minor is the determinant of the submatrix formed by deleting the i -th row and j -th column.
- ▶ The (i, j) -th cofactor $C_{ij} = (-1)^{i+j} M_{ij}$.

Definition

$$\det(A) = \sum_{j=1}^n (-1)^{1+j} a_{1j} M_{1j} = \sum_{i=1}^n a_{1i} C_{1i}$$

Expansion along any row or column

Expansion along any row or column

$$\det(A) = \sum_{j=1}^n (-1)^{i+j} a_{ij} M_{ij} \quad \text{for a fixed } i$$

Expansion along any row or column

$$\det(A) = \sum_{j=1}^n (-1)^{i+j} a_{ij} M_{ij} \quad \text{for a fixed } i$$

$$= \sum_{i=1}^n (-1)^{i+j} a_{ij} M_{ij} \quad \text{for a fixed } j$$

Important properties and identities

Property 1 : Determinant of a product is product of the determinants.

Important properties and identities

Property 1 : Determinant of a product is product of the determinants. Related identity : $\det(AB) = \det(A)\det(B)$

Important properties and identities

Property 2 : Switching two rows or columns changes the sign.

Important properties and identities

Property 3 : Adding multiples of a row to another row leaves the determinant unchanged.

Important properties and identities

Property 3 : Adding multiples of a row to another row leaves the determinant unchanged.

Property 3' : Adding multiples of a column to another column leaves the determinant unchanged.

Important properties and identities

Property 4 : Scalar multiplication of a row by a constant t multiplies the determinant by t .

Important properties and identities

Property 4 : Scalar multiplication of a row by a constant t multiplies the determinant by t .

Property 4' : Scalar multiplication of a column by a constant t multiplies the determinant by t .

Useful computational tips

- 1) The determinant of a matrix with a row or column of zeros is 0.

Useful computational tips

- 1) The determinant of a matrix with a row or column of zeros is 0.
- 2) The determinant of a matrix in which one row (or column) is a linear combination of other rows (resp. columns) is 0.

Useful computational tips

- 1) The determinant of a matrix with a row or column of zeros is 0.
- 2) The determinant of a matrix in which one row (or column) is a linear combination of other rows (resp. columns) is 0.
- 3) Scalar multiplication of a row by a constant t multiplies the determinant by t .

Useful computational tips

- 1) The determinant of a matrix with a row or column of zeros is 0.
- 2) The determinant of a matrix in which one row (or column) is a linear combination of other rows (resp. columns) is 0.
- 3) Scalar multiplication of a row by a constant t multiplies the determinant by t .
- 4) While computing the determinant, you can choose to compute it using expansion along a suitable row or column.

Thank you