MERIDIAN PACKAGING PVT LTD

Product specification sheet (sample)

Product code	MP-5R-604040
Description	RSC Carton 5 Ply 150 GSM KLB, plain
Internal dimensions (L x W x H)	600 x 400 x 400 mm, tolerance ±3 mm
Board construction	150 KLB / 120 fluting (B) / 150 test liner / 120 fluting (C) / 150 KLB
Flute combination	BC double wall, combined calliper 6.5 mm ±0.3
Board grammage	786 g/m² ±5%
Weight per box	1.283 kg ±5%
Bursting strength	14 kg/cm² minimum
Edge crush test (ECT)	8.5 kN/m minimum
Box compression test (BCT)	480 kgf minimum
Moisture content	7 to 9% at despatch
Cobb value (60 s)	below 30 g/m², outer liner
Joint	Glued manufacturer's joint, 40 mm flap
Bundling	25 boxes per bundle, strapped; 600 boxes per pallet
Test standards	IS 1060, IS 2771 (Part 1), ISO 3037, ISO 12048

Issued by Quality Assurance, Meridian Packaging, Chakan. Specification MP/QA/SPEC/5R-604040, revision 2, 11 August 2026.

Fabricated demonstration document for the Quoteline prototype. Not a real certificate or data sheet.