

```

create database hospital_management_system;
use hospital_management_system;
create table login(ID varchar(20), Password varchar(20))
select * from login;
insert into login value("Rahul", "Rahul24@01");
create table patient_info(ID varchar(20), Number varchar(40), Name varchar(20), Gender
varchar(20), Patient_Diseases varchar(20), Room_Number varchar(20), Time varchar(100),
Deposite varchar(20));
select * from patient_info;
create table Room(room_no varchar(20), Availability varchar(20), Price varchar(20),
Room_Type varchar(100));
insert into Room values("100","Available","500","G Bed 1");
insert into Room values("101","Available","500","G Bed 2");
insert into Room values("102","Available","500","G Bed 3");
insert into Room values("103","Available","500","G Bed 4");
insert into Room values("200","Available","1500","Private Room");
insert into Room values("201","Available","1500","Private Room");
insert into Room values("202","Available","1500","Private Room");
insert into Room values("203","Available","1500","Private Room");
insert into Room values("300","Available","3500","ICU Bed 1");
insert into Room values("301","Available","3500","ICU Bed 2");
insert into Room values("302","Available","3500","ICU Bed 3");
insert into Room values("303","Available","3500","ICU Bed 4");
insert into Room values("304","Available","3500","ICU Bed 5");
insert into Room values("305","Available","3500","ICU Bed 6");

```

```

select * from Room;

```

```

create table department(Department varchar(100), Phone_no varchar(20));
select * from department;
insert into department values("Surgical department", "123456789");
insert into department values("Nursing department", "123456789");
insert into department values("Operation theatre complex", "123456789");
insert into department values("Paramedical department", "123456789");

```

```

create table Emp_Info(Name varchar(20), Age varchar(20), Phone_No varchar(20), Salary
varchar(20), Gmail varchar(20), Aadhar_Number varchar(20));
select * from Emp_Info;
insert into Emp_Info values("Doctors1", "30", "123456789", "50000","gr@gmail.com",
"12345678965");

```

```
insert into Emp_Info values("Doctors2", "30", "123456789", "50000", "gr@gmail.com",  
"12345678965");
```

```
create table Ambulance(Name varchar(20), Gender varchar(20), Car_name varchar(20),  
Available varchar(20), Location varchar(20));  
insert into Ambulance values("av", "Male", "ZEN", "Available", "area 16");  
select * from Ambulance;
```