


Assignment Day – 3

1. Log in to your home Wi-Fi router's admin panel using its default IP address (usually 192.168.0.1 or 192.168.1.1) and take a screenshot of the login page.
Hint: If you don't know your router's IP, open Command Prompt and run 'ipconfig' — look for 'Default Gateway'.




2. Find and note down the current IP address, subnet mask, and default gateway assigned to your laptop or mobile device when connected to your Wi-Fi network.




Network Information	Value
IPv4 Address (IP Address)	192.168.1.8
Subnet Mask	255.255.255.0
Default Gateway	192.168.1.1

3. Change your device's IP address from 'Obtain IP automatically' (DHCP) to a static IP in the same range as your router (for example, set it to 192.168.1.50 if your router is 192.168.1.1), and test if you still have internet access.
Constraint: Remember to revert to automatic/DHCP after testing to avoid network issues.



4. In your router's admin panel, locate the section where you can view or change the DHCP range. Write down the current range, and explain in 2-3 lines what would happen if two devices are assigned the same IP address in this range.



Current DHCP Range: 192.168.1.100 – 192.168.1.200

If two devices are assigned the same IP address, an **IP address conflict** occurs. Both devices may lose network/internet connectivity or experience unstable communication because the network cannot correctly identify which device owns that IP address.