

Client Script Specifications

Project: Implement Client Script & UI Policy (Incident)

Document Reference: PRJ-INC-P5-002

Milestone: M4 - Implementation

Owner: Abisheknathan

Status: Submission Ready

All scripts target table **Incident [incident]**, are **Active**, and use UI Type **All** (the `onCellEdit` script applies to the desktop list). Source files are in `client_scripts/`.

#	File	Name	Type	Field	Rule
1	01_onLoad_incident_form_init.js	Incident - Init on load	onLoad	-	Urgency = High if Impact = High; show note if Priority = 1
2	02_onChange_category_clear_subcategory.js	Incident - Clear Subcategory	onChange	Category	Clear Subcategory when Category changes
3	03_onChange_priority_critical_warning.js	Incident - Critical Priority Warning	onChange	Priority	Show warning for 1; hide otherwise
4	04_onChange_impact_set_urgency_high.js	Incident - Impact sets Urgency	onChange	Impact	Impact 1 sets Urgency 1; hide message otherwise
5	05_onSubmit_validate_short_description.js	Incident - Validate Short description	onSubmit	-	Block blank or under 10 characters
6	06_onCellEdit_block_state_list_edit.js	Incident - Block State list edit	onCellEdit	State	Reject inline State change

Key g_form Methods Used

Method	Purpose
<code>getValue(field)</code>	Read the current value
<code>setValue(field, value)</code>	Set a value (works on read-only fields)
<code>clearValue(field)</code>	Empty a field
<code>showFieldMsg / hideFieldMsg</code>	Message under a field
<code>addInfoMessage / addErrorMessage</code>	Banner at top of the form

Coding Standards Followed

1. Every `onChange` returns early when `isLoading` is true.
2. Choice values are compared as strings ('1').
3. `onSubmit` returns `false` to block and `true` to continue.
4. `onCellEdit` always calls `callback(...)` exactly once.
5. Messages are single sentences with a clear action.

Offline Verification

`automated_tests/client_script_simulation.js` loads each file against a mocked `g_form` and checks 15 behaviours.