Nasuni cluster access

Kind cluster on nas-vm

Snapshot: Inspected on 3 November 2026 at 05:53 UTC. The cluster was healthy with three Ready nodes, a Ready appliance, and a Ready volume. Addresses and status can change.

Cluster details

Item	Value
Host / user	`nas-vm` / `automation`
Cluster / backend	`nasuni-cluster` / Kind; three nodes
Kubernetes context	`kind-nasuni-cluster`
Kubernetes API	`https://127.0.0.1:44191` on `nas-vm` only
Protocol VIP	`10.89.0.200`; NFS TCP `2049`, SMB TCP `445`
Azure-backed volume	`vol-azure-c1b4a8bb` — Ready
Volume GUID	`vol-azure-c1b4a8bb-guid`

Connect and select the cluster

From your workstation, connect to the host. The tools below are installed on `nas-vm`; do not run the cluster commands on your workstation.

```
ssh nas-vm
export STRIDER_DEPLOY_PATH=/home/automation/strider-deploy
export PATH="$STRIDER_DEPLOY_PATH/.venv/bin:$PATH"
```

The existing kubeconfig below was verified on `nas-vm`. It lives under `/tmp` and may disappear on reboot or cleanup. It contains credentials: keep it private and do not paste it into chat.

```
export KUBECONFIG=/tmp/kubeconfig-nasuni-cluster-1yx082ad.yaml
kubectl config current-context
kubectl get --raw=/readyz
kubectl get nodes
```

The expected context is `kind-nasuni-cluster` and `/readyz` returned `ok`. Explicitly set `KUBECONFIG`: the host's default may point to a different cluster. The API address is loopback on `nas-vm`, not the protocol VIP.

If the temporary kubeconfig no longer exists, request a new one on `nas-vm` using the command below and set `KUBECONFIG` to the **path printed**. The command is documented but was not re-run during the read-only inspection; it creates a temporary kubeconfig.

```
cluster-manager kubeconfig --backend kind \
  --cluster-name nasuni-cluster \
  --strider-deploy-path "$STRIDER_DEPLOY_PATH"
```

Check health and volume

```
cluster-manager status --backend kind \
  --cluster-name nasuni-cluster \
  --strider-deploy-path "$STRIDER_DEPLOY_PATH"
kubectl -n nasuni get appliance-config
kubectl -n nasuni get volumes,nfs-exports,smb-shares
```

The status command reported healthy during deployment. At the later inspection, the API, all three nodes, appliance and volume were Ready. The `kubectl get` resource-list commands above are inspection commands; their exact invocations were not re-run in the later check.

NFS and SMB access

The protocol service exposes `10.89.0.200` on the Kind Podman network. The route was verified from `nas-vm`; reachability from other hosts was not verified. **There were no NFS export or SMB share resources** at inspection, so the Ready volume is not yet a confirmed mountable share. Create and verify an export or share through the supported Strider workflow before attempting a mount. Do not treat the VIP as the Kubernetes API.

Grafana

Grafana was running in namespace `o11y`. From `nas-vm`, the login page returned HTTP 200 at `http://10.89.0.7:30300/login`. This is a Kind node address and may change; `127.0.0.1:30300` was not reachable. Authentication, dashboards, and workstation access were not verified.

```
kubectl -n o11y get svc grafana-nodeport
kubectl -n o11y get pods
```

Do not expose Grafana or copy kubeconfig credentials to another machine without an approved secure-access setup.