

Ildar92 August 4, 2020 at 09:32 AM

Spring transaction management. Isolation and

Programming, Java

Introduction

In my opinion transaction management is a really important topic for each backend developer it while using Spring framework.

But I think, it is important to know how to use transactions properly. Because sometimes can he thrown inside your method, but transaction was not rolled back and it is not clear why? Or sor

@Transactional

In spring there is @Transactional annotation that can be used for wrapping a method in a tran (lowest priority), classes or certain methods (highest priority).

@Transactional is applied only for public methods and method must be invoked from outside

@Transactional annotation has multiple parameters. I would like to focus on two of them: Isola

Яндекс Дирне прячься, Сидоров! Я чувствую – Ты Где-то Тут! Учительница Ве

Русский язык для всех

Научись анализировать правила орфографии, пунктуации и применять их на практике

Узнать больше

fondfilm.ru

Isolation is one of the main properties of transactions (Atomicity, Consistency, Isolation, Durability). It describes visibility of changes applied by concurrent transactions to each other.

In Spring it is possible to set one of the 5 isolation level values: DEFAULT, READ_UNCOMMITTED, READ_COMMITED, REPETABLE_READ and SERIALIZABLE.


For example,

```
@Transactional (isolation=Isolation.READ COMMITED)
```

Each of these isolation levels may have or haven't different side effects: "dirty" read, non-repeatable read and phantom read. What each of them means?

"Dirty" read — one transaction can read changes of a concurrent transaction, that were not committed yet.

If you like more diagrams as I do:




Transaction T1 begins first, then we start transaction T2.


After that T1 changes row with id=10 in database and T2 reads it. Something wrong happens and T1 is rolled back. And recording in T2

is dirty now.

Non-repeatable read — one transaction reads the same row twice, but gets different values because between these reads the data was updated by the concurrent transaction.



Phantom read — one transaction runs the same query twice, but gets a different set of rows as result, because of the changes applied by another concurrent transaction.



Let's go back to the isolation levels and check their possible side effects.

- 1. DEFAULT value is used when we want to use default isolation level of our RDBMS. Default value for PostgreSQL, Oracle and SQL server is READ_COMMITTED, for MySQL REPEATABLE_READ.
- 2. with READ_UNCOMMITTED isolation level, we can have all three side effects
- 3. READ_COMMITTED isolation level has one change in comparison with READ_UNCOMMITTED it prevents "dirty" reads.

- 4. REPEATABLE_READ prevents "dirty" and non-repeatable reads.
- 5. SERIALIZABLE isolation level prevents all mentioned above side effects. It performs all transactions in sequence.

Isolation level	Phantom read	Non-repeatable read	"Dirty" read
READ_UNCOMMITTED	possible	possible	possible
READ_COMMITTED	possible	possible	not possible
REPEATABLE_READ	possible	not possible	not possible
SERIALIZABLE	not possible	not possible	not possible

There is also another important parameter of @Transactional: propagation.

Propagation can be set to REQUIRED, REQUIRES_NEW, MANDATORY, SUPPORTS, NOT_SUPPORTED, NESTED or NEVER. Example:

All streams Development Administrating Design Management Marketing PopSci



- 1. REQUIRED propagation level uses an existing transaction if there is one. Otherwise creates a new transaction.
- 2. REQUIRES_NEW propagation level says to suspend outer transaction (if there is one) and create a new one.
- 3. MANDATORY propagation uses an existing transaction if there is one. Otherwise, an exception will be thrown.

- 4. SUPPORTS propagation level uses the current transaction if there is one. Otherwise, doesn't create a new one.
- 5. NOT_SUPPORTED suspends current transaction if there is one.
- 6. NESTED creates nested transaction when there is an existing transaction already or works like REQUIRED if there is no transaction.
- 7. NEVER throws an exception if there is an active transaction.

Propagation	Calling method (outer)	Called method (inner)
REQUIRED	No	T2
REQUIRED	T1	T1
REQUIRES_NEW	No	T2
REQUIRES_NEW	T1	T2
MANDATORY	No	Exception
MANDATORY	T1	T1
NOT_SUPPORTED	No	No
NOT_SUPPORTED	T1	No
SUPPORTS	No	No

Propagation	Calling method (outer)	Called method (inner)	
SUPPORTS	T1	T1	
NEVER	No	No	
NEVER	T1	Exception	
NESTED	No	T2	
NESTED	T1	T2	

Also interesting is that Spring framework does automatic transaction rollback only for unchecked (Runtime) exceptions. To change it we can use rollbackFor parameter.

For example, we can put

@Transactional (rollbackFor=Exception.class)

Conclusion


In the article, I tried to describe how to use Isolation and Propagation parameters of @Transactional in Spring.


I remember how several years ago I had some problems with the chain of transactional method and I hope that my article can help other developers to avoid them and have more clear understanding of the topic.

Tags: java, spring, transactions


Hubs: Programming, Java









Ads



Comments 0

Only users with full accounts can post comments. Log in, please.





Your account	Sections	Info		Services	
Log in	Posts	How it works		Ads	
Sign up	Hubs	For Authors		Subscription plans	
	Companies	For Companie	S	Content	
	Users	Documents		Seminars	
	Sandbox	Agreement		Megaprojects	
		Terms of servi	ce		
© 2006 – 2021 « Habr »	Language settings	About	Support	Mobile version	y f ⊲