SRAM Timing Analysis Chip (STAC) Test Board

STAC Top Level

STAC_Power
STAC_Test_Board_v1_Power

SMA connectors
Silkscreen: signal names

NET CLASS SE50
clock_clock
J7
142-0701-801

All SMAs should be 50 ohm controlled impedance traces.

NET CLASS SE50
SRAM_SAE_CLK
J8
142-0701-801

NET CLASS SE50
PLL_DIV_OUT
J11
142-0701-801

NET CLASS SE50
PLL_REF_IN
J13
142-0701-801

NET CLASS SE50
PLL_CLK_OUT
J16
142-0701-801

SMA connector for cable to spectrum analyzer (using an SMA-connectorized DC blocking capacitor at the spectrum analyzer's input) for measuring noise on these power domains.

VDDD1V8
J18
142-0701-801

VDDIO3V3
J19
142-0701-801

PMOD A for serial TL (use 0.1" pitch right angle thru hole male connector)
Silk: TILELINK

J6
TSW-106-08-L-D-RA

serial_tl_clock	1	7	clock_clock_isolated
serial_tl_bits_in_valid	2	8	serial_tl_bits_out_valid
serial_tl_bits_in_ready	3	9	serial_tl_bits_out_ready
serial_tl_bits_in_bits	4	10	serial_tl_bits_out_bits
	5	11	
	6	12	

Note that power is not connected via the PMOD; we think it may be simpler to not share supplies between this board and the FPGA connected to the other end of the PMOD. Power would normally be on pins 6 and 12 of the PMOD connector.

clock_clock
R15
0
clock_clock_isolated
NET CLASS
SE50

The split between clock_clock and Not found should be done at a 45 degree bend, so that if R15 is not placed, clock_clock does not see any sharp bends.

PMOD C for SRAM + PLL control (use 0.1" pitch right angle thru hole male connector)
Silk: PLL + SRAM_SCAN_MODE

J10
TSW-106-08-L-D-RA

SRAM_SCAN_MODE	1	7	PLL_SCAN_IN
PLL_ARSTB	2	8	PLL_SCAN_OUT
PLL_SCAN_CLK	3	9	PLL_SCAN_RSTN
PLL_SCAN_EN	4	10	PLL_SEL
	5	11	
	6	12	

Place close to STAC chip; minimize trace lengths
Silk: SourceMeter

VDDDEXT1V8
J9
TSW-104-07-L-S

1	
2	SENSE_P_VDDD1V8
3	SENSE_N_GND
4	

Silk: FORCE+ (VDDDEXT1V8)
Silk: SENSE+ (VDDD1V8)
Silk: SENSE- (GND)
Silk: FORCE- (GND)

PMOD D for SRAM control (use 0.1" pitch right angle thru hole male connector)
Silk: SRAM CONTROL

J12
TSW-106-08-L-D-RA

SRAM_BIST_START	1	7	SRAM_SCAN_IN
SRAM_EN	2	8	SRAM_SCAN_OUT
SRAM_BIST_EN	3	9	SRAM_SCAN_EN
SRAM_EXT_EN	4	10	SRAM_BIST_DONE
	5	11	
	6	12	

QSPI
STAC_Test_Board_v1_QSPI.SchDoc

spi_0_dq_0	spi_0_dq_0
spi_0_dq_1	spi_0_dq_1
spi_0_dq_2	spi_0_dq_2
spi_0_dq_3	spi_0_dq_3
spi_0_sck	spi_0_sck
spi_0_cs_0	spi_0_cs
qspi_sel	qspi_sel
spi_mux_enb	spi_mux_enb

0.1" headers
Silk: all pin names

J15
TSW-108-07-L-D

SRAM_SCAN_MODE	1	2	
clksel_1	3	4	
clksel_0	5	6	
resetn	7	8	
VDDIO3V3	9	10	
custom_boot	11	12	
uart_0_txd	13	14	
uart_0_rxd	15	16	

USB
STAC_Test_Board_v1_USB.SchDoc

uart_0_txd	uart_0_txd
uart_0_rxd	uart_0_rxd
JTAG_TCK	JTAG_TCK
JTAG_TDI	JTAG_TDI
JTAG_TDO	JTAG_TDO
JTAG_TMS	JTAG_TMS
JTAG_SRST	JTAG_SRST
FTDI_RESETN	FTDI_RESETN

J17
TSW-108-07-L-D

spi_0_dq_0	1	2	JTAG_TCK
spi_0_dq_1	3	4	JTAG_TMS
spi_0_dq_2	5	6	JTAG_TDI
spi_0_dq_3	7	8	JTAG_TDO
spi_0_cs_0	9	10	
spi_0_sck	11	12	
VDDIO3V3	13	14	
VDDD1V8	15	16	

SWITCHES
STAC_Test_Board_v1_SwitchesButtons.SchDoc

resetn	resetn
PLL_ARSTB	PLL_ARSTB
clksel_0	clksel_0
clksel_1	clksel_1
custom_boot	custom_boot
qspi_sel	qspi_sel
JTAG_SRST	JTAG_SRST
FTDI_RESETN	FTDI_RESETN
spi_mux_enb	spi_mux_enb

SENSE_N_GND
NT1

U6A
TESTCHIP_STAC_v1

		1	VSSA_W4
SRAM_SCAN_IN		2	SRAM_SCAN_IN
SRAM_SCAN_OUT		3	SRAM_SCAN_OUT
SRAM_SCAN_EN		4	SRAM_SCAN_EN
SRAM_BIST_DONE		5	SRAM_BIST_DONE
		6	NC_W9
uart_0_txd		7	uart_0_txd
uart_0_rxd		8	uart_0_rxd
VDDD1V8		9	VDDA_W12
		10	VSSD_W13
serial_tl_bits_out_ready		11	serial_tl_bits_out_ready
serial_tl_bits_out_valid		12	serial_tl_bits_out_valid
serial_tl_bits_in_ready		13	serial_tl_bits_in_ready
serial_tl_bits_in_bits		14	serial_tl_bits_in_bits
serial_tl_bits_out_bits		15	serial_tl_bits_out_bits
serial_tl_bits_in_valid		16	serial_tl_bits_in_valid
VDDIO3V3		17	VDDIO_W21
VDDD1V8		18	VDDD_W22
		19	NC_QFN19
		20	VSSA_S1
resetn		21	resetn
clock_clock		22	clock_clock
		23	VSSD_S4
JTAG_TCK		24	JTAG_TCK
JTAG_TMS		25	JTAG_TMS
JTAG_TDI		26	JTAG_TDI
JTAG_TDO		27	JTAG_TDO
clksel_0		28	clksel[0]
		29	VSSIO_S10
VDDD1V8		30	VDDA_S11
serial_tl_clock		31	serial_tl_clock
spi_0_sck		32	spi_0_sck

U6B
TESTCHIP_STAC_v1

spi_0_cs_0		33	spi_0_cs_0
spi_0_dq_3		34	spi_0_dq_3
spi_0_dq_2		35	spi_0_dq_2
spi_0_dq_1		36	spi_0_dq_1
spi_0_dq_0		37	spi_0_dq_0
		38	VSSA_E13
		39	VSSD_E12
VDDD1V8		40	VDDA_E11
clksel_1		41	clksel[1]
PLL_SEL		42	PLL_SEL
PLL_SCAN_EN		43	PLL_SCAN_EN
PLL_SCAN_RSTN		44	PLL_SCAN_RST
PLL_SCAN_CLK		45	PLL_SCAN_CLK
PLL_DIV_OUT		46	PLL_DIV_OUT
VDDD1V8		47	VDDA_DCO_E4
PLL_CLK_OUT		48	PLL_CLK_OUT
VDDD1V8		49	VDDD_E2
PLL_REF_IN		50	PLL_REF_IN
custom_boot		51	custom_boot
		52	VSSA_N10
PLL_SCAN_IN		53	PLL_SCAN_IN
PLL_SCAN_OUT		54	PLL_SCAN_OUT
PLL_ARSTB		55	PLL_ARSTB
		56	VSSIO_N6
SRAM_EXT_EN		57	SRAM_EXT_EN
SRAM_BIST_EN		58	SRAM_BIST_EN
SRAM_EN		59	SRAM_EN
SRAM_SCAN_MODE		60	SRAM_SCAN_MODE
SRAM_BIST_START		61	SRAM_BIST_START
SRAM_SAE_CLK		62	SRAM_SAE_CLK
VDDD1V8		63	VDDD_W2
VDDIO3V3		64	VDDIO_W3
		65	THERMAL_GND_E21

SENSE_P_VDDD1V8
NT2

Note that the VDDA pins on the STAC chip are connected to VDDD1V8 . This is because no on-chip circuitry uses VDDA.

All caps close to chip package (1 cap per pin)

VDDIO3V3	VDDIO3V3	VDDD1V8	VDDD1V8	VDDD1V8	VDDD1V8	VDDD1V8	VDDD1V8
C15 10uF	C16 10uF	C17 10uF	C18 10uF	C19 10uF	C20 10uF	C21 10uF	C22 10uF

Silk: all pin names

J14
CON_012pin_2x6

JTAG_TDO	1	2	JTAG_TDI
	3	4	JTAG_TMS
JTAG_TCK	5	6	JTAG_SRST
uart_0_txd	7	8	uart_0_rxd
	9	10	
	11	12	

VDDIO3V3
VDDIO3V3

Title	STAC Top Level
Size: B	Number:
Revision:	X1
Date:	11/17/2023
Sheet 1 of	5
File:	C:\Users\..\STAC_Test_Board_v1.SchDoc
Drawn By:	Rahul Kumar

STAC Power Supplies and Regulators

Shunt jumpers for selecting between external and LDO supplies

Silk: net names

VDDDEXT1V8
VDDD1V8
VDDDREG1V8
J1
TSW-104-07-L-S

Silk: pin 1 = REG, pin 2 = VDDIO, pin 3 = EXT. pin 4 = GND, J1 = VDDD1V8.

VDDIOEXT3V3
VDDIO3V3
VDDIOREG3V3
J3
TSW-104-07-L-S

Silk: pin 1 = REG, pin 2 = VDDIO, pin 3 = EXT. pin 4 = GND, J3 = VDDIO3V3.

Silk: all net names

VDDIOEXT3V3
Main power input connection
+C2 220uF
VSUPPLYIN6V
J2
VDDDEXT1V8
Silk: GND
+C5 220uF
1053141106

Silk: VSUPPLYPROT6V

1st stage LDO (6V->5V)

REG5V
Silk: 5V
VSUPPLYPROT6V
U1
IN OUT OUT VCONTROL SET NC
LT3083EQ#PBF
C1 10uF
C3 10uF
R1 909
SET_Z
C4 0.1uF
R2 100K
T1
TST GND GND GND

Power Protection for board supply (6V)

PROT6V_INT
U2
BUK9K12-60EX
D1 D1 D2 D2 S1 S2 G2 G1
VSUPPLYIN6V
VSUPPLYPROT6V
Silk: VSUPPLYPROT6V
R3 200K
+C6 220uF
R4 510K
R5 2.7M
+C7 220uF
+C8 220uF
T2
TST GND GND GND
U4
VIN GATE SHDNB UV VOUT OV FAULTB GND
LTC4365
GATE
UV
OV
SHDN_N
R7 82.5K
R10 215K
FAULT_N
S1
450301014042

This switch is debounced by the LTC4365 with a 36ms debounce time. No additional debouncing is necessary.

Silk: pin 3 = OFF, pin 1 = ON.

Silk: VSUPPLYPROT6V ON
VSUPPLYPROT6V
R11 301
VSUPPLYPROT6V_LED
D1 SML-LX0603GW-TR (green)

Silk: 5V ON
5V
R12 250
5V_LED
D2 SML-LX0603GW-TR (green)

Power test points for probes

Silk: net names

SHDN_N T6
FAULT_N T7
VDDD1V8 T8
VDDIO3V3 T9
TST GND GND GND

T10 5006 (black)

Silk: GND

Silk: VDDD1V8 EN

J4
TSW-103-07-G-S
5V
ENABLE_1V8
C9 4.7uF

LDO for digital

U3
IN IN EN/UV PG ILIM GND OUT OUTS GND SET PGFB
LT3042
VDDD_ILIM
R8 301
SET_C
R6 15K
C11 0.47uF
T4
5008 (orange)
VDDD_TUNE
R9
3214X-1-502E (5K)
Place pot and caps as close to LDO as possible
VDDDREG1V8
C10 4.7uF
T3
TST GND GND GND
Silk: VDDDREG1V8

LDO for VDDIO

Silk: VDDIO3V3 EN
J5
TSW-103-07-G-S
5V
ENABLE_VDDIO
U5
IN IN EN/UV PG ILIM GND OUT OUTS GND SET PGFB
LT3042
C12 4.7uF
VDDIO_ILIM
R14 301
SET_E
R13 33.2K
C14 0.47uF
C13 4.7uF
VDDIOREG3V3
T5
TST GND GND GND
Silk: VDDIOREG3V3

Title	STAC Power Supplies and Regulators	
Size: B	Number	Revision: X1
Date: 11/17/2023	Sheet 2of 5	
File: C:\Users\..\STAC_Test_Board_v1_Power.SchDoc	Drawn By: Rahul Kumar	

STAC USB to UART/JTAG



Title	STAC USB to UART/JTAG	
Size: B	Number:	Revision: X1
Date: 11/17/2023	Sheet 3 of 5	
File: C:\Users\..\STAC_Test_Board_v1_USB.SchDoc	Drawn By: Rahul Kumar	

STAC Quad-SPI Peripherals













Title: STAC Quad-SPI Peripherals		
Size: B	Number:	Revision: X1
Date: 11/17/2023	Sheet 4 of 5	
File: C:\Users\..\STAC_Test_Board_v1_QSPI.SchDoc	Drawn By: Rahul Kumar	

STAC User Switches and Buttons



Title	STAC User Switches and Buttons	
Size: B	Number	Revision: X1
Date: 11/17/2023	Sheet 5 of 5	
File: C:\Users\..\STAC_Test_Board_v1_SwitchesButtons.SchDoc	Drawn By: Rahul Kumar	