

Atta ***EXPERT***

Semi Automatic Stone Mill

15% Power Saving

VFD Controlled Feeder

Semi-Auto




WE NEVER FORGET HOW MUCH YOU RELY ON US

Flour mill engineered for precision

Size - 600 mm/24"	Size - 750 mm/30"	Size - 1200 mm/48"	
150-200	400-450	600-650	15%
(Kg/Hr) Grinding Capacity	(Kg/Hr) Grinding Capacity	(Kg/Hr) Grinding Capacity	Power Saving
15 HP	25 HP	40 HP	3
Power Load	Power Load	Power Load	Models Available

CORE CAPABILITIES

Energy Efficiency & Performance - Up to 15% power saving - VFD controlled feeder - Optimized milling performance - VFD-based feed control - Semi-automatic grain feeding system	Smart Automation & Control - Semi-automatic operation - Feeder motor control panel included - Manual, pneumatic & hydraulic pressure options	Reliability & Monitoring - Easy operation & low maintenance - High performance & reliability
--	---	---




Heavy Duty Emery Stone



Integrated Magnet



VFD Feeder with Conical Hopper



Stainless Steel Grinding Chamber



Heavy Duty Spiral Bevel Gear



Size Available	600mm/750mm/1200mm
Hopper Capacity	100-150 Kg
Pressure Type	Manual
Screw Feeder	0.5 HP, VFD Controlled
Power (600 mm)	15 HP 960 RPM
Power (750 mm)	25 HP 960 RPM
Power (1200 mm)	40 HP 960 RPM



Size Available	600mm/750mm/1200mm
Hopper Capacity	100-150 Kg
Pressure Type	Hydraulic
Screw Feeder	0.5 HP, VFD Controlled
Power (600 mm)	15 HP 960 RPM
Power (750 mm)	25 HP 960 RPM
Power (1200 mm)	40 HP 960 RPM



Size Available	600mm/750mm/1200mm
Hopper Capacity	100-150 Kg
Pressure Type	Pneumatic
Screw Feeder	0.5 HP, VFD Controlled
Power (600 mm)	15 HP 960 RPM
Power (750 mm)	25 HP 960 RPM
Power (1200 mm)	40 HP 960 RPM

Manufacturers & Exporters

CHOYAL GRINDING SOLUTION PVT. LTD.

Regd. & City Office: Choyal Tower, 1180/28, Adarsh Nagar, Nasirabad Road, Ajmer, Rajasthan, India - 305002

Works: Arjunpura NH 58. Ajmer, Rajasthan, India, 305206

CIN NO.: U28299RJ2025PTC101719

Contact No.: +91 9240 289 259
WhatsApp No.: +91 88902 11444
Email: info@rschoyalgroup.com
Website: www.rschoyalgroup.com



Numbers, type of items shown in the picture may differ or may not be the part of standard equipment depending upon the specification, requirement, situation, model no. and need of R&D. All specifications are approximate and are not binding to details. We reserve rights to amend and alter without notice.

NEOMATIC

Flour & grain conveying system

Power Saving

Digitally Operated

High Precision Operation



WE NEVER FORGET HOW MUCH YOU RELY ON US

Flour mill engineered for precision

Energy Efficiency

- Significant power savings
- High loading capacity
- Low air consumption
- Reduced operating cost
- Higher plant productivity

Smart Automation

- Fully automated operation
- Digital touchscreen panel
- Intelligent process control
- Automated Material Handling
- Consistent material flow

High-Performance Conveying

- Long distance conveying
- Smaller diameter pipelines
- High conveying efficiency
- Smooth material transfer
- Suitable for high capacities

Compact & Sustainable Design

- Space-saving construction
- Low noise operation
- Maintains product quality
- Reliable operation

Low Maintenance & Reliability

- Eliminates duct choking
- Reduced damage to product
- Longer equipment life
- High system reliability

Versatile Applications

- Flour Conveying
- Grain Conveying
- Besan Handling
- Spice Conveying
- Hundreds of food products



Master control panel



Vibro-Discharge Flow Control



Wi-Fi Enabled Touchscreen



Pneumatic Gates for Free Flow

Manufacturers & Exporters

CHOYAL GRINDING SOLUTION PVT. LTD.

Regd. & City Office: Choyal Tower, 1180/28, Adarsh Nagar,
Nasirabad Road, Ajmer, Rajasthan, India - 305002

Works: Arjunpura NH 58. Ajmer, Rajasthan,
India, 305206

CIN NO.: U28299RJ2025PTC101719

Contact No.: +91 9240 289 259

WhatsApp No.: +91 88902 11444

Email: info@rschoyalgroup.com

Website: www.rschoyalgroup.com



Certified



Wifi Enabled



Touch



Solar Energy



Energy Saver

Numbers, type of items shown in the picture may differ or may not be the part of standard equipment depending upon the specification, requirement, situation, model no. and need of R&D. All specifications are approximate and are not binding to details. We reserve rights to amend and alter without notice.