

Horizontal square type flour mill

Compact Design Manual



WE NEVER FORGET HOW MUCH YOU RELY ON US

Flour mill engineered for precision

24", 30" & 48"

Emery Stones sizes

25 HP

Power Load

CORE CAPABILITIES

Energy Efficiency & Performance

- High Capacity Flour Grinding
- Consistent Grinding Quality
- Coarse, Medium & Fine Atta Production
- Optimized Milling Performance
- Efficient Grain Processing

Smart Automation & Control

- Integrated Motor Control Panel
- Automated Grain Feeding Option
- Smooth Machine Operation
- Enhanced Process Control

Safety & Monitoring

- Motor Stand with Safety Guard
- Grain Level Sensor Integration
- Secure Machine Operation
- Enhanced Operator Safety



Heavy Duty Emery Stone



Integrated Magnet



VFD Feeder with Conical Hopper



Motor Fitted with Belt Guard



Heavy Duty Spiral Bevel Gear

Square Mill with Magnet



Size Available	600mm/750mm/1200mm
Hopper Capacity	N/A
Pressure Type	Manual
Screw Feeder	N/A
Power (600 mm)	15 HP 960 RPM
Power (750 mm)	25 HP 960 RPM
Power (1200 mm)	40 HP 960 RPM

Square Mill with Magnet Traditional Hopper



Size Available	600mm/750mm/1200mm
Hopper Capacity	10-15 Kg
Pressure Type	Manual
Screw Feeder	N/A
Power (600 mm)	15 HP 960 RPM
Power (750 mm)	25 HP 960 RPM
Power (1200 mm)	40 HP 960 RPM

Square Mill with Hopper & VFD Feeder



Size Available	600mm/750mm/1200mm
Hopper Capacity	100-150 Kg
Pressure Type	Manual
Screw Feeder	0.5 HP, VFD Controlled
Power (600 mm)	15 HP 960 RPM
Power (750 mm)	25 HP 960 RPM
Power (1200 mm)	40 HP 960 RPM

Manufacturers & Exporters

CHOYAL GRINDING SOLUTION PVT. LTD.

Regd. & City Office: Choyal Tower, 1180/28, Adarsh Nagar,
Nasirabad Road, Ajmer, Rajasthan, India - 305002

Works: Arjunpura NH 58. Ajmer, Rajasthan,
India, 305206

CIN NO.: U28299RJ2025PTC101719

Contact No.: +91 9240 289 259
WhatsApp No.: +91 88902 11444
Email: info@rschoyalgroup.com
Website: www.rschoyalgroup.com



Numbers, type of items shown in the picture may differ or may not be the part of standard equipment depending upon the specification, requirement, situation, model no. and need of R&D. All specifications are approximate and are not binding to details. We reserve rights to amend and alter without notice.