

Neural Network Basics

9/10 points (90%)

Quiz, 10 questions

✓ Congratulations! You passed![Next Item](#)0 / 1
points

1.

What does a neuron compute?



A neuron computes the mean of all features before applying the output to an activation function

A neuron computes a function g that scales the input x linearly ($Wx + b$)A neuron computes an activation function followed by a linear function ($z = Wx + b$)**This should not be selected**No. It is the other way round. A neuron computes a linearity ($Wx + b$) and then an activation g (sigmoid, tanh, ReLU, ...).A neuron computes a linear function ($z = Wx + b$) followed by an activation function1 / 1
points

2.

Which of these is the "Logistic Loss"?



)

**Correct**

Correct, this is the logistic loss you've seen in lecture!



1 / 1
points

Neural Network Basics

9/10 points (90%)

Quiz, 10 questions

3.

Suppose `img` is a (32,32,3) array, representing a 32x32 image with 3 color channels red, green and blue. How do you reshape this into a column vector?

- ☐ `x = img.reshape((32*32,3))`
- ☒ `x = img.reshape((32*32*3,1))`

**Correct**

- ☐ `x = img.reshape((3,32*32))`
- ☐ `x = img.reshape((1,32*32,*3))`

1 / 1
points

4.

Consider the two following random arrays "a" and "b":

```
1 a = np.random.randn(2, 3) # a.shape = (2, 3)
2 b = np.random.randn(2, 1) # b.shape = (2, 1)
3 c = a + b
```

What will be the shape of "c"?

`c.shape = (2, 3)`**Correct**

Yes! This is broadcasting. `b` (column vector) is copied 3 times so that it can be summed to each column of `a`.

- ☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!
- ☐ `c.shape = (3, 2)`
- ☐ `c.shape = (2, 1)`

1 / 1
points

5.

Neural Network Basics

9/10 points (90%)

Quiz, 10 questions

```
1 a = np.random.randn(4, 3) # a.shape = (4, 3)
2 b = np.random.randn(3, 2) # b.shape = (3, 2)
3 c = a*b
```

What will be the shape of "c"?

- ☐ c.shape = (4,2)
- ☒ The computation cannot happen because the sizes don't match. It's going to be "Error"!

**Correct**

Indeed! In numpy the "*" operator indicates element-wise multiplication. It is different from "np.dot()". If you would try "c = np.dot(a,b)" you would get c.shape = (4, 2).

- ☐ c.shape = (3, 3)
- ☐ c.shape = (4, 3)

1 / 1
points

6.

Suppose you have n_x input features per example. Recall that $X = [x^{(1)} \ x^{(2)} \ \dots \ x^{(m)}]$. What is the dimension of X ?

- ☐ $(m,1)$
- ☐ $(1,m)$
- ☐ (m,n_x)
- ☒ (n_x, m)

**Correct**1 / 1
points

7.

Recall that "np.dot(a,b)" performs a matrix multiplication on a and b, whereas "a*b" performs an element-wise multiplication.

Neural Network Basics

9/10 points (90%)

Quiz, 10 questions Consider the two following random arrays "a" and "b":

```
1 a = np.random.randn(12288, 150) # a.shape = (12288, 150)
2 b = np.random.randn(150, 45) # b.shape = (150, 45)
3 c = np.dot(a,b)
```

What is the shape of c?



c.shape = (12288, 45)



Correct

Correct, remember that a np.dot(a, b) has shape (number of rows of a, number of columns of b). The sizes match because :

"number of columns of a = 150 = number of rows of b"



c.shape = (12288, 150)



c.shape = (150,150)



The computation cannot happen because the sizes don't match. It's going to be "Error"!



1 / 1
points

8.

Consider the following code snippet:

```
1 # a.shape = (3,4)
2 # b.shape = (4,1)
3
4 for i in range(3):
5     for j in range(4):
6         c[i][j] = a[i][j] + b[j]
```

How do you vectorize this?



c = a + b.T



Correct



c = a.T + b



c = a.T + b.T



c = a + b

1 / 1
points

Neural Network Basics

9/10 points (90%)

Quiz, 10 questions Consider the following code:

```

1 a = np.random.randn(3, 3)
2 b = np.random.randn(3, 1)
3 c = a*b

```

What will be c? (If you're not sure, feel free to run this in python to find out).

- ☒ This will invoke broadcasting, so b is copied three times to become (3,3), and $***$ is an element-wise product so c.shape will be (3, 3)




Correct

- ☐ This will invoke broadcasting, so b is copied three times to become (3, 3), and $***$ invokes a matrix multiplication operation of two 3x3 matrices so c.shape will be (3, 3)
- ☐ This will multiply a 3x3 matrix a with a 3x1 vector, thus resulting in a 3x1 vector. That is, c.shape = (3,1).
- ☐ It will lead to an error since you cannot use $***$ to operate on these two matrices. You need to instead use np.dot(a,b)

1 / 1
points

10.

Consider the following computation graph.



What is the output J?

- ☐ $J = (c - 1) * (b + a)$
- ☒ $J = (a - 1) * (b + c)$