
An Introduction to Git and Github

Poruri Sai Rahul,
Software Developer,
Enthought Inc.

Why?

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

@rahulporuri

Why?

- Made a change to code, realised it was a mistake and wanted to revert back?
 - Lost code or had a backup that was too old?
 - Had to maintain multiple versions of a product?
 - Wanted to see the difference between two (or more) versions of your code?
 - Wanted to prove that a particular change broke or fixed a piece of code?
-

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

@rahulporuri

Why? (continued)

- Wanted to review the history of some code?
- Wanted to submit a change to someone else's code?
- Wanted to share your code, or let other people work on your code?
- Wanted to see how much work is being done, and where, when and by whom?
- Wanted to experiment with a new feature without interfering with working code?

Source - <https://goo.gl/GoW6My>

What?


-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

What? - Git


- One of many Distributed Version Control Software
- [Hg](#) and [SVN](#) are two other popular alternatives

@rahulporuri

What? - Git (continued)



What? - Distributed Version Control software



-
- Why?
 - What?
 - Git
 - **GitHub**
 - How?
 - Basic
 - Advanced

What? - Github

- For a beginner - it's a place to backup all of your code
- For a professional - it's a place to collaboratively develop software

@rahulporuri

How?

-
- Why?
 - What?
 - Git
 - GitHub
 - **How?**
 - Basic
 - Advanced


How? - Workflows

- A Basic workflow, which introduces commands for single user to get up and running with Git.
- An advanced workflow, which introduces commands that allow multiple users to work on the same repository(?).


@rahulporuri

repository - a directory being tracked/versioned using Git.

How? - Basic Workflow



How? - Basic Workflow (continued)



-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

How? - Basic Workflow

- `git add 'file-name'`
- `git commit -m "commit message"`
- `git push`

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced


How? - Basic workflow (continued)

- What is happening behind the scenes?

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

First mistake - Not a Git repository

A screenshot of a macOS terminal window. The title bar shows the user 'rahulporuri' and the shell '-bash' with a window size of '70x5'. The terminal content shows a user prompt '~\$' followed by the command 'git status'. The output is an error message: 'fatal: Not a git repository (or any of the parent directories): .git'. The prompt '~\$' appears again on the next line.

```
~$ git status
fatal: Not a git repository (or any of the parent directories): .git
~$
```

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Second mistake - defaults aren't set

```
ab-tmp (master)$ git commit
[master (root-commit) cfa7b85] ealsdjaldfkj
Committer: Poruri Sai Rahul <rahulporuri@Prashants-MacBook-Pro.local>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly:
```

```
git config --global user.name "Your Name"
git config --global user.email you@example.com
```

After doing this, you may fix the identity used for this commit with:

```
git commit --amend --reset-author
```

```
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 me
```

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Third mistake - Origin hasn't been set

```
[ab-tmp (master)]$ git push
fatal: No configured push destination.
Either specify the URL from the command-line or configure a remote repository using

    git remote add <name> <url>

and then push using the remote name

    git push <name>
```

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

What? - Basic workflow (continued)

Helpful commands

- `git log`
- `git show 'commit-hash'`
- `git commit --amend`
- `git reset HEAD^`
- `git diff 'file-name'`

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - **Advanced**

Advanced Workflow

- `git branch 'branch-name'`
- `git checkout 'branch-name'`
- `git add`
- `git commit`
- `git push origin 'branch-name'`
- `git merge 'branch-name'`


-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

How? - Advanced Workflow (continued)

- What's happening behind the scenes?

@rahulporuri


What? - Advanced Workflow (continued)




What? - Advanced Workflow (continued)




What? - Advanced Workflow (continued)




What? - Advanced Workflow (continued)



What? - Advanced Workflow (continued)



What? - Advanced Workflow (continued)



-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

How? - Advanced Workflow (continued)

Helpful commands

- `git branch -l`
- `git branch -d 'branch-name'`

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - **Advanced**

Fourth mistake - Merge conflicts

```
ab-tmp (test)$ git checkout master
Switched to branch 'master'
ab-tmp (master)$
ab-tmp (master)$ git merge test
Auto-merging me
CONFLICT (content): Merge conflict in me
Automatic merge failed; fix conflicts and then commit the result.
ab-tmp (master|MERGING)$ git status
On branch master
You have unmerged paths.
  (fix conflicts and run "git commit")

Unmerged paths:
  (use "git add <file>..." to mark resolution)


        both modified:   me

no changes added to commit (use "git add" and/or "git commit -a")
```

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Fourth mistake - Merge conflicts (continued)



The screenshot shows a Vim editor window titled 'ab-tmp — vim me — 33x13'. The editor is displaying a file named 'me' with the following content:

```
1 <<<<<<< HEAD
2 asdfasdfasdfasdf
3 asdf
4 asdfasdf
5 asdf
6 =====
7 asdfasd
8 asdasdff
9 >>>>>> test
```

The status bar at the bottom of the window shows 'me' on the left, '1,8' in the center, and 'All' on the right.

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Time travel using Git

- Using `git checkout` to travel back in time.

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Correcting your mistakes

- Using `git revert 'commit-hash'` to correct your mistakes

@rahulporuri

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Rewriting history

- Using `git reset 'commit-hash'` to undo commits and bring back changes to the staging area.

-
- Why?
 - What?
 - Git
 - GitHub
 - How?
 - Basic
 - Advanced

Prepare for mind=blown

- `git bisect` and how it can be used to pinpoint breaking changes.
- Followed by `git blame` to play the blame game

@rahulporuri

Credits

- All images are from - <https://git-scm.com/book/en/v2/>, which is awesome.
-