

Self-Regulating Roof/Gutter De-Icing Cable



Model Code:

SR 12 3 -250
A B C D

A: Self Regulating Cable

B: 12 - 120V

24 - 240V

C: Watts per foot

D: Linear Length in feet

SR Series Self-Regulating Heating Cable is designed for a variety of industrial and commercial de-icing applications.

SR Self-Regulating Heating Cable Features

- Cable will not overheat or burn out when overlapped
- 2 year warranty

- Suitable for metallic and nonmetallic gutters and downspouts
- Wattage rating is determined at 32°F (0°C).



AVAILABLE LENGTHS

	VOLTS	DE-ICING RATING** WATTS/FT.	AVAILABLE LENGTHS				WEIGHT/FT.
			100 FT. LENGTH MODEL / UPC	250 FT. LENGTH MODEL / UPC	500 FT. LENGTH MODEL / UPC	1000 FT. LENGTH MODEL / UPC	
120V	120	5	SR123-100 / 40513	SR123-250 / 40414	SR123-500 / 48735	SR123-1000 / 40416	0.080 LBS./FT.
	120	8	SR125-100 / 40514	SR125-250 / 40418	SR125-500 / 48736	SR125-1000 / 40420	0.080 LBS./FT.
	120	12.1	SR128-100 / 40515	SR128-250 / 40422	SR128-500 / 48737	SR128-1000 / 40424	0.080 LBS./FT.
	120	14.8	SR1210-100 / 40516	SR1210-250 / 40426	SR1210-500 / 48733	SR1210-1000 / 40428	0.080 LBS./FT.
240V	240	5	SR243-100 / 40517	SR243-250 / 40430	SR243-500 / 48739	SR243-1000 / 40432	0.080 LBS./FT.
	240	8	SR245-100 / 40518	SR245-250 / 40434	SR245-500 / 48740	SR245-1000 / 40436	0.080 LBS./FT.
	240	12.1	SR248-100 / 40519	SR248-250 / 40438	SR248-500 / 48741	SR248-1000 / 40440	0.080 LBS./FT.
	240	14.8	SR2410-100 / 40520	SR2410-250 / 40442	SR2410-500 / 48738	SR2410-1000 / 40444	0.080 LBS./FT.

**Wattage rating for roof and gutter de-icing application is determined at 32°F (0°C).

*Approved for 208, 220, 277 volt operation, refer to wattage adjustment tables for output rating (Table 4 Page 28).

Controls and thermostats should always be used with King heating cable systems.

SR ACCESSORIES Refer to page 36 for SR Accessories

MODEL	UPC	DESCRIPTION	WEIGHT
CWRK-35	48732	19 Roof Clips & 16 Spacers	0.09 lbs.
SRK00	40462	Hard wired power connection kit, includes end seal	0.3 lbs.
SRK02	40461	Connection kit, includes end seal	0.3 lbs.
SRK08	40466	Plug in 120V connection kit with GFEP device, includes end seal	1.0 lbs.
SRK10	40468	Weatherproof splice/tee kit, includes end seal	0.2 lbs.
SRK12	40470	End seal kit (2 per package)	0.1 lbs.
SRK13	40472	Roof Clip (25 per package)	0.2 lbs.
SRK14	40473	3M VHB double sided acrylic foam pads (25 per package)	0.1 lbs.
SRK15	40476	Downspout hanger and cable ties	0.3 lbs.
SRK17	40477	11 & 13mm Gel end seal	0.1 lbs.