

# ASSIGNMENT

## INTERNET PROTOCOL LAB

**NAME:** Rahul Raj

**REG NO:** CYS22011

**DATE OF ASSIGNMENT PROVIDED:** 31/10/2022

**TITLE:** Analyzing DHCP using protocol analyzer

**AIM:** To analyze DHCP using protocol analyzer

---

### PROCEDURE-

1.a) Begin by opening the Windows Command Prompt application. Type “ipconfig /release”.

```
C:\Users\HP>ipconfig/release

Windows IP Configuration

No operation can be performed on Ethernet while it has its media disconnected.
No operation can be performed on Local Area Connection* 1 while it has its media disconnected.
No operation can be performed on Local Area Connection* 2 while it has its media disconnected.
No operation can be performed on Bluetooth Network Connection while it has its media disconnected.

Ethernet adapter Ethernet:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::b1ee:a3cd:bd11:2216%18
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

Wireless LAN adapter Local Area Connection* 1:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::d0c8:4327:461:1085%9
    Default Gateway . . . . . :

Ethernet adapter Bluetooth Network Connection:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
```

b) Start up the Wireshark packet sniffer.

c) Now go back to the Windows Command Prompt and enter “ipconfig /renew”.

```
C:\Users\HP>ipconfig /renew

Windows IP Configuration

No operation can be performed on Ethernet while it has its media disconnected.
No operation can be performed on Local Area Connection* 1 while it has its media disconnected.
No operation can be performed on Local Area Connection* 2 while it has its media disconnected.
No operation can be performed on Bluetooth Network Connection while it has its media disconnected.

Ethernet adapter Ethernet:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::b1ee:a3cd:bd11:2216%18
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

Wireless LAN adapter Local Area Connection* 1:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    IPv6 Address. . . . . : 2409:4072:6e83:25bf:d0c8:4327:461:1085
    Temporary IPv6 Address. . . . . : 2409:4072:6e83:25bf:d1d8:bae4:b699:78c5
    Link-local IPv6 Address . . . . . : fe80::d0c8:4327:461:1085%9
    IPv4 Address. . . . . : 192.168.0.42
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : fe80::6882:5ff:fe2c:677b%9
                                192.168.0.216

Ethernet adapter Bluetooth Network Connection:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
```

d) Wait until the “ipconfig /renew” has terminated. Then enter the same command “ipconfig /renew” again.

```
C:\Users\HP>ipconfig /release

Windows IP Configuration

No operation can be performed on Ethernet while it has its media disconnected.
No operation can be performed on Local Area Connection* 1 while it has its media disconnected.
No operation can be performed on Local Area Connection* 2 while it has its media disconnected.
No operation can be performed on Bluetooth Network Connection while it has its media disconnected.

Ethernet adapter Ethernet:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::b1ee:a3cd:bd11:2216%18
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

Wireless LAN adapter Local Area Connection* 1:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    IPv6 Address. . . . . : 2409:4072:6e83:25bf:d0c8:4327:461:1085
    Temporary IPv6 Address. . . . . : 2409:4072:6e83:25bf:d1d8:bae4:b699:78c5
    Link-local IPv6 Address . . . . . : fe80::d0c8:4327:461:1085%9
    Default Gateway . . . . . : fe80::6882:5ff:fe2c:677b%9

Ethernet adapter Bluetooth Network Connection:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
```

e) When the second “ipconfig /renew” terminates, enter the command “ipconfig/release” to release the previously-allocated IP address to your computer.

```
C:\Users\HP>ipconfig /renew

Windows IP Configuration

No operation can be performed on Ethernet while it has its media disconnected.
No operation can be performed on Local Area Connection* 1 while it has its media disconnected.
No operation can be performed on Local Area Connection* 2 while it has its media disconnected.
No operation can be performed on Bluetooth Network Connection while it has its media disconnected.

Ethernet adapter Ethernet:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::blee:a3cd:bd11:2216%18
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

Wireless LAN adapter Local Area Connection* 1:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :


Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    IPv6 Address. . . . . : 2409:4072:6e83:25bf:d0c8:4327:461:1085
    Temporary IPv6 Address. . . . . : 2409:4072:6e83:25bf:d1d8:bae4:b699:78c5
    Link-local IPv6 Address . . . . . : fe80::d0c8:4327:461:1085%9
    IPv4 Address. . . . . : 192.168.0.42
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : fe80::6882:5ff:fe2c:677b%9
                                192.168.0.216

Ethernet adapter Bluetooth Network Connection:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
```

g) Stop Wireshark packet capture.



No.	Time	Source	Destination	Protocol	Length	Info	Source code
108	50.252090	192.168.0.42	192.168.0.216	DHCP	358	DHCP Request - Transaction ID 0x7b5ef984	68
109	50.268397	192.168.0.216	192.168.0.42	DHCP	352	DHCP ACK - Transaction ID 0x7b5ef984	67
151	68.819550	192.168.0.42	192.168.0.216	DHCP	358	DHCP Request - Transaction ID 0x61e104b8	68
152	68.953371	192.168.0.216	192.168.0.42	DHCP	352	DHCP ACK - Transaction ID 0x61e104b8	67
212	129.853153	192.168.0.42	192.168.0.216	DHCP	342	DHCP Release - Transaction ID 0xc3cc8a96	68
468	146.164751	0.0.0.0	255.255.255.255	DHCP	344	DHCP Discover - Transaction ID 0xa441a7fa	68
469	146.175098	192.168.0.216	192.168.0.42	DHCP	352	DHCP Offer - Transaction ID 0xa441a7fa	67
470	146.179041	0.0.0.0	255.255.255.255	DHCP	370	DHCP Request - Transaction ID 0xa441a7fa	68
481	146.220199	192.168.0.216	192.168.0.42	DHCP	352	DHCP ACK - Transaction ID 0xa441a7fa	67
950	169.805574	192.168.0.42	192.168.0.216	DHCP	358	DHCP Request - Transaction ID 0xc3001e9a	68
951	169.928275	192.168.0.216	192.168.0.42	DHCP	352	DHCP ACK - Transaction ID 0xc3001e9a	67

After finishing capturing we get total of 11 dhcp packets.

## 2.a) Are DHCP messages sent over UDP or TCP?


No.	Time	Source	Destination	Protocol	Length	Info
108	50.252090	192.168.0.42	192.168.0.216	DHCP	358	DHCP
109	50.268397	192.168.0.216	192.168.0.42	DHCP	352	DHCP
151	68.819550	192.168.0.42	192.168.0.216	DHCP	358	DHCP
152	68.953371	192.168.0.216	192.168.0.42	DHCP	352	DHCP
212	129.853153	192.168.0.42	192.168.0.216	DHCP	342	DHCP
468	146.164751	0.0.0.0	255.255.255.255	DHCP	344	DHCP
469	146.175098	192.168.0.216	192.168.0.42	DHCP	352	DHCP
470	146.179041	0.0.0.0	255.255.255.255	DHCP	370	DHCP
481	146.220199	192.168.0.216	192.168.0.42	DHCP	352	DHCP
950	169.805574	192.168.0.42	192.168.0.216	DHCP	358	DHCP
951	169.928275	192.168.0.216	192.168.0.42	DHCP	352	DHCP

> Frame 108: 358 bytes on wire (2864 bits), 358 bytes captured (2864 bits) on interface 0	0000	6a 8
> Ethernet II, Src: LiteonTe_98:79:99 (54:8c:a0:98:79:99), Dst: 6a 8	0010	01 :
> Internet Protocol Version 4, Src: 192.168.0.42, Dst: 192.168.0.2	0020	00 c
> User Datagram Protocol, Src Port: 68, Dst Port: 67	0030	f9 :
Source Port: 68	0040	00 :
Destination Port: 67	0050	00 :
Length: 324	0060	00 :
Checksum: 0xd6c9 [unverified]	0070	00 :

DHCP messages are sent over UDP.

b) Draw a timing diagram illustrating the sequence of the first four-packet Discover/Offer/Request/ACK DHCP exchange between the client and server. For each packet, indicated the source and destination port numbers.



c) What is the link-layer (e.g., Ethernet) address of your host?

> Frame 42: 342 bytes on wire (2736 bits), 342 bytes captured (2736 bits)
> Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: Broadcast (ff:ff:ff:ff)

The address of the link-layer is called MAC address.

d) What values in the DHCP discover message differentiate this message from the DHCP request message?

<pre> boot file name not given Magic cookie: DHCP &gt; Option: (53) <u>DHCP Message Type (Request)</u> &gt; Option: (61) Client identifier &gt; Option: (50) Requested IP Address (192.168.1.101) &gt; Option: (54) <u>DHCP Server Identifier (192.168.1.1)</u> &gt; Option: (12) Host Name &gt; Option: (60) Vendor class identifier &gt; Option: (55) Parameter Request List &gt; Option: (255) End </pre>	<pre> Boot file name not given Magic cookie: DHCP &gt; Option: (53) <u>DHCP Message Type (Discover)</u> &gt; Option: (116) DHCP Auto-Configuration &gt; Option: (61) Client identifier &gt; Option: (50) Requested IP Address (192.168.1.101) &gt; Option: (12) Host Name &gt; Option: (60) Vendor class identifier &gt; Option: (55) Parameter Request List &gt; Option: (255) End </pre>
--	--

e) What is the value of the Transaction-ID in each of the first four (Discover/Offer/Request/ACK) DHCP messages? What are the values of the Transaction-ID in the second set (Request/ACK) set of DHCP messages? What is the purpose of the Transaction-ID field?

The transaction ID in the first four packets is "0x3e5e0ce3".

The transaction ID in the second set of DHCP messages is "0x3a5d7d9".

<pre> Transaction ID 0x3a5df7d9 Transaction ID 0x3a5df7d9 Transaction ID 0x3a5df7d9 Transaction ID 0x3a5df7d9 </pre>	<pre> - Transaction ID 0x3e5e0ce3 - Transaction ID 0x3e5e0ce3 - Transaction ID 0x3e5e0ce3 - Transaction ID 0x3e5e0ce3 </pre>
--	--

f) A host uses DHCP to obtain an IP address, among other things. But a host's IP address is not confirmed until the end of the four-message exchange! If the IP address is not set until the end of the four-message exchange, then what values are used in the IP datagrams in the four-message exchange? For each of the four DHCP messages (Discover/Offer/Request/ACK DHCP), indicate the source and destination IP addresses that are carried in the encapsulating IP datagram.

For discover and request: Source IP= 0.0.0.0 and Destination= 255.255.255.255

For offer and ACK: Source IP= 172.17.18.2 and Destination= 172.17.136.155

0.0.0.0	255.255.255.255	DHCP	344 DHCP Discover
172.17.18.2	172.17.136.155	DHCP	361 DHCP Offer
0.0.0.0	255.255.255.255	DHCP	370 DHCP Request
172.17.18.2	172.17.136.155	DHCP	361 DHCP Offer

g) What is the IP address of your DHCP server?

IP=192.168.1.1

192.168.1.1	255.255.255.255	DHCP	590 DHCP Offer	-
-------------	-----------------	------	----------------	---

h) What IP address is the DHCP server offering to your host in the DHCP Offer message? Indicate which DHCP message contains the offered DHCP address.

IP=192.168.1.101

```
> Bootp flags: 0x0000 (Unicast)
  Client IP address: 0.0.0.0
  Your (client) IP address: 192.168.1.101
```

i) In the example screenshot in this assignment, there is no relay agent between the host and the DHCP server. What values in the trace indicate the absence of a relay agent? Is there a relay agent in your experiment? If so what is the IP address of the agent?

```
> Bootp flags: 0x0000 (Unicast)
  Client IP address: 0.0.0.0
  Your (client) IP address: 0.0.0.0
  Next server IP address: 0.0.0.0
  Relay agent IP address: 0.0.0.0
```

Therefore, there is no Relay agent.

j) Explain the purpose of the router and subnet mask lines in the DHCP offer message.

```
✓ Option: (1) Subnet Mask (255.255.255.0)
  Length: 4
  Subnet Mask: 255.255.255.0
✓ Option: (3) Router
  Length: 4
  Router: 192.168.1.1
```

The router forwards the request packet to the network and it reaches the DHCP server in the other LAN network, when the DHCP server is not present in our network and if it is present in some other LAN then the DHCP DISCOVER message is sent to the router in its network.

k) In the DHCP trace file, the DHCP server offers a specific IP address to the client. In the client's response to the first server OFFER message, does the client accept this IP address? Where in the client's RESPONSE is the client's requested address?

Yes, the server accepted the offered IP address.

```
> Bootp flags: 0x0000 (Unicast)
Client IP address: 0.0.0.0
Your (client) IP address: 192.168.1.101
```

l) Explain the purpose of the lease time. How long is the lease time in your experiment?

```
Option: (51) IP Address Lease Time
Length: 4
IP Address Lease Time: (86400s) 1 day
```

m) What is the purpose of the DHCP release message? Does the DHCP server issue an acknowledgment of receipt of the client's DHCP request? What would happen if the client's DHCP release message is lost?

The purpose of releasing messages is to release IP address to the computer. NO, the DHCP server does not send ACK receipt of client's DHCP request.

n) Clear the DHCP filter from your Wireshark window. Were any ARP packets sent or received during the DHCP packet-exchange period? If so, explain the purpose of those ARP packets

Yes, it is visible that many ARP packets that were transferred in the experiment.

arp						
No.	Time	Source	Destination	Protocol	Length	Info
3	7.588881	LinksysG_da:af:73	Broadcast	ARP	60	Who has 192.168.1.101? Tell 192.168.1.1
7	8.638148	Dell_4f:36:23	Broadcast	ARP	42	ARP Announcement for 192.168.1.101
8	9.285757	Dell_4f:36:23	Broadcast	ARP	42	ARP Announcement for 192.168.1.101
9	10.285814	Dell_4f:36:23	Broadcast	ARP	42	ARP Announcement for 192.168.1.101
11	11.311090	LinksysG_da:af:73	Broadcast	ARP	60	Who has 192.168.1.101? Tell 192.168.1.1
12	11.311102	Dell_4f:36:23	LinksysG_da:af:73	ARP	42	192.168.1.101 is at 00:08:74:4f:36:23
23	16.130580	Dell_4f:36:23	Broadcast	ARP	42	Who has 192.168.1.117? Tell 192.168.1.101
24	16.131598	Hp-UxE90_0d:c8:06	Dell_4f:36:23	ARP	60	192.168.1.117 is at 00:10:83:0d:c8:06
43	30.870874	LinksysG_da:af:73	Broadcast	ARP	60	Who has 192.168.1.101? Tell 192.168.1.1
47	31.912478	Dell_4f:36:23	Broadcast	ARP	42	ARP Announcement for 192.168.1.101
48	32.286862	Dell_4f:36:23	Broadcast	ARP	42	ARP Announcement for 192.168.1.101
49	33.286915	Dell_4f:36:23	Broadcast	ARP	42	ARP Announcement for 192.168.1.101
51	34.310968	LinksysG_da:af:73	Broadcast	ARP	60	Who has 192.168.1.101? Tell 192.168.1.1
52	34.310980	Dell_4f:36:23	LinksysG_da:af:73	ARP	42	192.168.1.101 is at 00:08:74:4f:36:23