ALL-IN-ONE dvLED DISPLAY

Technical Reference — Dimensions, Mounting & Electrical | BRIGHTLUXX

PRODUCT SPECIFICATIONS

Model	Pitch	Size	Resolution	Weight	Depth	Power
AIO-110	P1.2	110" (2440x1372mm)	3840x2160 (4K)	65 kg	42mm	350W
AIO-136	P1.5	136" (3008x1692mm)	3840x2160 (4K)	80 kg	42mm	450W
AIO-163	P1.8	163" (3610x2030mm)	3840x2160 (4K)	95 kg	42mm	550W
AIO-216	P1.2	216" (4800x2700mm)	7680x4320 (8K)	150 kg	42mm	850W

MOUNTING & STRUCTURE

Wall bracket (supplied). Min wall: reinforced concrete or steel stud with bracing. Rear gap: 50mm minimum for ventilation. Front-service: all modules accessible from front.

ELECTRICAL REQUIREMENTS

Single-phase 220V. Dedicated 16A circuit (110/136) or 32A circuit (163/216). Include surge protection.

NOTES FOR ARCHITECTS

This reference document provides typical dimensions and specifications. Actual dimensions vary by manufacturer and configuration. Contact Brightluxx for project-specific technical drawings, Revit families, and structural calculations.

For custom Revit families or AutoCAD blocks: WhatsApp +971 55 991 0711 or email info@brightluxx.com