FINE-PITCH LED VIDEO WALL

Technical Reference — Cabinet Dimensions & Wall Configurations | BRIGHTLUXX

PRODUCT SPECIFICATIONS

Cabinet	Pitch	Dimensions	Resolution	Weight	Power/cab
FP-500	P0.9	600x337.5mm	667x375	5.5 kg	75W
FP-500	P1.2	600x337.5mm	500x281	5.5 kg	65W
FP-500	P1.5	600x337.5mm	400x225	5.5 kg	60W
FP-500	P1.9	600x337.5mm	320x180	5.2 kg	55W

MOUNTING & STRUCTURE

Steel mounting frame (custom fabricated per wall size). Floor-standing or wall-mounted. Rear service: 600mm gap minimum. Front service: cabinets are magnetically attached, tool-free removal.

ELECTRICAL REQUIREMENTS

Three-phase for walls >10sqm. Per cabinet: 55-75W. Total = cabinets x power. Add 20% headroom.

NOTES FOR ARCHITECTS

This reference document provides typical dimensions and specifications. Actual dimensions vary by manufacturer and configuration. Contact Brightluxx for project-specific technical drawings, Revit families, and structural calculations.

For custom Revit families or AutoCAD blocks: WhatsApp +971 55 991 0711 or email info@brightluxx.com