OUTDOOR LED CABINET

Technical Reference — Cabinet Dimensions & Weather Protection | BRIGHTLUXX

PRODUCT SPECIFICATIONS

Cabinet	Pitch	Dimensions	Resolution	Weight	IP	Nits
OD-960	P3.9	960x960mm	246x246	32 kg	IP65	5500
OD-960	P4.8	960x960mm	200x200	30 kg	IP65	6500
OD-960	P6	960x960mm	160x160	28 kg	IP65	7000
OD-960	P8	960x960mm	120x120	26 kg	IP65	8000
OD-960	P10	960x960mm	96x96	24 kg	IP65	10000

MOUNTING & STRUCTURE

Steel structure with anti-corrosion coating. Wind load: designed for 120 km/h. Foundation: concrete pad or building structural steel. Front service: module removal from front with quick-lock.

ELECTRICAL REQUIREMENTS

Three-phase 380V for large installations. Per sqm: 600-800W peak. Dual power input per cabinet. Surge protection required.

NOTES FOR ARCHITECTS

This reference document provides typical dimensions and specifications. Actual dimensions vary by manufacturer and configuration. Contact Brightluxx for project-specific technical drawings, Revit families, and structural calculations.

For custom Revit families or AutoCAD blocks: WhatsApp +971 55 991 0711 or email info@brightluxx.com