

# HTML Anchor Tag and Hyperlinks

## 1. HTML Anchor Tag:

- a. The HTML anchor tag defines a hyperlink that links one page to another page.
- b. Hyperlinks are used to join multiple webpages.
- c. To provide hyperlinks in webpage we have to use `<a>.....</a>` tag in HTML.
- d. Anchor tag is a paired tag in HTML.
- e. **Syntax:** `<a href="">.....</a>`

## 2. Anchor tag related attributes:

- a. Anchor tag consists of 2 attributes:
  - i. **href** attribute  $\Rightarrow$  It is used to provide a link to a webpage which you want to join or redirect.
  - ii. **target** attribute  $\Rightarrow$  It is used to provide behaviour for opening of a link. Like we have to open the link in the same tab or another tab. There are 4 values for target attribute:
    - iii. *target = \_self (default)*
    - iv. *target = \_blank*
    - v. *target = \_top*
    - vi. *target = \_parent*

## 3. Appearance of HTML Anchor Tag:

- a. Unvisited Link  $\rightarrow$  Displayed underlined and blue.
- b. Visited Link  $\rightarrow$  Displayed underlined and purple.
- c. Active Link  $\rightarrow$  Underlined and red color.

#### 4. Link to same website (Default):

- a. If we want to redirect the same or current page then we can pass the value **#** inside the **href** attribute.
- b. And by default the value for target attribute is **\_self**.
- c. **Example** ⇒ `<a href="#">Same Page</a>`

#### 5. Link to other website:

- a. If we want to redirect to another page then we have to pass the reference of that page or source to the href attribute.
- b. And if you want to open that source in another tab then we must pass the value as **\_blank** for target attribute.
- c. Because by default its target is **\_self** and it will open in the current page or tab.
- d. **Example** ⇒  
`<a href="https://www.google.com/" target="_blank">Google Home</a>`

#### 6. Link that runs mail (**mailto**):

- a. *Mailto* links are used to redirect to an email address instead of a web page URL.
- b. When a user clicks on the Mailto link, the default email client on the visitor's computer opens and suggests sending a message to the email address mentioned in the Mailto link.
- c. To create a Mailto link, you need to use the HTML tag with its **href** attribute, and insert a " **mailto:** " parameter.
- d. **Example** ⇒ `<a href="mailto:abc@gmail.com">Click Here to Mail</a>`

#### 7. How to download source on clicking link (**download**):

- a. The **download** attribute specifies that the target (the file specified in the **href** attribute) will be downloaded when a user clicks on the hyperlink.

b. **Example** ⇒ `<a href="/assets/devlogo.jpg" download>Download</a>`

c. **NOTE** ⇒ If we do not provide the value for download attribute by default it will take the name of the file name that we have provided in the *href* attribute as source.

d. **Example** ⇒

`<a href="/assets/devlogo.jpg" download="Developer">Download</a>`