

[SIGN OUT](#)

QHACK

Quantum Coding Challenges



RANK



TEAM



CHALLENGES



SUBMISSIONS



SUPPORT

[▼ Jump to code](#)[— Collapse text](#)

7. Optimize This

0 points

Welcome to the QHack 2023 daily challenges! Every day for the next four days, you will receive two new challenges to complete. These challenges are worth no points — they are specifically designed to get your brain active and into the right mindset for the competition. You will also learn about various aspects of PennyLane that are essential to quantum computing, quantum machine learning, and quantum chemistry. Have fun!


Tutorial #7 — Quantum machine learning

The Coding Challenge Competition is now closed, but you are welcome to continue working on the challenges until QHack ends on Feb 28 @5pm ET.



models might offer significant speedups for performing certain tasks like classification, image processing, and regression.

In this challenge, you'll learn the meat and potatoes of training a quantum machine learning model. Specifically, you will implement a procedure for embedding classical numbers into a quantum computer, construct a simple quantum machine learning model, and perform three optimization steps. The quantum circuit in the model that you will implement looks like this:



Challenge code

In the code below, you must complete the following functions:

- `three_optimization_steps`: performs three optimization steps. **You must complete this function.**
- `cost`: this is within the `three_optimization_steps` function. **You must complete this function.** `cost` is a QNode that does a few things:
 - acts on 3 qubits only;
 - embeds the input `data` via [amplitude embedding](#);
 - defines some differentiable gates via a template called [qml.BasicEntanglerLayers](#); and
 - returns the expectation value of $\sum_{i=1}^n Z_i$, where n is the number of qubits.

Within the `three_optimization_steps` function is a variable called `weights`. These are the changeable parameters that help define the `qml.BasicEntanglerLayers` template

The Coding Challenge Competition is now closed, but you are welcome to continue working on the challenges until QHack ends on Feb 28 @5pm ET.

To perform three optimization steps, use a gradient decent optimizer — `qml.GradientDescentOptimizer` — with a step size of **0.01**.

Here are some helpful resources:

- [Optimizing a quantum circuit — YouTube video](#)
- [Basic tutorial: qubit rotation — Optimization](#)

Input

As input to this problem, you are given classical `data` (`list(float)`) that you must embed into a quantum circuit via [amplitude embedding](#).

Output

This code must output the evaluation of `cost` after three optimization steps have been performed.

If your solution matches the correct one within the given tolerance specified in `check` (in this case it's a `1e-4` relative error tolerance), the output will be `"Correct!"`. Otherwise, you will receive a `"Wrong answer"` prompt.

Good luck!

Code

 Help



```
1 import json
2 import pennylane as qml
3 import pennylane.numpy as np
```



The Coding Challenge Competition is now closed, but you are welcome to continue working on the challenges until QHack ends on Feb 28 @5pm ET.

```

4  def three_optimization_steps(data):
5      """Performs three optimization steps on a quantum machine learning model
6
7      Args:
8          data (list(float)): Classical data that is to be embedded in a quantum circuit
9
10     Returns:
11         (float): The cost function evaluated after three optimization steps
12     """
13
14     normalize = np.sqrt(np.sum(data[i] ** 2 for i in range(len(data))))
15     data /= normalize
16
17     dev = qml.device("default.qubit", wires=3)
18
19     @qml.qnode(dev)
20     def cost(weights, data=data):
21         """A circuit that embeds classical data and has quantum gates with tunable parameters
22
23         Args:
24             weights (numpy.array): An array of tunable parameters that have an effect on the circuit
25
26         Kwargs:
27             data (list(float)): Classical data that is to be embedded in a quantum circuit
28
29         Returns:
30             (float): The expectation value of the sum of the Pauli Z operators
31         """
32

```

```

33         # Put your code here #
34
35         return
36

```

```

37     # initialize the weights
38     shape = qml.BasicEntanglerLayers.shape(n_layers=2, n_wires=dev.num_wires)
39     weights = np.array([0.1, 0.2, 0.3, 0.4, 0.5, 0.6], requires_grad=True, dtype=float)
40     shape
41 )
42

```

The Coding Challenge Competition is now closed, but you are welcome to continue working on the challenges until QHack ends on Feb 28 @5pm ET.

```
47 # Optimize the cost function for three steps
48
49 return cost(weights, data=data)
50
51 # These functions are responsible for testing the solution.
52 def run(test_case_input: str) -> str:
53     data = json.loads(test_case_input)
54     cost_val = three_optimization_steps(data)
55     return str(cost_val)
56
57 def check(solution_output: str, expected_output: str) -> None:
58     solution_output = json.loads(solution_output)
59     expected_output = json.loads(expected_output)
60     assert np.allclose(solution_output, expected_output, rtol=1e-4)
61
62 test_cases = [['[1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0]', '0.066040']]
63 for i, (input_, expected_output) in enumerate(test_cases):
64     print(f"Running test case {i} with input '{input_}'...")
65
66     try:
67         output = run(input_)
68
69     except Exception as exc:
70         print(f"Runtime Error. {exc}")
71
72     else:
73         if message := check(output, expected_output):
74             print(f"Wrong Answer. Have: '{output}'. Want: '{expected_out}"
75
76         else:
77             print("Correct!")
```

 Copy all

Submit

Open Notebook 

The Coding Challenge Competition is now closed, but you are welcome to continue working on the challenges until QHack ends on Feb 28 @5pm ET.

The Coding Challenge Competition is now closed, but you are welcome to continue working on the challenges until QHack ends on Feb 28 @5pm ET.