

AUSTIN ALLOY CAST PVT. LTD.

Survey No.177 P 17, Plot No.4,Rajkot-Gondal NH 27,BHARUDI,,Gondal,Pin:360311,INDIA Tel:+91-2825-280299,280288,,Fax:,e-mail:info@austinalloycast.com,sales@austinalloycast.com

ISO 9001 : 2015 Certificate No. 011001837527

INSPECTION CERTIFICATE EN 10204 - type 3.1

Page 1 of 2

F01/24

M/s. L & T VALVES LIMITED, L & T CAMPUS, L & T BYPASS ROAD,

MALUMICHAMPATTI, POST BAG No. 607 - 656. COIMBATORE, Pin: 641050 T.C No : G/2275/18-19/1

D.C No : G/2275/18-19

Date: 25/12/2018

O.A No : P2488

Date: 01/10/2018

Date: 25/12/2018

P.O No: 10162987

Date: 01/10/2018

SPECIFICATION

: ASTM A216-16 GR.WCB

							CHE	MICA	L ANA	LYSIS	5			
HEAT#	C.%	Mn.%	Si.%	S.%	P.%	Cr.%	Ni.%	Mo.%	V.%	Cu.%	AI.%	CE.%	TRE.%	
MIN	• ***	•	-	-		2.5	•			(1				
MAX	0.300	1.000	0.600	0.030	0.035	0.500	0.500	0.200	0.030	0.300	0.060	0.500	0.500	
4ZAB	0.173	0.799	0.308	0.014	0.015	0.089	0.143	0.017	0.009	0.057	0.002	0.343	0.315	-
4ZAC	0.165	0.821	0.328	0.014	0.016	0.066	0.143	0.011	0.008	0.045	0.003	0.331	0.258	
4ZAC	0.165	0.821	, 0.328	0.014	0.0,16	0.066	0.143	0.011	0.008	0.045	0.003	0.331	0.258	
4YJE	0.168	0.823	0.428	0.011	0.024	0.109	0.148	0.010	0.007	0.071	0.003	0.345	0.347	
4ZAD	0.184	0.851	0.304	0.012	0.015	0.070	0.163	0.014	0.006	0.048	0.002	0.358	0.302	

MECHANICAL PROPERTIES

HEAT#	Y.S (0.2%) M Pa	Y.S (1.0%) M Pa	T.S MPa	% Elgn	% Red in Area	Hardness BHN	Shear Area	Impact Test at °C (J) SIZE: 10 X 10 X 55 MM				Lateral Expansion (in MM)			
				GL=25mm				ī	11	111	AVG	ı	11	ill ill	AVG
MIN	250	-	485	22	35	-	-	-	; -	i -	•	-	-	-	Ţ -
MAX	-	-	655	-	9.■	235	-	-	-	•	7 2	10	-	-	T -
4ZAB	355.10	-	516.00	31.44	61.23	135 - 144		-	-	-	; - 1	-	-	-	-
4ZAC	309.10	3 2	524.00	36.92	64.61	139 - 144	_	7 .	-	-			.=	-	-
4ZAC	309.10	-	524.00	36.92	64.61	139 - 144	_	-	-	-	-	-	-	-	
4YJE	326.20	(I=	520.00	32.24	63.92	144 - 156	_	_			- 1	-	19-	-	
4ZAD	310.20	-	515.00	32.52	58.98	137 - 144	_	-			1 .		15.5		

HEAT TREATMENT DETAILS

HEAT#	HEAT TR	HEAT TREATMENT PROCESS - II				HEAT TREATMENT PROCESS - III						
	Type of H/T	Soaked Temp. °C	Soaked Time Hrs	Cooling Media	Type of H/T	Soaked Temp. °C	Soaked Time Hrs	Cooling Media	Type of H/T	Soaked Temp. °C	Soaked Time Hrs	Cooling Media
4ZAB	NORMALIZE	900	2 Hr.	AC			OLD EPCM A				000000000000000000000000000000000000000	
4ZAC	NORMALIZE	900	2 Hr.	AC								
4ZAC	NORMALIZE	900	2 Hr.	AC								
4YJE	NORMALIZE	900	2 Hr.	AC								
4ZAD	NORMALIZE	900	2 Hr.	AC						N 15		

DESPATCH DETAILS							
HEAT#	POUR DATE	MOULD #	ITEM DESCRIPTION	PART#	DRAWING#	DESP. QTY	
4ZAB	10/12/2018	DW1719C	BODY, SIZE: 2", CLASS - 150	BL0001V-Y-A10C0KA	BL0001V-B REV.000	8	
4ZAC	10/12/2018	DW1719C	BODY, SIZE: 2", CLASS - 150	BL0001V-Y-A10C0KA	BL0001V-B REV.000	1	
4ZAC	10/12/2018	DW1722C	COVER, SIZE: 2", CLASS: 150/300	BL0037V-Y-A10C0KA	BL0037V-B REV.000	28	
4YJE	18/11/2018	DW1722C	COVER, SIZE: 2", CLASS: 150/300	BL0037V-Y-A10C0KA	BL0037V-B REV.000	9	
4ZAD	10/12/2018	DW1722C	COVER, SIZE: 2", CLASS : 150/300	BL0037V-Y-A10C0KA	BL0037V-B REV.000	28	
	AND ASSESSMENT CONTRACTOR				NAMES OF THE PARTY	AND THE RESIDENCE OF THE PARTY	

We hereby certify that items mentioned above confirms to : ASTM A216-16 GR.WCB

FOR AUSTIN ALLOY CAST PVT. LTD.

Amdt No.: 00

Date

: 15.1.2015

Tested By: JAYDEEP BHATT L&T Valves Limited, Coimbatore

KETANBHAI

Q.A. DEPARTMENT



Survey No.177 P 17, Plot No.4,Rajkot-Gondal NH 27,BHARUDI,,Gondal,Pin:360311,INDIA Tel:+91-2825-280299,280288,,Fax:,e-mail:info@austinalloycast.com,sales@austinalloycast.com

TEST CERTIFICATE EN 10204 - type 3.1

ISO 9001 : 2015 Certificate No. 011001837527

F01/24

M/s. L & T VALVES LIMITED.

L & T CAMPUS, L & T BYPASS ROAD,

MALUMICHAMPATTI,

POST BAG No. 607 - 656.

COIMBATORE, Pin:641050

SPECIFICATION

: ASTM A216-16 GR.WCB

T.C No: G/2275/18-19/1

D.C No: G/2275/18-19

O.A No : P2488

P.O No: 10162987

Date: 25/12/2018

Date: 25/12/2018

Date: 01/10/2018 Date: 01/10/2018

We hereby certify that items mentioned above confirms to : ASTM A216-16 GR.WCB

Casting surface finish complies to MSS-SP-55 Example (Type II to XII A)

Steel is Fully Killed and Fine Grained.

Delivered Materials are Free of Radioactive Contamination.

Material conforms to NACE MR 0175/ISO 15156-2015 & NACE MR 0103-2016

Materials confirms to customer specification TDC-001 REV.026

No Major Weld Repair done on Casting.

YS is measured by 0.2% offset method.

MPI REPORT NO.0359/18,0360/18,0361/18 REPORT DATE:25.12.2018

MANUFACTURER'S MARK



or

1850-14

Reviewed & Recepted
K.P. REJUL Shimesh
Quality Control
L&T Valves Limited, Calmbatore

For AUSTIN ALLOY

KETANBHAI Q.A. DEPARTMENT

Amdt No.: 00

Date : 15.1.2015

Tested By: JAYDEEP BHATT