


Introduction to MapReduce

Dr. Amit Praseed


What is MapReduce?

- MapReduce is a software framework for processing large datasets in a distributed fashion
 - Map data into multiple $\langle \text{key}, \text{value} \rangle$ pairs
 - Reduce over all keys having the same data
- Consider a simple example of finding the count of every word present in a document

Word Count using MapReduce



MapReduce Workflow



Handling Node Failures

- Worker Node Failure
 - Any map task or reduce task in progress on a failed worker is set to idle and rescheduled
 - Any completed map task is also restarted, as output is stored on local disk
 - Completed reduce tasks don't need to be restarted as output is written to a global file
- Master Node Failure
 - Periodic check pointing
 - Restart on a different master

Handling Stragglers

- Straggler : a machine that takes an unusually long time to complete one of the last few map or reduce tasks in the computation
 - a machine with a bad disk may experience slow read performance
 - Other scheduled other tasks on the machine
- When a MapReduce operation is close to completion
 - The master schedules backup executions of the remaining in-progress tasks
 - The task is marked as completed whenever either the primary or the backup execution completes

PageRank using MapReduce

- PageRank is the magic algorithm behind Google search results
- Every web site is awarded a rank based on certain features, most notable of which is the number of links from other sites to itself
- This algorithm needs to be executed on a large amount of data – hence MapReduce is a good option

Random Surfer Model

- Intuition for PageRank
- Imagine a surfer who starts on a randomly chosen page and then follows outgoing links at random
 - Markov Process
- PageRank is probability that user will arrive at a given page during this random walk

A little more complex!

- Model assumes that surfer doesn't always follow a link, but sometimes e.g. bookmarks instead.
- Before each move, surfer flips a coin
 - With probability α , follows an out-link
 - With probability $1 - \alpha$, moves to a (uniformly chosen) random page

Simplified Page Rank



- PageRank of a page is based on the number of pages which link to it
 - But what if a page owner creates a swarm of dummy pages pointing to his website?
- PageRank of a page is based on the PageRank of the pages which link to it
 - A page divides its PageRank equally among all its outgoing links

$$P(n) = \sum_{m \in L(n)} \frac{P(m)}{C(m)}$$

$L(n)$ is the pages connected to n and $C(m)$ is the number of pages that m is connected to



Example

Iteration 1



Example

Iteration 2



PageRank using MapReduce

- Full algorithm is iterative
- Initialize the nodes to uniform distribution
- Run the two MR jobs described iteratively
 - Map job emits page rank distributions continuously
 - Reduce job constantly collects these emitted page ranks and combines them for every node
- Until convergence (no change)
- At the end there is a clean up/normalization phase to correct the distributions

$$p' = \alpha \frac{1}{|G|} + (1 - \alpha) \left(\frac{m}{|G|} + p \right)$$