

Support Recovery for Orthogonal Matching Pursuit

Upper and Lower bounds

Raghav Somani, Chirag Gupta, Prateek Jain and Praneeth Netrapalli

September 24, 2018

Sparse Regression

$$\bar{\mathbf{x}} = \arg \min_{\|\mathbf{x}\|_0 \leq s^*} f(\mathbf{x}) \quad (1.1)$$

$\mathbf{x} \in \mathbb{R}^d$ and $s^* \ll d$.

ℓ_0 norm counts the number of non-zero elements.

Applications

- Resource constrained Machine Learning
- High dimensional Statistics
- Bioinformatics

Sparse Regression

$$\bar{\mathbf{x}} = \arg \min_{\|\mathbf{x}\|_0 \leq s^*} f(\mathbf{x}) \quad (1.1)$$

$\mathbf{x} \in \mathbb{R}^d$ and $s^* \ll d$.

ℓ_0 norm counts the number of non-zero elements.

Applications

- Resource constrained Machine Learning
- High dimensional Statistics
- Bioinformatics

Sparse Linear Regression (SLR)

- Sparse *Linear* Regression is a representative problem. Results typically extend easily to general case.
- With $f(\mathbf{x}) = \|\mathbf{Ax} - \mathbf{y}\|_2^2$, SLR's objective is to find

$$\bar{\mathbf{x}} = \arg \min_{\|\mathbf{x}\|_0 \leq s^*} \|\mathbf{Ax} - \mathbf{y}\|_2^2 \quad (2.1)$$

where $\mathbf{A} \in \mathbb{R}^{n \times d}$, $\mathbf{x} \in \mathbb{R}^d$ and $\mathbf{y} \in \mathbb{R}^n$.

- Unconditionally, it is NP hard (reduction to 3 set cover problem).

Sparse Linear Regression (SLR)

- Sparse *Linear* Regression is a representative problem. Results typically extend easily to general case.
- With $f(\mathbf{x}) = \|\mathbf{Ax} - \mathbf{y}\|_2^2$, SLR's objective is to find

$$\bar{\mathbf{x}} = \arg \min_{\|\mathbf{x}\|_0 \leq s^*} \|\mathbf{Ax} - \mathbf{y}\|_2^2 \quad (2.1)$$

where $\mathbf{A} \in \mathbb{R}^{n \times d}$, $\mathbf{x} \in \mathbb{R}^d$ and $\mathbf{y} \in \mathbb{R}^n$.

- Unconditionally, it is NP hard (reduction to 3 set cover problem).

Sparse Linear Regression (SLR)

- Sparse *Linear* Regression is a representative problem. Results typically extend easily to general case.
- With $f(\mathbf{x}) = \|\mathbf{Ax} - \mathbf{y}\|_2^2$, SLR's objective is to find

$$\bar{\mathbf{x}} = \arg \min_{\|\mathbf{x}\|_0 \leq s^*} \|\mathbf{Ax} - \mathbf{y}\|_2^2 \quad (2.1)$$

where $\mathbf{A} \in \mathbb{R}^{n \times d}$, $\mathbf{x} \in \mathbb{R}^d$ and $\mathbf{y} \in \mathbb{R}^n$.

- Unconditionally, it is NP hard (reduction to 3 set cover problem).

Assumptions of interest

Despite being NP hard, SLR is tractable under certain assumptions.

- **Incoherence** -

If $\Sigma = \mathbf{A}^T \mathbf{A}$, then $\max_{i \neq j} |\Sigma_{ij}| \leq M$

If $M \leq \frac{1}{2s^* - 1}$ and $\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} \implies \bar{\mathbf{x}}$ is unique sparsest solution, and OMP can recover $\bar{\mathbf{x}}$ in s^* steps.

- **Restricted Isometry Property (RIP)** -

$$\|\mathbf{A}_S^T \mathbf{A}_S - \mathbf{I}\|_2 \leq \delta_{|S|} \quad (\delta_s \leq M(s-1) \quad \forall s \geq 2)$$

$$\implies (1 - \delta_s) \|\mathbf{v}\|_2^2 \leq \|\mathbf{A}\mathbf{v}\|_2^2 \leq (1 + \delta_s) \|\mathbf{v}\|_2^2 \quad \forall \mathbf{v} \text{ s.t. } \|\mathbf{v}\|_0 \leq s.$$

- **Null space property** -

$\forall S \in [d]$ s.t. $|S| \leq s$, if $\mathbf{v} \in \text{Null}(\mathbf{A}) \setminus \{0\}$, then $\|\mathbf{v}_S\|_1 \leq \|\mathbf{v}_{S^c}\|_1$

$$\implies \{\mathbf{v} \in \mathbb{R}^d \mid \mathbf{A}\mathbf{v} = 0\} \cap \{\mathbf{v} \in \mathbb{R}^d \mid \|\mathbf{v}_{S^c}\|_1 \leq \|\mathbf{v}_S\|_1\} = 0$$

- **Restricted Strong Convexity (RSC)** -

$$\|\mathbf{A}\mathbf{x} - \mathbf{A}\mathbf{z}\|_2^2 \geq \rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \quad \forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d \text{ s.t. } \|\mathbf{x} - \mathbf{z}\|_0 \leq s$$

Incoherence \implies RIP \implies Null space property \implies RSC

RSC is the weakest and the most popular assumption.

Assumptions of interest

Despite being NP hard, SLR is tractable under certain assumptions.

- Incoherence** -

If $\Sigma = \mathbf{A}^T \mathbf{A}$, then $\max_{i \neq j} |\Sigma_{ij}| \leq M$

If $M \leq \frac{1}{2s^*-1}$ and $\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} \implies \bar{\mathbf{x}}$ is unique sparsest solution, and OMP can recover $\bar{\mathbf{x}}$ in s^* steps.

- Restricted Isometry Property (RIP)** -

$$\|\mathbf{A}_S^T \mathbf{A}_S - \mathbf{I}\|_2 \leq \delta_{|S|} \quad (\delta_s \leq M(s-1) \quad \forall s \geq 2)$$

$$\implies (1 - \delta_s) \|\mathbf{v}\|_2^2 \leq \|\mathbf{A}\mathbf{v}\|_2^2 \leq (1 + \delta_s) \|\mathbf{v}\|_2^2 \quad \forall \mathbf{v} \text{ s.t. } \|\mathbf{v}\|_0 \leq s.$$

- Null space property** -

$$\forall S \in [d] \text{ s.t. } |S| \leq s, \text{ if } \mathbf{v} \in \text{Null}(\mathbf{A}) \setminus \{\mathbf{0}\}, \text{ then } \|\mathbf{v}_S\|_1 \leq \|\mathbf{v}_{S^c}\|_1$$

$$\implies \{\mathbf{v} \in \mathbb{R}^d \mid \mathbf{A}\mathbf{v} = \mathbf{0}\} \cap \{\mathbf{v} \in \mathbb{R}^d \mid \|\mathbf{v}_{S^c}\|_1 \leq \|\mathbf{v}_S\|_1\} = \mathbf{0}$$

- Restricted Strong Convexity (RSC)** -

$$\|\mathbf{A}\mathbf{x} - \mathbf{A}\mathbf{z}\|_2^2 \geq \rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \quad \forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d \text{ s.t. } \|\mathbf{x} - \mathbf{z}\|_0 \leq s$$

Incoherence \implies RIP \implies Null space property \implies RSC

RSC is the weakest and the most popular assumption.

Assumptions of interest

Despite being NP hard, SLR is tractable under certain assumptions.

- Incoherence** -

If $\Sigma = \mathbf{A}^T \mathbf{A}$, then $\max_{i \neq j} |\Sigma_{ij}| \leq M$

If $M \leq \frac{1}{2s^*-1}$ and $\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} \implies \bar{\mathbf{x}}$ is unique sparsest solution, and OMP can recover $\bar{\mathbf{x}}$ in s^* steps.

- Restricted Isometry Property (RIP)** -

$$\|\mathbf{A}_S^T \mathbf{A}_S - \mathbf{I}\|_2 \leq \delta_{|S|} \quad (\delta_s \leq M(s-1) \quad \forall s \geq 2)$$

$$\implies (1 - \delta_s) \|\mathbf{v}\|_2^2 \leq \|\mathbf{A}\mathbf{v}\|_2^2 \leq (1 + \delta_s) \|\mathbf{v}\|_2^2 \quad \forall \mathbf{v} \text{ s.t. } \|\mathbf{v}\|_0 \leq s.$$

- Null space property** -

$\forall S \in [d]$ s.t. $|S| \leq s$, if $\mathbf{v} \in \text{Null}(\mathbf{A}) \setminus \{\mathbf{0}\}$, then $\|\mathbf{v}_S\|_1 \leq \|\mathbf{v}_{S^c}\|_1$

$$\implies \{\mathbf{v} \in \mathbb{R}^d \mid \mathbf{A}\mathbf{v} = \mathbf{0}\} \cap \{\mathbf{v} \in \mathbb{R}^d \mid \|\mathbf{v}_{S^c}\|_1 \leq \|\mathbf{v}_S\|_1\} = \mathbf{0}$$

- Restricted Strong Convexity (RSC)** -

$$\|\mathbf{A}\mathbf{x} - \mathbf{A}\mathbf{z}\|_2^2 \geq \rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \quad \forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d \text{ s.t. } \|\mathbf{x} - \mathbf{z}\|_0 \leq s$$

Incoherence \implies RIP \implies Null space property \implies RSC

RSC is the weakest and the most popular assumption.

Assumptions of interest

Despite being NP hard, SLR is tractable under certain assumptions.

- Incoherence** -

If $\Sigma = \mathbf{A}^T \mathbf{A}$, then $\max_{i \neq j} |\Sigma_{ij}| \leq M$

If $M \leq \frac{1}{2s^*-1}$ and $\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} \implies \bar{\mathbf{x}}$ is unique sparsest solution, and OMP can recover $\bar{\mathbf{x}}$ in s^* steps.

- Restricted Isometry Property (RIP)** -

$$\|\mathbf{A}_S^T \mathbf{A}_S - \mathbf{I}\|_2 \leq \delta_{|S|} \quad (\delta_s \leq M(s-1) \quad \forall s \geq 2)$$

$$\implies (1 - \delta_s) \|\mathbf{v}\|_2^2 \leq \|\mathbf{A}\mathbf{v}\|_2^2 \leq (1 + \delta_s) \|\mathbf{v}\|_2^2 \quad \forall \mathbf{v} \text{ s.t. } \|\mathbf{v}\|_0 \leq s.$$

- Null space property** -

$\forall S \in [d]$ s.t. $|S| \leq s$, if $\mathbf{v} \in \text{Null}(\mathbf{A}) \setminus \{0\}$, then $\|\mathbf{v}_S\|_1 \leq \|\mathbf{v}_{S^c}\|_1$

$$\implies \{\mathbf{v} \in \mathbb{R}^d \mid \mathbf{A}\mathbf{v} = 0\} \cap \{\mathbf{v} \in \mathbb{R}^d \mid \|\mathbf{v}_{S^c}\|_1 \leq \|\mathbf{v}_S\|_1\} = \mathbf{0}$$

- Restricted Strong Convexity (RSC)** -

$$\|\mathbf{A}\mathbf{x} - \mathbf{A}\mathbf{z}\|_2^2 \geq \rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \quad \forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d \text{ s.t. } \|\mathbf{x} - \mathbf{z}\|_0 \leq s$$

Incoherence \implies RIP \implies Null space property \implies RSC

RSC is the weakest and the most popular assumption.

Assumptions of interest

Despite being NP hard, SLR is tractable under certain assumptions.

- Incoherence -**

If $\Sigma = \mathbf{A}^T \mathbf{A}$, then $\max_{i \neq j} |\Sigma_{ij}| \leq M$

If $M \leq \frac{1}{2s^*-1}$ and $\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} \implies \bar{\mathbf{x}}$ is unique sparsest solution, and OMP can recover $\bar{\mathbf{x}}$ in s^* steps.

- Restricted Isometry Property (RIP) -**

$$\|\mathbf{A}_S^T \mathbf{A}_S - \mathbf{I}\|_2 \leq \delta_{|S|} \quad (\delta_s \leq M(s-1) \quad \forall s \geq 2)$$

$$\implies (1 - \delta_s) \|\mathbf{v}\|_2^2 \leq \|\mathbf{A}\mathbf{v}\|_2^2 \leq (1 + \delta_s) \|\mathbf{v}\|_2^2 \quad \forall \mathbf{v} \text{ s.t. } \|\mathbf{v}\|_0 \leq s.$$

- Null space property -**

$\forall S \in [d]$ s.t. $|S| \leq s$, if $\mathbf{v} \in \text{Null}(\mathbf{A}) \setminus \{0\}$, then $\|\mathbf{v}_S\|_1 \leq \|\mathbf{v}_{S^c}\|_1$

$$\implies \{\mathbf{v} \in \mathbb{R}^d \mid \mathbf{A}\mathbf{v} = 0\} \cap \{\mathbf{v} \in \mathbb{R}^d \mid \|\mathbf{v}_{S^c}\|_1 \leq \|\mathbf{v}_S\|_1\} = \mathbf{0}$$

- Restricted Strong Convexity (RSC) -**

$$\|\mathbf{A}\mathbf{x} - \mathbf{A}\mathbf{z}\|_2^2 \geq \rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \quad \forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d \text{ s.t. } \|\mathbf{x} - \mathbf{z}\|_0 \leq s$$

Incoherence \implies RIP \implies Null space property \implies RSC

RSC is the weakest and the most popular assumption.

Assumptions of interest

Despite being NP hard, SLR is tractable under certain assumptions.

- Incoherence -**

If $\Sigma = \mathbf{A}^T \mathbf{A}$, then $\max_{i \neq j} |\Sigma_{ij}| \leq M$

If $M \leq \frac{1}{2s^*-1}$ and $\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} \implies \bar{\mathbf{x}}$ is unique sparsest solution, and OMP can recover $\bar{\mathbf{x}}$ in s^* steps.

- Restricted Isometry Property (RIP) -**

$$\|\mathbf{A}_S^T \mathbf{A}_S - \mathbf{I}\|_2 \leq \delta_{|S|} \quad (\delta_s \leq M(s-1) \quad \forall s \geq 2)$$

$$\implies (1 - \delta_s) \|\mathbf{v}\|_2^2 \leq \|\mathbf{A}\mathbf{v}\|_2^2 \leq (1 + \delta_s) \|\mathbf{v}\|_2^2 \quad \forall \mathbf{v} \text{ s.t. } \|\mathbf{v}\|_0 \leq s.$$

- Null space property -**

$\forall S \in [d]$ s.t. $|S| \leq s$, if $\mathbf{v} \in \text{Null}(\mathbf{A}) \setminus \{0\}$, then $\|\mathbf{v}_S\|_1 \leq \|\mathbf{v}_{S^c}\|_1$

$$\implies \{\mathbf{v} \in \mathbb{R}^d \mid \mathbf{A}\mathbf{v} = 0\} \cap \{\mathbf{v} \in \mathbb{R}^d \mid \|\mathbf{v}_{S^c}\|_1 \leq \|\mathbf{v}_S\|_1\} = \mathbf{0}$$

- Restricted Strong Convexity (RSC) -**

$$\|\mathbf{A}\mathbf{x} - \mathbf{A}\mathbf{z}\|_2^2 \geq \rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \quad \forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d \text{ s.t. } \|\mathbf{x} - \mathbf{z}\|_0 \leq s$$

Incoherence \implies RIP \implies Null space property \implies RSC

RSC is the weakest and the most popular assumption.

Goals of SLR

SLR can be modelled as

$$\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} + \boldsymbol{\eta} \quad (2.2)$$

where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, $\text{supp}(\bar{\mathbf{x}}) = \mathbf{S}^*$ and $|\mathbf{S}^*| = s^*$.

$$\implies \mathbf{y} = \mathbf{A}_{\mathbf{S}^*} \bar{\mathbf{x}}_{\mathbf{S}^*} + \boldsymbol{\eta} \quad (2.3)$$

Model with deterministic conditions on $\boldsymbol{\eta}$ can also be analyzed.

Goals of SLR

- **Bounding Generalization error** - Upper bound $G(\mathbf{x}) := \frac{1}{n} \|\mathbf{A}(\mathbf{x} - \bar{\mathbf{x}})\|_2^2$ where the rows of \mathbf{A} are i.i.d.
- **Support Recovery** - Recover the true features of \mathbf{A} , i.e., find a $\mathbf{S} \supseteq \mathbf{S}^*$.

Goals of SLR

SLR can be modelled as

$$\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} + \boldsymbol{\eta} \quad (2.2)$$

where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, $\text{supp}(\bar{\mathbf{x}}) = \mathbf{S}^*$ and $|\mathbf{S}^*| = s^*$.

$$\implies \mathbf{y} = \mathbf{A}_{\mathbf{S}^*} \bar{\mathbf{x}}_{\mathbf{S}^*} + \boldsymbol{\eta} \quad (2.3)$$

Model with deterministic conditions on $\boldsymbol{\eta}$ can also be analyzed.

Goals of SLR

- **Bounding Generalization error** - Upper bound $G(\mathbf{x}) := \frac{1}{n} \|\mathbf{A}(\mathbf{x} - \bar{\mathbf{x}})\|_2^2$ where the rows of \mathbf{A} are i.i.d.
- **Support Recovery** - Recover the true features of \mathbf{A} , i.e., find a $\mathbf{S} \supseteq \mathbf{S}^*$.

Goals of SLR

SLR can be modelled as

$$\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} + \boldsymbol{\eta} \quad (2.2)$$

where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, $\text{supp}(\bar{\mathbf{x}}) = \mathbf{S}^*$ and $|\mathbf{S}^*| = s^*$.

$$\implies \mathbf{y} = \mathbf{A}_{\mathbf{S}^*} \bar{\mathbf{x}}_{\mathbf{S}^*} + \boldsymbol{\eta} \quad (2.3)$$

Model with deterministic conditions on $\boldsymbol{\eta}$ can also be analyzed.

Goals of SLR

- ➊ **Bounding Generalization error** - Upper bound $G(\mathbf{x}) := \frac{1}{n} \|\mathbf{A}(\mathbf{x} - \bar{\mathbf{x}})\|_2^2$ where the rows of \mathbf{A} are i.i.d.
- ➋ **Support Recovery** - Recover the true features of \mathbf{A} , i.e., find a $\mathbf{S} \supseteq \mathbf{S}^*$.

Goals of SLR

SLR can be modelled as

$$\mathbf{y} = \mathbf{A}\bar{\mathbf{x}} + \boldsymbol{\eta} \quad (2.2)$$

where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, $\text{supp}(\bar{\mathbf{x}}) = \mathbf{S}^*$ and $|\mathbf{S}^*| = s^*$.

$$\implies \mathbf{y} = \mathbf{A}_{\mathbf{S}^*} \bar{\mathbf{x}}_{\mathbf{S}^*} + \boldsymbol{\eta} \quad (2.3)$$

Model with deterministic conditions on $\boldsymbol{\eta}$ can also be analyzed.

Goals of SLR

- 1 **Bounding Generalization error** - Upper bound $G(\mathbf{x}) := \frac{1}{n} \|\mathbf{A}(\mathbf{x} - \bar{\mathbf{x}})\|_2^2$ where the rows of \mathbf{A} are i.i.d.
- 2 **Support Recovery** - Recover the true features of \mathbf{A} , i.e., find a $\mathbf{S} \supseteq \mathbf{S}^*$.

Algorithms to solve SLR

The literature mainly studies 3 classes of algorithms

Existing SLR algorithms

- ℓ_1 minimization based (LASSO based). E.g. - Dantzig selector
- Non-convex penalty based. E.g. - IHT, SCAD penalty, Log-sum penalty
- Greedy methods. E.g. - Orthogonal Matching Pursuit (OMP)

We study SLR under RSC assumption for OMP algorithm.

Algorithms to solve SLR

The literature mainly studies 3 classes of algorithms

Existing SLR algorithms

- ℓ_1 minimization based (LASSO based). E.g. - Dantzig selector
- Non-convex penalty based. E.g. - IHT, SCAD penalty, Log-sum penalty
- Greedy methods. E.g. - Orthogonal Matching Pursuit (OMP)

We study SLR under RSC assumption for OMP algorithm.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \emptyset$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|(\mathbf{A}_{i_1, \mathbf{r}_{k-1}})| \quad |(\mathbf{A}_{i_2, \mathbf{r}_{k-1}})| \quad \dots \quad |(\mathbf{A}_{i_j, \mathbf{r}_{k-1}})| \quad \dots \quad |(\mathbf{A}_{i_{n-k+1}, \mathbf{r}_{k-1}})|]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[(\mathbf{A}_{i_1, S_{k-1}^c}, \mathbf{r}_{k-1}), (\mathbf{A}_{i_2, S_{k-1}^c}, \mathbf{r}_{k-1}), \dots, (\mathbf{A}_{i_j, S_{k-1}^c}, \mathbf{r}_{k-1}), \dots, (\mathbf{A}_{i_{n-k+1}, S_{k-1}^c}, \mathbf{r}_{k-1})]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \emptyset$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$\left[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle| \right]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \emptyset$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$\left[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle| \right]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $S_0 = \emptyset$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{S_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $S_k = S_{k-1} \cup \{i_j\}$.
- Fully optimize on S_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq S_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $\mathbf{S}_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{\mathbf{S}_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $\mathbf{S}_k = \mathbf{S}_{k-1} \cup \{i_j\}$.
- Fully optimize on \mathbf{S}_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq \mathbf{S}_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Set initial support set $\mathbf{S}_0 = \phi$ & $\mathbf{x}_0 = \mathbf{0}$.

\therefore residual $\mathbf{r}_0 = \mathbf{y} - \mathbf{A}\mathbf{x}_0 = \mathbf{y}$.

At k^{th} iteration ($k \geq 1$)

- From the left-over columns of \mathbf{A} (in $\mathbf{A}_{\mathbf{S}_{k-1}^c}$), find the column with maximum absolute inner product with \mathbf{r}_{k-1} .

$$[|\langle \mathbf{A}_{i_1}, \mathbf{r}_{k-1} \rangle| \quad |\langle \mathbf{A}_{i_2}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_j}, \mathbf{r}_{k-1} \rangle| \quad \dots \quad |\langle \mathbf{A}_{i_{d-k+1}}, \mathbf{r}_{k-1} \rangle|]$$

- Include i_j into the set: $\mathbf{S}_k = \mathbf{S}_{k-1} \cup \{i_j\}$.
- Fully optimize on \mathbf{S}_k : $\mathbf{x}_k = \arg \min_{\text{supp}(\mathbf{x}) \subseteq \mathbf{S}_k} \|\mathbf{y} - \mathbf{A}\mathbf{x}\|_2^2$ (Simple least squares).
- Update residual: $\mathbf{r}_k = \mathbf{y} - \mathbf{A}\mathbf{x}_k$.

Orthogonal Matching Pursuit for SLR

Result: OMP sparse estimate $\hat{\mathbf{x}}_s^{\text{OMP}} = \mathbf{x}_s$

$\mathbf{S}_0 = \emptyset, \mathbf{x}_0 = \mathbf{0}, \mathbf{r}_0 = \mathbf{y}$

for $k = 1, 2, \dots, s$ **do**

$j \leftarrow \arg \max_{i \notin \mathbf{S}_{k-1}} |\mathbf{A}_i^T \mathbf{r}_{k-1}|$ (Greedy selection)

$\mathbf{S}_k \leftarrow \mathbf{S}_{k-1} \cup \{j\}$

$\mathbf{x}_k \leftarrow \arg \min_{\text{supp}(\mathbf{x}) \subseteq \mathbf{S}_k} \|\mathbf{A}\mathbf{x} - \mathbf{y}\|_2^2$

$\mathbf{r}_k \leftarrow \mathbf{y} - \mathbf{A}\mathbf{x}_k$

end

Algorithm 1: Orthogonal Matching Pursuit (OMP) for SLR

Note that $\mathbf{A}_i^T \mathbf{r}_{k-1} \propto [\nabla f(\mathbf{x}_{k-1})]_i$ for $f(\mathbf{x}) = \|\mathbf{A}\mathbf{x} - \mathbf{y}\|_2^2$

Orthogonal Matching Pursuit for SLR

Result: OMP sparse estimate $\hat{\mathbf{x}}_s^{\text{OMP}} = \mathbf{x}_s$

$\mathbf{S}_0 = \emptyset, \mathbf{x}_0 = \mathbf{0}, \mathbf{r}_0 = \mathbf{y}$

for $k = 1, 2, \dots, s$ **do**

$j \leftarrow \arg \max_{i \notin \mathbf{S}_{k-1}} |\mathbf{A}_i^T \mathbf{r}_{k-1}|$ (Greedy selection)

$\mathbf{S}_k \leftarrow \mathbf{S}_{k-1} \cup \{j\}$

$\mathbf{x}_k \leftarrow \arg \min_{\text{supp}(\mathbf{x}) \subseteq \mathbf{S}_k} \|\mathbf{A}\mathbf{x} - \mathbf{y}\|_2^2$

$\mathbf{r}_k \leftarrow \mathbf{y} - \mathbf{A}\mathbf{x}_k$

end

Algorithm 1: Orthogonal Matching Pursuit (OMP) for SLR

Note that $\mathbf{A}_i^T \mathbf{r}_{k-1} \propto [\nabla f(\mathbf{x}_{k-1})]_i$ for $f(\mathbf{x}) = \|\mathbf{A}\mathbf{x} - \mathbf{y}\|_2^2$

Orthogonal Matching Pursuit for general $f(\mathbf{x})$

Result: OMP sparse estimate $\hat{\mathbf{x}}_s^{\text{OMP}} = \mathbf{x}_s$

$\mathbf{S}_0 = \emptyset, \mathbf{x}_0 = \mathbf{0}$

for $k = 1, 2, \dots, s$ **do**

$j := \arg \max_{i \notin \mathbf{S}_{k-1}} |[\nabla f(\mathbf{x}_{k-1})]_i|$

$\mathbf{S}_k := \mathbf{S}_{k-1} \cup \{j\}$

$\mathbf{x}_k := \arg \min_{\text{supp}(\mathbf{x}) \subseteq \mathbf{S}_k} f(\mathbf{x})$

end

Algorithm 2: OMP for a general function $f(\mathbf{x})$

Key quantities

- Restricted Smoothness (ρ^+) & Restricted Strong Convexity (ρ^-)

$$\rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \leq \|\mathbf{Ax} - \mathbf{Az}\|_2^2 \leq \rho_s^+ \|\mathbf{x} - \mathbf{z}\|_2^2 \quad (4.1)$$

$\forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d$ s.t. $\|\mathbf{x} - \mathbf{z}\|_0 \leq s$.

- Restricted condition number ($\tilde{\kappa}_s$)

$$\tilde{\kappa}_s = \frac{\rho_1^+}{\rho_s^-} \quad (4.2)$$

- We also define

$$\kappa_s = \frac{\rho_s^+}{\rho_s^-} \geq \tilde{\kappa}_s \quad (4.3)$$

Key quantities

- Restricted Smoothness (ρ^+) & Restricted Strong Convexity (ρ^-)

$$\rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \leq \|\mathbf{Ax} - \mathbf{Az}\|_2^2 \leq \rho_s^+ \|\mathbf{x} - \mathbf{z}\|_2^2 \quad (4.1)$$

$\forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d$ s.t. $\|\mathbf{x} - \mathbf{z}\|_0 \leq s$.

- Restricted condition number ($\tilde{\kappa}_s$)

$$\tilde{\kappa}_s = \frac{\rho_1^+}{\rho_s^-} \quad (4.2)$$

- We also define

$$\kappa_s = \frac{\rho_s^+}{\rho_s^-} \geq \tilde{\kappa}_s \quad (4.3)$$

Key quantities

- Restricted Smoothness (ρ^+) & Restricted Strong Convexity (ρ^-)

$$\rho_s^- \|\mathbf{x} - \mathbf{z}\|_2^2 \leq \|\mathbf{Ax} - \mathbf{Az}\|_2^2 \leq \rho_s^+ \|\mathbf{x} - \mathbf{z}\|_2^2 \quad (4.1)$$

$\forall \mathbf{x}, \mathbf{z} \in \mathbb{R}^d$ s.t. $\|\mathbf{x} - \mathbf{z}\|_0 \leq s$.

- Restricted condition number ($\tilde{\kappa}_s$)

$$\tilde{\kappa}_s = \frac{\rho_1^+}{\rho_s^-} \quad (4.2)$$

- We also define

$$\kappa_s = \frac{\rho_s^+}{\rho_s^-} \geq \tilde{\kappa}_s \quad (4.3)$$

Lower bounds for Fast rates

- If $\hat{\mathbf{x}}_{\ell_0}$ is the best ℓ_0 estimate in the set of s^* -sparse vectors then one can show

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\ell_0} - \bar{\mathbf{x}})\|_2^2 \right] \lesssim \frac{\sigma^2 s^*}{n} \quad (4.4)$$

- Non-tractable since computing $\hat{\mathbf{x}}_{\ell_0}$ involves searching all $\binom{d}{s^*}$ subsets.
- (Y. Zhang, Wainwright & Jordan'15) $\exists \mathbf{A} \in \mathbb{R}^{n \times d}$ s.t. any poly-time algorithm satisfies

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\text{poly}} - \bar{\mathbf{x}})\|_2^2 \right] \gtrsim \frac{\sigma^2 s^{*1-\delta} \tilde{\kappa}_{s^*}}{n} \quad \forall \delta > 0 \quad (4.5)$$

Consequence - Any estimator $\hat{\mathbf{x}}$ achieving fast rate must either **not be poly-time** or must return $\hat{\mathbf{x}}_{\text{poly}}$ that is **not** s^* -sparse.

\lesssim and \gtrsim are inequalities up to constant & poly-log d factors

Lower bounds for Fast rates

- If $\hat{\mathbf{x}}_{\ell_0}$ is the best ℓ_0 estimate in the set of s^* -sparse vectors then one can show

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\ell_0} - \bar{\mathbf{x}})\|_2^2 \right] \lesssim \frac{\sigma^2 s^*}{n} \quad (4.4)$$

- Non-tractable since computing $\hat{\mathbf{x}}_{\ell_0}$ involves searching all $\binom{d}{s^*}$ subsets.
- (Y. Zhang, Wainwright & Jordan'15) $\exists \mathbf{A} \in \mathbb{R}^{n \times d}$ s.t. any poly-time algorithm satisfies

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\text{poly}} - \bar{\mathbf{x}})\|_2^2 \right] \gtrsim \frac{\sigma^2 s^{*1-\delta} \tilde{\kappa}_{s^*}}{n} \quad \forall \delta > 0 \quad (4.5)$$

Consequence - Any estimator $\hat{\mathbf{x}}$ achieving fast rate must either **not be poly-time** or must return $\hat{\mathbf{x}}_{\text{poly}}$ that is **not** s^* -sparse.

\lesssim and \gtrsim are inequalities up to constant & poly-log d factors

Lower bounds for Fast rates

- If $\hat{\mathbf{x}}_{\ell_0}$ is the best ℓ_0 estimate in the set of s^* -sparse vectors then one can show

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\ell_0} - \bar{\mathbf{x}})\|_2^2 \right] \lesssim \frac{\sigma^2 s^*}{n} \quad (4.4)$$

- Non-tractable since computing $\hat{\mathbf{x}}_{\ell_0}$ involves searching all $\binom{d}{s^*}$ subsets.
- (Y. Zhang, Wainwright & Jordan'15) $\exists \mathbf{A} \in \mathbb{R}^{n \times d}$ s.t. any poly-time algorithm satisfies

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\text{poly}} - \bar{\mathbf{x}})\|_2^2 \right] \gtrsim \frac{\sigma^2 s^{*1-\delta} \tilde{\kappa}_{s^*}}{n} \quad \forall \delta > 0 \quad (4.5)$$

Consequence - Any estimator $\hat{\mathbf{x}}$ achieving fast rate must either **not be poly-time** or must return $\hat{\mathbf{x}}_{\text{poly}}$ that is **not** s^* -sparse.

\lesssim and \gtrsim are inequalities up to constant & poly-log d factors

Lower bounds for Fast rates

- If $\hat{\mathbf{x}}_{\ell_0}$ is the best ℓ_0 estimate in the set of s^* -sparse vectors then one can show

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\ell_0} - \bar{\mathbf{x}})\|_2^2 \right] \lesssim \frac{\sigma^2 s^*}{n} \quad (4.4)$$

- Non-tractable since computing $\hat{\mathbf{x}}_{\ell_0}$ involves searching all $\binom{d}{s^*}$ subsets.
- (Y. Zhang, Wainwright & Jordan'15) $\exists \mathbf{A} \in \mathbb{R}^{n \times d}$ s.t. any poly-time algorithm satisfies

$$\sup_{\|\bar{\mathbf{x}}\|_0 \leq s^*} \frac{1}{n} \mathbb{E} \left[\|\mathbf{A}(\hat{\mathbf{x}}_{\text{poly}} - \bar{\mathbf{x}})\|_2^2 \right] \gtrsim \frac{\sigma^2 s^{*1-\delta} \tilde{\kappa}_{s^*}}{n} \quad \forall \delta > 0 \quad (4.5)$$

Consequence - Any estimator $\hat{\mathbf{x}}$ achieving fast rate must either **not be poly-time** or must return $\hat{\mathbf{x}}_{\text{poly}}$ that is **not** s^* -sparse.

\lesssim and \gtrsim are inequalities up to constant & poly-log d factors

Upper bounds on Generalization error

- Tightest known upper bounds for poly-time algorithms like IHT, OMP and Lasso were at least $\tilde{\kappa}$ times worse than known lower bounds (Jain'14, T. Zhang'10, Y. Zhang'17).
- (T. Zhang'10) If $\hat{\mathbf{x}}_s$ be the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*}^2 \log \kappa_{s+s^*}. \quad (4.6)$$

- With slight modification to T. Zhang's analysis we get

Generalization error for OMP

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}. \quad (4.7)$$

Matches the fast rate lower bound up to log factors.

Upper bounds on Generalization error

- Tightest known upper bounds for poly-time algorithms like IHT, OMP and Lasso were at least $\tilde{\kappa}$ times worse than known lower bounds (Jain'14, T. Zhang'10, Y. Zhang'17).
- (T. Zhang'10) If $\hat{\mathbf{x}}_s$ be the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*}^2 \log \kappa_{s+s^*}. \quad (4.6)$$

- With slight modification to T. Zhang's analysis we get

Generalization error for OMP

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}. \quad (4.7)$$

Matches the fast rate lower bound up to log factors.

Upper bounds on Generalization error

- Tightest known upper bounds for poly-time algorithms like IHT, OMP and Lasso were at least $\tilde{\kappa}$ times worse than known lower bounds (Jain'14, T. Zhang'10, Y. Zhang'17).
- (T. Zhang'10) If $\hat{\mathbf{x}}_s$ be the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*}^2 \log \kappa_{s+s^*}. \quad (4.6)$$

- With slight modification to T. Zhang's analysis we get

Generalization error for OMP

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}. \quad (4.7)$$

Matches the fast rate lower bound up to log factors.

Upper bounds on Generalization error

- Tightest known upper bounds for poly-time algorithms like IHT, OMP and Lasso were at least $\tilde{\kappa}$ times worse than known lower bounds (Jain'14, T. Zhang'10, Y. Zhang'17).
- (T. Zhang'10) If $\hat{\mathbf{x}}_s$ be the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*}^2 \log \kappa_{s+s^*}. \quad (4.6)$$

- With slight modification to T. Zhang's analysis we get

Generalization error for OMP

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, then with high probability

$$\frac{1}{n} \|\mathbf{A}(\mathbf{x}_s - \bar{\mathbf{x}})\|_2^2 \lesssim \frac{1}{n} \sigma^2 s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}. \quad (4.7)$$

Matches the fast rate lower bound up to log factors.

Support Recovery upper bound

- Support recovery results are known for SCAD/MCP penalty based methods under bounded incoherence (Loh'14).
- For greedy algorithms like HTP and PHT, known support recovery results require poor dependence of $\tilde{\kappa}$ on $|\bar{x}_{\min}|$ (Shen'17).
- If S is the support set of the s^{th} OMP iterate \hat{x}_s , and if $S^* \setminus S \neq \emptyset$, then there is a **large additive decrease** in objective if $|\bar{x}_{\min}|$ is larger than the appropriate noise level.

Large decrease in objective

If \hat{x}_s is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations s.t. $S^* \setminus S \neq \emptyset$ and $|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$ then with high probability

$$\|\mathbf{A}\hat{x}_s - \mathbf{y}\|_2^2 - \|\mathbf{A}\hat{x}_{s+1} - \mathbf{y}\|_2^2 \gtrsim \sigma^2 \quad (4.8)$$

where $\left\| \mathbf{A}_{S^* \setminus S}^T \mathbf{A}_S (\mathbf{A}_S^T \mathbf{A}_S)^{-1} \right\|_{\infty} \leq \gamma$ and $S = \text{supp}(\hat{x}_s)$.

γ is similar to standard incoherence condition.

Support Recovery upper bound

- Support recovery results are known for SCAD/MCP penalty based methods under bounded incoherence (Loh'14).
- For greedy algorithms like HTP and PHT, known support recovery results require poor dependence of $\tilde{\kappa}$ on $|\bar{x}_{\min}|$ (Shen'17).
- If S is the support set of the s^{th} OMP iterate \hat{x}_s , and if $S^* \setminus S \neq \emptyset$, then there is a **large additive decrease** in objective if $|\bar{x}_{\min}|$ is larger than the appropriate noise level.

Large decrease in objective

If \hat{x}_s is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations s.t. $S^* \setminus S \neq \emptyset$ and $|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$ then with high probability

$$\|\mathbf{A}\hat{x}_s - \mathbf{y}\|_2^2 - \|\mathbf{A}\hat{x}_{s+1} - \mathbf{y}\|_2^2 \gtrsim \sigma^2 \quad (4.8)$$

where $\left\| \mathbf{A}_{S^* \setminus S}^T \mathbf{A}_S (\mathbf{A}_S^T \mathbf{A}_S)^{-1} \right\|_\infty \leq \gamma$ and $S = \text{supp}(\hat{x}_s)$.

γ is similar to standard incoherence condition.

Support Recovery upper bound

- Support recovery results are known for SCAD/MCP penalty based methods under bounded incoherence (Loh'14).
- For greedy algorithms like HTP and PHT, known support recovery results require poor dependence of $\tilde{\kappa}$ on $|\bar{x}_{\min}|$ (Shen'17).
- If S is the support set of the s^{th} OMP iterate \hat{x}_s , and if $S^* \setminus S \neq \emptyset$, then there is a **large additive decrease** in objective if $|\bar{x}_{\min}|$ is larger than the appropriate noise level.

Large decrease in objective

If \hat{x}_s is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations s.t. $S^* \setminus S \neq \emptyset$ and $|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$ then with high probability

$$\|\mathbf{A}\hat{x}_s - \mathbf{y}\|_2^2 - \|\mathbf{A}\hat{x}_{s+1} - \mathbf{y}\|_2^2 \gtrsim \sigma^2 \quad (4.8)$$

where $\left\| \mathbf{A}_{S^* \setminus S}^T \mathbf{A}_S (\mathbf{A}_S^T \mathbf{A}_S)^{-1} \right\|_\infty \leq \gamma$ and $S = \text{supp}(\hat{x}_s)$.

γ is similar to standard incoherence condition.

Support Recovery upper bound

- Support recovery results are known for SCAD/MCP penalty based methods under bounded incoherence (Loh'14).
- For greedy algorithms like HTP and PHT, known support recovery results require poor dependence of $\tilde{\kappa}$ on $|\bar{x}_{\min}|$ (Shen'17).
- If S is the support set of the s^{th} OMP iterate \hat{x}_s , and if $S^* \setminus S \neq \emptyset$, then there is a **large additive decrease** in objective if $|\bar{x}_{\min}|$ is larger than the appropriate noise level.

Large decrease in objective

If \hat{x}_s is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations s.t. $S^* \setminus S \neq \emptyset$ and $|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$ then with high probability

$$\|\mathbf{A}\hat{x}_s - \mathbf{y}\|_2^2 - \|\mathbf{A}\hat{x}_{s+1} - \mathbf{y}\|_2^2 \gtrsim \sigma^2 \quad (4.8)$$

where $\left\| \mathbf{A}_{S^* \setminus S}^T \mathbf{A}_S (\mathbf{A}_S^T \mathbf{A}_S)^{-1} \right\|_{\infty} \leq \gamma$ and $S = \text{supp}(\hat{x}_s)$.

γ is similar to standard incoherence condition.

Support Recovery upper bound

- Support recovery results are known for SCAD/MCP penalty based methods under bounded incoherence (Loh'14).
- For greedy algorithms like HTP and PHT, known support recovery results require poor dependence of $\tilde{\kappa}$ on $|\bar{x}_{\min}|$ (Shen'17).
- If S is the support set of the s^{th} OMP iterate \hat{x}_s , and if $S^* \setminus S \neq \emptyset$, then there is a **large additive decrease** in objective if $|\bar{x}_{\min}|$ is larger than the appropriate noise level.

Large decrease in objective

If \hat{x}_s is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations s.t. $S^* \setminus S \neq \emptyset$ and $|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$ then with high probability

$$\|\mathbf{A}\hat{x}_s - \mathbf{y}\|_2^2 - \|\mathbf{A}\hat{x}_{s+1} - \mathbf{y}\|_2^2 \gtrsim \sigma^2 \quad (4.8)$$

where $\left\| \mathbf{A}_{S^* \setminus S}^T \mathbf{A}_S (\mathbf{A}_S^T \mathbf{A}_S)^{-1} \right\|_{\infty} \leq \gamma$ and $S = \text{supp}(\hat{x}_s)$.

γ is similar to standard incoherence condition.

Support Recovery upper bound

Since $\|\mathbf{Ax} - \mathbf{y}\|_2^2 \geq 0 \ \forall \mathbf{x} \in \mathbb{R}^d$, the number of extra iterations cannot be too large.

Support recovery and infinity norm bound

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, s.t.

$|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$, then with high probability

$$1 \quad \mathbf{S}^* \subseteq \text{supp}(\hat{\mathbf{x}}_s)$$

$$2 \quad \|\hat{\mathbf{x}}_s - \bar{\mathbf{x}}\|_\infty \lesssim \sigma \sqrt{\frac{\log s}{\rho_s^-}}$$

where $\left\| \mathbf{A}_{\mathbf{S}^* \setminus \mathbf{S}}^T \mathbf{A}_{\mathbf{S}} (\mathbf{A}_{\mathbf{S}}^T \mathbf{A}_{\mathbf{S}})^{-1} \right\|_\infty \leq \gamma$ and $\mathbf{S} = \text{supp}(\hat{\mathbf{x}}_s)$.

- Condition on $|\bar{x}_{\min}|$ scales as $\frac{1}{\sqrt{n}}$ since both $\rho_{s+s^*}^-$ and ρ_1^+ have a factor of n . Also it is better by at-least $\sqrt{\tilde{\kappa}}$ than that in other recent works.
- γ is allowed to be very large.

Support Recovery upper bound

Since $\|\mathbf{Ax} - \mathbf{y}\|_2^2 \geq 0 \quad \forall \mathbf{x} \in \mathbb{R}^d$, the number of extra iterations cannot be too large.

Support recovery and infinity norm bound

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, s.t.

$|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$, then with high probability

$$\textcircled{1} \quad \mathbf{S}^* \subseteq \text{supp}(\hat{\mathbf{x}}_s)$$

$$\textcircled{2} \quad \|\hat{\mathbf{x}}_s - \bar{\mathbf{x}}\|_\infty \lesssim \sigma \sqrt{\frac{\log s}{\rho_s^-}}$$

where $\left\| \mathbf{A}_{\mathbf{S}^* \setminus \mathbf{S}}^T \mathbf{A}_{\mathbf{S}} (\mathbf{A}_{\mathbf{S}}^T \mathbf{A}_{\mathbf{S}})^{-1} \right\|_\infty \leq \gamma$ and $\mathbf{S} = \text{supp}(\hat{\mathbf{x}}_s)$.

- Condition on $|\bar{x}_{\min}|$ scales as $\frac{1}{\sqrt{n}}$ since both $\rho_{s+s^*}^-$ and ρ_1^+ have a factor of n . Also it is better by at-least $\sqrt{\tilde{\kappa}}$ than that in other recent works.
- γ is allowed to be very large.

Support Recovery upper bound

Since $\|\mathbf{Ax} - \mathbf{y}\|_2^2 \geq 0 \quad \forall \mathbf{x} \in \mathbb{R}^d$, the number of extra iterations cannot be too large.

Support recovery and infinity norm bound

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, s.t.

$|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$, then with high probability

$$\textcircled{1} \quad \mathbf{S}^* \subseteq \text{supp}(\hat{\mathbf{x}}_s)$$

$$\textcircled{2} \quad \|\hat{\mathbf{x}}_s - \bar{\mathbf{x}}\|_\infty \lesssim \sigma \sqrt{\frac{\log s}{\rho_s^-}}$$

where $\left\| \mathbf{A}_{\mathbf{S}^* \setminus \mathbf{S}}^T \mathbf{A}_{\mathbf{S}} (\mathbf{A}_{\mathbf{S}}^T \mathbf{A}_{\mathbf{S}})^{-1} \right\|_\infty \leq \gamma$ and $\mathbf{S} = \text{supp}(\hat{\mathbf{x}}_s)$.

- Condition on $|\bar{x}_{\min}|$ scales as $\frac{1}{\sqrt{n}}$ since both $\rho_{s+s^*}^-$ and ρ_1^+ have a factor of n . Also it is better by at-least $\sqrt{\tilde{\kappa}}$ than that in other recent works.
- γ is allowed to be very large.

Support Recovery upper bound

Since $\|\mathbf{Ax} - \mathbf{y}\|_2^2 \geq 0 \quad \forall \mathbf{x} \in \mathbb{R}^d$, the number of extra iterations cannot be too large.

Support recovery and infinity norm bound

If $\hat{\mathbf{x}}_s$ is the output of OMP after $s \gtrsim s^* \tilde{\kappa}_{s+s^*} \log \kappa_{s+s^*}$ iterations, s.t.

$|\bar{x}_{\min}| \gtrsim \frac{\sigma \gamma \sqrt{\rho_1^+}}{\rho_{s+s^*}^-}$, then with high probability

$$\textcircled{1} \quad \mathbf{S}^* \subseteq \text{supp}(\hat{\mathbf{x}}_s)$$

$$\textcircled{2} \quad \|\hat{\mathbf{x}}_s - \bar{\mathbf{x}}\|_\infty \lesssim \sigma \sqrt{\frac{\log s}{\rho_s^-}}$$

where $\left\| \mathbf{A}_{\mathbf{S}^* \setminus \mathbf{S}}^T \mathbf{A}_{\mathbf{S}} (\mathbf{A}_{\mathbf{S}}^T \mathbf{A}_{\mathbf{S}})^{-1} \right\|_\infty \leq \gamma$ and $\mathbf{S} = \text{supp}(\hat{\mathbf{x}}_s)$.

- Condition on $|\bar{x}_{\min}|$ scales as $\frac{1}{\sqrt{n}}$ since both $\rho_{s+s^*}^-$ and ρ_1^+ have a factor of n . Also it is better by at-least $\sqrt{\tilde{\kappa}}$ than that in other recent works.
- γ is allowed to be very large.

Lower bound instance construction

- (Y. Zhang'15)'s lower bounds were for algorithms that output s^* -sparse solutions which does not apply for OMP when it is run for more than s^* iterations.
- We provide matching lower bounds for Support recovery as well as generalization error for OMP.
- Fool OMP into picking incorrect indexes. Large support size \implies large generalization error.
- Construct an evenly distributed $\bar{\mathbf{x}}$

$$\bar{x}_i = \begin{cases} \frac{1}{\sqrt{s^*}} & \text{if } 1 \leq i \leq s^* \\ 0 & \text{if } i > s^* \end{cases} \implies \text{supp}(\bar{\mathbf{x}}) = \{1, 2, \dots, s^*\}$$

- Construct $\mathbf{M}^{(\epsilon)} \in \mathbb{R}^{n \times d}$ parameterized by ϵ
 - $\mathbf{M}_{1:s^*}^{(\epsilon)}$ are random s^* orthogonal column vectors s.t. $\|\mathbf{M}_i^{(\epsilon)}\|_2^2 = n \ \forall i \in [s^*]$.
 - $\mathbf{M}_i^{(\epsilon)} = \sqrt{1-\epsilon} \left[\frac{1}{\sqrt{s^*}} \sum_{j=1}^{s^*} \mathbf{M}_j^{(\epsilon)} \right] + \sqrt{\epsilon} \mathbf{g}_i \ \forall i \notin [s^*]$ where \mathbf{g}_i 's are orthogonal to each other and $\mathbf{M}_{1:s^*}^{(\epsilon)}$ with $\|\mathbf{g}_i\|_2^2 = n$.

Lower bound instance construction

- (Y. Zhang'15)'s lower bounds were for algorithms that output s^* -sparse solutions which does not apply for OMP when it is run for more than s^* iterations.
- We provide matching lower bounds for Support recovery as well as generalization error for OMP.
- Fool OMP into picking incorrect indexes. Large support size \implies large generalization error.
- Construct an evenly distributed \bar{x}

$$\bar{x}_i = \begin{cases} \frac{1}{\sqrt{s^*}} & \text{if } 1 \leq i \leq s^* \\ 0 & \text{if } i > s^* \end{cases} \implies \text{supp}(\bar{x}) = \{1, 2, \dots, s^*\}$$

- Construct $M^{(\epsilon)} \in \mathbb{R}^{n \times d}$ parameterized by ϵ
 - $M_{1:s^*}^{(\epsilon)}$ are random s^* orthogonal column vectors s.t. $\|M_i^{(\epsilon)}\|_2^2 = n \ \forall i \in [s^*]$.
 - $M_i^{(\epsilon)} = \sqrt{1-\epsilon} \left[\frac{1}{\sqrt{s^*}} \sum_{j=1}^{s^*} M_j^{(\epsilon)} \right] + \sqrt{\epsilon} g_i \ \forall i \notin [s^*]$ where g_i 's are orthogonal to each other and $M_{1:s^*}^{(\epsilon)}$ with $\|g_i\|_2^2 = n$.

Lower bound instance construction

- (Y. Zhang'15)'s lower bounds were for algorithms that output s^* -sparse solutions which does not apply for OMP when it is run for more than s^* iterations.
- We provide matching lower bounds for Support recovery as well as generalization error for OMP.
- Fool OMP into picking incorrect indexes. Large support size \implies large generalization error.
- Construct an evenly distributed \bar{x}

$$\bar{x}_i = \begin{cases} \frac{1}{\sqrt{s^*}} & \text{if } 1 \leq i \leq s^* \\ 0 & \text{if } i > s^* \end{cases} \implies \text{supp}(\bar{x}) = \{1, 2, \dots, s^*\}$$

- Construct $M^{(\epsilon)} \in \mathbb{R}^{n \times d}$ parameterized by ϵ
 - $M_{1:s^*}^{(\epsilon)}$ are random s^* orthogonal column vectors s.t. $\|M_i^{(\epsilon)}\|_2^2 = n \ \forall i \in [s^*]$.
 - $M_i^{(\epsilon)} = \sqrt{1-\epsilon} \left[\frac{1}{\sqrt{s^*}} \sum_{j=1}^{s^*} M_j^{(\epsilon)} \right] + \sqrt{\epsilon} g_i \ \forall i \notin [s^*]$ where g_i 's are orthogonal to each other and $M_{1:s^*}^{(\epsilon)}$ with $\|g_i\|_2^2 = n$.

Lower bound instance construction

- (Y. Zhang'15)'s lower bounds were for algorithms that output s^* -sparse solutions which does not apply for OMP when it is run for more than s^* iterations.
- We provide matching lower bounds for Support recovery as well as generalization error for OMP.
- Fool OMP into picking incorrect indexes. Large support size \implies large generalization error.
- Construct an evenly distributed \bar{x}

$$\bar{x}_i = \begin{cases} \frac{1}{\sqrt{s^*}} & \text{if } 1 \leq i \leq s^* \\ 0 & \text{if } i > s^* \end{cases} \implies \text{supp}(\bar{x}) = \{1, 2, \dots, s^*\}$$

- Construct $M^{(\epsilon)} \in \mathbb{R}^{n \times d}$ parameterized by ϵ
 - $M_{1:s^*}^{(\epsilon)}$ are random s^* orthogonal column vectors s.t. $\|M_i^{(\epsilon)}\|_2^2 = n \ \forall i \in [s^*]$.
 - $M_i^{(\epsilon)} = \sqrt{1-\epsilon} \left[\frac{1}{\sqrt{s^*}} \sum_{j=1}^{s^*} M_j^{(\epsilon)} \right] + \sqrt{\epsilon} g_i \ \forall i \notin [s^*]$ where g_i 's are orthogonal to each other and $M_{1:s^*}^{(\epsilon)}$ with $\|g_i\|_2^2 = n$.


Lower bound instance construction

- (Y. Zhang'15)'s lower bounds were for algorithms that output s^* -sparse solutions which does not apply for OMP when it is run for more than s^* iterations.
- We provide matching lower bounds for Support recovery as well as generalization error for OMP.
- Fool OMP into picking incorrect indexes. Large support size \implies large generalization error.
- Construct an evenly distributed \bar{x}

$$\bar{x}_i = \begin{cases} \frac{1}{\sqrt{s^*}} & \text{if } 1 \leq i \leq s^* \\ 0 & \text{if } i > s^* \end{cases} \implies \text{supp}(\bar{x}) = \{1, 2, \dots, s^*\}$$

- Construct $\mathbf{M}^{(\epsilon)} \in \mathbb{R}^{n \times d}$ parameterized by ϵ
 - $\mathbf{M}_{1:s^*}^{(\epsilon)}$ are random s^* orthogonal column vectors s.t. $\|\mathbf{M}_i^{(\epsilon)}\|_2^2 = n \ \forall i \in [s^*]$.
 - $\mathbf{M}_i^{(\epsilon)} = \sqrt{1-\epsilon} \left[\frac{1}{\sqrt{s^*}} \sum_{j=1}^{s^*} \mathbf{M}_j^{(\epsilon)} \right] + \sqrt{\epsilon} \mathbf{g}_i \ \forall i \notin [s^*]$ where \mathbf{g}_i 's are orthogonal to each other and $\mathbf{M}_{1:s^*}^{(\epsilon)}$ with $\|\mathbf{g}_i\|_2^2 = n$.

Lower bound instance construction




Visualizing in $d = 3$ with

- $s^* = 2$

- $\epsilon = 0.25$


Lower bound instance construction



Visualizing in $d = 3$ with

- $s^* = 2$
- $\epsilon = 0.25$


Lower bound instance construction




Visualizing in $d = 3$ with

- $s^* = 2$
- $\epsilon = 0.25$


Lower bound instance construction



Lower bound instance construction




Lower bound instance construction




Visualizing in $d = 3$ with

- $s^* = 2$
- $\epsilon = 0.25$

Lower bound instance construction



Lower bound instance construction



Visualizing in $d = 3$ with

- $s^* = 2$
- $\epsilon = 0.25$

Smaller $\epsilon \implies$ more correlation.
 $\therefore \epsilon$ is a proxy for $\tilde{\kappa}_s$.

Lower bounds

Noiseless case

For $s^* \leq d \leq n$, $\exists \epsilon > 0$ s.t. when OMP is executed on SLR problem with $y = \mathbf{M}^{(\epsilon)} \bar{\mathbf{x}}$ for $s \leq d - s^*$ iterations

- $\tilde{\kappa}_s(\mathbf{M}^{(\epsilon)}) \lesssim \frac{s}{s^*}$ and $\gamma \leq \sqrt{\frac{2}{3}}$
- $\mathbf{S}^* \cap \text{supp}(\hat{\mathbf{x}}_s) = \emptyset$

Noisy case

For $s^* \leq s \leq d^{1-\alpha}$ where $\alpha \in (0, 1)$, $\exists \epsilon > 0$ s.t. when OMP is executed on SLR problem with $y = \mathbf{M}^{(\epsilon)} \bar{\mathbf{x}} + \boldsymbol{\eta}$ where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, then

- $\tilde{\kappa}_s(\mathbf{M}^{(\epsilon)}) \lesssim \frac{s}{s^*}$ and $\gamma \leq \frac{1}{2}$
- with high probability $\frac{1}{n} \|\mathbf{A} \hat{\mathbf{x}}_s - \mathbf{A} \bar{\mathbf{x}}\|_2^2 \gtrsim \frac{1}{n} \sigma^2 \tilde{\kappa}_{s+s^*} s^*$
- with high probability $\mathbf{S}^* \cap \text{supp}(\hat{\mathbf{x}}_s) = \emptyset$

$\implies s \gtrsim \tilde{\kappa}_s s^*$ iterations are indeed necessary.

Addition of noise can only help.

Lower bounds

Noiseless case

For $s^* \leq d \leq n$, $\exists \epsilon > 0$ s.t. when OMP is executed on SLR problem with $y = \mathbf{M}^{(\epsilon)} \bar{\mathbf{x}}$ for $s \leq d - s^*$ iterations

- $\tilde{\kappa}_s(\mathbf{M}^{(\epsilon)}) \lesssim \frac{s}{s^*}$ and $\gamma \leq \sqrt{\frac{2}{3}}$
- $\mathbf{S}^* \cap \text{supp}(\hat{\mathbf{x}}_s) = \emptyset$

Noisy case

For $s^* \leq s \leq d^{1-\alpha}$ where $\alpha \in (0, 1)$, $\exists \epsilon > 0$ s.t. when OMP is executed on SLR problem with $y = \mathbf{M}^{(\epsilon)} \bar{\mathbf{x}} + \boldsymbol{\eta}$ where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, then

- $\tilde{\kappa}_s(\mathbf{M}^{(\epsilon)}) \lesssim \frac{s}{s^*}$ and $\gamma \leq \frac{1}{2}$
- with high probability $\frac{1}{n} \|\mathbf{A} \hat{\mathbf{x}}_s - \mathbf{A} \bar{\mathbf{x}}\|_2^2 \gtrsim \frac{1}{n} \sigma^2 \tilde{\kappa}_{s+s^*} s^*$
- with high probability $\mathbf{S}^* \cap \text{supp}(\hat{\mathbf{x}}_s) = \emptyset$

$\implies s \gtrsim \tilde{\kappa}_s s^*$ iterations are indeed necessary.

Addition of noise can only help.

Lower bounds

Noiseless case

For $s^* \leq d \leq n$, $\exists \epsilon > 0$ s.t. when OMP is executed on SLR problem with $y = \mathbf{M}^{(\epsilon)} \bar{\mathbf{x}}$ for $s \leq d - s^*$ iterations

- $\tilde{\kappa}_s(\mathbf{M}^{(\epsilon)}) \lesssim \frac{s}{s^*}$ and $\gamma \leq \sqrt{\frac{2}{3}}$
- $\mathbf{S}^* \cap \text{supp}(\hat{\mathbf{x}}_s) = \emptyset$

Noisy case

For $s^* \leq s \leq d^{1-\alpha}$ where $\alpha \in (0, 1)$, $\exists \epsilon > 0$ s.t. when OMP is executed on SLR problem with $y = \mathbf{M}^{(\epsilon)} \bar{\mathbf{x}} + \boldsymbol{\eta}$ where $\boldsymbol{\eta} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_{n \times n})$, then

- $\tilde{\kappa}_s(\mathbf{M}^{(\epsilon)}) \lesssim \frac{s}{s^*}$ and $\gamma \leq \frac{1}{2}$
- with high probability $\frac{1}{n} \|\mathbf{A} \hat{\mathbf{x}}_s - \mathbf{A} \bar{\mathbf{x}}\|_2^2 \gtrsim \frac{1}{n} \sigma^2 \tilde{\kappa}_{s+s^*} s^*$
- with high probability $\mathbf{S}^* \cap \text{supp}(\hat{\mathbf{x}}_s) = \emptyset$


$\implies s \gtrsim \tilde{\kappa}_s s^*$ iterations are indeed necessary.

Addition of noise can only help.


Simulations

We perform simulations on the lower bound instance class.

$\mathbf{M}^{(\epsilon)} \in \mathbb{R}^{1000 \times 100}$ and $s^* = 10$.



(a) Varying condition number



(b) Varying noise variance

Figure: Number of iterations required for recovering the full support of $\bar{\mathbf{x}}$ with respect to the restricted condition number ($\tilde{\kappa}_{s+s^*}$) of design matrix and the variance of noise (σ^2).