University of KwaZulu-Natal (Howard College)

MASTERS THESIS

Discrete Energy Minimisation Optimisation using Graph Cuts for Fluorescence Microscopy

Author:
Ryan NAIDOO

Supervisor: Dr. Jules-Raymond TAPAMO

A thesis submitted in fulfillment of the requirements for the degree of Master of Science in Engineering

in the

Department of Electrical, Electronic and Computer Engineering School of Engineering

September 19, 2016

Declaration of Authorship

I, Ryan NAIDOO, declare that this thesis titled, "Discrete Energy Minimisation Optimisation using Graph Cuts for Fluorescence Microscopy" and the work presented in it are my own. I confirm that:

- This work was done wholly or mainly while in candidature for a research degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this University or any other institution, this has been clearly stated.
- Where I have consulted the published work of others, this is always clearly attributed.
- Where I have quoted from the work of others, the source is always given. With the exception of such quotations, this thesis is entirely my own work.
- I have acknowledged all main sources of help.
- Where the thesis is based on work done by myself jointly with others, I have made clear exactly what was done by others and what I have contributed myself.

Signea:		
Date:		

"Thanks to my solid academic training, today I can write hundreds of words on virtually any topic without possessing a shred of information, which is how I got a good job in journalism."

Dave Barry

UNIVERSITY OF KWAZULU-NATAL (HOWARD COLLEGE)

Abstract

Faculty of Engineering School of Engineering

Master of Science in Engineering

Discrete Energy Minimisation Optimisation using Graph Cuts for Fluorescence Microscopy

by Ryan NAIDOO

The Thesis Abstract is written here (and usually kept to just this page). The page is kept centered vertically so can expand into the blank space above the title too...

Acknowledgements

The acknowledgments and the people to thank go here, don't forget to include your project advisor...

Contents

D	eclara	ation of Authorship	iii
A	bstrac	et	vii
A	cknov	wledgements	ix
Li	st of]	Figures	xiii
Li	st of	Tables	xv
Li	st of .	Abbreviations	xix
Pł	nysica	al Constants	xxi
Li	st of	Symbols	xiii
1	Intro 1.1 1.2	oduction Outline and Contributions	1 1 1
2	2.1 2.2 2.3 2.4	Physics of Fluorescence	3 3 5 6 8 8 12 14
3	Mat 3.1 3.2 3.3	Labelling Problems MAP Estimation for Discrete Models 3.2.1 Random Fields 3.2.2 Markov Random Fields 3.2.3 Conditional Random Fields 3.2.4 CRFs for Image Segmentation 3.2.5 MAP-MRF Estimation Graph Cuts 3.3.1 Network Theory and the Min-cut Problem 3.3.2 Image Segmentation Framework/Graph Construction Images Energy Minimisation	17 18 19 19 19 19 19 19 19 23 23
	3.4	Energy Minimisation	2

R	Inte	odusti	on to Graph Theory	35
A	Pro	of of M	aximum Flow - Minimum Cut Equivalence	33
5	Cor	clusio	n and Future Work	31
	4.4	Contr	ast Enhancement	29
		4.3.1	Total-Variation Denoising	29
	4.3	Poisso	on Denoising	29
		4.2.2	Coherence Enhancing Diffusion with Optimised Rotational Invariance .	29
		4.2.1	Coherence Enhancing Diffusion	29
	4.2	Aniso	otropic Diffusion	29
	4.1	Remo	val of Artifacts using Connected Components	29
4	Pre	-Proces	sing and Post-Processing Scheme for Fluorescence Microscopy Images	29
			Push-Relabel Speed Optimisation Heuristics	27
			Push-Relabel	24
			Dinic/Edmond-Karp	
			Ford-Fulkerson	
		3.4.3	Energy Minimisation Algorithms	23
		3.4.2	Submodular Functions	

List of Figures

2.1	(a) Simplified fluorescence process. (b) The Jabłoński diagram depicting the	
	electronics states from photon absorption to photo emission	4
2.2	Normalised Excitation and Emmision Spectra of the Alexa Fluor 532 flurophore.	
	The emmission maximum is at $553nm$ which is a more yellow-green than exci-	
	tation maximum at 5534nm. Data obtained from ThermoFisher Scientific [13].	5
	https://www.thermofisher.com/us/en/home/life-science/cell-ar	nalysis/
	labeling-chemistry/fluorescence-spectraviewer.html	
2.3	(a) FISH (Fluorescent 'in-situ' Hybridization) in mouse chromosomes using a	
	BAC clone labeled with Spectrum Orange. The picture shows two metaphases	
	and one interphase with two signals in each exampling a homozygous mouse	
	for a transgenic clone. Image Source: "All About the Human Genome Project"	
	Genetic and Genomic Image and Illustration Database. (b) p53 Binding Protein	
	1 (53BP1) was detected in perfusion fixed frozen sections of rat kidney using	
	Goat Anti-Human 53BP1 Antigen Affinity-purified Polyclonal Antibody (Cat-	
	alog # AF1877) at 15 μ g/mL overnight at 4°C. Tissue was stained using the	
	NorthernLights TM 557-conjugated Anti-Goat IgG Secondary Antibody (red; Cat-	
	alog # NL001) and counterstained with DAPI (blue). Specific staining was lo-	
	calized to nuclei of epithelial cells in convoluted tubules. Image Source: R&D	
	Systems' IHC image database	7
	https://unlockinglifescode.org/media/images/	
	https://www.rndsystems.com/resources/ihc-images/53bp1	
2.4	The schematic of the epifluorescence microscope	7
2.5	The effect of nonuniform illumination on segmentation. (a) Original image. Im-	
	age source: The Cell Image Library [30]. (b) Nonuniformly illuminated image.	
	The Vignette effect. (c) K-means clustering using the Euclidean distance metric	
	and 2 clusters. The blue curve is from the original, the red curve is from the	
	nonuniformly illuminated image. Notice that less of the object is recognised	
	towards the edges	9
	http://www.cellimagelibrary.org/images/2173	
2.6	The effect of photobleaching. Image Source: Molecular Expressions [32]. (a)	
	Original image at $t=0s$. (b) Image after $t=10s$. (c) Image after $t=20s$	10
2.7	The image formation process. Image source: [34]	11
2.8	The effect of noise on segmentation. (a) Original image. (b) Poisson noise cor-	
	rupted image. (c) ACWE Chan-Vese segmentated output. The red curve is from	
	the original, the green curve is from the Poisson noise corrupted image. Notice	
	that there are more artifacts and the segmented output is less accurate especially	40
	towards the bottom left from the green curve	12
3.1	Network N with no flow. The in-degree and out-degree for the source, s, and	
	the sink, t , are shown next to the corresponding node	19

3.2	Network N with flow. The flow out of the source node, s , is equal to the flow into the sink node, t . For all other nodes, the flow-in is equal to the flow-out. This is the conservation of flow principle. This is only part of the network. The	
	remaining part is the residual graph which shows the amount of reverse flow is available on an edge	20
3.3	Network N with with a valid cut C . The nodes within the red region are reach-	20
	able from the source and the nodes within the blue region are able to reach the sink. The cut set, C , is show in the orange filled block	21
3.4	Network N with with a invalid cut C . The cut does not partition source node s and sink node t into distinct sets.	21
3.5	Network N with with a invalid cut C . The cut partition partitions the graph into more than two sets and the cut intersects the edges ab and ad twice	22
3.6	Network N with maximum flow. There is no way to push more flow out of the source into the sink without breaking the rules for conservation of flow	22
3.7	Network N with minimal cut C . The sum of the capacity of all the edges in the cut set is the minimum of all possible valid cuts on the network N	23
B.1	Undirected weighted graph G . The degree of each node is shown next to the corresponding node. The graph is simple. The red box shows the vertex set, V_G ,	
B.2	and edge set, E_G , and their corresponding norm	36
	the vertex set, V_D , and edge set, E_D , and their corresponding norm	37
B.3	Undirected weighted graph H is a subgraph of G in Figure XX, $\mathbf{H} \subseteq \mathbf{G}$. Directed weighted graph I is a subgraph of D in Figure XX, $\mathbf{I} \subseteq \mathbf{D}$. The degree of each	
	node is shown next to the corresponding node. The red box shows the vertex	38
B.4	set, the edge set and their corresponding norms	38
B.5	Network N with no flow. The in-degree and out-degree for the source, s , and	
B.6	the sink, t , are shown next to the corresponding node	39
	into the sink node, t . For all other nodes, the flow-in is equal to the flow-out. This is the conservation of flow principle. This is only part of the network. The remaining part is the residual graph which shows the amount of reverse flow is	
	available on an edge	39
B.7	Network N with with a valid cut C . The nodes within the red region are reach-	
	able from the source and the nodes within the blue region are able to reach the sink. The cut set, C , is show in the orange filled block	40
B.8	Network N with with a invalid cut C . The cut does not partition source node s	40
2.0	and sink node t into distinct sets	40
B.9	Network N with with a invalid cut C . The cut partition partitions the graph into	
	more than two sets and the cut intersects the edges ab and ad twice	41
B.10	Network N with maximum flow. There is no way to push more flow out of the	4.4
D 11	source into the sink without breaking the rules for conservation of flow Network N with minimal cut C. The sum of the capacity of all the edges in the	41
D.11	Network N with minimal cut C . The sum of the capacity of all the edges in the cut set is the minimum of all possible valid cuts on the network N	42

List of Tables

3.1	The impact of the number of cites and labels on the solution space	18
-----	--	----

List of Algorithms

1	Euclid's algorithm	24
2	Push Operation	26
3	Relabel Operation	26
4	Push-Relabel Main-loop	27

List of Abbreviations

ACWE Active Contours Without Edges

AOD Average Optical DensityBCC Boundary Chain Code

CED Coherence Enhancing Diffusion

CCD Charge-Coupled Device

CLSM Confocal Laser Scanning Microscopy

CRF Conditional Random Field
DCC Differential Chain Code
DNA Deoxyribonucleic Acid
DP Dynamic Programming
DT Delaunay Triangulation

EGFP Enhanced Green Fluorescent Protein

EM Expectation Maximisation

FCS Fluorenscence Correlation Spectroscopy

FIFO First-In First-Out

FISH Fluorenscence in-situ Hybridisation

FLIM Fluorenscence Lifetime Imaging Microscopy
FRAP Fluorenscence Recovery After Photobleaching
FRET Fluorenscence Resonance Energy Transfer

GFP Green Fluorescent Protein

GLCM Gray Level Co-occurrence Matrix GMM Guassian Mixture Modelling

ICC ImmunocytochemistryICF ImmunocytofluorescenceIHC ImmunohistochemistryIHF ImmunohistofluorescenceIOD Integrated Optical Density

Laser Light Amplification by Stimulated Emission of Radiation

LED Light Emitting Diode
 LoG Laplacian of Gaussian
 MAP Maximum A Posteriori
 MIS Medical Image Segmentation

MLP Multi-Layered Perceptron
MRF Markov Random Field
MST Minimum Spanning Tree

NA Numerical Aperture

ORI Optimised Rotational Invariance

OTF Optical Transfer Function
PSF Point Spread Function
RNA Ribonucleic Acid
SNR Signal-to-Noise Ratio

TV Total Variation UV Ultraviolet

Physical Constants

 $\begin{array}{ll} \text{Speed of Light} & c = 2.997\,924\,58\times10^8\,\mathrm{m\,s^{-1}}\ \text{(exact)} \\ \text{Planck's Constant} & h = 6.626\,070\,04\times10^{-34}\,\mathrm{m^2\,kg\,s^{-1}}\ \text{(exact)} \end{array}$

List of Symbols

a distance

 \mathbf{m}

P power

 $W (J s^{-1})$

 ω angular frequency rad

For/Dedicated to/To my...

Chapter 1

Introduction

1.1 Outline and Contributions

The introduction is here.

1.2 Thesis Overview

The remainder of the thesis outline.

Chapter 2 is where we cover the mathematical foundation to Graph Cut image segmenation.

Chapter 3 is where we cover the mathematical foundation to Graph Cut image segmenation.

Chapter ?? is where we cover the mathematical foundation to Graph Cut image segmenation.

Chapter ?? is where we cover the mathematical foundation to Graph Cut image segmenation.

Chapter ?? is where we cover the mathematical foundation to Graph Cut image segmenation.

Chapter 4 is where we cover the mathematical foundation to Graph Cut image segmenation.

Chapter 5 concludes the thesis with suggestions for further work.

Chapter 2

Fluorescence Microscopy

What is fluorescence microscopy? What's it's purpose in the thesis? Photoluminescence -> fluorescence and phosphorescence. Discovery of fluorescence: Brief history and evolution. Brief discussion on the remainder of the chapter. Fluorescence microscopy has become an essential tool in diverse fields, such as petrology, semiconductors, etc, and has especially been established as a choice imaging technique in cellular and molecular biology for visualisation of cells and tissues [1–5]. In this thesis we confine our attention to its use in cellular biology.

Certain substances emit radiation when irradiated with a higher intensity light, such as ultraviolet (UV), blue or green, which is off a longer wavelength than that of the exciting light, this is known as *Stokes' Law*. This phenomenon is known as *photoluminescence* [6–9]. There are two types of photoluminescence. If emission persists at an appreciable level after the exciting light is turned off, then we call this *phosphorescence*. If emission persist only so long as the exciting light is on, then we call this *fluorescence* [6, 10].

The first observance and publishing of fluorescence is credited to Sir John Frederick William Herschel around 1852. In 1852, Sir John George Stokes published a 100 page treatise about this luminescent phenomenon and coined the term *fluorescence*, over Herschel's *dispersive reflection*, when he observed that the mineral *fluorite* emitted red light when irradiated by ultraviolet (UV) light [2, 11].

In the remainder of this chapter we present the underlying principles of fluorescence, how specimens are fluorescently marked, the optical principles of microscope design, image acquisition, image processing and common analysis in cellular biology. We only go so far in depth as to present a rudimentary understanding of fluorescence microscopy as is necessary for the comprehension of this thesis.

2.1 Physics of Fluorescence

Why is it necessary to understand the principles of fluroescence? Simple description of the fluorescence process. A more in-depth explanation of the fluorescence process and why stuff goes wrong e.g. phosphorescence, fading, etc. Fluorescence microscopy is a cross-disciplinary field. It is encouraged, if not necessary, to have a photophysical understanding of the principles of fluorescence, for biologists and computer scientists. The knowledge of the "under the hood" mechanics of fluorescence empower computer scientists to make informed and directed research in terms of image processing. The aim here is to present an elementary introduction into the physics of fluorescence.

The overall principle of fluorescence can be explained in three steps [12] as illustrated in 2.1(a): (1) Energy is absorbed by an atom upon collision with a photon. (2) The atom becomes excited and an electron jumps to a higher energy level. (3) Shortly after jumping to the higher energy level the electron returns to the ground state and emits a photon.




FIGURE 2.1: **(a)** Simplified fluorescence process. **(b)** The Jabłoński diagram depicting the electronics states from photon absorption to photo emission.

Excitation and emission One of the best ways to visualise the fluorescing process is using a Jabłoński diagram. A detailed Jabłoński diagram is shown in 2.1(b). When a photon collides with an atom, all its energy is transferred to the atom. The energy of the photon is inversely related to it's wavelength, $E = h\frac{c}{\lambda}$, where h is Planck's constant and c and λ are the speed and wavelength of light in a vacuum respectively. This increase in energy moves an electron from the ground state S_0 to a higher level energy state. Depending on the energy of the photon and the number of photons absorbed by the photon the electron can move to different energy levels e.g. S_1, S_2, etc . This process happens almost immediately in the order of femtoseconds($10^{-15}s$). Before moving to the lowest next higher energy level (S_1), some energy is lost due to internal conversion and vibrational relaxation. When the electron spontaneously decays from S_1 to S_0 it emits a photon of longer wavelength than the absorption photon. This happens few nanoseconds ($10^{-9}s$) after excitation.

The difference in wavelength of the emission photon and excitation photon is known as the *Stokes' Shift* or *Stokes' Law*. The larger the Stokes' Shift the easier it is to separate the emission light from the excitation light [1]. The emission curve is often a mirror image and shifted to longer wavelengths than the excitation curve as illustrated in Figure 2.2.

Fluorophores Substances that exhibit the fluorescent property are called fluorophores, also known as *fluorochromes* or *fluoresent dyes*. Early investigations showed that many substance naturally posess fluorescent properties, such as minerals, crystals, resins, crude drugs, butter, chlorophyll, vitamins, etc [1]. This is known as *autofluorescence*. Substances that do not fluoresce must be *stained* such that it can be observed through a fluorescent microscope, more on this later.

Intersystem crossing If the electron spin as the electron transfer between energy states is preserved then the energy states are known as *singlet states*. It is also possible for the electron to reverse it's spin. This is very unlikely and is known as *forbidden transition* in Quantum mechanics. When this happens the electron is said to be in a *triplet state*, see 2.1(b). The only way for the electron to reach the ground state is to again undergo another forbidden transition which is unlikely. When this does eventually happen the electron may emit a photon and this phenomenon is known as *phosphorescence*. This process takes much longer, in the order of microseconds $(10^{-6}s)$.




FIGURE 2.2: Normalised Excitation and Emmission Spectra of the Alexa Fluor 532 flurophore. The emmission maximum is at 553nm which is a more yellow-green than excitation maximum at 5534nm. Data obtained from ThermoFisher Scientific [13].

2.2 Specimen Labelling

Why do specimens have to be stained? What is is staining? Many of the components of interest, such as cell nuclei, cytoplasm, genes, chrosomes, proteins, do not possess a high degree of, if not any, autofluorescence. In this scenario, these components can be marked with a fluorescent dye [14], also known as a fluorophore or fluorochrome, a substance that can bind to a specific target whose excitation and emission spectra are well known. This is known as staining [2, 3, 11]. Once the specimen is stained it can be indirectly observed using a fluorescence microscope.

What are the most common staining protocols? The most prevalent staining techniques are fluorescence in-situ hybridisation (FISH) and immunostaining [2, 4, 15, 16].

FISH staining What is FISH? What is the FISH staining techniques used for? FISH is a molecular cytogenetic technique that uses flourophores that bind to selected regions in nucleic acids [2, 4]. FISH is the most frequently used staining technique used primarily for visualisation and localisation of nucleic acid sequences, chromosomes, cytplasm or organelles which contain those acids [3]. This makes FISH highly attractive for finding specific features in DNA and RNA used in genetic diagnosis and research, medicine and species identification [4, 17]. Figure 2.3(a) is a capture of mouse chromosomes using the FISH staining technique.

Immunostaining What is Immunofluorescence and the two main types, what is the difference between the two, and which is more common? What is the Immunofluorescence staining techniques used for? Immunofluorescence is the detection method where an antibody is used to detect an antigen in a tissue or a cell using fluorescence. Flourophores are usually conjugated onto antibodies, which are proteins that are designed bind to specific antigens, target proteins, on a cell [18]. The two types of immunofluorescent detection are immunocytofluorescence (ICF) and immunohystofluorescence (IHF). It must not be confused with immunocytochemistry (ICC) and immunohistochemistry (IHC). Immuno refers to the immunological technique, i.e. the binding of antibodies to antigens. Cyto refers to cells, i.e. cells without the extracellular membrane. Histo refers to tissue i.e. cells with the extracellular membrane. Chemistry refers to the chemical method of detection, e.g. a change in colour. Fluorescence detection by emission of light [19]. Figure 2.3(b) shows the detection of the p53 Binding Protein 1 in perfusion fixed frozen sections of rat kidney.

Live-cell staining FISH and IHC cannot stain live cells. Why? How can we stain live cells? The previously discussed staining techniques are not suitable to observe living cells. The fluorescent dyes used are phototoxic and cause cells to die. The circumvent this problem an elegant solution has been devised. Instead of staining, the cells are modified to produce a fluorescent substance in the target structures. Derivatives of the *green fluorescent protein* (GFP), isolated from the *Aequorea victoria* jellyfish [4, 14, 20], are used as it generates a strong photon emission and is non-toxic to living cells [2, 3, 11].

Important notes about fluorophores and the impact on image quality?

2.3 The Epifluorescence Microscope and Image Acquisition

What is a fluorescent microscope? Schematic layout of a fluorescence microscope? Function and purpose of each component in the fluorescent microscope? A fluorescence microscope is an optical microscope that is designed specifically to exploit the principle of fluorescence to allow for the observation of flourescently labelled specimens [3, 4, 8, 11, 21]. There are many types of fluorescent microscopes available but the favoured type among many biologists and geneticists is the epifluorescent microscope [9, 22]. The schematic of the epifluorescent microscope is illustrated in Figure 2.4.

Light source What sort of light needs to be generated? What sort of lamps are used? Advantages and disadvantages of certain lamps. The light source is typically a high-luminance light source e.g. Mercury or Xenon arc lamps, LEDs, lasers, etc [2, 3, 22–24]. The primary criterion for choosing a light sources is that its characeristic peaks must coincide with the excitation spectrum of the fluorophores being used [1, 4, 20]. Wavelength coverage spans from near infra-red to UV. Mercury and Xenon arc lamps are expensive, an inexpensive and lightweight alternative is bright LEDs [4, 6, 11, 23].

Excitation filter What is an excitation filter? Why is it needed? The incoming light from the light source is typically mulispectral [10]. The excitation filter is a wavelength selection filter which is placed in the path of the incoming light and filters through only those wavelengths in the absorption spectrum of the fluorescent dye [1–4, 11, 18, 20, 24].

Dichroic mirror What is a dichroic mirror? Why is it needed? Also known as a *dichroic beam* splitter. This is placed at a 45° angle and reflects the short-wavelenght light filtered through the




FIGURE 2.3: **(a)** FISH (Fluorescent 'in-situ' Hybridization) in mouse chromosomes using a BAC clone labeled with Spectrum Orange. The picture shows two metaphases and one interphase with two signals in each exampling a homozygous mouse for a transgenic clone. Image Source: "All About the Human Genome Project" Genetic and Genomic Image and Illustration Database. **(b)** p53 Binding Protein 1 (53BP1) was detected in perfusion fixed frozen sections of rat kidney using Goat Anti-Human 53BP1 Antigen Affinity-purified Polyclonal Antibody (Catalog # AF1877) at 15 μ g/mL overnight at 4°C. Tissue was stained using the NorthernLightsTM557-conjugated Anti-Goat IgG Secondary Antibody (red; Catalog # NL001) and counterstained with DAPI (blue). Specific staining was localized to nuclei of epithelial cells in convoluted tubules. Image Source: R&D Systems' IHC image database.




FIGURE 2.4: The schematic of the epifluorescence microscope.

excitation filter at a 90° angle towards the specimen [1–3, 18] and allows the long-wavelength light from the fluorescing specimen to pass through to the detector [6, 20], thus serving as a separation filter between the absorption and emission light [4, 11].

Objective What is the objective? Why is it needed? The incoming light reflected of the

dichroic mirror passes through the objective lens before reaching the specimen [1–3, 20]. Emission light from the fluorescing specimen is gathered in the objective lens and passed through to the dichroic mirror.

Specimen Say something about the specimen, for wholeness sake. The specimen is irradiated by the incoming light from the objective and emits long-wavelength light in all directions. The specimen is stained with a flourophore whose absorption and emission curves are well known. This is important since the light source and the interference filters are chosen using the peaks of these curves.

Emission filter What is an emission filter? Why is it needed? Also known as a barrier filter [1, 6, 20]. The light coming from the specimen contains multiple wavelengths and the dichroic mirror is used to filter out the shorter wavelength light. The emission filter is further used to filter out the wavelengths that correspond to the emission wavelengths of the fluorophore [2, 3, 10, 18, 24].

Detector What is the detector why is it needed? The dector is used to capture the emission light and can further digital form the image. The detector is usually a photodector such as a CCD (charge-coupled device) camera or a photomultipler tube [1–3, 20, 25]. It is vital that an appropriate detector be chosen as this has direct impact on image quality [4].

Other Types of Fluorescence Microscopes: Confocal, TIRF. Acquisition: CCD, Hardware setup effect on image quality, Numerical Aperture, Sub-diffraction The type of fluorescence image data that needs to be captured is application dependant and this impacts the decision on which type of microscope to use. The *widefield*, or conventional, microscope produces 2D image data. 3D image data cannot be captured directly. Instead, a series od 2D images are captured to form a 2D stack. The 3D image is then constructed in software. In this scenario, the most common choice of microcope is the *confocal laser scanning microscope* (CLSM). This microscope system is expensive and acquisition is slower. An economical alternative is the *confocal spinning disk miscroscope*. To detect single molecules, the favoured technique is *total internal reflection fluorescence* (TIRF) which can be achieved by a modification of the epifluorescence microscope.

2.4 Image Processing

Limitations in Fluorescence Imaging. Preprocessing: Point Spread Function deconvolution, etc. Segmentation Due to the physical nature of the fluorescence and image acquisition process, there are many factors that can degrade image quality. There are measures that can be taken to largely mitigate some problems but they can never be completely abated. The presence of these factors directly affect segmentation accuracy and subsequently higher level analysis. Therefore, images are processed prior to segmentation to suppress the artefacts and reconstruct the original data [2] or better yet enhance it. Chapter 4 takes a step in this vain. Here we present some of the commonly occurring factors that reduce image quality and the methods used to mitigate them, and some of the techniques employed for segmentation.

2.4.1 Preprocessing

Write a little something on preprocessing.




FIGURE 2.5: The effect of nonuniform illumination on segmentation. (a) Original image. Image source: The Cell Image Library [30]. (b) Nonuniformly illuminated image. The Vignette effect. (c) K-means clustering using the Euclidean distance metric and 2 clusters. The blue curve is from the original, the red curve is from the nonuniformly illuminated image. Notice that less of the object is recognised towards the edges.

Nonuniform illumination What causes uneven illumination? What techniques are done to reduce it's effect. Vignette effect, etc. There are many factors that could contribute to nonuniform illumination. The specimen layer will not be uniformly lit if the arc lamp is not properly focussed on the black aperture. To prevent this from happening, a liquid light guide-based light source, which provide even illumination may be used [20]. If the light brightness diminished towards the edges of the image then this is known as the *Vignette effect*. Common techniques to suppress this distortion is *background correction*, also known as *flat-field correction*, *background flattening* or *shading correction* [2, 4, 25]. Other causes of nonuniform illumination are inhomogenous detector sensitivity, autofluorescence, dirt particles in the optical system or nonspecific sample staining. An example of the Vignette effect is illustrated in 2.5(b). Computational schemes to eliminate nonuniform illumination have been well researched, although recently it hasn't recived too much attention [26–29].

Fading What causes quenching and bleaching? What techniques are done to reduce it's effect. Why is photobleaching worse? The reduction of emission intensity is called *fading*, of which there are two types: *quenching* and *bleaching*.

Quenching is a reversible loss of fluorescence owing to a variety of nonradiative energy-loss mechanisms such as collisions with nearby acceptor molecules, a phenomenon known as resonance energy transfer. This phenomenon is useful in studying molecular interactions below the lateral resolution of the light microscope through a technique called *fluorescence resonance energy transfer* (FRET) [1, 2, 20].

Bleaching refers to all processes that cause a fluorescent signal to fade permanently [20]. From the fluorescence process presented in Section 2.1, one may assume that, under the proper conditions, a fluorochrome has the ability to fluoresce indefinitely. However, this is not the case. There is a limit number of cycles before permanent bleaching [20]. Figure 2.6 illustrates the effect of photobleaching. *Photobleaching* is the most prominent form of bleaching. It is due the interaction of the fluorophore with an oxygen molecule. This can move the oxygen molecule to an excited singlet state, which then becomes a reactive molecule. When in this state, the oxygen molecule can participate in many chemically destructive reaction with




FIGURE 2.6: The effect of photobleaching. Image Source: Molecular Expressions [32]. (a) Original image at t=0s. (b) Image after t=10s. (c) Image after t=20s.

organic molecules causing *phototoxicity* [2]. Photobleaching is used to study diffusion and motion through a technique called *fluorescence recovery after photobleaching* (FRAP) [9, 20].

Photobleaching cannot be avoided but it be can pushed back. The aim in the measures to avoid photobleaching is to take a longer time to reach *reciprocity failure* [9]. This is done by shortening exposure times and using less intensive excitation light. This, however, yields low contrast images. These images with low signal-to-noise [25] ratio (SNR) are more difficult to segment hence contrast enhancement must be performed on the images prior to segmentation [31].

Image distortion What causes image distortion (PSF)? What techniques are done to reduce it's effect. The major contributing factors to image distortion are: The *point spread function* (PSF) and noise [8]. Image formation can be approximated by

$$O = n(s \otimes h), \tag{2.1}$$

where O is the formed image, n is the noise function, s is the exact image and h is the specific PSF of the optical system. We discuss the PSF first. The observed image isn't an exact representation of the real object. Optical systems have an inherent property called the point spread function which is the systems optical response to a point light source [2]. The final image is dependant on the spatial position of a point, numerical aperture (NA) and furthermore differs for various emission wavelengths [3, 33]. The final image is a superposition of all points in the illuminated volume where the contribution of each is described by the PSF.

Theoretically the exact image can be obtained by deconvolution of the observed image with the PSF. However, there are secondary factors that prevent this. Deconvolution seeks to reconstruct the original image given the PSF and certain assumptions about noise [33]. This is an *ill-posed problem* as little is known about the specific PSF or the noise model. Additionally, if the image is corrupted by too much of noise, deconvolution might still produce unsatisfactory results. The PSF is generally experimentally determined or theoretically modelled, and so the true PSF is never attained. Hence, the original image can never be attained by deconvolving with an approximated PSF. The image formation and restroration process is illustrated in Figure 2.7.

Deconvolution has recieved a lot of attention in the passed with very creative approaches [35–39]. Fluorescence microscopy deconvolution is still a very active field of research. Bayesian




FIGURE 2.7: The image formation process. Image source: [34]

methods have become popular in fluorescence microscopy image deconvolution, however noise in low SNR imaging conditions still poses a challenge [40]. Recent trends in 3D deconvolution in widefield microscopy use blind depth-invariant of the PSF [41]. Most PSF deconvolution systems naïvely assume depth-invariance however, the PSF changes significantly along the optical axis. There are also deconvolution methods that can preserve detail and possibly enhance image quality in diffraction-limited/superresolution imaging modalilities [42].

Noise What types of noise are most prevalent? How do they arise? What techniques are done to reduce it's effect. As previously stated, fluorescence imaging is a low light, low constrast and low SNR imaging technique to counter the effects of bleaching. For these reasons, noise becomes prominent. The three types of noise recorded by a camera is *dark noise*, *read noise* and *photon noise* [2, 3, 5, 11].

The electrons in a CCD of film are always in motion due to thermal energy. Dark current is due to the extraneous electrons which excited into the signal. This signal carries a statistical fluctuation known as dark noise. Dark current effects can be reduced by ground image subtraction or cooling the CCD. If there is a significant amount of dark noise then the background won't be as black as it should be. For this reason it is common to mistake dark noise for low-level autofluorescence [11, 43].

Read noise is a result of the conversion process from charge build-up to a voltage and then digitisation.

Photon noise, also known as *shot noise*, is the signal dependant statical variation of the counting of photons incident on the CCD or film. This is a naturally occurring phenomenon and cannot be reduced by camera design of system optimisation [43].

In low-light imaging techniques, such as is common in fluorescence imaging, the dominant form of noise is photon noise. Photon noise and dark noise are Poisson distributed [2, 43, 44]. Noise is low-light images used to modelled using the Gaussian distribution but was found to be a poor description of the noise. The Poisson distribution provides a more physically accurate model especially in photon-limited recording [8]. We study deonising in Section 4.3. The effect of noise on segementation accuracy is illustrated in Figure 2.8.




FIGURE 2.8: The effect of noise on segmentation. (a) Original image. (b) Poisson noise corrupted image. (c) ACWE Chan-Vese segmentated output. The red curve is from the original, the green curve is from the Poisson noise corrupted image. Notice that there are more artifacts and the segmented output is less accurate especially towards the bottom left from the green curve.

2.4.2 Segmentation

Write a little something on segmentation in cell imaging. Basic historical track of cell segmentation. Focus on specfic segmentation techniques. The primary aim of using fluorescence microscopy imaging is to make diagnoses and to study molecular behaviour and interaction. This means that biologists, geneticists and other professionals alike, not only have a superabundance of microscopic imaging techniques at their disposal, but also have an immense amount of image data to analyse since the outburst of image acquisition technology. The abundance, diversity, dimensionality and complexity of fluorescence image data obviates manual image processing as this isn't tractable, by any means, in terms of time or quality [43, 45]. Consequently, the task has fallen to computers to perform these tasks and has now become of essential in advancing these fields [46, 47]. The crux of image analysis lies on the accuracy of image segmentation and has become the principle focus in many studies [48].

Anton van Leeuwenhoek, a Dutch draper and scientist, is credited with the invention of the first real compound microscope in the late 17th century. However, it wasn't until the mid-1950s that computers became involved when systems were developed to automate the classification of smears of exfoliated cells. These systems used simple thresholding rules on 1D scanning of microscopic lines [49]. In the 1960s, automated systems were developed to count leukocytes on 2D image data based on their colour and morphological measurements [50]. In the 1980s the invention of the confocal microscope made it possible to study cells in 3D but it wasn't until the 1990s that computer became powerful enough to process 3D image data or complex 2D images [51]. The trends of increased computing power has made possible the use of more sophisticated cell analysis techniques as well as the ability to use more computationally demanding segmentation methods. The literature on cell segmentation and analysis has experienced exponential growth in the last couple of decades. Many studies comparing segmentation algorithms for cells have been pubished [52–54]. We review some of the common techniques used in fluorescence microscopy image segmentation.

Intensity thresholding Say something about this section. Intensity thresholding assumes a

non-overlapping intensity levels between the objects and the background. It is still one of the most common thresholding methods for cell segmentation [55–57]. Locally adaptive thresholding techniques are used when illumination varies across the image. Automated threshold segmentation techniques are usually based on global or local intensity using the histogram [48]. Thresholding produces suboptimal results due to the naïve assumption of mutually exclusive intensity levels.

Morphological segmentation Say something about this section. This method uses non-linear mathematical morphological operators like erosion, dilation, opening, closing, etc with geometrical and topological properties to segment the image [56, 58–61]. Generally, this method is used as a post-processing step to polish up coarse segmentation or a pre-processing step to suppress certain image structures [48].

Region accumulation Say something about this section. This method starts with selected points, called seeds. The idea is to iteratively add points neighboring previously labelled pixels based on some conformity measure, usually intensity. The most common implementation is called *region growing*. Most cases assume an image model similar to that of thresholding and suffers the same segmented results problems. Another approach is called the *watershed method* which converts the image into an open 3D shape and "fills the shape with water". The different regions are separated by those "filled with water" and those that aren't. A common problem with this method is oversegmentation and usually requires post-processing methods, like *region merging*, to get a meaningful result [48, 62, 63].

Edge-based segmentation Say something about this section. There are basically two types of edge-based segmentation: *gradient based methods* and *Laplacian based methods*.

Gradient methods are based on the assumption that there is a rapid intensity gradient between the object and the background. Edges are detected by searching for the maximum and minimum in the first derivative, e.g. Prewitt, Roberts and Sobel operators.

Laplacian methods search for zero-crossings in the second derivative, e.g. Marr-Hildreth, Laplacian of Gaussian (LoG), Canny edge detection.

These algorithms are very fast to compute but the drawback is when closed curves are desired [48], which is a common criterion in biological and molecular segmentation. A solution to this is to use snakes or active shape models.

Energy minimisation Two types: Deformable models and Graph cuts The most recent segmentation methods are based on energy minimisation. Most current state-of-the-art techniques fall under this category. This is due to their flexibility and robustness [2]. This group encompasses two main subgroups: *deformable models* and *discrete combinatorial optimisation*.

The aim of deformable model techniques is to fit a deformable model, either a curve or a surface, to the image data. They may be formulated either explicitely, as a parametric contour (2D) or a surface, e.g. snakes [64] or active contours [65–67], or implicitely as a zero-level of a function with one dimension higher than that of the image data, e.g. as a level set [68]. This technique widely used in fluorescence image segmentation [69–74].

The aim discrete combinatorial optimisation is to search a finite countable solution space for the optimal solution. Optimality is defined with respect to some energy function, which embeds one or more criteria, which is to be minimised. The most common implementation exploits the graph cut framework. Graph cut segmentation has recently gained a lot of popularity and momentum in medical image segmentation (MIS) [75–82].

Other miscellaneous techniques Unsupervised clustering (k-means), Otsu binarization, dynamic programming, Voronoi diagrams, ellipse fitting, template matching, model matching, gradient flow tracking. The techniques presented are just a select few in a plethora segmentation techniques that have been used in microscopy image segmentation. A few other common techniques are unsupervised clustering segmentation using the k-means [83–85], Otsu binarization [86], dynamic programming [87, 88], Voronoi diagrams [89, 90], gradient flow tracking [91], etc. This is just a few more. Instead of cell segmentation converging to a robust, flexible and unified solution, the number of available options is steadily increasing [45]. There probably exists as many individual unique solutions for cell segmentation as there are problems.

2.5 Object Measurement and Analysis

What is the purpose of object analysis in FM? What is measured? The aim in fluorescence image analysis is to measure specific properties of interest which enable higher level decision making. Typically, these properties are quantitative measures. In this section we review some of the important quantitative measurements in digital image analysis. It is important to note that for some of the properties of interest, the accuracy of the measurements depend heavily on the accuracy on the segmentation. The properties of interest are application dependent, one might require just the object morphology of structure and hence properties like perimeter, area, shape, intensity, colour, etc are of significance. Alternatively, if one requires the colocalisation of cells, then distance discriminants, such as Euclidean distance, Manhattan distance, Chessboard distance, etc, are of significance [2, 92].

Object measures can be loosely classified into four catergories: geometric measures, histogram-based measures, intensity based measures and temporal measures. One can also argue a fifth catergory statistical classifiers although this is generally used in higher level analysis.

Size measures Perimeter, area and volume are common measures to describe the size of objects. Area and volume are suitable measures to describe the general size of an object. The perimeter of an object is distinctly useful in discriminating its shape complexity. Complex and irregular shapes need a larger perimeter to enclose its area.

Pose measures This measure is defines an objects location and orientation. The centroid is used as an objects' locale and its orientation is the measure of the angle subtended by its major axis.

Shape measures Shape features are used to distinguish objects from one another. These measures are generally translationally, rotationally and scale invariant and can be used independent of, or in conjunction with, the size measures. Commonly assessed shape parameters are thinness ratio to describe the regularity of an object, rectangularity, circularity, Euler number, moments, central moments, object dispersion, rotationally invariant moments, Zernike moments and elongation.

Shape descriptors Shapes descriptors provide a more wholesome way of decribing an object's shape than compared to the single parameter shape measures. Differential chain codes, and its two most common descriptors boundary chain code (BCC) and differential chain code (DCC), are used to represent the distance around an object. Fourier descriptors is another object distance measure that explicits the periodicity of BCC. There are also graph respresentations of which the two most common are minimum spanning tree (MST) [93, 94] and Delaunay triagulation (DT) [95, 96].

Distance measures There are many ways to compute the separation between objects. The most commonly assessed distance measures are Euclidean distance, Manhattan distance (also known as the City-block distance or absolute value metric), which is a more computationally efficient approximation of Euclidean distance, and the Chessboard distance (also known as the maximum value metric) [97, 98].

Intensity measures Images are segmented generally into region with low intra-region intensity distribution and high inter-region intensity distribution [56, 99]. Common intensity measures are integrated optical density (IOD) [100, 101], is simply the sum of all the gray levels that compose the object, its a reflection of the object's "mass" or "weight", average optical density (AOD), is the IOD divided by the objects area, and contrast.

Histogram measures These measure provide a measure of an object's intensity distribution. Common histogram-based measures are mean, standard deviation, skew, entropy and energy [102, 103].

Texture measures In image analysis texture refers to the spatial arrangement of gray level values [104] and hence a texture feature quantifies some characteristic of the intensity variation within an object. Common texture measures are statistical texture measures, gray-level co-occurrence matrix (GLCM) [105, 106] and power spectrum features [107, 108].

Ratiometric measures Some fluorescent dye respond to the changes in Calcium and Hydrogen ion concentration by changing its spectral properties of the fluorescent emission bands. In this case, a ratio of the intensity can be used to calculate concentration of calcium of pH value [11].

Temporal measures Considering the time domain, many interesting properties can be observed. Commonly computed properties of interest are motility [109–111], like velocity and acceleration, rate of growth, rate of change of colour, etc.

These measures are used in higher decision making processes such as the evaluation of a hypothesis to detect the presence of a certain disease. They are also used to aid in the understanding of biological mechanisms, events and interactions [2].

Chapter 3

Mathematical Background

Optimisation approach in vision, "machinery/mechanics", literature review, ill-posed inverse problems.

Image segmentation falls under the mathemtical classification as being an ill-posed inverse problem [112, 113]. It is an inverse problem since we require a model from the observation, this simply means given the results, what are the causes. In image segmentation this translates to, given a 2D matrix of intensity values, which pixels belong to the object and which belong to the background. Image segmentation is also an ill-posed problem since their is a lack of uniqueness or stability of a solution [114], which are two of the three requirements for a solution to be well-posed, the other being existence. Image segmentation is an ill-posed because immense amount of information is suppressed in the acquisition processed [115–117]. Many tasks in vision are inherently or can be reformulated as ill-posed inverse problems e.g. scene reconstruction, stereo matching, image restoration, image deconvolution, etc. Computer vision is used heavily in industry, medicine and life science fields included, hence there is a need for robust, environmentally resistant approach. The *optimisation approach* is an elegant way to obtain a solution. In computer vision, a problem can be posed as an optimisation problem as follows: We are given a coarse, discrete and noisy, approximation of the visual data, d, we aim to infer some hidden quantities x, labels, depth, probable pixel intensty, etc, based on it. We then have to design an *objective function*, also known as an *energy function* or *cost function*,

$$E: (x,d) \to \Re, \tag{3.1}$$

which has to be optimised such that the optimisation of the function provides a solution to the problem. E(x,d) assigns an energy or a cost to each combination (x,d) of the input and hidden quantities. E provides a measure of goodness to how well the candidate solution x fits the expectation given the data d. In optimisation of this function we seek a minimum energy,

$$x^* = \arg\min_{x} E(x, d), \tag{3.2}$$

which has roots in Statistical Physics where lower energies correspond to more stable solutions. This gives us a general idea of how we should assign energies to solutions; better a solution, the lower an energy we should assign to it. In this case, a huge number of inference problems in vision can be solved by minimising the associated energy. A solution is only as good as the energy model and the optimisation technique. Once a precice energy and minimising algorithm are found, the problem is essentially solved [118].

Early attempts in computer vision would solve problems like these using iteration or relaxation methods [119, 120]. In these attempts the problems are solved in a Calculus of variations framework, this is still a popular approach to optimisation in vision since Poggio et al. [112] proposed an integrated framework to regularisation theory for vision [121]. Many important

advancements in computer vision are proposals for a better energy, a better algorithm or both [118, 122–125]. In this thesis we focus on discrete energy optimisation using graph cuts for image segmentation.

Plan for the chapter. Image segmentation falls under a broader catergory of problems known as *labelling problems*. The aim is to find the best label, foregound/object or background, for each pixel. In Section 3.1 we briefly discuss labelling problems and its formulation as an energy minimisation problem.

3.1 Labelling Problems

Among the many computer vision problems, image segmentation is the most easy to understand labelling problem. A labelling problem is simply assigning, to an observation, a label that most accurately explains it. An observation can be anything that we wish to classify e.g. pixels, features, salient points, depth measurement, etc. A label is a description of that observation. There are two types of labels: *semantic labelling* (person, car, tree, sky, face, eye, etc) or *pixel-wise labelling* (texture, shape, colour, background/object, etc) [118, 126].

To formulate a labelling problem we need a set of *cites*, intuitively known as observations, and a set of *labels*, a set of explanations. The goal is to find the best explanation given the observations. In computer vision, the observations, can be features, image segments, etc. However, they will typically represent pixels in an image with some natual structure or ordering. Let

$$\mathcal{P} = \{1, 2, \dots, n\}$$

be the set of n cites and

$$\mathcal{L} = \{l_1, l_2, \dots, l_k\}$$

be the set of k labels. A discrete labelling is a map $f: \mathcal{P} \to \mathcal{L}$ that assigns each discrete variable f_p one value from \mathcal{L} and $f = \{f_p\}_{p \in \mathcal{P}}$ which is known as a *configuration*. We are interested in binary segmentation, also known as *binarization*, which implies we have two explanations in our label set, k = 2. The labels of interest are the *background* and the *object*. Although the solution space is finite, it is very large and grows exponentially as the image size increases or as the number of labels increases. The number of possible configurations is given by $|\mathcal{L}|^{|\mathcal{P}|}$. Table 3.1 shows the largeness of the solution space even for very small images and a few labels. In pratice, the image sizes used in Table 3.1 is too small, hence finding a solution is not easy. Most often we have to settle for an approximate solution, one that is "good enough".

TABLE 3.1: The impact of the number of cites and labels on the solution space	9
---	---

Image (P)	Number of cites ($ \mathcal{P} $)	Number of labes (\mathcal{L})	Number of configurations $ \mathcal{L} ^{ \mathcal{P} }$
64×64	$2^{12} = 4096$	2	$2^{2^{12}} = 2^{4096} = n$
128×128	$2^{14} = 16384$	2	$2^{2^{14}} = 2^{16384} = n^4$
64×64	$2^{12} = 4096$	3	$3^{2^{12}} = 3^{4096} \approx n^{1.585}$

3.2 MAP Estimation for Discrete Models

- 3.2.1 Random Fields
- 3.2.2 Markov Random Fields
- 3.2.3 Conditional Random Fields
- 3.2.4 CRFs for Image Segmentation
- 3.2.5 MAP-MRF Estimation

3.3 Graph Cuts

3.3.1 Network Theory and the Min-cut Problem

In this section we cover Graph Theory and specifically Flow Networks, which is a branch of Graph Theory, which is fundamental to the understanding of image segmentation via graph cuts. With it roots in Germany where Euler tried to find the solution to the Konigsberg bridge problem, graph theory has since blossomed into a rich field of Mathematics with seemingly endless amounts of application. Graph Theory is a huge topic in mathematics and can be applied to many other sciences. Graph theory is part of another more encompassing field of Mathematics known as Combinatronics. Graph theory and applications are more useful than the average person would recognise. They're used in Google Maps to find shortest routes to destinations, in Molecular Chemistry to model the structure of atoms, and the list goes on for quite a while. It is no surprise that it is also found to be useful in image segmentation.

Network A network N=(V,E) is a directed graph with a source node s, a sink node t and a strictly positive capacity on every edge. That is, for each edge $e \in E$, the capacity, c(.), obeys $c(e) \in \Re^+$.




FIGURE 3.1: Network **N** with no flow. The in-degree and out-degree for the source, **s**, and the sink, **t**, are shown next to the corresponding node.

The **source node** only has out-going edges, $d_{in}(s) = 0$ and $d_{out}(s) \ge 0$. The **sink node** only has incoming edges, $d_{in} \ge 0$ and $d_{out} = 0$.

Flow A flow $f: V^2 \longrightarrow \Re^+$ is associated with each edge e = (u, v) such that:

- 1. for each edge $e \in E$ we have $0 \le f(e) \le c(e)$. That is, the flow is positive and cannot excees the capacity of the edge.
- 2. for each intermediate node $v \in V \setminus \{s, t\}$ the in- and out-flow of that node $\sum_{u \in V^-(v)} f(u, v) = \sum_{u \in V^+(v)} f(v, u)$.

The **total flow** F of a network is then what leave the source s or reaches the sink t:

$$F(N) := \sum_{u \in V} f(s, u) - \sum_{u \in V} f(u, s) = \sum_{u \in V} f(u, t) - \sum_{u \in V} f(t, u)$$
(3.3)




FIGURE 3.2: Network **N** with flow. The flow out of the source node, **s**, is equal to the flow into the sink node, **t**. For all other nodes, the flow-in is equal to the flow-out. This is the conservation of flow principle. This is only part of the network. The remaining part is the residual graph which shows the amount of reverse flow is available on an edge.

Cut A cut of a network N=(V,E) is a partitioning of the vertex set $V=P\bigcup \bar{P}$ into two disjoint sets P containing the source node s and \bar{P} containing the sink node t. $P\cap \bar{P}=\emptyset$.

The **capacity** of a cut is the sum of the edges $(u, v) \in V$ where $u \in P$ and $v \in \bar{P}$:

$$\kappa(P,\bar{P}) = \sum_{u \in P; v \in \bar{P}} c(u,v) \tag{3.4}$$

Maximal Flow The largest amount of flow that can be sent through the source that is able to reach the sink is known as the maximal flow.

Minimal Cut A cut C on a network N=(V,E) is a minimal cut if there exists no other cut C' where $\kappa(C')<\kappa(C)$.

3.3. Graph Cuts




FIGURE 3.3: Network **N** with with a valid cut **C**. The nodes within the red region are reachable from the source and the nodes within the blue region are able to reach the sink. The cut set, **C**, is show in the orange filled block.




Figure 3.4: Network N with with a invalid cut C. The cut does not partition source node s and sink node t into distinct sets.

In the next section we show that the Maximal Flow problem and the Minimal Cut problem are duals of each other, commonly known as the Max-Flow/Min-Cut problem.




FIGURE 3.5: Network N with with a invalid cut C. The cut partition partitions the graph into more than two sets and the cut intersects the edges ab and ad twice.




Figure 3.6: Network **N** with maximum flow. There is no way to push more flow out of the source into the sink without breaking the rules for conservation of flow.




FIGURE 3.7: Network **N** with minimal cut **C**. The sum of the capacity of all the edges in the cut set is the minimum of all possible valid cuts on the network **N**.

3.3.2 Image Segmentation Framework/Graph Construction Images

3.4 Energy Minimisation

3.4.1 General Form of Energy Functions

3.4.2 Submodular Functions

3.4.3 Energy Minimisation Algorithms

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Aliquam ultricies lacinia euismod. Nam tempus risus in dolor rhoncus in interdum enim tincidunt. Donec vel nunc neque. In condimentum ullamcorper quam non consequat. Fusce sagittis tempor feugiat. Fusce magna erat, molestie eu convallis ut, tempus sed arcu. Quisque molestie, ante a tincidunt ullamcorper, sapien enim dignissim lacus, in semper nibh erat lobortis purus. Integer dapibus ligula ac risus convallis pellentesque.

Ford-Fulkerson

Nunc posuere quam at lectus tristique eu ultrices augue venenatis. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Aliquam erat volutpat. Vivamus sodales tortor eget quam adipiscing in vulputate ante ullamcorper. Sed eros ante, lacinia et sollicitudin et, aliquam sit amet augue. In hac habitasse platea dictumst.

Algorithm 1 Euclid's algorithm

```
1: procedure EUCLID(a, b)
                                                                                           ⊳ The g.c.d. of a and b
       r \leftarrow a \bmod b
       while r \neq 0 do
                                                                                 \triangleright We have the answer if r is 0
3:
            a \leftarrow b
4:
            b \leftarrow r
            r \leftarrow a \bmod b
6:
7:
       end while
       return b
                                                                                                     ⊳ The gcd is b
8.
9: end procedure
```

Dinic/Edmond-Karp

Morbi rutrum odio eget arcu adipiscing sodales. Aenean et purus a est pulvinar pellentesque. Cras in elit neque, quis varius elit. Phasellus fringilla, nibh eu tempus venenatis, dolor elit posuere quam, quis adipiscing urna leo nec orci. Sed nec nulla auctor odio aliquet consequat. Ut nec nulla in ante ullamcorper aliquam at sed dolor. Phasellus fermentum magna in augue gravida cursus. Cras sed pretium lorem. Pellentesque eget ornare odio. Proin accumsan, massa viverra cursus pharetra, ipsum nisi lobortis velit, a malesuada dolor lorem eu neque.

Push-Relabel

Originally developed by Andrew V. Goldberg and Robert E. Tarjan. Previous algorithms, such as Ford-Fulkerson, used the concept of residual networks and augmenting paths to determine max-flow. Push-Relabel used the concept of preflow to determine max-flow instead of augmenting paths. Sometimes referred as the Preflow-Push Algorithm. Preflow is a concept originally developed by A.V. Karzanov.

The algorithm works at converting a preflow, f, into a normal flow and then terminates. This flow also turns out to be the maximum flow. Goldberg and Tarjan defined a generic Push-Relabel algorithm which solves the maximum flow problem.

Preflow A preflow is a real-valued function, f, on vertice pairs. The total flow into a vertex can exceed the flow out of a vertex but not vice versa.

A preflow where all $v \in V - \{s, t\}$ has a flow excess of zero, $e_f(v) = 0$, is a normal flow. The preflow function is also referred to as the **s-t preflow**.

Preflow must satisfy:

- 1. Capacity Constraint $\forall u, v \in V, f(u, v) \leq c(u, v)$
- 2. Antisymmetry/Skew Symmetry $\forall u, v, \in V, f(u, v) = -f(v, u)$
- 3. Nonnegative Constrain The flow into $v \in V \{s\}$ must be greater than or equal to the flow out of v. $\forall u \in V, v \in V \{s\}, \sum f(u,v) > 0$

Flow Excess Flow excess, $e_f(v)$, is the net flow into v where $v \in V$ for some preflow f.

$$e_f(v) = \begin{cases} \infty & \text{if } v = s \\ \sum_{u \in V} f(u, v) & \text{if } v \in V - \{s\} \end{cases}$$

Active Vertex An active vertex/node is a vertex v which satisfies all of the properties:

- 1. Not a source or sink, $v \in V \{s, t\}$
- 2. Positive flow excess, $e_f(v) > 0$
- 3. Has a valid label, $d(v) < \infty$

Push-Relabel also uses the concept of a residual graph, $G_f = (V, E_f)$.

Residual Capacity The residual capacity of a preflow is defined as $r_f(v, w) = c(v, w) - f(v, w)$.

Residual Edges The residual edges for a preflow f is defined as the set of edges with positive residual capacity. $E_f = \{(v, w)\}|r - f(v, w) > 0$.

Labelling Push-Relabel also use a valid labelling function, *d*, to determine which vertex pairs should be selected for the push operation.

A valid labelling , d, is a nonnegative integer function applied to all vertices to denote a label. The labelling is often referred as the height or distance from the sink node, t. This function is sometimes compared to the physical intuition that liquids naturally flow downhill.

A valid labelling for a preflow consists of:

- 1. For $v \in V$, $0 \le d(v) \le \infty$
- 2. d(s) = |V| (source condition)
- 3. d(t) = 0 (sink condition)
- 4. d(v) = d(w) + 1 for every residual edge $(v, u) \in E_f$

A labelling d and a preflow f are said to be compatible id d adheres to the properties above.

The algorithm pushes flow excess starting at the source, s, along all vertices towards the sink, t. The algorithm maintains a compatible vertex labelling function, d, to the preflow, f. The labelling is used to determine where to puch the flow excess. The algorithm repeatedly performs either a push or a relabel operation so long as there is an active vertex in G_f .

Push Operation The push operation is used to move flow from one vertex to another. The transfer of excess can be performed across the vertex pair $(v, w) \in E_f$ if:

- 1. v is an active vertex
- 2. the edge has positive residual capacity, $r_f(v, w) > 0$
- 3. the label distance d(v) = d(w) + 1

This allows the algorithm to move δ excess flow: $\delta = min(e_f(v), r_f(v, w))$ from v to w. A push is considered **saturating** if no more flow can be sent over the edge, $\delta = r_f(v, w)$. A push is considered to be **non-saturating** if all the excess from v the push over the dge and the edge still has some cpacity, $\delta = e_f(v)$.

Algorithm 2 Push Operation

```
Input: Preflow f, labels d, and (v, w) where v, w \in V
Output: Preflow f
Applicable: if v \in V - \{s, t\}, d(v) < \infty, e_f(v) > 0, r_f(v, w) > 0 and d(v) = d(w) + 1
 1: procedure PUSH(v, w)
        \delta := min(e_f(v), r_f(v, w))
        f(v, w) := f(v, w) + \delta
 3:
 4:
        f(w,v) := f(w,v) - \delta
        e_f(v) := e_f(v) - \delta
 5:
        e_f(w) := e_f(w) + \delta
 6:
 7:
        return f
 8: end procedure
```

Relabel Operation The relabel operation is used to increase the label value of a single active vertex so that excess flow can be pushed out of the active vertex. The relabel operation is performed when all the residual edges of the active vertex have positive residual capacity, $r_f(v,w)>0$. This implies that v's label is less than or equal to all vertices, $d(v)\leq d(w)$, meaning that no push operation across the edges is possible given the push condition d(v)=d(w)+1.

The relabel operation for some vertex v selects the smallest label for the vertices with positive residual edges, $r_f(v,w)>0$. The active vertex is then assigned the smallest label value +1 such that $d(v):=mind(v)+1|(v,w)\in E_f$. This will allow the vertex v to potentially push its excess flow to atleast one of the othe vertices during the algorithm's next iteration.

Algorithm 3 Relabel Operation

```
Input: Preflow f, labels d, and v \in V - \{s, t\}
Output: Labels d
Applicable: if v \in V - \{s, t\}, d(v) < \infty, e_f(v) > 0, and \forall w \in V, r_f(v, w) > 0 which implies
d(v) \le d(w)
 1: procedure RELABEL(v)
        if \{(v, w) \in E_f\} \neq 0 then
            d(v) := min(d(w) + 1 | (v, w) \in E_f)
 3:
 4:
        else
 5:
           d(v) := \infty
        end if
 6:
        return d
 7:
 8: end procedure
```

The algorithm initialises the following values in the residual graph before the push andrelabel operations in the main loop.

- 1. Initialise the preflow of all edges in the residual graph
- 2. Initialise the labellings such that:

(a)
$$d(s) = |V|$$

(b) $d(v) = 0$ for $v \in V - \{s\}$

3. Performs saturation, pushes along all residual edges out of the source $(s, v) \in E_f$ and $v \in V$.

Once complete the algorithm repeatedly performs either a push or a relabel operation against all vertices. The algorithm continues until no operation can be performed. The algorithm terminates when there are no more active vertices.

```
Algorithm 4 Push-Relabel Main-loop
```

```
Input: Network flow graph G = (V, E), s, t and c
Output: Maximum flow f
 1: procedure MAIN(v)
        for all (v, w) \in (V - \{s\})(V - \{s\}) do
            f(v,w) \leftarrow 0
 3:
            f(w,v) \leftarrow 0
 4:
        end for
 5:
        for all v \in V do
 6:
            f(s,v) \leftarrow r_f(s,v)
 7:
            f(v,s) \leftarrow -r_f(s,v)
 8:
 9:
        end for
       d(s) \leftarrow |V|
10:
        for all v \in V - \{s\} do
11:
12:
            d(v) \leftarrow 0
            e_f(v) \leftarrow f(s,v)
13:
        end for
14:
        While there exists an active vertex
15:
        while \exists v \in V - \{s, t\} do
                                         ▶ with either applicable PUSH() or RELABEL() operation
16:
17:
            Perform either a PUSH or a RELABEL operation on v
        end while
18:
19:
        return f
20: end procedure
```

The analaysis and the proof of correctness of the Push-Relabel algorithm can be found in Appendix B.

Push-Relabel Speed Optimisation Heuristics

Discharge Push-Relabel also use a valid labelling function ,*d*, to determine which vertex pairs should be selected for the push operation.

FIFO Push-Relabel also use a valid labelling function ,*d*, to determine which vertex pairs should be selected for the push operation.

Highest Label First Push-Relabel also use a valid labelling function ,*d*, to determine which vertex pairs should be selected for the push operation.

Global Relabel Push-Relabel also use a valid labelling function ,*d*, to determine which vertex pairs should be selected for the push operation.

Gap Relabel Push-Relabel also use a valid labelling function ,*d*, to determine which vertex pairs should be selected for the push operation.

Chapter 4

Pre-Processing and Post-Processing Scheme for Fluorescence Microscopy Images

- 4.1 Removal of Artifacts using Connected Components
- 4.2 Anisotropic Diffusion
- 4.2.1 Coherence Enhancing Diffusion
- 4.2.2 Coherence Enhancing Diffusion with Optimised Rotational Invariance
- 4.3 Poisson Denoising
- 4.3.1 Total-Variation Denoising
- 4.4 Contrast Enhancement

Chapter 5

Conclusion and Future Work

Appendix A

Proof of Maximum Flow - Minimum Cut Equivalence

Write your Appendix content here.

Appendix B

Introduction to Graph Theory

In this section we cover Graph Theory and specifically Flow Networks, which is a branch of Graph Theory, which is fundamental to the understanding of image segmentation via graph cuts. With it roots in Germany where Euler tried to find the solution to the Konigsberg bridge problem, graph theory has since blossomed into a rich field of Mathematics with seemingly endless amounts of application. Graph Theory is a huge topic in mathematics and can be applied to many other sciences. Graph theory is part of another more encompassing field of Mathematics known as Combinatronics. Graph theory and applications are more useful than the average person would recognise. They're used in Google Maps to find shortest routes to destinations, in Molecular Chemistry to model the structure of atoms, and the list goes on for quite a while. It is no surprise that it is also found to be useful in image segmentation.

Graph A graph G is a pair (V, E), where V is the set of nodes/vertices and E is the set of edges consisting of pairs (u, v) where $u, v \in V$. The graph is assumed to be finite i.e. |V| = n and |E| = m.

In an **undirected graph**, the edge (u,v) and (v,u) are not distinct. That is, they refer to the same edge. However, in a **directed graph**, the two edge are now distinct. In a directed graph with edge (u,v), u is known as the **tail** and v is known as the **head**. In directed graphs, edges, also known as arcs, are depicted by placing arrowheads at the head of the edge. Given an edge e=(u,v), u and v are said to be **incident** on e. A graph is said to be **simple** if it does not contain any self-loops. A **self-loop** is an edge with of its end points being the same vertex.

Degree The degree of a vertex v is the number of edges incident on it. $deg(v) = |\{(u, v), (v, u) \in E\}|$. A self-loop counts for 2.

If a graph is directed, also known as a **digraph**, then a node v has an **in-degree** $d_{in}(v)$ and an **out-degree** $d_{out}(v)$. A digraph is said to be **balanced** if $d_{in}(v) = d_{out}(v), \forall v \in V$.

Subgraph A graph G' = (V', E') is said to be a sub-graph of G = (V, E), denoted as $G' \subseteq G$, if $V' \subseteq V$ and $E' \subseteq E$.

Clique A clique is a maximal subgraph.

Network A network N=(V,E) is a directed graph with a source node s, a sink node t and a strictly positive capacity on every edge. That is, for each edge $e \in E$, the capacity, c(.), obeys $c(e) \in \Re^+$.




FIGURE B.1: Undirected weighted graph G. The degree of each node is shown next to the corresponding node. The graph is simple. The red box shows the vertex set, V_G , and edge set, E_G , and their corresponding norm.

The **source node** only has out-going edges, $d_{in}(s) = 0$ and $d_{out}(s) \ge 0$. The **sink node** only has incoming edges, $d_{in} \ge 0$ and $d_{out} = 0$.

Flow A flow $f: V^2 \longrightarrow \Re^+$ is associated with each edge e = (u, v) such that:

- 1. for each edge $e \in E$ we have $0 \le f(e) \le c(e)$. That is, the flow is positive and cannot excees the capacity of the edge.
- 2. for each intermediate node $v \in V \setminus \{s, t\}$ the in- and out-flow of that node $\sum_{u \in V^-(v)} f(u, v) = \sum_{u \in V^+(v)} f(v, u)$.

The **total flow** *F* of a network is then what leave the source *s* or reaches the sink *t*:

$$F(N) := \sum_{u \in V} f(s, u) - \sum_{u \in V} f(u, s) = \sum_{u \in V} f(u, t) - \sum_{u \in V} f(t, u)$$
(B.1)

Cut A cut of a network N=(V,E) is a partitioning of the vertex set $V=P\bigcup \bar{P}$ into two disjoint sets P containing the source node s and \bar{P} containing the sink node t. $P\cap \bar{P}=\emptyset$.

The **capacity** of a cut is the sum of the edges $(u, v) \in V$ where $u \in P$ and $v \in \overline{P}$:

$$\kappa(P,\bar{P}) = \sum_{u \in P: v \in \bar{P}} c(u,v) \tag{B.2}$$

Maximal Flow The largest amount of flow that can be sent through the source that is able to reach the sink is known as the maximal flow.




FIGURE B.2: Directed weighted graph (Digraph) \mathbf{D} . The in-degree and out-degree is shown next to each node. The graph is simple and not balanced. The red box shows the vertex set, V_D , and edge set, E_D , and their corresponding norm.

Minimal Cut A cut C on a network N = (V, E) is a minimal cut if there exists no other cut C' where $\kappa(C') < \kappa(C)$.

In the next section we show that the Maximal Flow problem and the Minimal Cut problem are duals of each other, commonly known as the Max-Flow/Min-Cut problem.




Figure B.3: Undirected weighted graph H is a subgraph of G in Figure XX, $H \subseteq G$. Directed weighted graph I is a subgraph of D in Figure XX, $I \subseteq D$. The degree of each node is shown next to the corresponding node. The red box shows the vertex set, the edge set and their corresponding norms.




FIGURE B.4: Cliques of the undirected weighted graph **G**. The maximal cliques are shown by the hyperedges that encompass the nodes of that clique.




FIGURE B.5: Network **N** with no flow. The in-degree and out-degree for the source, **s**, and the sink, **t**, are shown next to the corresponding node.




FIGURE B.6: Network N with flow. The flow out of the source node, s, is equal to the flow into the sink node, t. For all other nodes, the flow-in is equal to the flow-out. This is the conservation of flow principle. This is only part of the network. The remaining part is the residual graph which shows the amount of reverse flow is available on an edge.




FIGURE B.7: Network **N** with with a valid cut **C**. The nodes within the red region are reachable from the source and the nodes within the blue region are able to reach the sink. The cut set, **C**, is show in the orange filled block.




Figure B.8: Network N with with a invalid cut C. The cut does not partition source node s and sink node t into distinct sets.




FIGURE B.9: Network **N** with with a invalid cut **C**. The cut partition partitions the graph into more than two sets and the cut intersects the edges *ab* and *ad* twice.




FIGURE B.10: Network **N** with maximum flow. There is no way to push more flow out of the source into the sink without breaking the rules for conservation of flow.




Figure B.11: Network ${\bf N}$ with minimal cut ${\bf C}$. The sum of the capacity of all the edges in the cut set is the minimum of all possible valid cuts on the network ${\bf N}$.

Bibliography

- [1] Kenneth R. Spring. *Encyclopedia of Optical Engineering Fluorescence Microscopy*. 270 Madison Avenue, New York, New York 10016: Marcel Dekker, Inc., 2003, pp. 548–555. DOI: 10.1081/E-EOE.
- [2] Ondřej Daněk. "Graph Cut Based Image Segmentation in Fluorescence Microscopy [online]". Doctoral theses, Dissertations. Masaryk University, Faculty of Informatics, Brno, 2012 [cit. 2016-09-08]. URL: http://is.muni.cz/th/60931/fi_d/thesis-final.pdf.
- [3] Jan Hubený. "Applications of PDE Based Image Processing in Fluorescence Microscopy [online]". Doctoral theses, Dissertations. Masaryk University, Faculty of Informatics, Brno, 2008 [cit. 2016-09-07]. URL: http://is.muni.cz/th/4012/fi_d/.
- [4] Fatima A. Merchant and Ammasi Periasamy. "Fluorescence Imaging". In: *Microscope Image Processing*. USA: Elsevier Inc, 2008, pp. 247–271. ISBN: 978-0-12-372578-3.
- [5] Pavel Matula. "Image Processing in Fluorescence Microscopy and its Utilization in Cell Biology Experiments [online]". Doctoral theses, Dissertations. Masaryk University, Faculty of Informatics, Brno, 2012 [cit. 2016-09-09].
- [6] Karl-Friedrich Koch. Fluorescence Microscopy Instruments, Methods, Applications. Lietz Wetzlar, 1972.
- [7] Andrew Vaughan. *Principles of Fluorescence Microscopy*. Document. (accessed September 6, 2016).
- [8] Pinaki Sarder and Arye Nehorai. "Deconvolution Methods for 3-D Fluorescence Microscopy Images". In: *IEEE Signal Processing Magazine* 23.3 (2006), 32—45. DOI: 10.1046/j.1365-2818.2000.00754.x.
- [9] Mortimer Abramowitz and Michael W. Davidson. *Introduction to Fluorescence*. Website. (accessed September 6, 2016). URL: http://www.olympusmicro.com/primer/lightandcolor/fluorointroduction.html.
- [10] Kenneth R. Spring and Michael W. Davidson. *Introduction to Fluorescence Microscopy*. Website. (accessed September 6, 2016). URL: http://www.microscopyu.com/techniques/fluorescence/introduction-to-fluorescence-microscopy.
- [11] Jurek W. Dobrucki. "Fluorescence Microscopy". In: Fluorescence Microscopy: From Principles to Biological Applications. 1st Edition. Wiley-VCH Verlag GmbH & Co., 2013, pp. 97–142.
- [12] Nobel Media AB. *The Fluorescence Microscopy*. Website. (accessed September 6, 2016). URL: http://www.nobelprize.org/educational/physics/microscopes/fluorescence/.
- [13] Fluorescence SpectraViewer. Website. (accessed September 18, 2016). URL: https://www.thermofisher.com/us/en/home/life-science/cell-analysis/labeling-chemistry/fluorescence-spectraviewer.html.

[14] Roger Y. Tsien. "The Green Fluorescent Protein". In: *Annual Review of Biochemistry* 67 (1998), pp. 509–544.

- [15] Michal Kozubek. "FISH imaging". In: Confocal and Two-Photon Microscopy: Foundations, Applications and Advances (2001), 389—429.
- [16] Z. Theodosiou et al. "Automated Analysis of FISH and immunohistochemistry images: A Review". In: *Cytometry Part A* 71.7 (2007), pp. 439–450.
- [17] Rudolf Amann and Bernhard M. Fuchs. "Single-cell identification in microbial communities by improved fluorescence in situ hybridization techniques". In: *Nature Reviews Microbiology* 6.5 (2008), 339—348. DOI: 10.1038/nrmicrol888.
- [18] Kelly Cude and Kelly Burke. "Introduction to Fluorescence Microscopy". In: (14 July 2012).
- [19] Kishore Reddy Katikireddy and Finbarr O'Sullivan. "Immunohistochemical and Immunofluorescence Procedures for Protein Analysis". In: *Gene Expression Profiling: Methods and Protocols*. Ed. by Lorraine O'Driscoll. Totowa, NJ: Humana Press, 2011, pp. 155–167. ISBN: 978-1-61779-289-2. DOI: 10.1007/978-1-61779-289-2_11. URL: http://dx.doi.org/10.1007/978-1-61779-289-2_11.
- [20] Jeff W. Lichtman and José-Angel Conchello. *Nature Methods Fluorescence microscopy*. Vol. 2. 12. Nature Publishing Group, Decmeber 2005, pp. 910–919. DOI: 10.1038/NMETH817. URL: http://www.nature.com/naturemethods.
- [21] Paul D. Andrews, Ian S. Harper, and Jason R. Swedlow. "To 5D and Beyond: Quantitative Fluorescence Microscopy in the Postgenomic Era". In: *Traffic*. Vol. 3. Munksgaard International Publishers, 2002, pp. 29–36.
- [22] George Rice. Fluorescent Microscopy. Website. (accessed September 6, 2016). URL: http://serc.carleton.edu/microbelife/research_methods/microscopy/fluromic.html.
- [23] Kavita Aswani, Tushare Jinadasa, and Claire M. Brown. "Fluorescence Microscopy Light Sources". In: *Microscopy Today*. 2012, pp. 22–28. DOI: 10.1017/S1551929512000399. URL: www.microscopy-today.com.
- [24] Thermo Fisher Scientific. Fundamentals of Fluorescence Microscopy. Website. (accessed September 6, 2016). URL: https://www.thermofisher.com/us/en/home/life-science/cell-analysis/cell-analysis-learning-center/molecular-probes-school-of-fluorescence/fundamentals-of-fluorescence-microscopy.html.
- [25] Douglas B. Murphy. Fundamentals of Light Microscopy and Electronic Imaging. 2nd Edition. USA: John Wiley & Sons, Inc., 2001. ISBN: 0-471-25391-X.
- [26] Ian T. Young. "Shading Correction: Compensation for Illumination and Sensor Inhomogeneities". In: Current Protocols in Cytometry. John Wiley & Sons, Inc., 2001. ISBN: 9780471142959. DOI: 10.1002/0471142956.cy0211s14. URL: http://dx.doi.org/10.1002/0471142956.cy0211s14.
- [27] Ghauharali, Hofstraat, and Brakenhoff. "Fluorescence photobleaching-based shading correction for fluorescence microscopy". In: *Journal of Microscopy* 192.2 (1998), pp. 99–113. ISSN: 1365-2818. DOI: 10.1046/j.1365-2818.1998.00412.x. URL: http://dx.doi.org/10.1046/j.1365-2818.1998.00412.x.

[28] Michael Model. "Intensity Calibration and Flat-Field Correction for Fluorescence Microscopes". In: Current Protocols in Cytometry. John Wiley & Sons, Inc., 2001. ISBN: 9780471142959. DOI: 10.1002/0471142956.cy1014s68. URL: http://dx.doi.org/10.1002/0471142956.cy1014s68.

- [29] Michael A. Model and Janis K. Burkhardt. "A standard for calibration and shading correction of a fluorescence microscope". In: *Cytometry* 44.4 (2001), pp. 309–316. ISSN: 1097-0320. DOI: 10.1002/1097-0320(20010801) 44: 4<309::AID-CYT01122> 3.0.CO; 2-3. URL: http://dx.doi.org/10.1002/1097-0320(20010801) 44: 4<309::AID-CYT01122>3.0.CO; 2-3.
- [30] Anne Carpenter. CIL 21739. Picture. (accessed September 9, 2016). URL: http://www.cellimagelibrary.org/images/21739.
- [31] Stephen A. Boppart et al. "Optical probes and techniques for molecular contrast enhancement in coherence imaging". In: *Journal of Biomedical Optics* 10.4 (2005), pp. 041208–041208–14. DOI: 10.1117/1.2008974. URL: http://dx.doi.org/10.1117/1.2008974.
- [32] Molecular Expressions. *Photobleaching*. Picture. (accessed September 9, 2016). URL: http://micro.magnet.fsu.edu/primer/java/fluorescence/photobleaching/.
- [33] Margret Keuper. "Segmentation of Cells and Sub-cellular Structures from Microscopic Recordings [online]". Doctoral theses, Dissertations. Albert-Ludwigs-Universität, 2012 [cit. 2016-09-12]. URL: http://lmb.informatik.uni-freiburg.de/Publications/2012/Keu12/Dissertation_Keuper.pdf.
- [34] Arjan Tibbe. CIL 40968. Picture. (accessed September 9, 2016). URL: http://www.cellimagelibrary.org/images/40968.
- [35] Eran A. Mukamel, Hazen Babcock, and Xiaowei Zhuang. "Statistical Deconvolution for Superresolution Fluorescence Microscopy". In: Biophysical Journal 102.10 (2012), pp. 2391– 2400. DOI: 10.1038/srep09894. URL: http://dx.doi.org/10.1016/j.bpj. 2012.03.070.
- [36] Peter J Verveer et al. "High-resolution three-dimensional imaging of large specimens with light sheet-based microscopy". In: *Nature Methods* 4 (2007), pp. 311–313. DOI: 10. 1038/nmeth1017. URL: http://www.nature.com/nmeth/journal/v4/n4/abs/nmeth1017.html.
- [37] Ammassi Periasamy, Paul Skoglundand Colten Noakes, and Raymond Keller. "An Evaluation of Two-Photon Excitation Versus Confocal and Digital Deconvolution Fluorescence Microscopy Imaging in Xenopus Morphogenesis". In: *Microscopy Research and Technique* 4 (2007), pp. 311–313. DOI: 10.1038/nmeth1017.URL: http://www.nature.com/nmeth/journal/v4/n4/abs/nmeth1017.html.
- [38] Jason R. Swedlow. "Quantitative Fluorescence Microscopy and Image Deconvolution". In: Digital Microscopy, 3rd Edition. Vol. 81. Methods in Cell Biology. Academic Press, 2007, pp. 447–465. DOI: http://dx.doi.org/10.1016/S0091-679X(06) 81021-6. URL: http://www.sciencedirect.com/science/article/pii/ S0091679X06810216.

[39] Johan J. de Rooi, Cyril Ruckebusch, and Paul H. C. Eilers. "Sparse Deconvolution in One and Two Dimensions: Applications in Endocrinology and Single-Molecule Fluorescence Imaging". In: *Analytical Chemistry* 86.13 (2014). PMID: 24893114, pp. 6291–6298. DOI: 10.1021/ac500260h. eprint: http://dx.doi.org/10.1021/ac500260h.

- [40] Alexander Wong, Xiao Yu Wang, and Maud Gorbet. "Bayesian-based deconvolution fluorescence microscopy using dynamically updated nonstationary expectation estimates". In: *Scientific Reports* 5.10849 (2015), pp. 1–9. DOI: 10.1038/srep10849. URL: http://dx.doi.org/10.1038/srep10849.
- [41] Boyoung Kim and Takeshi Naemura. "Blind Depth-variant Deconvolution of 3D Data in Wide-field Fluorescence Microscopy". In: *Scientific Reports* 5.9894 (2015), pp. 1–9. DOI: 10.1038/srep09894. URL: http://dx.doi.org/10.1038/srep09894.
- [42] Jing Qin et al. "Detail-preserving Fluorescence Microscopy Image Deconvolution". In: Conference on Lasers and Electro-Optics. Optical Society of America, 2016, STh4G.7. DOI: 10.1364/CLEO_SI.2016.STh4G.7. URL: http://www.osapublishing.org/abstract.cfm?URI=CLEO_SI-2016-STh4G.7.
- [43] Ryan Naidoo anad Jules-Raymond Tapamo. "A Preprocessing Scheme for Fluorescence Microscopy Image Segmentation". In: *International Journal of Imaging and Robotics* 16.4 (2016), pp. 1–23. ISSN: ISSN 2231–525X.
- [44] Gijsbert Michiel Peter Van Kempen. "Image Restoration in Fluorescence Microscopy [online]". Doctoral theses, Dissertations. Technische Universiteit Delft, 1999 [cit. 2016-09-08]. URL: http://www.tnw.tudelft.nl/fileadmin/Faculteit/TNW/Over_de_faculteit/Afdelingen/Imaging_Science_and_Technology/Research/Research_Groups/Quantitative_Imaging/Publications/List_Publications/doc/thesis_kempen.pdf.
- [45] Erik Meijering. "Cell Segmentation: 50 Years Down the Road [Life Sciences]". In: *IEEE Signal Processing Magazine* 29.5 (2012), pp. 140–145. ISSN: 1053-5888. DOI: 10.1109/MSP.2012.2204190.
- [46] Bruce Alberts et al. *Molecular Biology of the Cell*. 5th Edition. New York, NY, USA: Garland Science, 2007. ISBN: 9780815341055.
- [47] Cédrik Vonesch et al. "The Colored Revolution of Bioimaging [An introduction to fluorescence microscopy]". In: *IEEE Signal Processing Magazine* 29.5 (2006), pp. 20–31.
- [48] Ewert Bengtsson, Carolina Wählby, and Joakim Lindblad. "Robust cell image segmentation methods". In: *Pattern Recognition and Image Analysis: Advances in Mathematical Theory and Applications* 14.52 (2004), pp. 157–167. ISSN: 1054-6618.
- [49] W.E. Tolles. "Section of Biology: The Cytoanalyzer—An Example of Physics in Medical Research*". In: *Transactions of the New York Academy of Sciences* 17.3 Series II (1955), pp. 250–256. ISSN: 2164-0947. DOI: 10.1111/j.2164-0947.1955.tb01204.x. URL: http://dx.doi.org/10.1111/j.2164-0947.1955.tb01204.x.
- [50] Judith M. S. Prewitt and Mortimer L. Mendelsohn. "The Analysis of Cell Images*". In: Annals of the New York Academy of Sciences 128.3 (1966), pp. 1035–1053. ISSN: 1749-6632. DOI: 10.1111/j.1749-6632.1965.tb11715.x. URL: http://dx.doi.org/10.1111/j.1749-6632.1965.tb11715.x.
- [51] Metin N. Gurcan et al. "Histopathological image analysis: A review". In: *IEEE Reviews in Biomedical Engineering* (2009), pp. 147–171.

[52] Alden A. Dima et al. "Comparison of segmentation algorithms for fluorescence microscopy images of cells". In: *Cytometry Part A* 79A.7 (2011), pp. 545–559. ISSN: 1552-4930. DOI: 10.1002/cyto.a.21079. URL: http://dx.doi.org/10.1002/cyto.a.21079.

- [53] Z. Pincus and J.A. Theriot. "Comparison of quantitative methods for cell-shape analysis". In: *Journal of Microscopy* 227.2 (2007), pp. 140–156. ISSN: 1365-2818. DOI: 10.1111/j.1365-2818.2007.01799.x. URL: http://dx.doi.org/10.1111/j.1365-2818.2007.01799.x.
- [54] Luís Pedro Coelho, Aabid Shariff, and Robert F. Murphy. "Nuclear Segmentation in Microscope Cell Images: A Hand-Segmented Dataset and Comparison of Algorithms". In: Proc IEEE Int Symp Biomed Imaging 5.193098E6.2 (2009), pp. 518–521. ISSN: 1365-2818. DOI: 10.1111/j.1365-2818.2007.01799.x. URL: http://www.ncbi.nlm.nih.gov/pmc/articles/PMC2901896/.
- [55] Qiang Wu, Fatima A. Merchant, and Kenneth R. Castleman. *Encyclopedia of Optical Engineering Fluorescence Microscopy*. 1st Edition. Elsevier Inc., 2008. ISBN: 978-0-12-372578-3.
- [56] E. Meijering et al. "Design and validation of a tool for neurite tracing and analysis in fluorescence microscopy images". In: *Cytometry Part A* 58A.2 (2004), pp. 167–176. ISSN: 1552-4930. DOI: 10.1002/cyto.a.20022. URL: http://dx.doi.org/10.1002/cyto.a.20022.
- [57] Quanli Wang et al. "Image segmentation and dynamic lineage analysis in single-cell fluorescence microscopy". In: *Cytometry Part A* 77A.1 (2010), pp. 101–110. ISSN: 1552-4930. DOI: 10.1002/cyto.a.20812. URL: http://dx.doi.org/10.1002/cyto.a.20812.
- [58] Rafael C. Gonzalez and Richard E. Woods. *Digital Image Processing*. 3rd Edition. New Jersey, USA: Prentice Hall, Inc., 2002.
- [59] L.B. Dorini, R. Minetto, and N. J. Leite. "White blood cell segmentation using morphological operators and scale-space analysis". In: *Computer Graphics and Image Processing*, 2007. SIBGRAPI 2007. XX Brazilian Symposium on. 2007, pp. 294–304. DOI: 10.1109/SIBGRAPI.2007.33.
- [60] D. Anoraganingrum. "Cell segmentation with median filter and mathematical morphology operation". In: *Image Analysis and Processing, 1999. Proceedings. International Conference on.* 1999, pp. 1043–1046. DOI: 10.1109/ICIAP.1999.797734.
- [61] B.R. Kumar, D.K. Joseph, and T.V. Sreenivas. "Teager energy based blood cell segmentation". In: *Digital Signal Processing*, 2002. *DSP* 2002. 2002 14th International Conference on. Vol. 2. 2002, pp. 619–622. DOI: 10.1109/ICDSP.2002.1028167.
- [62] Kan Jiang, Qing-Min Liao, and Sheng-Yang Dai. "A novel white blood cell segmentation scheme using scale-space filtering and watershed clustering". In: *Machine Learning and Cybernetics*, 2003 International Conference on. Vol. 5. 2003, pp. 2820–2825. DOI: 10.1109/ICMLC.2003.1260033.
- [63] Gang Lin et al. "A hybrid 3D watershed algorithm incorporating gradient cues and object models for automatic segmentation of nuclei in confocal image stacks". In: *Cytometry Part A* 56A.1 (2003), pp. 23–36. ISSN: 1552-4930. DOI: 10.1002/cyto.a.10079. URL: http://dx.doi.org/10.1002/cyto.a.10079.

[64] Michael Kass, Andrew Witkin, and Demetri Terzopoulos. "Snakes: Active contour models". In: *International Journal of Computer Vision* 1.4 (1988), pp. 321–331.

- [65] Vicent Caselles, Ron Kimmel, and Guillermo Sapiro. "Geodesic Active Contours". In: International Journal of Computer Vision 22.1 (1997), pp. 61–79. ISSN: 0920-5691. DOI: 10.1023/A:1007979827043. URL: http://dx.doi.org/10.1023/A: 1007979827043.
- [66] Hongsheng Li et al. "Automated actin filament segmentation, tracking and tip elongation measurements based on open active contour models". In: 2009 IEEE International Symposium on Biomedical Imaging: From Nano to Macro. 2009, pp. 1302–1305. DOI: 10.1109/ISBI.2009.5193303.
- [67] J. Cheng and J. C. Rajapakse ^{ast}. "Segmentation of Clustered Nuclei With Shape Markers and Marking Function". In: *IEEE Transactions on Biomedical Engineering* 56.3 (2009), pp. 741–748. ISSN: 0018-9294. DOI: 10.1109/TBME.2008.2008635.
- [68] Stanley Osher and Ronald P. Fedkiw. *Level set methods and dynamic implicit surfaces*. Applied mathematical science. New York, N.Y.: Springer, 2003. ISBN: 0-387-95482-1. URL: http://opac.inria.fr/record=b1099358.
- [69] O. Dzyubachyk, W. Niessen, and E. Meijering. "Advanced level-set based multiple-cell segmentation and tracking in time-lapse fluorescence microscopy images". In: 2008 5th IEEE International Symposium on Biomedical Imaging: From Nano to Macro. 2008, pp. 185–188. DOI: 10.1109/ISBI.2008.4540963.
- [70] C. Ortiz de Solórzano et al. "Segmentation of nuclei and cells using membrane related protein markers". In: *Journal of Microscopy* 201 (2001), pp. 404–415.
- [71] Alexandre Dufour et al. "Segmenting and tracking fluorescent cells in dynamic 3-D microscopy with coupled active surfaces." In: *IEEE Transactions on Image Processing* 14.9 (2005), pp. 1396–410. URL: https://hal.archives-ouvertes.fr/hal-00014483.
- [72] Oleh Dzyubachyk et al. "Advanced Level-Set-Based Cell Tracking in Time-Lapse Fluorescence Microscopy." In: *IEEE Trans. Med. Imaging* 29.3 (2010), pp. 852–867. URL: http://dblp.uni-trier.de/db/journals/tmi/tmi29.html#DzyubachykCENM10.
- [73] Fatima Boukari and Sokratis Makrogiannis. "Spatio-temporal Level-Set Based Cell Segmentation in Time-Lapse Image Sequences". In: *Advances in Visual Computing: 10th International Symposium, ISVC 2014, Las Vegas, NV, USA, December 8-10, 2014, Proceedings, Part II.* Ed. by George Bebis et al. Cham: Springer International Publishing, 2014, pp. 41–50. ISBN: 978-3-319-14364-4. DOI: 10.1007/978-3-319-14364-4_5. URL: http://dx.doi.org/10.1007/978-3-319-14364-4_5.
- [74] Martin Maška et al. "A Comparison of Fast Level Set-Like Algorithms for Image Segmentation in Fluorescence Microscopy". In: *Advances in Visual Computing: Third International Symposium, ISVC 2007, Lake Tahoe, NV, USA, November 26-28, 2007, Proceedings, Part II.* Ed. by George Bebis et al. Berlin, Heidelberg: Springer Berlin Heidelberg, 2007, pp. 571–581. ISBN: 978-3-540-76856-2. DOI: 10.1007/978-3-540-76856-2_56. URL: http://dx.doi.org/10.1007/978-3-540-76856-2_56.

[75] Ondřej Daněk et al. "Segmentation of Touching Cell Nuclei Using a Two-Stage Graph Cut Model". In: *Image Analysis: 16th Scandinavian Conference, SCIA 2009, Oslo, Norway, June 15-18, 2009. Proceedings.* Ed. by Arnt-Børre Salberg, Jon Yngve Hardeberg, and Robert Jenssen. Berlin, Heidelberg: Springer Berlin Heidelberg, 2009, pp. 410–419. ISBN: 978-3-642-02230-2. DOI: 10.1007/978-3-642-02230-2_42. URL: http://dx.doi.org/10.1007/978-3-642-02230-2_42.

- [76] C. Chen et al. "Constraint factor graph cut-based active contour method for automated cellular image segmentation in RNAi screening". In: *Journal of Microscopy* 230.2 (2008), pp. 177–191. ISSN: 1365-2818. DOI: 10.1111/j.1365-2818.2008.01974.x. URL: http://dx.doi.org/10.1111/j.1365-2818.2008.01974.x.
- [77] Y. Al-Kofahi et al. "Improved Automatic Detection and Segmentation of Cell Nuclei in Histopathology Images". In: *IEEE Transactions on Biomedical Engineering* 57.4 (2010), pp. 841–852. ISSN: 0018-9294. DOI: 10.1109/TBME.2009.2035102.
- [78] H. Kong, M. Gurcan, and K. Belkacem-Boussaid. "Partitioning Histopathological Images: An Integrated Framework for Supervised Color-Texture Segmentation and Cell Splitting". In: *IEEE Transactions on Medical Imaging* 30.9 (2011), pp. 1661–1677. ISSN: 0278-0062. DOI: 10.1109/TMI.2011.2141674.
- [79] Huei-Fang Yang and Yoonsuck Choe. "Cell tracking and segmentation in electron microscopy images using graph cuts". In: 2009 IEEE International Symposium on Biomedical Imaging: From Nano to Macro. 2009, pp. 306–309. DOI: 10.1109/ISBI.2009.5193045.
- [80] L. Zhang et al. "Automated segmentation of abnormal cervical cells using global and local graph cuts". In: 2014 IEEE 11th International Symposium on Biomedical Imaging (ISBI). 2014, pp. 485–488. DOI: 10.1109/ISBI.2014.6867914.
- [81] Lu Liu et al. "Interactive Separation of Segmented Bones in CT Volumes Using Graph Cut". In: *Medical Image Computing and Computer-Assisted Intervention MICCAI 2008:* 11th International Conference, New York, NY, USA, September 6-10, 2008, Proceedings, Part I. Ed. by Dimitris Metaxas et al. Berlin, Heidelberg: Springer Berlin Heidelberg, 2008, pp. 296–304. ISBN: 978-3-540-85988-8. DOI: 10.1007/978-3-540-85988-8_36. URL: http://dx.doi.org/10.1007/978-3-540-85988-8_36.
- [82] Nhat Vu and B.S. Manjunath. "Graph cut segmentation of neuronal structures from transmission electron micrographs". In: *IEEE International Conference on Image Processing* (2008).
- [83] H. P. Ng et al. "Medical Image Segmentation Using K-Means Clustering and Improved Watershed Algorithm". In: 2006 IEEE Southwest Symposium on Image Analysis and Interpretation. 2006, pp. 61–65. DOI: 10.1109/SSIAI.2006.1633722.
- [84] Kalpana Shrivastava, Neelesh Gupta, and Neetu Sharma. "Medical Image Segmentation using Modified K Means Clustering". In: *International Journal of Computer Applications* 103.16 (2014), pp. 12–16. ISSN: 0975-8887. DOI: 10.1109/TMI.2011.2141674.
- [85] Nameirakpam Dhanachandra, Khumanthem Manglem, and Yambem Jina Chanu. "Image Segmentation Using K-means Clustering Algorithm and Subtractive Clustering Algorithm". In: *Procedia Computer Science* 54 (2015), pp. 764–771. ISSN: 1877-0509. DOI: http://dx.doi.org/10.1016/j.procs.2015.06.090. URL: http://www.sciencedirect.com/science/article/pii/S1877050915014143.

[86] Xiaowei Chen, Xiaobo Zhou, and S.T.C. Wong. "Automated segmentation, classification, and tracking of cancer cell nuclei in time-lapse microscopy". In: *IEEE Transactions on Biomedical Engineering* 53.4 (2006), pp. 762–766. ISSN: 0018-9294. DOI: 10.1109/TBME.2006.870201.

- [87] Jihong Liu, Weina Ma, and Soo-Young Lee. "A Segmentation Method Based on Dynamic Programming for Breast Mass in MRI Images". In: *Medical Biometrics: First International Conference, ICMB 2008, Hong Kong, China, January 4-5, 2008. Proceedings.* Ed. by David Zhang. Berlin, Heidelberg: Springer Berlin Heidelberg, 2007, pp. 307–313. ISBN: 978-3-540-77413-6. DOI: 10.1007/978-3-540-77413-6_39. URL: http://dx.doi.org/10.1007/978-3-540-77413-6_39.
- [88] Y. Zhang, B. J. Matuszewski, and L. K. Shark. "A Novel Medical Image Segmentation Method using Dynamic Programming". In: *Medical Information Visualisation BioMedical Visualisation*, 2007. *MediVis* 2007. *International Conference on*. 2007, pp. 69–74.
- [89] R. Cardenes et al. "K-Voronoi diagrams computing in arbitrary domains". In: *Image Processing*, 2003. *ICIP* 2003. *Proceedings*. 2003 International Conference on. Vol. 2. 2003, pp. 941–944. DOI: 10.1109/ICIP.2003.1246838.
- [90] Chunyan Jiang, Xinhua Zhang, and Christoph Meinel. "Hybrid Framework for Medical Image Segmentation". In: *Computer Analysis of Images and Patterns: 11th International Conference, CAIP 2005, Versailles, France, September 5-8, 2005. Proceedings.* Ed. by André Gagalowicz and Wilfried Philips. Berlin, Heidelberg: "Springer Berlin Heidelberg, 2005, pp. 264–271. ISBN: 978-3-540-32011-1. DOI: 10.1007/11556121_33. URL: http://dx.doi.org/10.1007/11556121_33.
- [91] G. Li et al. "Segmentation of Touching Cells Using Gradient Flow Tracking". In: 2007 4th IEEE International Symposium on Biomedical Imaging: From Nano to Macro. 2007, pp. 77–80. DOI: 10.1109/ISBI.2007.356792.
- [92] Fatima A. Merchant, Shishir K. Shah, and Kenneth R. Castleman. "Object Measurement". In: *Microscope Image Processing*. USA: Elsevier Inc, 2008, pp. 195–219. ISBN: 978-0-12-372578-3.
- [93] Charlotte Giesen et al. "Highly multiplexed imaging of tumor tissues with subcellular resolution by mass cytometry". In: *Nature Methods* 11.4 (2014), pp. 417–422. DOI: 10.1038/nmeth.2869. URL: http://dx.doi.org/10.1038/nmeth.2869.
- [94] Xiaosong Yuan et al. "MDL Constrained 3-D Grayscale Skeletonization Algorithm for Automated Extraction of Dendrites and Spines from Fluorescence Confocal Images".
 In: Neuroinformatics 7.4 (2009), pp. 213–232. ISSN: 1559-0089. DOI: 10.1007/s12021-009-9057-y. URL: http://dx.doi.org/10.1007/s12021-009-9057-y.
- [95] Michal Kozubek and Pavel Matula. "An efficient algorithm for measurement and correction of chromatic aberrations in fluorescence microscopy". In: *Journal of Microscopy* 200.3 (2000), pp. 206–217. ISSN: 1365-2818. DOI: 10.1046/j.1365-2818.2000.00754.x. URL: http://dx.doi.org/10.1046/j.1365-2818.2000.00754.x.
- [96] Dominique Attali and Annick Montanvert. "Computing and Simplifying 2D and 3D Continuous Skeletons". In: Elsevier Computer Vision and Image Understanding 67.3 (1997), pp. 261–273. ISSN: 1365-2818. DOI: 10.1006/cviu.1997.0536. URL: http://dx.doi.org/10.1046/j.1365-2818.2000.00754.x.

[97] Andrew P. French et al. "Colocalization of fluorescent markers in confocal microscope images of plant cells". In: *Nat. Protocols* 3 (4 2008), pp. 619–628. ISSN: 1754-2189. DOI: 10.1038/nprot.2008.31. URL: http://dx.doi.org/10.1038/nprot.2008.31.

- [98] Vadim Zinchuk, Olga Zinchuk, and Teruhiko Okada. "Quantitative Colocalization Analysis of Multicolor Confocal Immunofluorescence Microscopy Images: Pushing Pixels to Explore Biological Phenomena". In: *ACTA HISTOCHEMICA ET CYTOCHEMICA* 40.4 (2007), pp. 101–111. DOI: 10.1267/ahc.07002.
- [99] D. Pinkel, T. Straume, and J.W. Gray. "Cytogenetic analysis using quantitative, high-sensitivity, fluorescence hybridization". In: Proceedings of the National Academy of Sciences 83.9 (1986), pp. 2934–2938. eprint: http://www.pnas.org/content/83/9/2934.full.pdf. URL: http://www.pnas.org/content/83/9/2934.abstract.
- [100] M. Loferer-Krößbacher, J. Klima, and R. Psenner. "Determination of Bacterial Cell Dry Mass by Transmission Electron Microscopy and Densitometric Image Analysis". In: *Appl. Environ. Microbiol.* 64 (2 1998), pp. 688–694. DOI: 10.1038/nmeth929. URL: http://dx.doi.org/10.1038/nmeth929.
- [101] N. Watanabe et al. "Motility of bile canaliculi in the living animal: implications for bile flow." In: *The Journal of Cell Biology* 113.5 (1991), pp. 1069–1080. DOI: 10.1083/jcb. 113.5.1069. eprint: http://jcb.rupress.org/content/113/5/1069.full. pdf+html. URL: http://jcb.rupress.org/content/113/5/1069.abstract.
- [102] Michael J. Rust, Mark Bates, and Xiaowei Zhuang. "Sub-diffraction-limit imaging by stochastic optical reconstruction microscopy (STORM)". In: *Nat Meth* 3 (10 2006), pp. 793–796. DOI: 10.1038/nmeth929. URL: http://dx.doi.org/10.1038/nmeth929.
- [103] Michael V. Boland and Robert F. Murphy. "A neural network classifier capable of recognizing the patterns of all major subcellular structures in fluorescence microscope images of HeLa cells". In: Bioinformatics 17.12 (2001), pp. 1213–1223. DOI: 10.1093/bioinformatics/17.12.1213.eprint: http://bioinformatics.oxfordjournals.org/content/17/12/1213.full.pdf+html.URL: http://bioinformatics.oxfordjournals.org/content/17/12/1213.abstract.
- [104] R.O. Duda, P.E. Hart, and D.G. Stork. Pattern Classification. John Wiley & Sons, 2001.
- [105] V. Atlamazoglou et al. "Texture analysis of fluorescence microscopic images of colonic tissue sections". In: *Medical and Biological Engineering and Computing* 39.2 (2001), pp. 145–151. ISSN: 1741-0444. DOI: 10.1007/BF02344796. URL: http://dx.doi.org/10.1007/BF02344796.
- [106] Riccardo Cicchi et al. "Scoring of collagen organization in healthy and diseased human dermis by multiphoton microscopy". In: *Journal of Biophotonics* 3.1-2 (2010), pp. 34–43. ISSN: 1864-0648. DOI: 10.1002/jbio.200910062. URL: http://dx.doi.org/10.1002/jbio.200910062.
- [107] Erik J. Sánchez, Lukas Novotny, and Xie Sunney. "Near-Field Fluorescence Microscopy Based on Two-Photon Excitation with Metal Tips". In: *Phys. Rev. Lett.* 82 (20 1999), pp. 4014–4017. DOI: 10.1103/PhysRevLett.82.4014. URL: http://link.aps.org/doi/10.1103/PhysRevLett.82.4014.

[108] C. Xu et al. "Multiphoton fluorescence excitation: new spectral windows for biological nonlinear microscopy". In: *Proceedings of the National Academy of Sciences* 93.20 (1996), pp. 10763–10768. eprint: http://www.pnas.org/content/93/20/10763.full.pdf. URL: http://www.pnas.org/content/93/20/10763.abstract.

- [109] Rajesh Babu Sekar and Ammasi Periasamy. "Fluorescence resonance energy transfer (FRET) microscopy imaging of live cell protein localizations". In: *Journal of Cellular Biology* 160 (5 2004), pp. 629–633. DOI: 10.1083/jcb.200210140.
- [110] Mark J. Miller et al. "Two-Photon Imaging of Lymphocyte Motility and Antigen Response in Intact Lymph Node". In: Science 296.5574 (2002), pp. 1869–1873. ISSN: 0036-8075. DOI: 10.1126/science.1070051. eprint: http://science.sciencemag.org/content/296/5574/1869.full.pdf.URL: http://science.sciencemag.org/content/296/5574/1869.
- [111] Anshu Bagga Mathur, George A. Truskey, and W. Monty Reichert. "Atomic Force and Total Internal Reflection Fluorescence Microscopy for the Study of Force Transmission in Endothelial Cells". In: *Biophysical Journal* 78 (4 2000), pp. 1725–1735. DOI: 10.1016/S0006-3495 (00) 76724-5. URL: http://dx.doi.org/10.1016/S0006-3495 (00) 76724-5.
- [112] Tomaso Poggio, Vincent Torre, and Christof Koch. "Computational vision and regularization theory". In: *Nature* 317.6035 (1985), pp. 314–319. DOI: 10.1038/317314a0. URL: http://dx.doi.org/10.1038/317314a0.
- [113] D. Terzopoulos. "Regularization of Inverse Visual Problems Involving Discontinuities". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* PAMI-8.4 (1986), pp. 413–424. ISSN: 0162-8828. DOI: 10.1109/TPAMI.1986.4767807.
- [114] S.I. Kabanikhin. "Definitions and examples of inverse and ill-posed problems". In: *J. Inv. Ill-Posed Problems* 16 (2008), pp. 317–357. ISSN: 0162-8828. DOI: 10.1515/JIIP. 2008.069.
- [115] Albert Tarantola. *Inverse Problem Theory and Methods and Models for Parameter Estimation*. Philadelphia, PA, USA: Society for Industrial and Applied Mathematics, 2005, pp. 1–37. ISBN: 0-89871-572-5.
- [116] Mario Bertero and Patrizia Boccacci. *Introduction to Inverse Problems in Imaging*. Bath, UK: IOP Publishing Ltd, 1998, pp. 1–37. ISBN: 0 7503 0439 1.
- [117] M. Bertero and M. Piana. "Inverse problems in biomedical imaging: modeling and methods of solution". In: *Complex Systems in Biomedicine*. Ed. by Alfio Quarteroni, Luca Formaggia, and Alessandro Veneziani. Milano: Springer Milan, 2006, pp. 1–33. ISBN: 978-88-470-0396-5. DOI: 10.1007/88-470-0396-2_1. URL: http://dx.doi.org/10.1007/88-470-0396-2_1.
- [118] Andrew Thomas Delong. "Advances in Graph-Cut Optimization: Multi-Surface Models, Label Costs, and Hierarchical Costs [online]". Doctoral theses, Dissertations. The University of Western Ontario, London Ontario, Canada, 2011 [cit. 2016-09-19]. URL: http://www.psi.toronto.edu/~andrew/papers/thesis.pdf.
- [119] David Waltz. "Understanding Line Drawings of Scenes with Shadows". In: *The Psychology of Computer Vision*. McGraw-Hill, 1975, pp. 19–91.
- [120] Azriel Rosenfeld, Robert A. Hummel, and Steven W. Zucker. "Definitions and examples of inverse and ill-posed problems". In: *IEEE Transactions on Systems, MAN, and Cybernetics* 6.6 (1976), pp. 420–433.

[121] Katsuhiko Sakaue, Akira Amano, and Naokazu Yokoya. "Optimization Approaches in Computer Vision and Image Processing". In: *IEECE Trans. Inf. & Syst.* E82.3 (1999), pp. 534–547.

- [122] Yuri Boykov, Olga Veksler, and Ramin Zabih. "Fast approximate energy minimization via graph cuts". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 23 (2001), pp. 1222–1239.
- [123] Vladimir Kolmogorov. "Convergent Tree-Reweighted Message Passing for Energy Minimization". In: *Proc. Int'l Workshop Artificial Intelligence and Statistics*. 2005.
- [124] David Mumford. "Optimal approximation by piecewise smooth functions and associated variational problems". In: *Commun. Pure Applied Mathematics* (1989), pp. 577–685.
- [125] Jianbo Shi and Jitendra Malik. "Normalized Cuts and Image Segmentation". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 22 (1997), pp. 888–905.
- [126] T. Athanasiadis et al. "Semantic Image Segmentation and Object Labeling". In: *IEEE Transactions on Circuits and Systems for Video Technology* 17.3 (2007), pp. 298–312. ISSN: 1051-8215. DOI: 10.1109/TCSVT.2007.890636.