Busan API Service Documentation (V2)

Base URL:

https://1gamestopup.com/api/v1

Authentication:

All requests must include an x-api-key header:

x-api-key: <Your API KEY>

1. Check Balance

Endpoint:
GET /api-service/balance?currency=INR // currency=INR OR currency=USD

Description:
Retrieves the current account balance associated with your API key.

- Request Headers:
- x-api-key: <your_api_key_here> (required)

Sample Response:


```
{
    "statusCode": 200,
    "data": {
        "balance": 50  INR
     },
     "message": "Retrieved balance successfully.",
     "success": true
}
```


2. Create Order

Endpoint:
POST /api-service/order

Description:

Creates a new order for a product top-up.

- Request Headers:
- Content-Type: application/json (required) • x-api-key: <your_api_key_here> (required)

Request Body:

```
{
 "playerId": "1234",
 "zoneId": "124",
 "productId": "bgmi362_60197"
 “currency”: “INR”                    // “USD” or “INR”
}
```

Sample Response:

```
{
    "statusCode": 200,
    "data": {
          "orderId": "IN20250611210228XYZ",
           "status": "success",
           "productId": "bgmi362_60197",
           "title": "BGMI (60)",
           "price": 75 INR
     },
     "message": "Retrieved balance successfully.",
     "success": true }
```

3. Get Products

Endpoint:
GET /api-service/products?currency=INR // currency=INR OR currency=USD

Description:
Retrieves all the products.

- Request Headers:
- x-api-key: <your_api_key_here> (required)

Sample Response:

{
    "statusCode": 200,
    "data": [
        {
"productId": "pubg-mobile138_325961",
"productName": "PUBG Mobile (325)",
"price": "₹406.00"
        },
        {
"productId": "pubg-mobile138_325961",
"productName": "PUBG Mobile (325)",
"price": "₹406.00"
        },
    ],
    "message": "Retrieved products successfully. ",
    "success": true
}

Authentication & Security

- All requests require a valid x-api-key.
- Keep your API key private and rotate it periodically.
- The service does not use cookies or tokens for session-based auth.

Testing in Insomnia

You can test this service using Insomnia REST Client by importing the collection and setting up the API environment variable:

{
  "API": "https://1gamestopup.com/api/v1"
}

Error Handling

Typical error response format:

{

```
  "status": false,
  "error": "Invalid API key or missing parameters"
}
```