Busan API Service Documentation

Base URL

```
https://1gamestopup.com/api/v1
```

Authentication

All requests must include an **x-api-key** header:

```
x-api-key: <Your API Key>
```

1. Check Balance

GET `/api-service/balance?currency=INR`

Retrieves the current wallet balance associated with your API key. Use **currency=INR** or **currency=USD**.

Sample Response

```
{
  "statusCode": 200,
 "data": {
    "balance": "50.00 INR"
 },
 "message": "Retrieved balance successfully.",
 "success": true
}
```

2. Get Products

GET `/api-service/products?currency=INR`

Retrieves all available products with prices. Use **currency=INR** or **currency=USD**.

Sample Response

```
{
  "statusCode": 200,
 "data": [
    {
      "productId": "mobile-legends988_86990",
      "productName": "Mobile Legends (86)",
      "price": "Rs.102.00"
    },
```

```
    {
      "productId": "freefire-global368_110684",
      "productName": "Freefire Global (110)",
      "price": "Rs.74.29"
    }
  ],
  "message": "Retrieved products successfully.",
  "success": true
}
```

---

3. Validate Player

POST `/api-service/validate`

Validates a player ID before placing an order. Recommended to prevent failed orders.

Note: For single-field games (Free Fire, PUBG Mobile etc.), omit the zoneId field.

Request Body

```
{
  "productId": "mobile-legends988_86990",
  "playerId": "109774957",
  "zoneId": "2569"
}
```

Genshin / ZZZ / Honkai Star Rail — use server code as zoneId:

```
{
  "productId": "genshin-impact742_60112",
  "playerId": "808251881",
  "zoneId": "os_asia"
}
```

Available server codes: os_asia, os_euro, os_usa, os_cht

Success Response

```
{
  "statusCode": 200,
  "data": {
    "valid": true,
    "username": "Busan.",
    "playerId": "109774957",
    "zoneId": "2569"
  },
```

```
  "message": "Player validated successfully",
  "success": true
}
```

Error Response

```
{
  "statusCode": 400,
  "message": "Invalid player ID or server ID",
  "success": false
}
```

---

4. Create Order

POST `/api-service/order`

Creates a new top-up order. Balance is deducted from your wallet.

Request Body

```
{
  "playerId": "109774957",
  "zoneId": "2569",
  "productId": "mobile-legends988_86990",
  "currency": "INR"
}
```

Success Response

```
{
  "statusCode": 200,
  "data": {
    "orderId": "IN20260404112344585",
    "status": "success",
    "productId": "mobile-legends988_86990",
    "title": "Mobile Legends (86)",
    "price": "102.00 INR"
  },
  "message": "Order Successful",
  "success": true
}
```

Security & Error Handling

- All requests require a valid x-api-key header
- Keep your API key private — do not expose in frontend code
- Rotate your API key periodically from your account dashboard
- No cookies or session tokens used — stateless API key auth only

Typical Error Response

```
{
  "statusCode": 403,
 "message": "Invalid or inactive API key.",
 "success": false
}
```

Testing with curl

Validate Player:

```
curl -X POST https://1gamestopup.com/api/v1/api-service/validate \
 -H "Content-Type: application/json" \
 -H "x-api-key: YOUR_API_KEY" \
 -d '{"productId":"mobile-legends988_86990","playerId":"109774957","zoneId":"2569"}
'
```

Place Order:

```
curl -X POST https://1gamestopup.com/api/v1/api-service/order \
 -H "Content-Type: application/json" \
 -H "x-api-key: YOUR_API_KEY" \
 -d '{"productId":"mobile-legends988_86990","playerId":"109774957","zoneId":"2569",
"currency":"INR"}'
```