

OpenSEO Google Ads Keyword Planner

Tool Design and Compliance Documentation

Keyword research and historical metrics only

Applicant / tool	OpenSEO - self-hosted SEO research workspace
Primary website	https://openseo.mostee.com
Google Cloud project	321604194945
Manager account (MCC)	604-324-3227
API contact	rainco2026@gmail.com
Document date	16 August 2026

Prepared for Google Ads API Basic Access review

SECTION 1

Product overview

Purpose, business model, audience, and API scope

OpenSEO is an open-source and self-hostable SEO research and workflow platform. It combines keyword research, rank tracking, competitor analysis, backlink analysis, site auditing, Google Search Console data, and AI-assisted SEO workflows in one project workspace. The software is free and open source; deployments may use third-party data services that are billed separately.

The Google Ads Keyword Planner is a personal extension within OpenSEO. It uses the Google Ads API only to obtain keyword ideas and historical keyword metrics for manual SEO research. It does not create, edit, pause, or delete campaigns, ads, ad groups, budgets, billing arrangements, users, audiences, conversions, or remarketing data.

Permissible use requested: Researching keywords and recommendations. The tool requires KeywordPlanIdeaService access, which is restricted at Explorer Access and available after Basic Access approval.

Intended audience

- The current production deployment is privately controlled and protected by access controls.
- Access is limited to the owner and explicitly authorized team members who perform SEO and content research.
- The developer token in this application is not distributed with the open-source code and is not shared with unrelated self-hosted deployments.
- Each independent self-hosted deployment must configure and secure its own Google credentials and comply with Google Ads API requirements.

Business model

OpenSEO is positioned as an open-source alternative to commercial SEO suites. The application supports a hosted website and self-hosted deployments. The Google Ads integration described here is not sold as an advertising-management service and does not allow customers to supply or reuse this developer token.

SECTION 2

User interface and workflow

A user-initiated, read-only keyword research flow

Figure 1. OpenSEO Google Ads Keyword Planner - Keyword Ideas input screen. The customer identifier is masked in the user interface.

Keyword Ideas workflow

- 1 An authorized user opens a project and selects Google Ads Planner.
- 2 The page displays the configured customer in masked form, plus project-derived language, geographic market, currency, and API version.
- 3 The user enters up to ten seed keywords, an optional HTTPS landing page URL, or both.
- 4 The browser sends the validated request to an authenticated OpenSEO server function.
- 5 The Worker obtains a short-lived OAuth access token and calls the Google Ads API from the server.
- 6 OpenSEO normalizes the response. The user reviews the results and may explicitly save selected keywords to the project.

SECTION 3

Functional design

Supported operations, validation, and returned data

User function	Google Ads API method	Inputs	Purpose
Keyword ideas	KeywordPlanIdeaService.GenerateKeywordIdeas	Seed keywords and/or HTTPS URL; project language and geo target	Generate related keyword suggestions and planning metrics
Historical metrics	KeywordPlanIdeaService.GenerateKeywordHistoricalMetrics	Explicit keywords; project language and geo target	Retrieve monthly search history and aggregate planning metrics

Inputs and safeguards

- Keyword inputs are trimmed, length-limited, deduplicated, and validated at the server trust boundary.
- Landing page input, when provided, must be an HTTPS URL; adult keyword inclusion is disabled.
- The project market determines Google Ads language and geographic targeting automatically.
- Requests use GOOGLE_SEARCH as the keyword plan network.
- The application applies timeouts, limited retries for transient failures, and rate-limit handling.

Data returned to the user

Field	Use in OpenSEO	Storage behavior
Keyword and close variants	Display and keyword selection	Saved only when a user explicitly saves selected rows
Average monthly searches	Search-demand assessment	Mapped to a normalized project keyword record when saved
Monthly search volumes	Trend and seasonality review	Returned for display; retained only through explicit project actions
Competition and index	Relative advertising competition signal	Displayed as planning context
Average CPC and bid ranges	Commercial-intent context	Converted from micros to the configured currency

SECTION 4

System architecture and account model

Server-side OAuth, explicit account relationships, and least exposure

Request path

- 1 Authorized browser session - a user submits a keyword research request inside an OpenSEO project.
- 2 OpenSEO server function - authenticates the session, validates inputs, and resolves market settings.
- 3 Keyword Planner service - prepares the permitted read-only planning request.
- 4 OAuth token exchange - the Cloudflare Worker obtains a short-lived access token from Google's OAuth service.
- 5 Google Ads API - the Worker sends the OAuth bearer token, developer token, login customer ID, and target customer ID.
- 6 Normalized response - only fields required by the product are returned; credentials never enter the browser response.

Account relationship

OAuth user	A Google user authorized for the manager/client hierarchy
Manager account	604-324-3227 - supplied as login-customer-id
Target customer	920-177-7964 - supplied as the customer resource in requests
Google Cloud project	321604194945 - owns the OAuth client and has Google Ads API enabled
Developer token	Issued from the manager account API Center; requested access level: Basic

Credential boundary: OAuth client secret, refresh token, and developer token are Worker secrets. They are never rendered in HTML, sent to the browser, included in exported keyword data, or committed to the source repository.

SECTION 5

Data handling and security controls

How credentials, requests, responses, and logs are protected

Control area	Implementation
Authentication	The deployment is protected by access controls. Server functions require an authenticated application session and project context.
Secret storage	OAuth client secret, refresh token, and developer token are stored as Cloudflare Worker secrets and read only at runtime.
Transport	Browser-to-Worker, OAuth token exchange, and Google Ads API requests use HTTPS.
Token handling	The refresh token remains server-side. Short-lived access tokens are obtained only as needed and are not persisted in browser storage.
Input validation	Runtime schemas validate keywords, URLs, identifiers, currency codes, configuration shape, and Google response fields.
Response minimization	Only keyword planning fields required by the interface are mapped instead of exposing the full upstream response.
Logging	Structured logs retain safe status, error classification, message, and request ID. Authorization headers and credentials are excluded.
User-visible identifiers	The target customer ID is masked in the interface; only the final four digits are shown.

Retention and user control

Keyword ideas and metrics are displayed in response to a user request. OpenSEO does not automatically create permanent records for every API result. A user must select rows and invoke the save action before normalized keyword records are stored in the project database. Project data remains under the control of the deployment owner and authorized users.

No advertising mutations: The integration contains no workflow or API call for campaign management, account creation, user management, billing, payment, conversion tracking, Customer Match, audience creation, or remarketing.

SECTION 6

Policy boundaries and operational controls

Designed for transparent, user-directed keyword research

Permitted behavior

- Every Google Ads API request is initiated by an authorized user action.
- The purpose is limited to keyword research, recommendations, and historical planning metrics.
- Results support manual SEO and content-planning decisions; they are not used to claim guaranteed advertising outcomes.
- Google Ads data is labeled by source and presented with market and currency context.
- The application respects API errors, quota responses, token revocation, and access-level restrictions.

Explicitly out of scope

- Automated campaign, ad, budget, bidding, billing, or account changes
- User invitations or Google Ads account access management
- App conversion tracking, offline conversions, Customer Match, or remarketing
- Resale, sublicensing, publication, or distribution of the developer token
- Providing unrelated third parties with direct or indirect credential access
- Bulk scraping or unattended harvesting of Google Ads data

Monitoring and incident response

The deployment owner monitors structured Worker logs and Google Ads API responses. If a credential is suspected to be exposed, it is rotated or revoked and the Worker secret is updated. Authentication failures, expired grants, quota limits, permission errors, malformed responses, and upstream availability failures are handled as explicit error categories.

Access request: Basic Access is requested because KeywordPlanIdeaService planning methods are restricted under Explorer Access. The requested scope does not require unlimited Standard Access operations.

APPENDIX

Technical inventory and reviewer references

Endpoints, configuration categories, and official documentation

External endpoints used

Endpoint / service	Method	Purpose
https://oauth2.googleapis.com/token	POST	Exchange the server-held refresh token for a short-lived OAuth access token
googleads.googleapis.com/v25/...:generateKeywordIdeas	POST	Retrieve keyword ideas and associated planning metrics
googleads.googleapis.com/v25/...:generateKeywordHistoricalMetrics	POST	Retrieve historical search metrics for supplied keywords

Configuration categories

Category	Examples	Location
OAuth application	Client ID and client secret	Server runtime; secret value stored in Worker secrets
Google Ads authorization	Refresh token and developer token	Worker secrets only
Account routing	Target customer ID and login customer ID	Validated server configuration
Presentation	API version and currency code	Validated configuration and masked UI metadata

Official reviewer references

- Developer token: <https://developers.google.com/google-ads/api/docs/api-policy/developer-token>
- Access levels and permissible use:
<https://developers.google.com/google-ads/api/docs/api-policy/access-levels>
- OAuth and REST authorization: <https://developers.google.com/google-ads/api/rest/auth>
- Google Ads API call structure:
<https://developers.google.com/google-ads/api/docs/concepts/call-structure>

Application contact

Contact email	rainco2026@gmail.com
Product website	https://openseo.mostee.com
Production deployment	https://openseo.steer.workers.dev
Requested access	Basic Access - Researching keywords and recommendations

End of document