

# Design document for BDS feature:

## Workspace Notifications

### Overview and Requirements:

For the feature overview and details, refer to the document **Workspace Notifications** [\[1\]](#).

### Implementation Details:

The following changes are required to implement the feature:

#### 1. **Introducing a new flag for workspaces:**

- a. A new flag should be added to the table *fds\_package\_ext* named *is\_notification\_enabled* and the data type should be String.
- b. The possible values of *is\_notification\_enabled* should be "Y" (Workspace notification is enabled) and "N" (Workspace notification is disabled).

#### 2. **Introducing a new field for workspaces:**

- a. A new field should be added to the table *fds\_package\_ext* named *default\_notification\_settings* and the data type will be String.
- b. The default notification settings will be stored as a JSON string in the *default\_notification\_settings* field.

#### 3. **Upgrading database:**

- a. The *is\_notification\_enabled* should be set to "Y" and *default\_notification\_settings* should be kept *NULL* for all existing packages initially by using data model manager.
- b. A new property named "workspace.default.notification.settings" with an initial value (initial default notification settings converted to JSON string) should be entered into the table *fds\_init\_property*.

#### 4. **Setting the values of workspace notifications while creating workspace:**

- a. While creating a workspace if the notifications are enabled "Y" should be stored to *is\_notification\_enabled*.
- b. The value of notification settings should be processed and converted to a JSON string and stored to *default\_notification\_settings* field.
- c. If the notifications are disabled then *NULL* should be stored to *default\_notification\_settings* field.
- d. The *fds\_package\_user\_settings* table should be populated for all the users of the workspace according to the default notification settings.

#### 5. **Updating default workspace notifications:**

- a. The values of *notification\_enabled* and *default\_notification\_settings* of *fds\_package\_ext* table should be updated accordingly.
- b. If "Apply to all users" is enabled then the *fds\_package\_user\_settings* table should be updated for all the users of the workspace according to the new default notification settings.

**6. Updating workspace notifications for a specific user:**

- a. The *fds\_package\_user\_settings* table should be updated according to the new notification settings only for the specific user of the workspace.

**7. Updating notifications for all the workspaces of a specific user:**

- a. The *fds\_package\_user\_settings* table should be updated according to the new notification settings for all the workspaces of the user.

**References**

1. Workspace Notifications (Spec - BDS Secure Workspace Notifications)

**History**

Date	Version	Author	Comments
October 2, 2014	0.1	Raine	• Created.
October 9, 2014	0.2	Raine	• Added section 3.b and 7