NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in COADIS 123K

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (the Act) and Regulations. This notification has been carried out under the signed cooperative arrangement with Canada. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health. In conjunction with the Department of the Environment, NICNAS conducts the risk assessment for environmental, public health and occupational health and safety.

For the purposes of subsection 78(1) of the Act, this Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

March 2016

Table of Contents

SUM	MARY	. 2
CON	CLUSIONS AND REGULATORY OBLIGATIONS	. 2
ASS	ESSMENT DETAILS	. 4
	APPLICANT AND NOTIFICATION DETAILS	
	IDENTITY OF POLYMER	
3.	PLC CRITERIA JUSTIFICATION	. 4
4.	PHYSICAL AND CHEMICAL PROPERTIES	. 4
5.	INTRODUCTION AND USE INFORMATION	. 4
6.	HAZARD ASSESSMENT	. 5

SUMMARY

The following details will be published in the NICNAS Chemical Gazette:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1334	Arkema Pty Ltd Interchem Pty Ltd	Polymer in COADIS 123K	No	≤ 40 tonnes per annum	Additive in paints

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

• No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the (M)SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for Spray Painting and Powder Coating (Safe Work Australia, 2015) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified

polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from additive in paints, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

Arkema Pty Ltd (ABN: 44 000 330 772) Suite 103, Level 1, 313 Canterbury Road

CANTERBURY VIC 3126

Interchem Pty Ltd (ABN: 74 057 313 630)

20 Harper Street

ABBOTSFORD VIC 3067

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities and use details.

2. IDENTITY OF POLYMER

Marketing Name(s)

COADISTM 123 K (24% notified polymer in aqueous solution)

Molecular Weight

Number Average Molecular Weight (Mn) is > 1,000 Da

3. PLC CRITERIA JUSTIFICATION

Criterion met
Yes
Not applicable
Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa Liquid (polymer solubilised in water)

Glass Transition Temp 90 °C

Density $1,080 \text{ kg/m}^3 \text{ at } 20 \text{ °C}$ Water Solubility > 100 g/L at 20 °C

Dissociation Constant pKa = 6

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	20	30	30	40	40

Use

The notified polymer will not be manufactured in Australia. It will be imported in aqueous solution at 24% concentration for reformulation in Australia. The notified polymer will be blended into water-based paints by paint manufacturers. The final concentration of the notified polymer in end-use water-based paints will be $\leq 1\%$. The paints will be available to the general public for do-it-yourself (DIY) application.

6. HAZARD ASSESSMENT

The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. This is supported by tests submitted on a 24% solution of the notified polymer for the following toxicological endpoints.

Endpoint	Result	Effects Observed?	Test Guideline
1. Rat, acute oral	LD50> 2000 mg/kg bw	no	OECD TG 401
2. Rabbit, skin irritation	Slightly irritating	yes	OECD TG 404
3. Rabbit, eye irritation	Slightly irritating	yes	OECD TG 405
4. Fish Toxicity	LC50 > 100 mg/L (96h)	no	EEC Method C1
5. Daphnia Toxicity	EC50 > 100 mg/L (24 & 48h)	no	EEC Method C2
6. Algal Toxicity	EC50 > 100 mg/L (72h)	yes	EEC Method C3

All results were indicative of low hazard.

Although not considered in this risk assessment, NICNAS notes that the notified polymer contains residual monomers that are classified as hazardous according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia. These are not present in the notified polymer as introduced above the cut off concentrations for classification.