# NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

#### POLYMER OF LOW CONCERN PUBLIC REPORT

#### Polymer in T-40139 Intermediate for Sprayable Sealant Part B

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (Cwlth) (the Act) and Regulations. This notification has been carried out under the signed cooperative arrangement with Canada. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health and Ageing. In conjunction with the Department of Sustainability, Environment, Water, Population and Communities, NICNAS conducts the risk assessment for environmental, public health and occupational health and safety.

For the purposes of subsection 78(1) of the Act, this Full Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Full Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

March 2013

# **Table of Contents**

| SUMMAR | 27                                |
|--------|-----------------------------------|
|        | SIONS AND REGULATORY OBLIGATIONS2 |
|        | IENT DETAILS                      |
|        | LICANT AND NOTIFICATION DETAILS   |
|        | NTITY OF POLYMER                  |
|        | CRITERIA JUSTIFICATION            |
|        | SICAL AND CHEMICAL PROPERTIES4    |
|        | RODUCTION AND USE INFORMATION     |
|        | ARDASSESSMENT4                    |

# **SUMMARY**

The following details will be published in the NICNAS Chemical Gazette:

| ASSESSMENT<br>REFERENCE | APPLICANT(S)                        | CHEMICAL OR<br>TRADE NAME                                    | HAZARDOUS<br>SUBSTANCE | INTRODUCTION<br>VOLUME | USE                                      |
|-------------------------|-------------------------------------|--|------------------------|------------------------|--|
| PLC/1125                | PPG Industries<br>Australia Pty Ltd | Polymer in T-40139 Intermediate for Sprayable Sealant Part B | No                     | ≤ 50 tonnes per annum  | A component of sealant used on aircrafts |

# **CONCLUSIONS AND REGULATORY OBLIGATIONS**

#### **Human Health Risk Assessment**

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

#### **Environmental Risk Assessment**

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

# **Health and Safety Recommendations**

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself; however, these should be selected on the basis of all ingredients in the formulation.
  - Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.
- If aerosols are formed during the use of the notified polymer, engineering controls (i.e., local exhaust ventilation) and respiratory protection should be used to prevent inhalation exposure.
- A copy of the (M)SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2012) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System for the Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

#### **Environmental Recommendations**

 No specific control measures are required to minimise release of the notified polymer to the environment.

#### **Disposal**

• The notified polymer should be disposed of to landfill.

#### **Emergency Procedures**

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

# **Secondary Notification**

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
  - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.
     or
- (2) Under Section 64(2) of the Act; if
  - the function or use of the notified polymer has changed from a component of sealant used on aircrafts, or is likely to change significantly;
  - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
  - the notified polymer has begun to be manufactured in Australia;
  - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

# (Material) Safety Data Sheet

The (M)SDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

# **ASSESSMENT DETAILS**

#### 1. APPLICANT AND NOTIFICATION DETAILS

# **Applicants**

PPG Industries Australia Pty Ltd (ABN: 82 055 500 939)

23 Ovata Drive

**TULLAMARINE VIC 3043** 

# **Exempt Information (Section 75 of the Act)**

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, reactive functional groups, polymer constituents, residual monomers/impurities, use details and import volume

#### 2. IDENTITY OF POLYMER

#### **Marketing Name(s)**

T-40139 Intermediate for Sprayable Sealant Part B (product containing the notified polymer)

#### Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 Da

# 3. PLC CRITERIA JUSTIFICATION

| Criterion  | Criterion met |
|--|---------------|
| Molecular Weight Requirements                          | Yes           |
| Functional Group Equivalent Weight (FGEW) Requirements | Yes           |
| Low Charge Density                                     | Yes           |
| Approved Elements Only                                 | Yes           |
| Stable Under Normal Conditions of Use                  | Yes           |
| Not Water Absorbing                                    | Yes           |
| Not a Hazard Substance or Dangerous Good               | Yes           |

The notified polymer meets the PLC criteria.

#### 4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa Reddish brown to brown, clear liquid

Glass Transition Temp -52°C

Density  $1,197 \text{ kg/m}^3 \text{ at } 20^{\circ}\text{C}$ 

Water Solubility Not determined. The notified polymer reacts with water.

Dissociation Constant pKa estimated to be 5.32

Reactivity The notified polymer reacts with environmental moisture to

form high MW polymer.

Degradation Products

None under normal conditions of use

### 5. INTRODUCTION AND USE INFORMATION

# Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

| Year   | 1      | 2      | 3      | 4      | 5      |
|--------|--------|--------|--------|--------|--------|
| Tonnes | 1 - 50 | 1 - 50 | 1 - 50 | 1 - 50 | 1 - 50 |

#### Use

The notified polymer will not be manufactured in Australia. It will be imported into Australia at a concentration of 60 - 90% as a component of one part of a two-part aircraft sealant and will be applied by spray.

Products containing the notified polymer will not be reformulated in Australia.

# 6. HAZARDASSESSMENT

The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. This is supported by tests on a product containing the notified polymer submitted on the following toxicological endpoints.

| Endpoint           | Result                 | Effects   | Test Guideline |
|--------------------|------------------------|-----------|----------------|
|                    |                        | Observed? |                |
| 1. Rat, acute oral | LD50 > 2,000  mg/kg bw | No        | OECD TG 425    |

| <ul><li>2. Skin sensitisation - LLNA</li><li>3. Genotoxicity - bacterial</li></ul> | Evidence of sensitisation | Yes | OECD TG 429 (LLNA) |
|--|---------------------------|-----|--------------------|
|  | Non mutagenic             | No  | OECD TG 471        |
| reverse mutation   |                           |     |                    |

In the local lymph node assay (LLNA) for the notified polymer, slight erythema of the right ears of 2 animals at the low-dose group was observed and was not considered to have a toxicological significance on the activity of the lymph nodes. Enlarged lymph nodes in all animals at the high-dose group were noted. The assay results indicated that the product containing the notified polymer at 60 - 90% was sensitising. However, it was noted that the sensitising effect is likely to be caused by other hazardous ingredients of the product.