NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in RC-11050

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (the Act) and Regulations. This notification has been carried out under the signed cooperative arrangement(s) with Canada. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

May 2017

Table of Contents

1	APPLICANT AND NOTIFICATION DETAILS	4
	IDENTITY OF POLYMER	
3.	PLC CRITERIA JUSTIFICATION	. 4
4.	INTRODUCTION AND USE INFORMATION	. 4
5	HAZARD ASSESSMENT	5

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1411	Axalta Coating Systems Australia Pty Ltd	Polymer in RC- 11050	No	≤ 30 tonnes per annum	Component of industrial coatings

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health and Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public or to the environment.

Health and Safety Recommendations

• Water insoluble high molecular weight polymers used in the respirable size range ($< 10 \mu m$) have the potential to cause lung overloading. Respiratory protection and local exhaust ventilation should be used to prevent inhalation exposure.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2015) or relevant State or Territory Code of Practice.
- A copy of the (M)SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these

circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria;

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from a component of industrial coatings, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of products containing the notified polymer were provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicant

Axalta Coating Systems Australia Pty Ltd (ABN: 53 158 497 655)

15-23 Melbourne Road RIVERSTONE NSW 2765

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, analytical data, polymer constituents, residual monomers/impurities, use details and import volume.

Notification in Other Countries

The notified polymer was assessed in Canada under the Schedule 9 RRR (2011).

2. IDENTITY OF POLYMER

Marketing Name(s)

RC-11050 (product containing the notified polymer at < 40% concentration)

Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 Da

3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	< 10	10 - 20	10 - 20	20 - 30	20 - 30

Use

The notified polymer will be imported as a resin component of industrial and automotive paints. No local reformulation is expected. The finished coatings containing the notified polymer will be applied by professional spray painters in spray booths at industrial sites and refinish shops. No products containing the notified polymer will be made available to the public.

5. HAZARD ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be assumed to be of low hazard.

However, the notified polymer will be used in spray applications and is a water-insoluble high molecular weight polymer with Mn > 10,000 Da. Inhalation of polymers with molecular weights > 70,000 Da has been linked with irreversible lung damage due to lung overloading and impaired clearance of particles from the lung, particularly following repeated exposure (US EPA, 2015). There is a data gap for polymers with MW between 10,000 and 70,000 Da, and uncertainty may exist. If the notified polymer is inhaled at low levels and/or infrequently, it is assumed that it will be cleared from the lungs.

Finished coatings containing the notified polymer will only be used by professional spray painters in spray booths designed in compliance with AS/NZS 4114:2003. Given control measures in place to minimise inhalation, the notified polymer is not considered to pose an unreasonable risk to the health of workers. No products containing the notified polymer will be made available to the public and therefore inhalation exposure to the notified polymer by members of the public is not expected.

BIBLIOGRAPHY

Safe Work Australia (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/spray-painting-and-powder-coating.

US EPA (2015) High Molecular Weight Polymers in the New Chemicals Program https://www.epa.gov/reviewing-new-chemicals-under-toxic-substances-control-act-tsca/high-molecular-weight-polymers-new (Accessed on 22 March 2017).