NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in NP010

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

August 2017

Table of Contents

SUM	IMARY	2
CON	ICLUSIONS AND REGULATORY OBLIGATIONS	2
ASS	ESSMENT DETAILS	4
1.	APPLICANT AND NOTIFICATION DETAILS	4
2.	IDENTITY OF POLYMER	4
3.	PLC CRITERIA JUSTIFICATION	4
4.	PHYSICAL AND CHEMICAL PROPERTIES	4
5.	INTRODUCTION AND USE INFORMATION	5
6.	HUMAN HEALTH RISK ASSESSMENT	5
7.	ENVIRONMENTAL RISK ASSESSMENT	5

SUMMARY

The following details will be published in the NICNAS Chemical Gazette:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1429	AHG Coatings Pty Ltd Nippon Paint (India) Pvt Ltd	Polymer in NP010	No	≤ 1 tonnes per annum	Component of coatings and paints

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

• No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified

polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from a component of coatings and paints, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

Safety Data Sheet

The SDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

AHG Coatings Pty Ltd (ABN: 33 609 750 558)

21 Old Aberdeen Place WEST PERTH WA 6005

Nippon Paint (India) Pvt Ltd (ARBN: 619 138 868)

C/o Thomson Geer

Level 25, 1 O'Connell Street

SYDNEY NSW 2000

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)

NP010 (product containing the notified polymer at $\leq 45\%$)

Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 Da

3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa

Melting Point/Glass Transition Temp
Density

Colourless liquid
Not determined
990 kg/m³ at 25 °C*

Water Solubility Not determined. Expected to be low based on the

predominantly hydrophobic structure and high molecular

weight

Dissociation Constant The notified polymer does not contain functionality that is

expected to dissociate or ionise under environmental

conditions

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

^{*}Density of the product containing the notified polymer

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	< 1	< 1	< 1	< 1	< 1

Use

The notified polymer will be imported as a component of automotive refinish coatings. The notified polymer will not be reformulated or repackaged in Australia and will not be available to the general public. Products containing the notified chemical will be applied by spray.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. PLCs without significant ionic functionality are of low concern to the aquatic environment.

The notified polymer will be imported to Australia as a component of automotive refinish coatings. The imported products containing the notified polymer may be blended with other additives at enduser sites. Release of the notified polymer to the environment during import, storage, and transport is expected to be limited to accidental spills or leaks and residue in import packaging. During industrial use (mixing and transferring) it is estimated by the notifier that a maximum of < 2% of the total annual import volume of the notified polymer may remain as residues in the empty containers. Wastes from container residues and accidental spills are expected to be disposed of according to local regulation or be disposed of to landfill.

During use, coatings containing the notified polymer are expected to be applied by spray techniques. Therefore, the main release of the notified polymer is likely from overspray during use, and is estimated to account for up to 20% of the imported volume. The overspray will be collected and trapped onto filters prior to landfill disposal. The spray equipment will be cleaned using solvents. These wastes will be collected and disposed of via a licensed waste contractor.

The notified polymer contains a small proportion of biodegradable units. However, most of the notified polymer will be irreversibly incorporated within the coatings of the exterior of the metal products and expected to be stable. Coated articles will be either sent to landfill or subjected to metal recycling at the end of their useful lives. The notified polymer is expected to be thermally decomposed during the recycling of the metal substrates. In landfill, the notified polymer will be present as cured solids that will be neither bioavailable nor mobile.

Based on its high molecular weight, the notified polymer is not expected to cross biological membranes, and is therefore unlikely to bioaccumulate. The notified polymer is expected to eventually degrade to form oxides of carbon and water vapour by thermal decomposition or by abiotic and biotic processes.

Therefore, based on the low assumed hazard to aquatic organisms and low potential for aquatic exposure, the notified polymer is not expected to pose an unreasonable risk to the environment when used as proposed.