

File No: LTD/1290

April 2008

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME
(NICNAS)**

FULL PUBLIC REPORT

Polymer T3917 in Pro-Seal Sealants

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. This legislation is an Act of the Commonwealth of Australia. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health and Ageing, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Department of the Environment, Water, Heritage and the Arts.

For the purposes of subsection 78(1) of the Act, this Full Public Report may be inspected at our NICNAS office by appointment only at 334-336 Illawarra Road, Marrickville NSW 2204.

This Full Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	334 - 336 Illawarra Road MARRICKVILLE NSW 2204, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX	+ 61 2 8577 8888
Website:	www.nicnas.gov.au

**Director
NICNAS**

TABLE OF CONTENTS

<u>FULL PUBLIC REPORT</u>	3
1. APPLICANT AND NOTIFICATION DETAILS	3
2. IDENTITY OF CHEMICAL	3
3. COMPOSITION.....	3
4. PHYSICAL AND CHEMICAL PROPERTIES	3
5. INTRODUCTION AND USE INFORMATION	4
6. HUMAN HEALTH IMPLICATIONS.....	5
6.1 Exposure assessment	5
6.1.1 Occupational exposure	5
6.1.2 Public exposure.....	6
6.2 Human health effects assessment	6
6.3 Human health risk characterisation.....	6
6.3.1 Occupational health and safety	6
6.3.2 Public health	7
7. ENVIRONMENTAL IMPLICATIONS	7
7.1 Environmental Exposure & Fate Assessment.....	7
7.1.1 Environmental Exposure.....	7
7.1.2 Environmental fate	7
7.1.3 Predicted Environmental Concentration (PEC).....	7
7.2 Environmental effects assessment	7
7.3 Environmental risk assessment.....	8
8. CONCLUSIONS AND REGULATORY OBLIGATIONS	8
Hazard classification	8
Human health risk assessment	8
Environmental risk assessment	8
Recommendations	8
Regulatory Obligations.....	9
<u>APPENDIX A: PHYSICAL AND CHEMICAL PROPERTIES</u>	11
<u>BIBLIOGRAPHY</u>	13

FULL PUBLIC REPORT

Polymer T3917 in Pro-Seal Sealants

1. APPLICANT AND NOTIFICATION DETAILS

APPLICANT

PPG Industries Australia Pty Ltd (ABN 82 055 500 939)
21-23 Ovata Drive
Tullamarine VIC 3043

NOTIFICATION CATEGORY

Limited: Synthetic polymer with $M_n \geq 1000$ Da.

EXEMPT INFORMATION (SECTION 75 OF THE ACT)

Data items and details claimed exempt from publication:

Chemical Name, Other Names, CAS Number, Structural Formula, Molecular Weight, Spectral Data, Purity, Residual Monomers, Hazardous Impurities/Residual Monomers; Non-Hazardous Impurities/Residual Monomers; Additives and Adjuvants, Import Volume, and Identity of Manufacturers/Recipients

VARIATION OF DATA REQUIREMENTS (SECTION 24 OF THE ACT)

Variation to the schedule of data requirements is claimed as follows:

Vapour pressure, Hydrolysis as a function of pH, Partition coefficient, Adsorption/desorption, Dissociation constant, Flammability, Autoignition temperature.

PREVIOUS NOTIFICATION IN AUSTRALIA BY APPLICANT

None

NOTIFICATION IN OTHER COUNTRIES

Canada (1999)

2. IDENTITY OF CHEMICAL

MARKETING NAME

T3917

MOLECULAR WEIGHT

$M_n > 1,000$ Da

ANALYTICAL DATA

Reference IR and GPC spectra were provided.

3. COMPOSITION

DEGREE OF PURITY > 95%

4. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AT 20°C AND 101.3 kPa

Brown viscous liquid

Property	Value	Data Source/Justification
Melting Point/Freezing Point	Not determined	Test not conducted.
Pour Point	-23.6°C	Measured
Softening Point	-33.7°C	Measured
Glass Transition Temperature	-54.5°C	Measured

Boiling Point	177°C	MSDS
Density	1180 kg/m ³	Measured
Viscosity	102.4 Pa.s at 25°C	Measured
Vapour Pressure	< 1.3x10 ⁻⁹ kPa	Estimated. Molecular weight is > 1000 Da, which indicates that it is likely to have a vapour pressure of < 1.3x10 ⁻⁹ kPa (USEPA, 2007).
Water Solubility ^α	0.73	Measured
Hydrolysis as a Function of pH	Not determined	One functionality may hydrolyse readily but rate could be limited by poor water solubility.
Partition Coefficient (n-octanol/water)	log Pow < 3 for 85% and > 6.5 for 15% of the notified polymer mixture	Estimated
Adsorption/Desorption	log K _{OC} < 3	Estimated based on predicted low log Pow (despite its low water solubility).
Dissociation Constant	Not determined	Dissociation may occur, particularly on hydrolysis, however, it is likely to be limited due to low water solubility.
Particle Size	Not determined	N/A. The notified polymer is a liquid at room temperature.
Flash Point	121°C	Measured
Flammability	Not determined	Based on the flash point the notified polymer is not classified as flammable.
Autoignition Temperature	Not determined	The autoignition temperature will be > 121°C, based on its flash point.
Explosive Properties	Not expected to be explosive	Contains no explosives, and is imported as a paste without dust explosive hazard.
Refractive Index	1.5716	Measured
Ash Content	None	Measured
Acid Number ^β	5.5mg KOH/g	Measured
Mercaptan Equivalent ^δ	3252	Measured

^α The units associated with this value were not given. It is noted that the Environment Canada report (EC 1998) on the notified polymer assumes that the value would be 0.73%. For the purposes of the present report, the notified polymer will be assumed to have low water solubility.

^β The measured Acid Number is likely to indicate the presence of carboxylic acid groups within the polymer.

^δ The measured Mercaptan Equivalent indicates that there is a significant quantity of free thiol groups within the notified polymer.

DISCUSSION OF PROPERTIES

For full details of tests on physical and chemical properties, please refer to Appendix A.

Based on the flash point, the notified polymer is not classified as flammable according to the Australian Dangerous Goods classification (FORS, 2007). However, it is classified as a C1 combustible liquid according to the *National Standard for the Storage and Handling of Workplace Dangerous Goods* (NOHSC 2001).

Loss of Monomers, Other Reactants, Additives, Impurities

Stable under normal conditions of use. Following curing of the notified polymer, losses due to volatility, exudation or leaching are not expected to occur.

Degradation Products

None expected under normal conditions of use. In the event of a fire, combustion products of pyrolysis (oxygen limited) are likely to include miscellaneous hydrocarbons, water and oxides of carbon and sulphur.

Reactivity

The notified polymer is stable under normal conditions and reactivity to water and air is negligible.

5. INTRODUCTION AND USE INFORMATION

MODE OF INTRODUCTION OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

The notified polymer will be imported in a range of sealant products at concentrations between 1 and 90%. One such product, Pro-Seal 870, is a two-part sealant product, with Part B typically containing the notified polymer at concentrations of 1-10%, and Part A not containing the notified polymer.

MAXIMUM INTRODUCTION VOLUME OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

<i>Year</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>
<i>Tonnes</i>	< 1	< 1	< 1	< 1	< 1

PORT OF ENTRY

All major seaports throughout Australia, especially Melbourne.

IDENTITY OF MANUFACTURER/RECIPIENTS

PPG Industries Australia Pty Ltd.

TRANSPORTATION AND PACKAGING

The products containing the notified polymer will be imported into Australia in 20 L containers, 200 L drums, or plastic applicator containers. The product will then be transported by road or rail to customers. The applicator products will be sold in the original packages.

USE

The notified polymer is used in sealant products for aerospace industry applications.

OPERATION DESCRIPTION

No manufacture or reformulation of the notified polymer will occur in Australia.

Repackaging

Lids will be removed from the import containers, and transfer to a hopper will be performed using either a drum pump or a drum lift (for the 20L containers). The sealant product containing the notified polymer will then be extruded into two-compartment plastic applicator tubes. The tube compartment containing the notified polymer (Part B of the sealant product) will then be manually joined to the compartment containing Part A and placed within a Mylar foil bag (heat-sealed, nitrogen-filled and airtight). The tubes will then be packaged into cardboard boxes and may be stored on-site prior to distribution to customers. Small samples are used for quality control testing for shelf life.

Application

At the customer sites, prior to application of the sealant, Part B of the two-part sealant product will be injected into, and mixed manually with, Part A within the plastic applicator. Alternatively, mixing may be performed automatically by connecting the spoke of the applicator to an automatic mixer. A nozzle will then be attached to the applicator and a pressure gun will be used to pump the sealant out. Following application the equipment may be cleaned to remove any excess sealant. Each plastic applicator tube is designed for one use only and the entire contents of the tube will be applied to the substrate component.

The sealant will then be applied directly to the aerospace components, and may include application in confined spaces, such as fuel tanks.

6. HUMAN HEALTH IMPLICATIONS

6.1 Exposure assessment

6.1.1 Occupational exposure

NUMBER AND CATEGORY OF WORKERS

<i>Category of Worker</i>	<i>Number</i>	<i>Exposure Duration (hours/day)</i>	<i>Exposure Frequency (days/year)</i>
Transport and Storage Personnel	30	5	150
Manufacturing Personnel – Repackaging	25	8	250
Quality Assurance Personnel	10	2	100

EXPOSURE DETAILS

Transport and Storage

The notified polymer will be sealed within storage containers and as such, transport and storage workers are not expected to be exposed to the notified polymer, except if the packaging were accidentally breached.

Repackaging

During repackaging of the sealant products into applicator tubes accidental dermal or ocular exposure to the notified polymer (typically at concentrations of <10%, though possibly up to 90%) may occur. Significant exposure would be limited by performing such operations under general exhaust ventilation and the use of appropriate personal protective equipment (PPE) such as safety glasses, safety shoes, coveralls, apron and chemical resistant gloves.

Exposure of quality control personnel during testing may occur but is expected to be low as PPE will be worn, including chemical resistant gloves, safety shoes, eye protection and laboratory coats.

Application

Exposure to the notified polymer (typically at concentrations of <10%, though possibly up to 90%) during mixing of Part A and Part B of the sealant product is expected to be minimal, as it occurs within an enclosed applicator tube. The applicator tube allows the sealant product to be directly applied through a nozzle to the aerospace component, reducing worker exposure. Exposure will be further minimised by performing the operations under general exhaust ventilation. The use of PPE will be dependent upon the other components of the sealant products and the type of aerospace part to which it is applied, eg. in confined spaces, ventilation masks are likely to be worn.

6.1.2. Public exposure

The notified polymer will not be supplied directly to the public, so there will be no public exposure except in the occurrence of an accidental spill during transport. The public may come into contact with the notified polymer where it is used on aircrafts. However, in this form the notified polymer will be cured within the sealant, and will not be available for exposure.

6.2. Human health effects assessment

No toxicity data were submitted.

The notified polymer contains disulfide and thiol functional groups. Groups of this type are structural alerts for irritation or corrosion (Hulzebos 2005), and sensitisation (Barratt 1994). Whilst the relatively high molecular weight of the notified polymer may reduce the possibility of such effects, it should be noted that the proportion of low molecular weight species is significant (15-20% <1000, 10-15% <500). In addition, the chemical properties of the notified polymer, such as its water solubility and estimated partition coefficient ($\log P_{ow} = 1 - 4$ for majority of the notified polymer mixture) suggest that some dermal absorption may be possible. Hence, irritation, corrosion, and sensitisation effects of the notified polymer cannot be ruled out. It is noted that there have been several reports of skin effects such as contact allergies caused by polysulfide polymers, particularly from sealants used in the aircraft industry (Wilkinson 1993, Bruze 1996).

Classification

Based on the anticipated irritation (skin and eyes) and skin sensitisation effects, the notified polymer should be classified as hazardous under the *Approved Criteria for Classifying Hazardous Substances* (NOHSC, 2004). The notifier has independently applied hazard classifications to the notified polymer. The following risk phrases should be applied to the notified polymer:

R43 May cause sensitisation by skin contact

R36/38 Irritating to eyes and skin

6.3. Human health risk characterisation

6.3.1. Occupational health and safety

Dermal and ocular exposure of workers to the notified polymer may occur during its handling (repackaging and application). Given the relatively high concentrations at which the notified polymer may be present during such handling operations (up to 90% in some cases), skin and eye irritation, and/or skin sensitisation cannot be ruled out. Exposure is expected to be reduced by the use of engineering controls, the wearing of appropriate PPE and the enclosed nature of the applicator tubes. Whilst such measures should act to mitigate the health concerns, care should be taken by workers when handling products containing the notified polymer. Overall, the risk to occupational health and safety from the notified polymer is not considered to be unacceptable.

6.3.2. Public health

Members of the public will only occasionally come into contact with aerospace parts on which the notified polymer has been cured. As such, the risk to public health is considered to be low.

7. ENVIRONMENTAL IMPLICATIONS

7.1. Environmental Exposure & Fate Assessment

7.1.1 Environmental Exposure

RELEASE OF CHEMICAL AT SITE

The notified polymer will be imported in 20 L containers or 200 L drums and will not be manufactured in Australia. Local operations will include transport, storage and repackaging. Release to the environment during shipping, transport and warehousing will only occur in the unlikely event of accidental spills or leaks of the packaging.

The notified polymer is of high viscosity and release via evaporation is unlikely to occur. During repackaging approximately 1% (10 kg per annum) of the notified polymer will be spilt. These spills will be contained within plant bunding and disposed of by a licensed waste contractor. Less than 1% will be wasted through equipment cleaning. These washes will be stored in containers and disposed of by licensed waste contractors. Approximately 1% of the notified polymer may remain as residue in the drums. These will undergo drum recycling or be removed by licensed waste contractors. There will be no release to the environment or waterways during this process.

RELEASE OF CHEMICAL FROM USE

During use there will be minimal release of the notified polymer. However, as a worst case scenario, release of 1% of the notified polymer could be assumed during spills. This will be contained and disposed of by a licensed waste contractor. Approximately 1% (10 kg per annum) may remain in the tubing; this will be disposed of to licensed waste contractors. An additional 1% of the notified polymer may be lost during cleaning. This may be released in waterways. However, the release will be diffuse throughout Australia and is not likely to impact the environment.

RELEASE OF CHEMICAL FROM DISPOSAL

The notified polymer released on repackaging or during application will be disposed of predominantly by licensed waste contractors to landfill. There may be some drum recycling and minimal exposure to the environment that may occur as the result of cleaning of equipment in small applicator areas. Empty applicators will be land filled.

7.1.2 Environmental fate

The eventual fate of the notified polymer will ultimately depend on the substrate to which it is applied. At the end of the substrate's useful life, it is likely to undergo recycling processes and the notified polymer will be thermally decomposed to various oxides of carbon, sulfur, and water.

7.1.3 Predicted Environmental Concentration (PEC)

No significant concentrations of the notified polymer are expected in the aquatic environment based on the limited possibility for release and the low water solubility of the notified polymer. Therefore, the PEC for the notified polymer has not been calculated.

7.2. Environmental effects assessment

No ecotoxicity data were submitted. Non-ionic polymers of MW > 1000 are of limited concern to the aquatic compartment.

7.3. Environmental risk assessment

The notified polymer is not considered to pose an unacceptable risk to the environment based on its reported use pattern and its predicted low toxicity.

8. CONCLUSIONS AND REGULATORY OBLIGATIONS

Hazard classification

Based on the available data the notified chemical is classified as hazardous under the *Approved Criteria for Classifying Hazardous Substances* [NOHSC:1008(2004)]. The classification and labelling details indicated by the notifier are:

R43 May cause sensitisation by skin contact

R36/38 Irritating to eyes and skin

Human health risk assessment

Under the conditions of the occupational settings described, the notified polymer is not considered to pose an unacceptable risk to the health of workers.

When used in the proposed manner, the notified polymer is not considered to pose an unacceptable risk to public health.

Environmental risk assessment

The notified polymer is not considered to pose a risk to the environment based on its reported use pattern.

Recommendations

REGULATORY CONTROLS

Hazard Classification and Labelling

- Use the following risk phrases for products/mixtures containing the notified polymer:
 - Concentration ≥ 1% R43 May cause sensitisation by skin contact
 - Concentration ≥ 20% R36/38 Irritating to eyes and skin
- The following safety phrases should appear on the MSDS and label for the product containing the notified polymer:
 - S24 Avoid contact with skin
 - S36 Wear suitable protective clothing
 - S37 Wear suitable gloves

Health Surveillance

- As the notified polymer is a potential skin sensitizer, employers should carry out health surveillance for any worker who has been identified in the workplace risk assessment as having a significant risk of skin sensitisation.

CONTROL MEASURES

Occupational Health and Safety

- Employers should implement the following safe work practices to minimise occupational exposure during handling of the notified polymer:
 - Minimise spills and drips
 - Avoid skin and eye contact

- Employers should ensure that the following personal protective equipment is used by workers to minimise occupational exposure to the notified polymer:
 - Safety glasses
 - Gloves
 - Coveralls

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the MSDS should be easily accessible to employees.
- If products and mixtures containing the notified chemical are classified as hazardous to health in accordance with the *Approved Criteria for Classifying Hazardous Substances* [NOHSC:1008(2004)] workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

Disposal

- The notified polymer should be disposed of to landfill.

Emergency procedures

- Spills or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Regulatory Obligations

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the chemical under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified chemical, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified chemical is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the polymer has a number-average molecular weight of less than 1000;

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the chemical has changed from a sealant product for aerospace industry applications, or is likely to change significantly;
 - the amount of chemical being introduced has increased from one tonne per annum, or is likely to increase, significantly;
 - if the chemical has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the chemical on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

No additional secondary notification conditions are stipulated.

Material Safety Data Sheet

The MSDS of the notified polymer and products containing the notified polymer provided by the notifier were reviewed by NICNAS. The accuracy of the information on the MSDS remains the responsibility of the applicant.

APPENDIX A: PHYSICAL AND CHEMICAL PROPERTIES

Pour Point -23.6°C

Method	Thermomechanical Analysis
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988a)

Softening Point -33.7°C

Method	Thermomechanical Analysis
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988b)

Glass Transition Temperature -54.5°C

Method	Differential Scanning Calorimetry
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988c)

Density 1180 kg/m³

Method	ASTM E-12
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988d)

Viscosity 102.4 Pa.s at 25°C

Method	ASTM 1824
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988e)

Water Solubility 0.73

Method	ASTM D-1776
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification. The units associated with this value are not given.
Test Facility	Products Research and Chemical Corporation (1988f)

Hydrolysis as a Function of pH Measurement was not conducted

Remarks	Groups contained in the notified chemical may hydrolyse in water; however, it is difficult to test due to the expected limited water solubility. Considering the use pattern of the notified chemical, hydrolysis will not be a concern.
---------	--

Partition Coefficient (n-octanol/water) log Pow < 3 for 85% and > 6.5 for 15% of the notified polymer mixture

Method	Measurement not conducted
Remarks	Estimated and calculated based on data for an analogue polymer notified as LTD/1291, where HPLC TG 117 was employed.

Flash Point 121°C

Method	Pensky-Martin Closed Cup ASTM D-93
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988g)

Refractive Index 1.5716

Method	ASTM 1747 (25°C)
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988h)

Ash Content None

Method	ASTM D-1131
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988i)

Acid Number 5.5 mg KOH/g

Method	ASTM D-1638
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988j)

Mercaptan Equivalent 3252

Method	Iodine Titration
Remarks	A test report was not provided with the notification submission. The value, test method and test result were provided as attachments to the Canada substance notification.
Test Facility	Products Research and Chemical Corporation (1988k)

BIBLIOGRAPHY

- Barratt M.D., Basketter D.A., Chamberlain M., Payne M.P., Admans G.D., Langowski L.J. (1994). An expert system rulebase for identifying contact allergens. *Toxic in Vitro*. 8(5): 1053-1060.
- Bruze M., Edénholm M., Engström K., Svensson G. (1996). Occupational dermatoses in a Swedish aircraft plant. *Contact Dermatitis*. 24: 336-340.
- Environment Canada (1998) NSN Health Assessment Summary. (unpublished NSN document provided by Environment Canada).
- FORS (Federal Office of Road Safety) (1998) Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code), 6th Edition, Canberra, Australian Government Publishing Service
- Hulzebos E., Walker J.D., Gerner I., Schlegel K., (2005). Use of structural alerts to develop rules for identifying chemical substances with skin irritation or skin corrosion potential. *QSAR Comb. Sci.* 24: 332-342.
- NOHSC (1994) National Code of Practice for the Labelling of Workplace Substances [NOHSC:2012(1994)]. National Occupational Health and Safety Commission, Canberra, Australian Government Publishing Service.
- NOHSC (2001) *National Standard for the Storage and Handling of Workplace Dangerous Goods* [NOHSC:1015(2001)]. National Occupational Health and Safety Commission, Canberra, Australian Government Publishing Service.
- NOHSC (2004) Approved Criteria for Classifying Hazardous Substances, 3rd edition [NOHSC:1008(2004)]. National Occupational Health and Safety Commission, Canberra, AusInfo.
- NOHSC (2003) National Code of Practice for the Preparation of Material Safety Data Sheets, 2nd edition [NOHSC:2011(2003)]. National Occupational Health and Safety Commission, Canberra, Australian Government Publishing Service.
- Products Research & Chemical Corporation (1988a), T-3917: Pour Point. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988b), T-3917: Softening Point. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988c), T-3917: Glass Transition Temperature. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988d), T-3917: Density. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988e), T-3917: Viscosity. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988f), T-3917: Solubility in Water. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988g), T-3917: Flash Point. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988h), T-3917: Refractive Index. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988i), T-3917: Ash Content. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988j), T-3917: Acid Number. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- Products Research & Chemical Corporation (1988k), T-3917: Mercaptan Equivalent. Products Research & Chemical Corporation, California, USA (Unpublished report submitted by the notifier).
- United Nations (2003) Globally Harmonised System of Classification and Labelling of Chemicals (GHS). United Nations Economic Commission for Europe (UN/ECE), New York and Geneva.
- US EPA (2007) Interpretive Assistance for the Assessment of Polymers.

Wilkinson S.M., Beck, M.H. (1993). Allergic contact dermatitis from sealants containing polysulphide polymers (Thiokol®). *Contact Dermatitis*, 29:273-274.