

NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in SUPERPAINT® Interior Satin Latex Wall Paint, High Reflective White

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX:	+ 61 2 8577 8888
Website:	www.nicnas.gov.au

**Director
NICNAS**

July 2015

Table of Contents

SUMMARY	2
CONCLUSIONS AND REGULATORY OBLIGATIONS.....	2
ASSESSMENT DETAILS.....	4
1. APPLICANT AND NOTIFICATION DETAILS.....	4
2. IDENTITY OF POLYMER	4
3. PLC CRITERIA JUSTIFICATION	4
4. PHYSICAL AND CHEMICAL PROPERTIES.....	4
5. INTRODUCTION AND USE INFORMATION	5
6. HUMAN HEALTH RISK ASSESSMENT.....	5
7. ENVIRONMENTAL RISK ASSESSMENT	5

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1293	Sherwin-Williams Diversified Brands (Australia) Pty Ltd Woolworths Limited	Polymer in SUPERPAINT® Interior Satin Latex Wall Paint, High Reflective White	No	≤ 50 tonnes per annum	Additive in paints and coatings

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation, noting that the formulation may contain hazardous impurities classified as R43.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the (M)SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2012) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

- Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.or
- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from an additive in paints and coatings, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of the notified polymer and/or products containing the notified polymer were provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

Sherwin-Williams Diversified Brands (Australia) Pty Ltd (ACN: 604 851 658)
c/o Squire Patton Boggs (AU)
Level 21, 300 Murray Street
PERTH WA 6000

Woolworths Limited (ABN: 88 000 014 675)
3 City View Road
PENNANT HILLS NSW 2120

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)

SUPERPAINT® Interior Satin Latex Wall Paint, High Reflective White ($\leq 15\%$ notified polymer)

Molecular Weight

Number Average Molecular Weight (Mn) is $> 1,000$ Da

3. PLC CRITERIA JUSTIFICATION

<i>Criterion</i>	<i>Criterion met</i>
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa	Liquid dispersion*
Melting Point/Glass Transition Temp	Not determined. The notified polymer is not isolated from dispersion
Specific gravity	1.07*
Water Solubility	Expected to be dispersible, based on the presence of hydrophilic functional groups in the polymer structure, and use in aqueous systems
Reactivity	Stable under normal environmental conditions
Degradation Products	None under normal conditions of use
*as manufactured	

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	≤ 50	≤ 50	≤ 50	≤ 50	≤ 50

Use

The notified polymer will not be manufactured or reformulated in Australia. The notified polymer (at ≤ 15% concentration) will be introduced as an additive in paints and coating products. The products containing the notified polymer will be used by workers and members of the public and will be applied to surfaces by brush, roller and/or spray.

6. HUMAN HEALTH RISK ASSESSMENT

The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. This is supported by two toxicology studies provided by the notifier on a mixture containing approximately 40% notified polymer. The test substance was of low toxicity (LD₅₀ > 5000 mg/kg bw) in an acute oral toxicity study on female rats and was non-mutagenic in a bacterial reverse mutation test.

The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

Although not considered in this risk assessment, NICNAS notes that the notified polymer contains residual monomers that are classified as hazardous according to the *Approved Criteria for Classifying Hazardous Substances* (NOHSC, 2004). At least one of the residual monomers, classified as R43 – may cause sensitisation by skin contact, is present in the notified polymer above the cut off concentration for classification.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. The notified polymer is expected to have a cationic/potentially cationic functionality; however, the high FGEW (> 5000 daltons) indicates the notified polymer is not of concern to aquatic organisms.

The notified polymer will be imported into Australia as a component of finished paints and coating formulations; no reformulation or repackaging will occur in Australia. Products containing the notified polymer will be used by both professional and Do-It-Yourself (DIY) users. During use, paints and coatings containing the notified polymer are expected to be applied by brush, roller, and spray techniques. It is expected some of the coating product will be in the form of overspray during spraying operations, and will typically entail disposal to landfill after being collected. During use the notified polymer may also be released to the environment as accidental spills and container residues. These releases are expected to be collected and disposed of to landfill in accordance with local government regulations.

Residues containing the notified polymer on brushes and rollers are expected to be rinsed into containers, and then allowed to cure before disposal as solid wastes to landfill. As a worst case scenario, it is assumed that up to 5% of the notified polymer used by DIY users may be incorrectly disposed of to the sewer, drains, or ground from waste and washing of application equipment. Some of the notified polymer may remain in the water column and be released to surface waters with the effluent, due to its dispersibility in water. Assuming the releases occur nationwide and over the entire year, the predicted environmental concentration (PEC) is estimated to be 1.51 µg/L [$PEC_{river} = 6.85 \text{ kg notified polymer/day} \div (200 \text{ L/person/day} \times 22.613 \text{ million people}) \times 1 \text{ (dilution factor)}$]. The PEC is well below the EC₅₀ for algae of the most toxic polymers (EC₅₀ > 1 mg/L). Therefore, the notified polymer is not expected to be released to surface waters at ecotoxicologically significant concentrations.

The notified polymer in paints and coatings cured on the substrate will share the fate of the coated article, which ultimately is expected to be disposed of to landfill. In landfill, the notified polymer will be present as cured solids, which will be neither bioavailable nor mobile. Furthermore, the notified polymer is not expected to bioaccumulate due to its high molecular weight. In landfill, the notified polymer is expected to eventually degrade via biotic and abiotic processes to form water and oxides of carbon and nitrogen.

Therefore, based on its assumed low hazard and assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.