File No PLC/1358

NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polystabil 922

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX:	+ 61 2 8577 8888
Website:	www.nicnas.gov.au

Director
NICNAS

June 2016

Table of Contents

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette:*

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1358	Solenis Australia Pty Ltd	Polystabil 922	No	≤ 50 tonnes per annum	Mineral processing

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment
Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment
Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

  Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the (M)SDS should be easily accessible to employees.

- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS),* as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

- Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

(1) Under Section 64(1) of the Act; if
- the notified polymer is introduced in a chemical form that does not meet the PLC criteria;

or

(2) Under Section 64(2) of the Act; if
- the function or use of the notified polymer has changed from mineral processing, or is likely to change significantly;
- the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
- the notified polymer has begun to be manufactured in Australia;
- additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants
Solenis Australia Pty Ltd (ABN: 37 169 325 151)
7 Sir Thomas Mitchell Road
CHESTER HILL NSW 2162

Exempt Information (Section 75 of the Act)
Data items and details claimed exempt from publication: chemical name, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)
Polystabil 922

Molecular Weight
Number Average Molecular Weight (Mn) is > 1,000 Da

3. PLC CRITERIA JUSTIFICATION

Criterion	*Criterion met*
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa	Not determined. Polymer imported in aqueous solution
Melting Point/Glass Transition Temp	Not determined
Density	1,180 kg/m^3 at 25 °C
Water Solubility	> 550 g/L at 20 °C (commercial product contains < 60% polymer dissolved in water). Study report not provided. Expected to be water soluble based on the presence of hydrophilic functional groups in the chemical structure and use in aqueous systems.
Dissociation Constant	Not determined. The notified polymer is a salt and is expected to be ionised under normal environmental conditions (pH 4 – 9).
Reactivity	Stable under normal environmental conditions
Degradation Products	None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	*1*	*2*	*3*	*4*	*5*
Tonnes	< 50	< 50	< 50	< 50	< 50

Use
The notified polymer will not be manufactured in Australia and will be imported as an aqueous solution at < 60% concentration for use as an antiscalant at mineral processing plants.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be considered to be of low hazard.

Although not considered in this risk assessment, NICNAS notes that the notified polymer contains residual monomers that are classified as hazardous according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS),* as adopted for industrial chemicals in Australia. These are not present in the notified polymer as introduced above the cut off concentrations for classification.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Anionic polymers are generally of low toxicity to fish and daphnia, however they are known to be moderately toxic to algae. The mode of toxic action is over-chelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone. This may apply to the notified polymer. However, the toxicity to algae is likely to be reduced due to the presence of calcium ions in the aquatic compartment which will bind to the acid functional groups.

The notified polymer will be imported as a finished end-use product and will not be reformulated in Australia. The notified polymer will be used as a scale inhibitor in an antiscalant at mineral processing plants. Spills (up to 2% of the total import volume) and washings of empty IBCs are expected to be disposed of through a licensed waste disposal contractor. The remaining residues (up to 5% of the total import volume) in the empty containers are expected to be disposed of to landfill together with the empty containers.

The notified polymer is not expected to cross biological membranes due to its high molecular weight and is not expected to bioaccumulate. The notified polymer is soluble in water, but due to its anionic nature, is likely to be immobilised via adsorption onto soil particles and sediments in the aquatic environment. The majority of the notified polymer will end up in the tailing dams at the mining sites. Therefore, exposure to the aquatic environment is expected to be low. In the tailings dam and in landfill, the notified polymer is expected to undergo slow degradation under anaerobic conditions, eventually degrading to oxides of carbon and sulphur.

Therefore, based on its assumed low hazard and assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.