

File No: LTD/1892

February 2017

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME
(NICNAS)**

PUBLIC REPORT

Polymer in Efka® FL 3600 and Efka® FL 3650

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. This legislation is an Act of the Commonwealth of Australia. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX:	+ 61 2 8577 8888
Website:	www.nicnas.gov.au

**Director
NICNAS**

TABLE OF CONTENTS

SUMMARY	3
CONCLUSIONS AND REGULATORY OBLIGATIONS	3
ASSESSMENT DETAILS	6
1. APPLICANT AND NOTIFICATION DETAILS	6
2. IDENTITY OF CHEMICAL.....	6
3. COMPOSITION.....	6
4. PHYSICAL AND CHEMICAL PROPERTIES	6
5. INTRODUCTION AND USE INFORMATION	7
6. HUMAN HEALTH IMPLICATIONS	8
6.1. Exposure Assessment.....	8
6.1.1. Occupational Exposure.....	8
6.1.2. Public Exposure.....	9
6.2. Human Health Effects Assessment	9
6.3. Human Health Risk Characterisation	9
6.3.1. Occupational Health and Safety	9
6.3.2. Public Health	10
7. ENVIRONMENTAL IMPLICATIONS.....	10
7.1. Environmental Exposure & Fate Assessment	10
7.1.1. Environmental Exposure	10
7.1.2. Environmental Fate	11
7.1.3. Predicted Environmental Concentration (PEC).....	11
7.2. Environmental Effects Assessment.....	12
7.2.1. Predicted No-Effect Concentration	12
7.3. Environmental Risk Assessment	12
<u>APPENDIX A: PHYSICAL AND CHEMICAL PROPERTIES</u>	<u>13</u>
BIBLIOGRAPHY	14

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS CHEMICAL	INTRODUCTION VOLUME	USE
LTD/1892	BASF Australia Ltd	Polymer in Efka® FL 3600 and Efka® FL 3650	ND*	≤ 10 tonnes per annum	Component of industrial and automotive coatings

*ND = not determined

CONCLUSIONS AND REGULATORY OBLIGATIONS

Hazard classification

As no toxicity data were provided, the notified polymer cannot be classified according to the *Globally Harmonised System of Classification and Labelling of Chemicals* (GHS), as adopted for industrial chemicals in Australia, or the *Approved Criteria for Classifying Hazardous Substances* (NOHSC, 2004).

Human health risk assessment

Provided that the recommended controls are being adhered to, under the conditions of the occupational settings described, the notified polymer is not considered to pose an unreasonable risk to the health of workers.

When used in the proposed manner, the notified polymer is considered not considered to pose an unreasonable risk to public health.

However, the notified polymer is a potential precursor for perfluorohexanoic acid (PFHxA) in the environment, and PFHxA is persistent in the environment. Due to environmental distribution of PFHxA resulting from the use pattern of the notified polymer, secondary human exposure to PFHxA via the environment may occur. The notified polymer is proposed to replace perfluoroalkyl polymers that may release longer chain perfluorocarboxylic acids (PFCAs) in the environment. Longer chain PFCAs are known to be more hazardous to human health with higher bioaccumulation potential compared to shorter chain PFCAs. The overall human health risk posed by the notified polymer is anticipated to be less than that of the perfluoroalkyl polymers it replaces.

Environmental risk assessment

On the basis of the assessed use pattern, the notified polymer itself is not considered to directly pose an unreasonable short-term risk to the environment. However, the notified polymer contains fluorinated carbon groups that have the potential to degrade to the exceptionally persistent short-chain perfluorinated carboxylic acid, PFHxA.

Based on the currently available environmental hazard information, PFHxA is considered to have lower overall ecotoxicity concerns than homologous long-chain perfluorocarboxylic acids, which contain seven or more perfluorinated carbon atoms, such as perfluorooctanoic acid (PFOA).

The environmental degradation of the notified polymer is expected to contribute to the cumulative emissions of perfluorohexanoic acid to the environment. Based on the currently available evidence, the concentrations of PFHxA and other short chain perfluorinated carboxylic acids are not considered to pose a concern for the health of the environment. However, if additional hazard information becomes available to indicate that short-chain perfluorinated carboxylic acids have hazard characteristics of high concern for the environment (such as PBT properties), then the risks posed by industrial uses of precursors to these environmental degradants may need to be re-assessed.

Recommendations

CONTROL MEASURES

Occupational Health and Safety

- A person conducting a business or undertaking at a workplace should implement the following engineering controls to minimise occupational exposure to the notified polymer as introduced in Efka® FL 3600 and Efka® FL 3650:
 - Local exhaust ventilation
 - Spray booth if spray application occurs
- A person conducting a business or undertaking at a workplace should implement the following safe work practices to minimise occupational exposure during handling of the notified polymer as introduced in Efka® FL 3600 and Efka® FL 3650:
 - Avoid breathing in mists, vapours or aerosols
- A person conducting a business or undertaking at a workplace should ensure that the following personal protective equipment is used by workers to minimise occupational exposure to the notified polymer as introduced in Efka® FL 3600 and Efka® FL 3650:
 - Respiratory protection

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (SWA, 2015) or relevant State or Territory Code of Practice.
- A copy of the SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)* as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Environment

- The notified polymer should only be introduced as part of a strategy to phase out the use of long chain perfluorinated chemicals, or chemicals that degrade to long chain perfluorinated chemicals.
- The notifier should seek ways to minimise the level of residual polyfluoroalkyl monomers and impurities in the notified polymers. Such levels should be as low as practicable. Where possible, the total weight of these constituents should not exceed the levels attainable utilising international best practice.
- The following control measures should be implemented by users of the notified polymer, or products containing the notified polymer, to minimise exposure of the notified polymer to the environment:
 - Best practice on-site treatment of waste streams should be employed to maximise removal of the notified polymer from wastewaters.

Disposal

- If the notified polymers or products containing the notified polymers cannot feasibly be disposed of using a technique that will destroy or irreversibly transform the fluoroalkyl components of the notified polymers, disposal should be to landfill.

Emergency procedures

- Spills or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Regulatory Obligations

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the chemical under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified chemical, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the polymer has a number-average molecular weight of less than 1000 Da;
 - products containing the notified polymers are intended for use by the public;
 - information on the acute or repeated inhalation toxicity of the notified polymers becomes available;
 - additional information has become available as to an adverse effect of the polyfluoroalkyl degradation products of the notified polymer (such as perfluorohexanoic acid);or
- (2) Under Section 64(2) of the Act; if
 - the function or use of the polymer has changed from component of industrial and automotive coatings or is likely to change significantly;
 - the amount of polymer being introduced has increased, or is likely to increase significantly;
 - the polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

AICS Annotation

- When the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS) the entry is proposed to be annotated with the following statement(s):
 - This polymer has been assessed by NICNAS and there are specific secondary notification obligations that must be met. Potential introducers should contact NICNAS before introduction.

Safety Data Sheet

The SDS of products containing the notified chemical provided by the notifier was reviewed by NICNAS. The accuracy of the information on the SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

APPLICANT

BASF Australia Ltd (ABN: 62 008 437 867)
Level 12, 28 Freshwater Place
Southbank VIC 3006

NOTIFICATION CATEGORY

Limited: Synthetic polymer with $M_n \geq 1,000$ Da.

EXEMPT INFORMATION (SECTION 75 OF THE ACT)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, analytical data, degree of purity, polymer constituents, residual monomers, impurities, additives/adjuvants, import volume and use details.

VARIATION OF DATA REQUIREMENTS (SECTION 24 OF THE ACT)

Variation to the schedule of data requirements is claimed as follows: melting point/freezing point, density, hydrolysis as a function of pH, absorption/desorption, dissociation constant, flash point, flammability, autoignition temperature, explosive properties and oxidising properties.

PREVIOUS NOTIFICATION IN AUSTRALIA BY APPLICANT(S)

None

NOTIFICATION IN OTHER COUNTRIES

Canada (2012), China (2012), Korea (2013), USA

2. IDENTITY OF CHEMICAL

MARKETING NAME(S)

Efka® FL 3600 (contains < 90% notified polymer)
Efka® FL 3650 (contains < 60% notified polymer)

ANALYTICAL DATA

Reference IR and GPC spectra were provided.

3. COMPOSITION

The notified polymer contains a polyfluoroalkyl carbon side chain with six perfluorinated carbons.

DEGREE OF PURITY

> 95%

LOSS OF MONOMERS, OTHER REACTANTS, ADDITIVES, IMPURITIES

No losses are expected during use.

DEGRADATION PRODUCTS

The notified polymer is a potential precursor for PFHxA (perfluorohexanoic acid – CAS name: hexanoic acid, 2,2,3,3,4,4,5,5,6,6,6-undecafluoro-; CAS No. 307-24-4) in the environment.

4. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AT 20 °C AND 101.3 kPa: yellowish liquid

Property	Value	Data Source/Justification
Melting Point/Freezing Point	Not determined	Imported in aqueous solution
Boiling Point	378-385 °C at 100.8 kPa	Measured
Density	1,075 kg/m ³ at 20 °C (Efka FL 3600) 1,030 kg/m ³ at 20 °C (Efka FL 3650)	SDS
Vapour Pressure	4.7×10^{-8} kPa at 20 °C	Extrapolated from measured data

	7.4×10^{-8} kPa at 25 °C 5.8×10^{-7} kPa at 50 °C 0.014 and 0.074 g/L at 20 °C	Measured
Water Solubility		
Hydrolysis as a Function of pH	Not Determined	Contains hydrolysable functionality and may slightly hydrolyse under environmental conditions.
Partition Coefficient (n-octanol/water)	Log Pow \approx 2.5 at 20 °C	Measured
Adsorption/Desorption	Not Determined	May have low absorption based on the presence of perfluorinated functionalities which have both hydrophobic and lipophobic tendencies.
Dissociation Constant	Not Determined	Contains dissociable functionalities and may dissociate under environmental conditions (pH 4-9)
Flash Point	110 °C (Efka FL 3600) 44 °C (Efka FL 3650)	SDS
Flammability	Upper: 7%, Lower: 1.5% at 20 °C and 101.3 kPa (Efka FL 3650)	SDS
Autoignition Temperature	377 °C (Efka FL 3600) 333 °C (Efka FL 3650)	SDS
Explosive Properties	Not determined	Contains no functional groups that would imply explosive properties
Oxidising Properties	Not determined	Contains no functional groups that would imply oxidative properties

DISCUSSION OF PROPERTIES

For full details of tests on physical and chemical properties, refer to Appendix A. Flash point and flammability of Efka FL 3650 are expected to be primarily attributed to the solvent in the product.

Reactivity

The notified polymer is expected to be stable under normal conditions of use.

Physical hazard classification

Based on the submitted physico-chemical data depicted in the above table, the notified polymer is not recommended for hazard classification according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia.

5. INTRODUCTION AND USE INFORMATION

MODE OF INTRODUCTION OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

The notified polymer will not be manufactured in Australia. It will be imported as a component of formulations at < 90% concentration for local reformulation into industrial and automotive coatings.

MAXIMUM INTRODUCTION VOLUME OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

Year	1	2	3	4	5
Tonnes	1-10	1-10	1-10	1-10	1-10

PORT OF ENTRY
Melbourne

TRANSPORTATION AND PACKAGING

Efka FL 3600 containing < 90% notified polymer will be imported by sea in 25 kg or 210 kg steel drums. Efka FL 3650 containing < 60% notified polymer will be imported by sea in 20 kg plastic jerricans or 210 kg steel drums. The products will be then transported within Australia by road.

USE

The notified polymer is intended to be introduced to replace the use of partially fluorinated polymers containing fluorinated carbon chain lengths > 6 in various proportions (i.e., existing polymers). The use of the notified polymer is identical to that of the existing polymers they replace.

The notified polymer will be used as a component of industrial and automotive coatings (at $\leq 1\%$ concentration).

OPERATION DESCRIPTION

The notified polymer will not be manufactured in Australia. The notified polymer will be imported at < 90% concentration.

Reformulation

At the reformulation site, the imported products containing the notified polymer at < 90% concentration will be transferred to the mixing tank by gravity feed or by low pressure pumps. Hydrocarbon solvent will then be added to the mixing tank. Mixing process is expected to be enclosed and automated with local exhaust ventilation in place. Once mixing is complete sampling for quality assurance purposes will take place and the finished industrial and automotive coatings will be pumped to filling machines where it will be transferred to a variety of containers (1 L, 4 L and 10 L cans and 210 L steel drums) through gravity feed or low pressure pumps.

End-use

Industrial and automotive coatings containing the notified polymer at $\leq 1\%$ concentration will be used by professional workers in industrial settings and are expected to be applied by spray, roller or brush.

6. HUMAN HEALTH IMPLICATIONS**6.1. Exposure Assessment**

The notified polymer may undergo slow degradation in the environment. As such, most potential exposure to workers and the public is expected to be to the notified polymer itself, rather than to its degradation products. Exposure to the residual polyfluoroalkyl starting constituents and/or impurities of the notified polymer is also possible. Such exposure is limited by the relatively low concentration of polyfluoroalkyl impurities in the notified polymer in the imported products or in end-use products.

The notified polymer is a potential precursor for PFHxA in the environment. This may lead to secondary human exposure to PFHxA. This exposure is unquantifiable.

6.1.1. Occupational Exposure**CATEGORY OF WORKERS**

<i>Category of Worker</i>	<i>Exposure Duration (hours/day)</i>	<i>Exposure Frequency (days/year)</i>
Transportation and storage	1	4-5
Process operator	2-3	40-50
Quality control	0.5	40-50
Professional painters	1	50-70

EXPOSURE DETAILS*Transport and storage*

Transport and storage workers are expected to only come into contact with the notified polymer (at < 90% concentration) in the unlikely event of an accident.

Reformulation process

Dermal and ocular exposure may occur when workers manually weigh and pour imported products containing the notified polymer (at < 90% concentration) into mixing equipment, or when connecting and disconnecting transfer hoses, and during cleaning and maintenance operations. Inhalation exposure is not expected based on the measured low vapour pressure of the notified polymer and because aerosols are not expected during reformulation processes. The remainder of the reformulation process, including packaging is expected to be mostly automated and exposure is expected to be low.

End-use

Dermal and ocular exposure of workers to the notified polymer (at $\leq 1\%$ concentration) may occur when workers apply industrial and automotive coatings. There is also some potential for inhalation exposure when applying by low pressure spraying methods, though typically the notified polymer will be present at concentrations of up to 1% during such operations. Personal protective equipment (PPE) is expected to be worn, including gloves, protective clothing, safety glasses and respiratory protection when aerosols may be present. Professionals may be exposed on a repeated basis.

6.1.2. Public Exposure

Products containing the notified polymer will be used in industrial settings only and will not be made available to the public. The public may come into contact with surfaces that have been painted with products containing the notified polymer. However, once dried and cured, the notified polymer is bound within a solid matrix and will not be available for exposure.

6.2. Human Health Effects Assessment

No toxicity data were submitted for the notified polymer.

The notified polymer is a polyacrylate with a $M_n > 1,000$ Da and low percentage ($< 5\%$) of low molecular weight species ($M_n < 500$ Da). This type of polymers may generally be considered to be of low hazard. However, the notified polymer contains polyfluorinated carbon chains and fluorinated polymers have been known to cause lung injury, which is characterised by respiratory problems ranging from mild to severe effects associated with acute or repeated exposures. Uncertainties remain surrounding possible acute or chronic respiratory tract effects following acute or repeated exposures to the notified polymer. Moreover, the notified polymer may contain an impurity having reproductive toxicity potential. However, considering the very low concentration for the impurity and high molecular weight of the polymer, the reproductive toxicity potential is very low.

Health hazard classification

As no toxicity data were provided, the notified polymer cannot be classified according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, or the *Approved Criteria for Classifying Hazardous Substances* (NOHSC, 2004).

Hazard implication of breakdown products

The notified polymer contains polyfluoroalkyl side-chains that are potential precursors of PFHxA in the environment. PFHxA is a perfluorocarboxylic acid consisting of 5 perfluorinated carbons (a short chain perfluorinated chemical). The notified polymer is proposed to replace polymers that are expected to breakdown to form degradants with perfluorinated carbon chain lengths ranging from 6 to 12. It has been known that the toxicokinetic and toxicological properties of fluorinated substances are generally becoming less favourable with increase of perfluoroalkyl carbon chain length. It has also been reported that the bioaccumulation potential of perfluorocarboxylic acids increases with perfluoroalkyl carbon chain length (Conder, 2008; Giesy 2010).

A review of the literature indicates that PFHxA has a less hazardous human health profile, compared to PFOA (NICNAS, a). It is therefore inferred that the human health hazards associated with the expected breakdown product of the notified polymer (PFHxA) are likely to be similar or less than the human health hazards associated with the expected breakdown products (PFOA and longer chain perfluorocarboxylic acids) of many per- and polyfluoroalkyl chemicals currently on the market and that are intended for replacement by the notified polymer.

6.3. Human Health Risk Characterisation

6.3.1. Occupational Health and Safety

There are uncertainties surrounding possible acute or chronic respiratory tract effects from the notified polymer when inhaled. However, during the reformulation and end use, inhalation exposure of workers to the notified polymer is expected to be minimal due to the industrial nature of the processes, the presence of engineering controls (spray booths and local exhaust ventilations) and use of PPE including safety glasses, impervious gloves, chemical-resistant protective clothing and appropriate certified respirators.

Once the final paints are cured after end use, the notified polymer will be trapped in an inert polymer matrix and will not be available for further exposure.

Under the conditions of the occupational settings described, in the presence of engineering controls and PPE specified, the notified polymer is not considered to pose an unreasonable risk to occupational health.

Workers may also be exposed to per- and polyfluoroalkyl impurities of the notified polymer at low concentrations (< 0.1%), during reformulation. It is expected that the engineering controls and PPE utilised during these operations (as outlined above) will act to mitigate any risk associated with such exposure.

6.3.2. Public Health

The notified polymer is intended for industrial use only and therefore direct exposure of members of the public to the notified polymer is not expected. Once the final paints containing the notified polymer are cured, the polymer is expected to be bound within inert matrix and will not be available for exposure. When used in the proposed manner, the notified polymer is not considered to directly pose an unreasonable risk to public health.

Risk from exposure to degradants

The public may potentially be exposed indirectly to the environmentally persistent, fluorinated degradants of the notified polymer, such as PFHxA. Such exposure may increase over time due to the persistence of PFHxA in the environment. A quantitative risk assessment for this exposure was not conducted. However, the available data indicates that PFHxA has a more favourable toxicological profile and bioaccumulation potential than the long chain perfluoroalkyl substances that are the ultimate breakdown products of the long chain perfluoroalkyl polymers currently in Australian commerce (such as PFOA). In particular, it is noted that the polymers being replaced contain perfluoroalkyl carbon chain lengths > 6. It is concluded that the risks to human health from indirect exposure to breakdown products of perfluoroalkyl substances will decrease following introduction of the notified polymer, on the basis that the notified polymer is intended to replace currently available long chain perfluoroalkyl polymers.

7. ENVIRONMENTAL IMPLICATIONS

7.1. Environmental Exposure & Fate Assessment

7.1.1. Environmental Exposure

RELEASE OF CHEMICAL AT SITE

The notified polymer will be imported into Australia and therefore, release from manufacturing is not expected. Accidental spillage may occur during importation, transport and distribution. Any notified polymer that is spilled is expected to be adsorbed onto a suitable material and collected for disposal in accordance with local regulations.

The notified polymer will be reformulated to final industrial and automotive coatings locally. Reformulation is expected to be conducted following the standard operation procedure in a closed system. Therefore, release of the notified polymer from reformulation is not expected to be significant. Solvents used for equipment cleaning are expected to be recycled for reuse on site or disposed of via accredited waste disposal contractors. Wastes containing residues of the notified polymer (up to 1% of annual import volume as estimated by the notifier) are expected to be contained on-site and disposed of in accordance with local regulations. Empty import containers with residues of the notified polymer may be disposed of to landfill.

RELEASE OF CHEMICAL FROM USE

Industrial and automotive coatings containing the notified polymer will be applied to substrate by spray, roller or brush by professional workers in industrial facilities. The use of roller and brush is expected to be efficient and no significant loss of the products is expected. Any losses from overspray (estimated at 30% of annual import volume) during industrial use are expected to be collected using standard engineering controls such as spray booths. All wastes generated during use, including residues in application equipment washings and empty paint containers are expected to be disposed of in accordance with local regulations.

RELEASE OF CHEMICAL FROM DISPOSAL

The notified polymer in industrial and automotive coatings is expected to share the fate of articles to which it has been applied. Hence, the notified polymer is likely to be either thermally decomposed during metal reclamation processes or be disposed of to landfill at the end of the useful life of the article to which it has been applied.

7.1.2. Environmental Fate

No environmental fate data were submitted.

The notified polymer is an acrylate-methacrylate copolymer where one of the ester side chains is polyfluorinated. This polyfluorinated side-chain incorporates a chain segment of six perfluorinated carbon atoms including a terminal perfluoromethyl (CF₃) group. Under the NICNAS action plan for assessing and managing chemicals that could degrade to perfluorinated carboxylic acids, the notified polymer would be considered to be an indirect precursor to the exceptionally persistent perfluorinated carboxylic acid, perfluorohexanoic acid (PFHxA) (NICNAS, b).

The biodegradation potential of fluoroacrylate polymers in soils has been investigated and the studies show that analogous polymers have the potential to degrade to release fluorotelomer alcohols (Washington et al, 2009, 2015). The notified polymer is derived from 6:2 fluorotelomer methacrylate and can therefore, potentially, release the 6:2 fluorotelomer alcohol, 6:2 FTOH. This polyfluorinated alcohol is known to undergo environmental biodegradation to form short-chain perfluorocarboxylic acids, including perfluorohexanoic acid (PFHxA) (NICNAS, b).

When associated with the articles, the notified polymer is not likely to be mobile or bioavailable. Based on its high molecular weight, the notified polymer is not likely to cross biological membranes or to bioaccumulate.

The majority of the notified polymer is expected to adhere to the surface of articles to which it is applied. Treated articles and other dried residues containing the notified polymer are expected to ultimately be disposed of to landfill or subjected to metals reclamation.

The notified polymer will eventually degrade in landfill and has the potential to release per- and polyfluoroalkyl degradation products, including short-chain perfluorinated carboxylic acids, such as PFHxA.

PFHxA is a globally distributed pollutant and is expected to be recalcitrant in the environment, potentially undergo long range transport while mainly staying in the water column. In water, it is expected to be very persistent and will not hydrolyse, photolyse or biodegrade under environmental conditions (NICNAS, c).

PFHxA is expected to be less bioaccumulative than perfluorooctanoic acid (PFOA) and other long-chain perfluoroalkyl acids, supported by the available laboratory (Higgins et al., 2007; Martin et al., 2003a, b; Woodcroft et al., 2010) and field (Falandysz et al., 2006; Falandysz et al., 2007; Furdui et al., 2007) evidence. In general, bioaccumulation potential decreases when the length of the perfluorinated carbon chain is decreased (Ng and Hungerbühler, 2014; Giesy et al., 2010). The short-chain perfluorocarboxylic acids, including PFHxA, have been assessed to have low bioaccumulation potential based on the currently available information (NICNAS, c, d).

7.1.3. Predicted Environmental Concentration (PEC)

PEC for the notified polymer

A PEC has not been calculated for the notified polymer because, based on its reported use pattern (including during reformulation), significant quantities are not expected to be released to the aquatic environment.

PEC for PFHxA and other perfluorocarboxylic acids

The notified polymer has the potential to degrade and ultimately form the persistent degradant, PFHxA. However, the yield and rate of conversion of the notified polymer to PFHxA has not been established.

Environmental monitoring data shows that PFHxA and PFOA are widely found in the environment, particularly in fresh water close to industrial sources, but also in some biota. Water appears to be the main compartment where PFHxA is found. High measured concentrations of both PFHxA and PFOA in surface waters in Germany have been associated with the legal application of waste materials to agricultural soils (Skutlarek et al., 2006), indicating that these chemicals have the potential to enter the aquatic compartment following initial release into the soil compartment.

Some larger available data sets from the literature (McLachlan et al., 2007; Skutlarek et al., 2006; Nakayama et al., 2007; So et al., 2007; Ahrens et al., 2009) include monitoring from a range of rivers in Europe, the USA and China, along with data from the Atlantic Ocean. Using these data (n ≥ 60), the 10th, 50th and 90th percentile concentrations for PFHxA are 1.0, 6.15 and 22.5 ng/L respectively, while those for PFOA are 2.94, 11.85 and

231.9 ng/L respectively. As use of chemicals that degrade to form PFHxA increases, levels of PFHxA may build up further in the environment.

Analyses of drinking water samples from Europe, Canada, the USA, Japan, India and China have also detected PFHxA and other short chain perfluoroalkyl compounds. PFHxA was recently detected in all samples taken from the Parramatta River (main tributary of Sydney Harbour), with a mean concentration of 2.9 ng/L. Sampling of the Brisbane River catchment following a major flooding event in 2011 also found PFHxA present in water at Somerset Dam, Wivenhoe Dam, Jindalee, Oxley Creek, West End, Bulimba and Moreton Bay. The chemical was detected in all samples obtained at these sites in concentrations ranging between 0.06 and 6.2 ng/L (NICNAS, c).

PFHxA and other poly- and perfluoroalkyl compounds have also been found in landfill leachate, with concentrations of PFHxA ranging from 270 – 790 ng/L (Huset et al., 2011). As landfills are reservoirs of solid waste, and receive waste water treatment plant sludge, which may contain poly- and perfluoroalkyl compounds, landfills have the potential to continue to release PFHxA and homologous perfluorinated carboxylic acids well into the future.

The lifetime of PFHxA in the aquatic environment is unknown, but is expected to be comparable to the very long lifetimes established for homologous perfluorinated acids such as PFOA and PFOS (NICNAS, e, f).

7.2. Environmental Effects Assessment

Effects of the notified polymer

No ecotoxicity data were submitted. Anionic polymers are generally of low toxicity to fish and daphnia, however they are known to be moderately toxic to algae. The mode of toxic action is over-chelation of nutrient elements needed by algae for growth. However, the notified polymer is expected to have very limited aquatic exposure based on its use pattern.

Effects of PFHxA and other perfluorocarboxylic acids

The currently available data, summarised in the *NICNAS IMAP Environment Tier II Assessment for Short-Chain Perfluorocarboxylic Acids and their Direct Precursors*, indicate that PFHxA and other short-chain perfluorinated acids (i.e. those with five or fewer perfluorinated carbon atoms) have low toxicity to aquatic life (NICNAS, c, d) compared to PFOA and perfluorooctanesulfonic acid (PFOS) (NICNAS, e, f). However, no long-term intergenerational studies were identified for PFHxA and other short chain short-chain PFCAs. Emerging evidence suggest that the most significant aquatic toxicity effects of PFOA and PFOS may manifest in offspring when the parent generation is exposed to PFOA or PFOS (NICNAS, e, f).

7.2.1. Predicted No-Effect Concentration

A predicted no-effect concentration (PNEC) has not been calculated for the notified polymer as, based on its reported use pattern, significant quantities are not expected to be released to the aquatic environment.

7.3. Environmental Risk Assessment

The risk quotient ($Q = PEC/PNEC$) for the notified polymer has not been calculated because release to the aquatic environment in significant quantities is not expected based on its use pattern in industrial and automotive coatings.

However, the notified polymer has the potential to eventually degrade to form very persistent PFHxA. PFHxA is currently understood to have low potential for bioaccumulation (NICNAS, c). The currently available data also indicate that PFHxA and other short-chain perfluorocarboxylic acids and their direct precursors have low toxicity to aquatic life (NICNAS, c, d).

The main environmental risks associated with polyfluoroalkyl polymers relate to the release of perfluorinated degradation products such as PFHxA. It is not possible to quantify the release of PFHxA to the environment from the use of the notified polymer at present. However, as use of chemicals/polymers that degrade to form PFHxA increases, levels of PFHxA may build up in the environment. Hence, there is potential for environmentally significant concentrations to eventually be reached following its accumulation in the environment. In this eventuality, precursors of PFHxA such as the notified polymer cannot be recalled after release and are potential sources of PFHxA releases into the environment even long after their use ceases. Thus, use and disposal of the notified polymer will likely lead to increases in the levels of PFHxA in the environment.

Conclusions

On the basis of the assessed use pattern, the notified polymer itself is not considered to directly pose an unreasonable short-term risk to the environment. However, the notified polymer contains fluorinated carbon groups that have the potential to degrade to the exceptionally persistent short-chain perfluorinated carboxylic acid, PFHxA.

The environmental degradation of the notified polymer is expected to contribute to the cumulative emissions of perfluorohexanoic acid to the environment. Based on the currently available evidence, the concentrations of PFHxA and other short-chain perfluorinated carboxylic acids are not considered to pose a concern for the health of the environment. However, if additional hazard information becomes available to indicate that short-chain perfluorinated carboxylic acids have hazard characteristics of high concern for the environment (such as PBT properties), then the risks posed by industrial uses of precursors to these environmental degradants may need to be re-assessed.

APPENDIX A: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 378-385 °C at 100.8 kPa

Method OECD TG 103 Boiling Point.
EC Council Regulation No 440/2008 A.2 Boiling Temperature.
Remarks Differential scanning calorimetry method
Test Facility Siemens (2012a)

Vapour Pressure 4.7×10^{-8} kPa at 20 °C (extrapolated)
 7.4×10^{-8} kPa at 25 °C (extrapolated)
 5.8×10^{-7} kPa at 50 °C (extrapolated)

Method OECD TG 104 Vapour Pressure.
EC Council Regulation No 440/2008 A.4 Vapour Pressure.
Remarks Effusion method
Test Facility Siemens (2012b)

Water Solubility 0.0138 g/L at 20 °C, loading concentration of 1 g/l
0.0739 g/L at 20 °C, loading concentration of 10 g/l

Method OECD TG 105 Water Solubility.
EC Council Regulation No 440/2008 A.6 Water Solubility.
Remarks Flask Method
Test Facility Siemens (2012c)

Partition Coefficient (n-octanol/water) log Pow \approx 2.5 at 20 °C

Method OECD TG 107 Partition Coefficient (n-octanol/water).
EC Council Regulation No 440/2008 A.8 Partition Coefficient.
Remarks Flask Method. The saturation concentration of the test item in n-octanol could not be determined because there is no appropriate analytical method to measure the concentration of the test item in n-octanol. The results of the preliminary estimation were used to calculate the partition coefficient. This estimated log Pow value should be considered of low reliability for predicting the environmental partitioning behaviour of this fluoropolymer.
Test Facility Siemens (2012d)

BIBLIOGRAPHY

- Ahrens L, Felizeter S, Sturm R, Xie Z and Ebinghaus R (2009). Polyfluorinated compounds in wastewater treatment plant effluents and surface waters along the River Elbe, Germany. *Mar Pollut Bull*, 58(9):1326-1333.
- Conder JM, Hoke RA, de Wolf W, Russell MH, Buck RC (2008). Are PFCAs bioaccumulative? A critical review and comparison with regulatory criteria and persistent lipophilic compounds. *Environ Sci Technol*;42:995–1003.
- Falandysz J, Taniyasu S, Gulkowska A, Yamashita N and Schulte-Oehlmann U (2006) Is Fish A Major Source of Fluorinated Surfactants and Repellents in Humans Living on the Baltic Coast. *Environ Sci Technol*, 40(3):748-751.
- Falandysz J, Taniyasu S, Yamashita N, Rostkowski P, Zalewski K and Kannan K (2007) Perfluorinated compounds in some terrestrial and aquatic wildlife species from Poland. *J Environ Sci Health, Part A: Environ Sci Eng*. 42(6):715-719.
- Furdui V, Stock N, Ellis D, Butt C, Whittle D, Crozier P, Reiner E, Muir D and Mabury S (2007) Spatial Distribution of Perfluoroalkyl Contaminants in Lake Trout from the Great Lakes. *Environ Sci Technol*, 41(5):1554-1559.
- Giesy JP, Nail JE, Khim JS, Jones PD & Newsted JL (2010) Aquatic Toxicology of Perfluorinated Chemicals. *Rev Environ Contam Toxicol*, 202: 1-52.
- Higgins C, McLeod P, Macmanus-Spencer L and Luthy R (2007) Bioaccumulation of Perfluorochemicals in Sediments by the Aquatic Oligochaete *Lumbriculus variegatus*. *Environ Sci Technol*, 41(13):4600-4606.
- Huset C A, Barlaz M A, Barofsky D F and Field J A (2011). Quantitative determination of fluorochemicals in municipal landfill leachates, *Chemosphere*, Volume 82, Issue 10, 1380-1386.
- Martin J, Mabury S, Solomon K and Muir D (2003a) Bioconcentration and Tissue Distribution of Perfluorinated Acids in Rainbow Trout (*Oncorhynchus mykiss*). *Environ Sci Technol*, 22(1):196:204.
- Martin J, Mabury S, Solomon K and Muir D (2003b) Dietary Accumulation of Perfluorinated Acids in Juvenile Rainbow Trout (*Oncorhynchus mykiss*). *Environ Toxicol Chem*, 22(1):189-195.
- McLachlan M, Holmstrom K, Reth M and Berger U (2007) Riverine Discharge of Perfluorinated Carboxylates from the European Continent. *Environ Sci Technol*, 41(21):7260-7265.
- Nakayama S, Strynar M, Helfant L, Egeghy P, Ye X and Lindstrom A (2007) Perfluorinated Compounds in the Cape Fear Drainage Basin in North Carolina. *Environ Sci Technol*, 41(15):5271-5276.
- Ng CA and Hungerbühler K (2014). Bioaccumulation of Perfluorinated Alkyl Acids: Observations and Models. *Environmental Science and Technology*, **48**(9), pp 4637-4648.
- NICNAS a *IMAP Environment Tier II Assessment for Perfluoroheptanoic Acid (PFHpA) and its Direct Precursors*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, <https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/perfluoroheptanoic-acid-pfhp-a-and-its-direct-precursors>. Accessed on 22 February 2017.
- NICNAS b *IMAP Environment Tier II Assessment for Indirect Precursors to Short-Chain Perfluorocarboxylic Acids*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, <https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/indirect-precursors-to-short-chain-perfluorocarboxylic-acids>, Access on 22 February 2017.
- NICNAS c *IMAP Environment Tier II Assessment for Short-Chain Perfluorocarboxylic Acids and their Direct Precursors*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, <https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/short-chain-perfluorocarboxylic-acids-and-their-direct-precursors>. Accessed on 22 February 2017
- NICNAS d *IMAP Environment Tier II Assessment for Indirect Precursors to Short-Chain Perfluorocarboxylic Acids*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, <https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/indirect-precursors-to-short-chain-perfluorocarboxylic-acids>, Accessed on 22 February 2017
- NICNAS e *IMAP Environment Tier II Assessment for Perfluorooctanoic acid (PFOA) and its direct precursor*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia,

- <https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/perfluorooctanoic-acid-and-its-direct-precursors>. Accessed on 22 February 2017
- NICNAS f *IMAP Environment Tier II Assessment for Direct Precursors to Perfluorooctanesulfonate (PFOS)*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, <https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/direct-precursors-to-perfluorooctanesulfonate-pfos>. Accessed on 18 January 2017.
- NOHSC (2004) Approved Criteria for Classifying Hazardous Substances, 3rd edition [NOHSC:1008(2004)]. National Occupational Health and Safety Commission, Canberra, AusInfo.
- Russell M, Nilsson H and Buck R (2013) Elimination kinetics of perfluorohexanoic acid in humans and comparison with mouse, rat and monkey. *Chemosphere*, 93(10):2419-2425 (<http://dx.doi.org/10.1016/j.chemosphere.2013.08.060>)
- Siemens (2012a) Boiling Point A.2. (OECD 103, OCSPP 830.7220) (Report No. 20120248.01, October, 2012). Frankfurt am Main, Germany, Siemens AG (Unpublished report submitted by the notifier).
- Siemens (2012b) Vapour Pressure A.4. (OECD 104, OCSPP 830.7950) (Report No. 20120248.02, October, 2012). Frankfurt am Main, Germany, Siemens AG (Unpublished report submitted by the notifier).
- Siemens (2012c) Water Solubility A.6 (OECD 105) (Report No. 20120248.03, December, 2012). Frankfurt am Main, Germany, Siemens AG (Unpublished report submitted by the notifier).
- Siemens (2012d) Partition Coefficient n-Octanol/Water A.8 (OECD 107) (Report No. 20120248.04, December, 2012). Frankfurt am Main, Germany, Siemens AG (Unpublished report submitted by the notifier).
- Skutlarek D, Exner M & Färber H (2006) Perfluorinated Surfactants in Surface and Drinking Waters. *Environ Sci Pollut Res*, 13(5):299-307.
- So M, Miyake Y, Yeung W, Ho Y, Taniyasu S, Rostkowski P, Yamashita N, Zhou B, Shi X, Wang J, Giesy J, Yu H and Lam P (2007) Perfluorinated compounds in the Pearl River and Yangtze River of China. *Chemosphere*, 68(11):2085-2095.
- SWA (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, <http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/spray-painting-and-powder-coating>.
- United Nations (2009) Globally Harmonised System of Classification and Labelling of Chemicals (GHS), 3rd revised edition. United Nations Economic Commission for Europe (UN/ECE), <http://www.unece.org/trans/danger/publi/ghs/ghs_rev03/03files_e.html>.
- Washington J, Ellington J, Jenkins T, Evans J, Yoo H and Hafner S (2009) Degradability of an acrylate-linked, fluorotelomer polymer in soil. *Environmental Science and Technology*, 43(17):6617-6623.
- Washington J, Jenkins T, Rankin K, Naile J (2015) Decades-scale degradation of commercial, side-chain, fluorotelomer-based polymers in soils and water. *Environmental Science and Technology*, 49(2):915-923
- Woodcroft M, Ellis D, Rafferty S, Burns D, March R, Stock N, Trumpour K, Yee J and Munro K (2010) Experimental Characterization of the Mechanism of Perfluorocarboxylic Acids' Liver Protein Bioaccumulation: The Key Role of the Neutral Species. *Environ Toxicol Chem*, Early View. DOI: 10.1002/etc.199.