NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Acrylic copolymer in Turboset Ultra Eco

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment.

For the purposes of subsection 78(1) of the Act, this Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

August 2014

Table of Contents

SUM	IMARY	. 2
	ICLUSIONS AND REGULATORY OBLIGATIONS	
	ESSMENT DETAILS	
	APPLICANT AND NOTIFICATION DETAILS	
	IDENTITY OF POLYMER	
	PLC CRITERIA JUSTIFICATION	
	PHYSICAL AND CHEMICAL PROPERTIES	
	INTRODUCTION AND USE INFORMATION	
	HUMAN HEALTH RISK ASSESSMENT	
	FNVIRONMENTAL RISK ASSESSMENT	

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1220	Lubrizol	Acrylic copolymer in	No	\leq 20 tonnes per	Component of coatings
	International Inc.	Turboset Ultra Eco		annum	

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

• No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the (M)SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System for the Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• The notified polymer should be disposed of to landfill.

Storage

- The following precautions should be taken by workers regarding storage of the notified polymer:
 - Store in a segregated and approved area.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on

changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from a component of coatings, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of a product containing the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

Lubrizol International Inc (ABN: 52 073 495 603)

28 River Street

SILVERWATER NSW 2128

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, CAS number, structural formula, molecular weight, polymer constituents, residual monomers/impurities and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)

Turboset Ultra Eco (contains the notified polymer at 10–15% concentration in aqueous solution)

Other Name(s)

Z-145

Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 Da

3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa
Melting Point/Glass Transition Temp
Density

Opaque white liquid*
Not determined
1060 kg/m³ at 25 °C*

Water Solubility Not determined. Expected to be low based on the

predominantly hydrophobic structure and high molecular

weight of the notified polymer.

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

* For the imported product Turboset Ultra Eco

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	2-5	5-10	10-15	15-20	15-20

Use

The notified polymer will be imported to Australia in drums as a component of a finished coating product at 10–15% concentration in water. The product has end-use in coatings, including interior and exterior wood finishes, exterior clear and pigmented stains for wood decks and furniture, coatings for hardwood floors including high traffic sports and commercial floors, and as a specialty primer for professional painters. The notified polymer is designed to cross-link with a polyurethane that cures as the film dries.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Polymers without significant ionic functionality are generally of low concern to the environment.

The notified polymer will be imported to Australia as a component of a finished coating product. Products containing the notified polymer will be used by professional painters. During use, paints and coatings are expected to be applied by brush, roller and spray techniques. It is expected some of the coating product will be in the form of overspray during spraying operations and will typically entail landfill disposal, after being collected. Residues containing the notified polymer on brushes and rollers are expected to be rinsed into containers and then allowed to cure along with the container residues before disposal, as solid wastes, to landfill. It is expected that up to 5% of the notified polymer may be incorrectly disposed of to the sewer, drains or ground from waste and washing of application equipment. Assuming the releases occurs nationwide and over the entire year, this is unlikely to lead to ecotoxicologically relevant concentrations of the notified polymer in the aquatic environment.

The fate of the coating cured on the substrate will be shared with the fate of the coated article, which ultimately is expected to be sent to landfill. In landfill, the notified polymer will be present as cured solids which will be neither bioavailable nor mobile. Furthermore, the notified polymer is not expected to bioaccumulate due to its high molecular weight. It is expected to eventually degrade in the environment to form oxides of carbon, nitrogen, and water vapour. Therefore, based on its assumed low hazard and assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.