# NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

# POLYMER OF LOW CONCERN PUBLIC REPORT

# Poly-Stab 100 PS

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment.

For the purposes of subsection 78(1) of the Act, this Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

April 2014

# **Table of Contents**

SUM	[MARY	. 2
	ICLUSIONS AND REGULATORY OBLIGATIONS	
ASS]	ESSMENT DETAILS	. 3
1.	APPLICANT AND NOTIFICATION DETAILS	. 3
2.	IDENTITY OF POLYMER	. 3
3.	PLC CRITERIA JUSTIFICATION	. 4
4.	PHYSICAL AND CHEMICAL PROPERTIES	. 4
	INTRODUCTION AND USE INFORMATION	
	HUMAN HEALTH RISK ASSESSMENT	
	ENVIRONMENTAL RISK ASSESSMENT	

# **SUMMARY**

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1187	BASF Australia	Poly-Stab 100 PS	No	$\leq 1000$ tonnes	Component of cement
	Ltd			per annum	

# **CONCLUSIONS AND REGULATORY OBLIGATIONS**

#### **Human Health Risk Assessment**

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

#### **Environmental Risk Assessment**

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

## **Health and Safety Recommendations**

• No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- In the interest of occupational health and safety, the following precautions should be observed for use of the notified polymer as introduced in powder form:
  - The level of atmospheric nuisance dust should be maintained as low as possible. The Safe Work Australia exposure standard for atmospheric dust is 10 mg/m<sup>3</sup>.
- A copy of the (M)SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System for the Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

#### **Disposal**

• The notified polymer should be disposed to landfill.

#### Storage

- The following precautions should be taken by workers regarding storage of the notified polymer:
  - Store in a segregated and approved area.

# **Emergency Procedures**

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

#### **Secondary Notification**

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
  - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

orw

- (2) Under Section 64(2) of the Act; if
  - the function or use of the notified polymer has changed from a component of cement, or is likely to change significantly;
  - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
  - the notified polymer has begun to be manufactured in Australia;
  - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

## (Material) Safety Data Sheet

The (M)SDS of the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

# **ASSESSMENT DETAILS**

#### 1. APPLICANT AND NOTIFICATION DETAILS

#### **Applicants**

BASF Australia Ltd (ABN: 62 008 437 967) Level 12, 28 Freshwater Place

SOUTHBANK VIC 3006

## **Exempt Information (Section 75 of the Act)**

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume.

# 2. IDENTITY OF POLYMER

#### Marketing Name(s)

Poly-Stab 100 PS

#### Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 Da

#### 3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

## 4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa White to slightly coloured granules

Melting Point/Glass Transition Temp Not determined

Density Approx. 500 kg/m<sup>3</sup> at 20 °C

Water Solubility > 20 g/L at 20 °C (study report not provided). The notified

polymer is considered to be highly soluble in water based

on its predominantly hydrophilic structure.

Dissociation Constant Not determined. The notified polymer is a salt and is

expected to be ionised under environmental conditions.

Particle Size  $> 200 \mu m$ : min 80%

 $\leq 100~\mu m$ : max 10%

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

#### 5. INTRODUCTION AND USE INFORMATION

# Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	100-1000	100-1000	100-1000	100-1000	100-1000

#### Hea

The notified polymer will be imported into Australia at > 90% as part of a granule mixture in 25 kg bags, and reformulated into products at approximately 2% for use as an additive in cement.

#### 6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

Although not fully evaluated in this risk assessment, NICNAS notes that the notified polymer contains residual monomers that are classified as hazardous according to the *Globally Harmonised System for the Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia. These are not present in the notified polymer as introduced above the cut off concentrations for classification.

#### 7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted for the notified polymer. Anionic polymers are known to be moderately toxic to algae. The mode of toxic action is overchelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone. This may apply to the notified polymer. The toxicity to algae is likely to be reduced due to the presence of calcium ions, which will bind to the functional groups. Anionic polymers are generally of low hazard to fish and aquatic invertebrates.

The notified polymer will be imported into Australia as part of a granulated mixture for reformulation into products for use in concrete mixes. No significant release is expected from transportation and the blending/reformulation process. Any spills occurring during blending operations are expected to be collected for disposal to an approved facility for appropriate disposal. Residues in empty imported containers are estimated to be approximately 1% of the total import volume, and may be either collected from the container reconditioning process for disposal to landfill, or be directly sent to landfill with the containers. The vast majority of the notified polymer will be bound in the concrete matrix and will not be released to the environment in any significant quantity. Concrete from demolition operations is expected to be eventually disposed of to landfill.

Bioaccumulation is not likely based on the notified polymer's high molecular weight and the use pattern of being trapped in concrete solids after application. In landfill, leaching of the notified polymer is not expected given it is trapped in the concrete matrix. With time, it will be degraded via abiotic or biotic pathways into water, oxides of carbon, nitrogen and sulphur, and inorganic salts.

Therefore, based on its assumed low hazard and assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.