NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in High-Tg Acrylic Resin

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (the Act) and Regulations. This notification has been carried out under the signed cooperative arrangement(s) with Canada. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

December 2016

Table of Contents

1.	APPLICANT AND NOTIFICATION DETAILS	4
	IDENTITY OF POLYMER	
	PLC CRITERIA JUSTIFICATION	
	PHYSICAL AND CHEMICAL PROPERTIES	
5.	INTRODUCTION AND USE INFORMATION	4
6	HAZARD ASSESSMENT	5

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1390	PPG Industries Australia Pty Ltd	Polymer in High-Tg Acrylic Resin	No	< 150 tonnes per annum	Component of industrial automotive coatings

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health and Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public or to the environment.

Health and Safety Recommendations

• No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the (M)SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2015) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on

changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from a component of industrial automotive coatings, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of a product containing the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicant

PPG Industries Australia Pty Ltd (ABN: 82 055 500 939)

14-20 McNaughton Road CLAYTON VIC 3168

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other name(s), CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities and import volume.

Notification in Other Countries

Canada (2016) and China

2. IDENTITY OF POLYMER

Marketing Name

High-Tg Acrylic Resin (contains ≤ 75% notified polymer)

Molecular Weight

Number Average Molecular Weight (Mn) is > 1,000 Da.

3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa Solid

Density 1160 kg/m³ Water Solubility Insoluble

Dissociation Constant The polymer contains a carboxylic acid group that shows

typical weak acidity.

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	< 150	< 150	< 150	< 150	< 150

Mode of Introduction and Use

The notified polymer will not be manufactured in Australia. It will be introduced as a component of formulations at 75% concentration to make automotive coatings or as a component of finished automotive coatings at 30% concentration. The finished coatings containing the notified polymer at 30% concentration will be used by professionals in industrial settings only and will be applied by brush, roller or spray.

6. HAZARD ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be assumed to be of low hazard.

The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

BIBLIOGRAPHY

Safe Work Australia (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/spray-painting-and-powder-coating.