File No: LTD/1990

November 2017

# NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

## **PUBLIC REPORT**

## Fluoropolymer in HEXAFOR

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. This legislation is an Act of the Commonwealth of Australia. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

**Director NICNAS** 

## TABLE OF CONTENTS

SUMMARY	3
CONCLUSIONS AND REGULATORY OBLIGATIONS	3
ASSESSMENT DETAILS	6
1. APPLICANT AND NOTIFICATION DETAILS	6
2. IDENTITY OF CHEMICAL	6
3. COMPOSITION	
4. PHYSICAL AND CHEMICAL PROPERTIES	
5. INTRODUCTION AND USE INFORMATION	7
6. HUMAN HEALTH IMPLICATIONS	8
6.1. Exposure Assessment	8
6.1.1. Occupational Exposure	8
6.1.2. Public Exposure	8
6.2. Human Health Effects Assessment	9
6.3. Human Health Risk Characterisation	
6.3.1. Occupational Health and Safety	9
6.3.2. Public Health	9
7. ENVIRONMENTAL IMPLICATIONS	
7.1. Environmental Exposure & Fate Assessment	10
7.1.1. Environmental Exposure	10
7.1.2. Environmental Fate	10
7.1.3. Predicted Environmental Concentration (PEC)	11
7.2. Environmental Effects Assessment	12
7.2.1. Predicted No-Effect Concentration	12
7.3. Environmental Risk Assessment	12
BIBLIOGRAPHY	13

## **SUMMARY**

The following details will be published in the NICNAS Chemical Gazette:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS CHEMICAL	INTRODUCTION VOLUME	USE
LTD/1990	TDT Chemicals	Fluoropolymer in	ND*	< 10 tonnes per	Component of paints
		HEXAFOR		annum	and coatings

<sup>\*</sup>ND = not determined

## **CONCLUSIONS AND REGULATORY OBLIGATIONS**

#### **Hazard classification**

As no toxicity data were provided, the notified polymer cannot be classified according to the *Globally Harmonised System of Classification and Labelling of Chemicals* (GHS), as adopted for industrial chemicals in Australia.

#### Human health risk assessment

Provided that the recommended controls are being adhered to, under the conditions of the occupational settings described, the notified polymer is not considered to pose an unreasonable risk to the health of workers.

When used in the proposed manner, the notified polymer is not considered to pose an unreasonable risk to public health.

However, the notified polymer is anticipated to degrade in the environment to release fluorinated degradants similar to perfluorohexanoic acid (PFHxA) that is known to be persistent. Due to environmental distribution of the persistent chemicals, the use of the notified polymer may lead to secondary human exposure to the fluorinated degradants via the environment. The notified polymer is proposed to replace perfluoroalkyl polymers that may release longer chain perfluorocarboxylic acids (PFCAs) in the environment. Longer chain PFCAs are known to be more hazardous to human health with higher bioaccumulation potential compared to shorter chain PFCAs. The overall human health risk posed by the notified polymer is anticipated to be less than that of the perfluoroalkyl polymers it replaces.

#### **Environmental risk assessment**

On the basis of the assessed use pattern, the notified polymer itself is not considered to directly pose an unreasonable short-term risk to the environment. However, the notified polymer contains fluorinated carbon groups that have the potential to degrade to the exceptionally persistent short-chain perfluorinated carboxylic acid, PFHxA. The assessed use pattern of the notified polymer does not control the release of breakdown products into the environment during use and after disposal and the long-term environmental risk profile of PFHxA is currently unknown. Consequently, the long-term risk profile for the notified polymer and its degradation products is unknown.

The persistence of chemicals similar to PFHxA in the environment is of concern because they have potential to be globally distributed. Based on the currently available environmental hazard information, PFHxA is considered to have lower overall ecotoxicity concerns than homologous long-chain perfluorocarboxylic acids, which contain seven or more perfluorinated carbon atoms, such as perfluorocatanoic acid (PFOA).

The environmental degradation of the notified polymer is expected to contribute to the cumulative emissions of perfluorohexanoic acid to the environment. Based on the currently available evidence, the concentrations of PFHxA and other short chain perfluorinated carboxylic acids are not considered to pose a concern for the health of the environment. However, if additional hazard information becomes available to indicate that short-chain perfluorinated carboxylic acids have hazard characteristics of high concern for the environment (such as PBT properties), then the risks posed by industrial uses of precursors to these environmental degradants may need to be re-assessed.

The introduction and use of chemicals/polymers that release very persistent fluorinated degradants upon degradation should be considered a short-term measure until suitable alternatives, with less persistent chemistry, are identified.

#### Recommendations

#### CONTROL MEASURES

## Occupational Health and Safety

- A person conducting a business or undertaking at a workplace should implement the following engineering controls to minimise occupational exposure to the notified polymer as introduced:
  - Local exhaust ventilation
  - Ventilated spray painting booth
- A person conducting a business or undertaking at a workplace should implement the following safe work practices to minimise occupational exposure during handling of the notified polymer as introduced:
  - Avoid breathing in mists, vapours or aerosols
- A person conducting a business or undertaking at a workplace should ensure that the following personal
  protective equipment is used by workers to minimise occupational exposure to the notified polymer as
  introduced:
  - Respiratory protection

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (SWA, 2015) or relevant State or Territory Code of Practice.
- A copy of the SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)* as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

#### Environment

- The notified polymer should only be introduced as part of a strategy to phase out the use of long chain perfluorinated chemicals, or chemicals/polymers that degrade to long chain perfluorinated chemicals.
- The notifier should seek ways to minimise the level of residual polyfluoroalkyl monomers and
  impurities in the notified polymers. Such levels should be as low as practicable. Where possible, the
  total weight of these constituents should not exceed the levels attainable utilising international best
  practice.
- The following control measures should be implemented by users of the notified polymer, or products containing the notified polymer, to minimise exposure of the notified polymer to the environment:
  - Best practice on-site treatment of waste streams should be employed to maximise removal of the notified polymer from wastewaters.

## Disposal

• If the notified polymer or products containing the notified polymer cannot feasibly be disposed of using a technique that will destroy or irreversibly transform the fluoroalkyl components of the notified polymer, disposal should be to landfill.

#### Emergency procedures

 Spills or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

#### **Regulatory Obligations**

## Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the chemical under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified chemical, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
  - the polymer has a number-average molecular weight of less than 1000;
  - products containing the notified polymer are intended for use by the public;
  - information on the acute or repeated inhalation toxicity of the notified polymers becomes available;
  - additional information has become available as to an adverse effect of the per- or polyfluoroalkyl degradation products of the notified polymer.

or

- (2) Under Section 64(2) of the Act; if
  - the function or use of the polymer has changed from component of paints and coatings, or is likely to change significantly;
  - the amount of polymer being introduced has increased, or is likely to increase, significantly;
  - the polymer has begun to be manufactured in Australia;
  - additional information has become available to the person as to an adverse effect of the polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

## AICS Annotation

- When the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS) the entry is proposed to be annotated with the following statement(s):
  - This polymer has been assessed by NICNAS and there are specific secondary notification obligations that must be met. Potential introducers should contact NICNAS before introduction.

## Safety Data Sheet

The SDS of the product containing the notified polymer provided by the notifier was reviewed by NICNAS. The accuracy of the information on the SDS remains the responsibility of the applicant.

## **ASSESSMENT DETAILS**

## 1. APPLICANT AND NOTIFICATION DETAILS

APPLICANT(S)

TDT Chemicals (ABN: 79 272 885 443)

62 Albion Road

**ASHBURTON VIC 3147** 

NOTIFICATION CATEGORY

Limited: Synthetic polymer with Mn  $\geq$  1,000 Da

EXEMPT INFORMATION (SECTION 75 OF THE ACT)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers, impurities, additives/adjuvants, use details, and import volume.

VARIATION OF DATA REQUIREMENTS (SECTION 24 OF THE ACT)

Variation to the schedule of data requirements is claimed for all endpoints.

PREVIOUS NOTIFICATION IN AUSTRALIA BY APPLICANT(S)

None

NOTIFICATION IN OTHER COUNTRIES

None

#### 2. IDENTITY OF CHEMICAL

MARKETING NAME(S)

HEXAFOR (containing the notified polymer at ≤ 25% concentration)

MOLECULAR WEIGHT

Number Average Molecular Weight (Mn) is > 10,000 g/mol.

ANALYTICAL DATA

Reference GPC spectra was provided.

## 3. COMPOSITION

DEGREE OF PURITY

>90%

LOSS OF MONOMERS, OTHER REACTANTS, ADDITIVES, IMPURITIES

No losses are expected during use.

DEGRADATION PRODUCTS

The notified polymer is a potential precursor for PFHxA in the environment. (PFHxA is hexanoic acid, 2,2,3,3,4,4,5,6,6-undecafluoro-, with CAS No. 307-24-4).

## 4. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AT 20 °C AND 101.3 kPa: Colourless to straw yellow liquid

Property	Value	Data Source/Justification
Melting Point/Freezing Point	Not determined	Imported in solution.
Boiling Point	Not determined	Expected to decompose prior to boiling.
Density	Not determined	Imported in solution.
Vapour Pressure	$< 1.3 \times 10^{-9} \text{ kPa}$	Estimated based on the NAMW > 1,000 g/mol (US EPA, 2013)
Water Solubility	Not determined	The notified polymer is not expected to be

		water soluble based on the predominantly
		hydrophobic chemical structure and high
		molecular weight and presence of
		hydrophobic and lipophobic fluorinated
		carbon functionalities
Hydrolysis as a Function of pH	Not determined	Contains hydrolysable functionality and may slowly hydrolyse in the
		environmental pH range (4-9)
Partition Coefficient	Not determined	Contains perfluoroalkyl functionalities
(n-octanol/water)		that are both hydrophobic and lipophobic
Adsorption/Desorption	Not determined	May have low absorption based on the
		presence of perfluoroalkyl functionalities
		which have both hydrophobic and
		lipophobic tendencies
Dissociation Constant	Not determined	The notified polymer does not contain
		dissociable functionalities
Flash Point	Not determined	Expected to be high based on the
		expected low vapour pressure and
		fluorinated structure of the notified
		polymer.
Flammability	Not determined	Imported in solution.
Autoignition Temperature	Not determined	Imported in solution.
Explosive Properties	Not determined	Not expected to have explosive properties
		based on its molecular structure.
Oxidising Properties	Not determined	Not expected to have oxidising properties
		based on its molecular structure.

## Reactivity

The notified polymer is expected to be stable under normal conditions of use.

## Physical hazard classification

Based on the submitted physico-chemical data depicted in the above table, the notified polymer is not recommended for hazard classification according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia.

## 5. INTRODUCTION AND USE INFORMATION

MODE OF INTRODUCTION OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

The notified polymer will not be manufactured in Australia. It will be imported as a component of a formulation/solution at  $\leq 25\%$  concentration in water or in petroleum distillates for local reformulation into industrial paints and coatings.

MAXIMUM INTRODUCTION VOLUME OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

Year	1	2	3	4	5
Tonnes	< 10	< 10	< 10	< 10	< 10

PORT OF ENTRY Melbourne

## TRANSPORTATION AND PACKAGING

The notified polymer will be imported by sea in sealed 800 kg antistatic IBCs and transported throughout Australia by road. Finished paints and coatings containing the notified chemical will be sold in cans up to 10 L in size.

## Use

The notified polymer will be used as a component of oil and water repellent paints and coatings at concentrations up to 1%. Products containing the notified chemical are intended for industrial and commercial use only and will not be sold to the public.

## OPERATION DESCRIPTION

#### Reformulation

At the reformulation sites, the imported products containing the notified polymer at  $\leq 25\%$  concentration are expected to be transferred to the sealed mixing vessel by metered dosing. The mixing process is expected to be enclosed and automated with local exhaust ventilation in place. The resultant paints and coatings containing the notified polymer at a concentration of  $\leq 1\%$  will be dispensed into steel paint cans and pails using an automated filling machine under exhaust ventilation.

#### End-use

Products containing the notified polymer at  $\leq$  1% will predominantly be applied by spray. Spray applications are expected to be conducted in spray booths with local exhaust ventilation. Products containing the notified polymer may also applied by brush, roller and curtain coating.

#### 6. HUMAN HEALTH IMPLICATIONS

## 6.1. Exposure Assessment

The notified polymer may undergo slow degradation in the environment. As such, most potential exposure to workers and the public is expected to be to the notified polymer itself, rather than to its degradation products. Exposure to the residual polyfluoroalkyl starting constituents of the notified polymer is also possible.

The notified polymer is a potential precursor for PFHxA in the environment. This may lead to secondary human exposure to PFHxA. This exposure is unquantifiable.

## 6.1.1. Occupational Exposure

#### CATEGORY OF WORKERS

Category of Worker	Exposure Duration (hours/day)	Exposure Frequency (days/year)
Transport	2-3	10-15
Paint formulation	0.5 - 6	30
QC testing	3	30
Filling	8	30
Maintenance	8	30
Automotive industry	0.5 - 6	220

## EXPOSURE DETAILS

Transport and storage

Transport and warehouse workers are expected to only come into contact with the notified polymer (at  $\leq 25\%$  concentration) in the unlikely event of an accident.

#### Reformulation process

Dermal and ocular exposure of workers to the notified polymer may occur due to drips, spills and splashes during charging of mixer, blending, sampling and filling and maintenance processes. Exposure will be limited by the workers use of PPE such as coveralls, goggles and impervious gloves. Inhalation exposure of the notified polymer may also occur due to the potential release of aerosols during reformulation processes. However, inhalation exposure will be limited by the use of enclosed mixing and exhaust ventilation systems.

#### End-use

Dermal, ocular and inhalation exposure of workers to the notified polymer (at  $\leq$  1% concentration) may occur when workers apply industrial paints and coatings. Personal protective equipment (PPE) is expected to be worn, including gloves, protective clothing (anti-static flame retardant overalls for spray operators), safety glasses and cartridge type respiratory protection when aerosols may be present. Professionals may be exposed on a repeated basis.

#### 6.1.2. Public Exposure

Products containing the notified polymer will be used in industrial settings only and will not be made available to the public. The public may come into contact with surfaces that have been painted or coated with products containing the notified polymer. However, once dried and cured, the notified polymer is bound within a solid matrix and will not be available for exposure.

#### 6.2. Human Health Effects Assessment

No toxicity data were submitted for the notified polymer.

The notified polymer is a polymethacrylate with a Mn > 10,000 g/mol with low percentage of low molecular weight species. This type of polymers may generally be considered to be of low hazard. However, the notified polymer contains polyfluorinated carbon chains and fluorinated polymers have been known to cause lung injury, which is characterised by respiratory problems ranging from mild to severe effects associated with acute or repeated exposures. Uncertainties remain surrounding possible acute or chronic respiratory tract effects following acute or repeated exposures to the notified polymer.

## Health hazard classification

As no toxicity data were provided, the notified polymer cannot be classified according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia.

## Hazard implication of breakdown products

The notified polymer contains polyfluoroalkyl side-chains that are potential precursors of PFHxA in the environment. PFHxA is a perfluorocarboxylic acid consisting of 5 perfluorinated carbons (a short chain perfluorinated chemical). The notified polymer is proposed to replace polymers that are expected to breakdown to form degradants with perfluoroalkyl carbon chain lengths ranging from 6 to 12. It has been known that the toxicokinetic and toxicological properties of fluorinated substances are generally becoming less favourable with increase of perfluoroalkyl carbon chain length. It has also been reported that the bioaccumulation potential of perfluorocarboxylic acids increases with perfluoroalkyl carbon chain length (Conder, 2008; Giesy 2010).

A review of the literature indicates that PFHxA has a less hazardous human health profile, compared to PFOA (NICNAS, a). It is therefore inferred that the human health hazards associated with the expected breakdown products of the notified polymer (PFHxA) are likely to be similar or less than those associated with PFOA or longer chain perfluorocarboxylic acids, which are known degradants of many perfluoroalkyl polymers currently on the market and that are intended for replacement by the notified polymer.

#### 6.3. Human Health Risk Characterisation

#### 6.3.1. Occupational Health and Safety

There are uncertainties surrounding possible acute or chronic respiratory tract effects from the notified polymer when inhaled. However, during the reformulation and end use, inhalation exposure of workers to the notified polymer is expected to be minimal due to use of enclosed and automated systems and the use of engineering controls such as spray booths and local exhaust ventilation, and use of PPE including safety glasses, impervious gloves, protective clothing and respirators.

Once the final paints are cured after end use, the notified polymer will be trapped in an inert polymer matrix and will not be available for further exposure.

Therefore, under the conditions of the occupational settings described, in the presence of engineering controls and PPE specified, the notified polymer is not considered to pose an unreasonable risk to occupational health.

Workers may also be exposed to per- and polyfluoroalkyl impurities of the notified polymer at low concentrations (< 0.1%), during use. It is expected that the PPE utilised during these operations (as outlined above) will mitigate any risk associated with such exposure.

## 6.3.2. Public Health

The notified polymer is intended for industrial use only and therefore direct exposure of members of the public to the notified polymer is not expected. Once the final paints containing the notified polymer are cured, the polymer is expected to be bound within inert matrix and will not be available for exposure. Therefore, the notified polymer is not considered to pose an unreasonable risk to public health.

The public may be exposed indirectly to the ultimate break down product of the notified polymer, PFHxA, via the environment. Such exposure may increase over time due to the persistence of PFHxA in the environment. However, the available data indicates that PFHxA has lower bioaccumulation potential than the long chain

perfluoroalkyl substances (such as PFOA) that are the ultimate break down products of long chain perfluoroalkyl polymers currently in Australian commerce. In particular, it is noted that the polymer being replaced contains perfluoroalkyl carbon chain lengths > 6. It is concluded that the risks to human health from indirect exposure to breakdown products of perfluoroalkyl substances will decrease following introduction of the notified polymer, on the basis that the notified polymer is intended to replace a currently available long chain perfluoroalkyl polymers.

#### 7. ENVIRONMENTAL IMPLICATIONS

## 7.1. Environmental Exposure & Fate Assessment

## 7.1.1. Environmental Exposure

#### RELEASE OF CHEMICAL AT SITE

The notified polymer will be imported as a component of a formulation in water or in petroleum distillates for local reformulation into industrial paints and coatings. No significant release of the notified polymer is expected from transportation, storage and potential repackaging processes, except in the unlikely event of accidental spills or leaks. In the event of spills (up to 1% of annual import volume as estimated by the notifier), the notified polymer is expected to be collected with inert adsorbents, and disposed of to landfill in accordance with local government regulation.

The notified polymer will be reformulated to final industrial paints and coatings locally. Reformulation is expected to be conducted following the standard operation procedure within enclosed and automated system. The resultant paints and coatings will be dispensed into steel paint cans and pails using an automated filling machine. Therefore, release of the notified polymer from reformulation is not expected to be significant. Solvents used for equipment cleaning are expected to be recycled for reuse on site or disposed of via accredited waste disposal contractors. Wastes containing residues of the notified polymer (up to 1% of annual import volume as estimated by the notifier) are expected to be contained on-site and disposed of in accordance with local regulations. Empty import containers with residues of the notified polymer may be disposed of to landfill.

#### RELEASE OF CHEMICAL FROM USE

Industrial paints and coatings containing the notified polymer will be applied to substrate by spray, roller or brush and curtain coating by professional workers in industrial facilities. Spray applications will be predominant and are expected to occur within spray booths with engineering controls to collect particulate overspray. The notified polymer may be also applied to wood boards by curtain coating which involves a continuous film of paint which falls over the board as it passes on the conveyor. Excess paint will be collected and returned to the paint reservoir.

All wastes generated during use, including overspray, residues in application equipment washings and empty paint containers are expected to be recycled, or allowed to cure before disposal as solid wastes to landfill in accordance with local regulations.

## RELEASE OF CHEMICAL FROM DISPOSAL

The notified polymer in industrial paints and coatings is expected to share the fate of the article to which it has been applied. These are predominantly expected to be disposed to landfill, or thermally decomposed during metal reclamation at the end of the useful life of article.

#### 7.1.2. Environmental Fate

No environmental fate data were submitted.

The notified polymer is methacrylate-based where one of the ester side chains is polyfluorinated. This polyfluorinated side-chain incorporates a chain segment of six perfluorinated carbon atoms. Under the NICNAS action plan for assessing and managing chemicals that could degrade to perfluorinated carboxylic acids, the notified polymer would be considered to be an indirect precursor to the exceptionally persistent perfluorinated carboxylic acid, perfluorohexanoic acid (PFHxA) and shorter-chain perfluorinated carboxylic acid (NICNAS, b).

The biodegradation potential of fluoroacrylate polymers in soils has been investigated and the studies show that analogous polymers have the potential to degrade to release fluorotelomer alcohols (Washington *et al.*, 2009, 2015). The notified polymer is derived from 6:2 fluorotelomer methacrylate and can therefore, potentially, release the 6:2 fluorotelomer alcohol, 6:2 FTOH. This polyfluorinated alcohol is known to undergo

environmental biodegradation to form short-chain perfluorocarboxylic acids, including perfluorohexanoic acid (PFHxA) (NICNAS, b).

When associated with the articles, the notified polymer is not likely to be mobile or bioavailable. Based on its high molecular weight, the notified polymer is not likely to cross biological membranes or to bioaccumulate.

The majority of the notified polymer is expected to adhere to the surface of articles to which it is applied. Treated articles and other dried residues containing the notified polymer are expected to ultimately be disposed of to landfill or subjected to metals reclamation.

The notified polymer will eventually degrade in landfill and has the potential to release per- and polyfluoroalkyl degradation products, including short-chain perfluorinated carboxylic acids, such as PFHxA.

PFHxA is a globally distributed pollutant and is expected to be recalcitrant in the environment, potentially undergo long range transport while mainly staying in the water column. In water, it is expected to be very persistent and will not hydrolyse, photolyse or biodegrade under environmental conditions (NICNAS, c).

PFHxA is expected to be less bioaccumulative than perfluorooctanoic acid (PFOA) and other long-chain perfluoroalkyl acids, supported by the available laboratory (Higgins *et al.*, 2007; Martin *et al.*, 2003a, b; Woodcroft *et al.*, 2010) and field (Falandysz *et al.*, 2006; Falandysz *et al.*, 2007, Furdui *et al.*, 2007) evidence. In general, bioaccumulation potential decreases when the length of the perfluorinated carbon chain is decreased (Ng and Hungerbühler, 2014, Giesy *et al.*, 2010). The short-chain perfluorocarboxylic acids, including PFHxA, have been assessed to have low bioaccumulation potential based on the currently available information (NICNAS, b, c).

## 7.1.3. Predicted Environmental Concentration (PEC)

A PEC has not been calculated for the notified polymer because, based on its reported use pattern (including during reformulation), significant quantities are not expected to be released to the aquatic environment.

PEC for PFHxA and other perfluorocarboxylic acids

The notified polymer has the potential to degrade and ultimately form the persistent degradant, PFHxA. However, the yield and rate of conversion of the notified polymer to PFHxA and shorter-chain carboxylic acids has not been established and depends on environmental conditions (microbial communities, Eh, pH, soil characteristics and climate conditions)

Environmental monitoring data shows that PFHxA and PFOA are widely found in the environment, particularly in fresh water close to industrial sources, but also in some biota. Water appears to be the main compartment where PFHxA is found. High measured concentrations of both PFHxA and PFOA in surface waters in Germany have been associated with the legal application of waste materials to agricultural soils (Skutlarek et al., 2006), indicating that these chemicals have the potential to enter the aquatic compartment following initial release into the soil compartment.

Some larger available data sets from the literature (McLachlan *et al.*, 2007; Skutlarek *et al.*, 2006; Nakayama *et al.*, 2007; So *et al.*, 2007; Ahrens *et al.*, 2009) include monitoring from a range of rivers in Europe, the USA and China, along with data from the Atlantic Ocean. Using these data ( $n \ge 60$ ), the 10th, 50th and 90th percentile concentrations for PFHxA are 1.0, 6.15 and 22.5 ng/L respectively, while those for PFOA are 2.94, 11.85 and 231.9 ng/L respectively. As use of chemicals that degrade to form PFHxA increases, levels of PFHxA may build up further in the environment.

Analyses of drinking water samples from Europe, Canada, the USA, Japan, India and China have also detected PFHxA and other short chain perfluoroalkyl compounds. PFHxA was recently detected in all samples taken from the Parramatta River (main tributary of Sydney Harbour), with a mean concentration of 2.9 ng/L. Sampling of the Brisbane River catchment following a major flooding event in 2011 also found PFHxA present in water at Somerset Dam, Wivenhoe Dam, Jindalee, Oxley Creek, West End, Bulimba and Moreton Bay. The chemical was detected in all samples obtained at these sites in concentrations ranging between 0.06 and 6.2 ng/L (NICNAS, c).

PFHxA and other poly- and perfluoroalkyl compounds have also been found in landfill leachate, with concentrations of PFHxA ranging from 270 – 790 ng/L (Huset *et al.*, 2011). As landfills are reservoirs of solid waste, and receive waste water treatment plant sludge, which may contain poly- and perfluoroalkyl compounds,

landfills have the potential to continue to release PFHxA and homologous perfluorinated carboxylic acids well into the future.

The lifetime of PFHxA in the aquatic environment is unknown, but is expected to be comparable to the very long lifetimes established for homologous perfluorinated acids such as PFOA and PFOS (NICNAS, d, e).

#### 7.2. Environmental Effects Assessment

## Effects of the notified polymer

No ecotoxicity data were submitted. Non-ionic polymers are generally of low toxicity to aquatic life and the notified polymer is expected to have very limited aquatic exposure based on its use pattern.

## Effects of PFHxA and other perfluorocarboxylic acids

The currently available data, summarised in the NICNAS IMAP Environment Tier II Assessment for Short-Chain Perfluorocarboxylic Acids and their Direct Precursors, indicate that PFHxA and other short-chain perfluorinated acids (i.e. those with five or fewer perfluorinated carbon atoms) have low toxicity to aquatic life (NICNAS, b, c) compared to PFOA and perfluorocatnesulfonic acid (PFOS) (NICNAS, d, e). However, no long-term intergenerational studies were identified for PFHxA and other short chain short-chain PFCAs. Emerging evidence suggest that the most significant aquatic toxicity effects of PFOA and PFOS may manifest in offspring when the parent generation is exposed to PFOA or PFOS (NICNAS, d, e).

#### 7.2.1. Predicted No-Effect Concentration

A predicted no-effect concentration (PNEC) has not been calculated for the notified polymer as, based on its reported use pattern, significant quantities are not expected to be released to the aquatic environment.

#### 7.3. Environmental Risk Assessment

The risk quotient (Q = PEC/PNEC) for the notified polymer has not been calculated because release to the aquatic environment in significant quantities is not expected based on its use pattern in industrial paints and coatings.

However, the notified polymer has the potential to eventually degrade to form very persistent PFHxA. PFHxA is currently understood to have low potential for bioaccumulation (NICNAS, c). The currently available data also indicate that PFHxA and other short-chain perfluorocarboxylic acids and their direct precursors have low toxicity to aquatic life (NICNAS, b, c).

The main environmental risks associated with polyfluoroalkyl polymers relate to the release of perfluorinated degradation products such as PFHxA. It is not possible to quantify the release of PFHxA to the environment from the use of the notified polymer at present. However, as use of chemicals/polymers that degrade to form PFHxA increases, levels of PFHxA may build up in the environment. Hence, there is potential for environmentally significant concentrations to eventually be reached following its accumulation in the environment. In this eventuality, precursors of PFHxA such as the notified polymer cannot be recalled after release and are potential sources of PFHxA releases into the environment even long after their use ceases. Thus, use and disposal of the notified polymer will likely lead to increases in the levels of PFHxA in the environment.

## Conclusions

On the basis of the assessed use pattern, the notified polymer itself is not considered to directly pose an unreasonable short-term risk to the environment. However, the notified polymer contains fluorinated carbon groups that have the potential to degrade to the exceptionally persistent short-chain perfluorinated carboxylic acid, PFHxA.

The environmental degradation of the notified polymer is expected to contribute to the cumulative emissions of perfluorohexanoic acid to the environment. Based on the currently available evidence, the concentrations of PFHxA and other short-chain perfluorinated carboxylic acids are not considered to pose a concern for the health of the environment. However, if additional hazard information becomes available to indicate that short-chain perfluorinated carboxylic acids have hazard characteristics of high concern for the environment (such as PBT properties), then the risks posed by industrial uses of precursors to these environmental degradants may need to be re-assessed.

## **BIBLIOGRAPHY**

- Ahrens L, Felizeter S, Sturm R, Xie Z and Ebinghaus R (2009). Polyfluorinated compounds in wastewater treatment plant effluents and surface waters along the River Elbe, Germany. Mar Pollut Bull, **58**(9):1326-1333.
- Conder JM, Hoke RA, de Wolf W, Russell MH, Buck RC (2008). Are PFCAs bioaccumulative? A critical review and comparison with regulatory criteria and persistent lipophilic compounds. Environ Sci Technol;42:995–1003.
- Falandysz J, Taniyasu S, Gulkowska A, Yamashita N and Schulte-Oehlmann U (2006) Is Fish A Major Source of Fluorinated Surfactants and Repellents in Humans Living on the Baltic Coast. Environ Sci Technol, 40(3):748-751.
- Falandysz J, Taniyasu S, Yamashita N, Rostkowski P, Zalewski K and Kannan K (2007) Perfluorinated compounds in some terrestrial and aquatic wildlife species from Poland. J Environ Sci Health, Part A: Environ Sci Eng. **42**(6):715-719.
- Furdui V, Stock N, Ellis D, Butt C, Whittle D, Crozier P, Reiner E, Muir D and Mabury S (2007) Spatial Distribution of Perfluoroalkyl Contaminants in Lake Trout from the Great Lakes. Environ Sci Technol, 41(5):1554-1559.
- Giesy JP, Nail JE, Khim JS, Jones PD & Newsted JL (2010) Aquatic Toxicology of Perfluorinated Chemicals. Rev Environ Contam Toxicol, 202: 1-52.
- Higgins C, McLeod P, Macmanus-Spencer L and Luthy R (2007) Bioaccumulation of Perfluorochemicals in Sediments by the Aquatic Oligochaete Lumbriculus variegatus. Environ Sci Technol, **41**(13):4600-4606.
- Huset C A, Barlaz M A, Barofsky D F and Field J A (2011). Quantitative determination of fluorochemicals in municipal landfill leachates, <u>Chemosphere</u>, **82**(10):1380-1386.
- Martin J, Mabury S, Solomon K and Muir D (2003a) Bioconcentration and Tissue Distribution of Perfluorinated Acids in Rainbow Trout (*Oncorhynchus mykiss*). Environ Sci Technol, **22**(1):196:204.
- Martin J, Mabury S, Solomon K and Muir D (2003b) Dietary Accumulation of Perfluorinated Acids in Juvenile Rainbow Trout (*Oncorhynchus mykiss*). Environ Toxicol Chem, **22**(1):189-195.
- McLachlan M, Holmstrom K, Reth M and Berger U (2007) Riverine Discharge of Perfluorinated Carboxylates from the European Continent. Environ Sci Technol, **41**(21):7260-7265.
- Nakayama S, Strynar M, Helfant L, Egeghy P, Ye X and Lindstrom A (2007) Perfluorinated Compounds in the Cape Fear Drainage Basin in North Carolina. Environ Sci Technol, **41**(15):5271-5276.
- Ng CA and Hungerbühler K (2014). Bioaccumulation of Perfluorinated Alkyl Acids: Observations and Models. *Environmental Science and Technology*, **48**(9), pp 4637-4648.
- NICNAS a. *IMAP Human Health Tier II Assessment for Short Chain Perfluorocarboxylic Acids and their Direct Precursors*. National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia. http://www.nicnas.gov.au/chemical-information/imap-assessments/imap-group-assessment-report?assessment id=1686.
- NICNAS b *IMAP Environment Tier II Assessment for Indirect Precursors to Short-Chain Perfluorocarboxylic Acids*, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/indirect-precursors-to-short-chain-perfluorocarboxylic-acids, Access on 22 February 2017.
- NICNAS c IMAP Environment Tier II Assessment for Short-Chain Perfluorocarboxylic Acids and their Direct Precursors, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/short-chain-perfluorocarboxylic-acids-and-their-direct-precursors. Accessed on 22 February 2017
- NICNAS d IMAP Environment Tier II Assessment for Perfluorooctanoic acid (PFOA) and its direct precursor, National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia, https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/perfluorooctanoic-acid-and-its-direct-precursors. Accessed on 22 February 2017
- NICNAS e IMAP Environment Tier II Assessment for Direct Precursors to Perfluorooctanesulfonate (PFOS), National Industrial Chemicals Notification and Assessment Scheme, Sydney, Australia,

https://www.nicnas.gov.au/chemical-information/imap-assessments/imap-assessments/tier-ii-environment-assessments/direct-precursors-to-perfluorooctanesulfonate-pfos. Accessed on 18 January 2017.

- NTC (2017) Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code), Edition 7.5, National Transport Commission, Commonwealth of Australia
- Skutlarek D, Exner M & Färber H (2006) Perfluorinated Surfactants in Surface and Drinking Waters. Environ Sci Pollut Res, 13(5):299-307.
- So M, Miyake Y, Yeung W, Ho Y, Taniyasu S, Rostkowski P, Yamashita N, Zhou B, Shi X, Wang J, Giesy J, Yu H and Lam P (2007) Perfluorinated compounds in the Pearl River and Yangtze River of China. Chemosphere, 68(11):2085-2095.
- SWA (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, https://www.safeworkaustralia.gov.au/doc/model-code-practice-spray-painting-and-powder-coating.
- SWA (2012) Code of Practice: Managing Risks of Hazardous Chemicals in the Workplace, Safe Work Australia, https://www.safeworkaustralia.gov.au/doc/model-code-practice-managing-risks-hazardous-chemicals-workplace
- United Nations (2009) Globally Harmonised System of Classification and Labelling of Chemicals (GHS), 3rd revised edition. United Nations Economic Commission for Europe (UN/ECE), http://www.unece.org/trans/danger/publi/ghs/ghs rev03/03files e.html
- US EPA (United States Environmental Protection Agency) (2013), Interpretive Assistance Document for Assessment of Polymers. Sustainable Futures Summary Assessment. Updated June 2013: https://www.epa.gov/sites/production/files/2015-05/documents/06-iad\_polymers\_june2013.pdf Accessed (13 October 2017).
- Washington J, Ellington J, Jenkins T, Evans J, Yoo H and Hafner S (2009) Degradability of an acrylate-linked, fluorotelomer polymer in soil. Environmental Science and Technology, **43**(17):6617-6623.
- Washington J, Jenkins T, Rankin K, Naile J (2015) Decades-scale degradation of commercial, side-charn, fluorotelomer-based polymers in soils and water. Environmental Science and Technology, **49**(2):915-923
- Woodcroft M, Ellis D, Rafferty S, Burns D, March R, Stock N, Trumpour K, Yee J and Munro K (2010) Experimental Characterization of the Mechanism of Perfluorocarboxylic Acids' Liver Protein Bioaccumulation: The Key Role of the Neutral Species. Environ Toxicol Chem, Early View. DOI: 10.1002/etc.199.