

File No PLC/834

May 2009

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME  
(NICNAS)**

**FULL PUBLIC REPORT**

**Polymer in R9915 Polyester Resin**

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. This legislation is an Act of the Commonwealth of Australia. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health and Ageing, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Department of the Environment, Water, Heritage and the Arts.

For the purposes of subsection 78(1) of the Act, this Full Public Report may be inspected at our NICNAS office by appointment only at 334-336 Illawarra Road, Marrickville NSW 2204.

This Full Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	334 - 336 Illawarra Road MARRICKVILLE NSW 2204, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX	+ 61 2 8577 8888.
Website:	<a href="http://www.nicnas.gov.au">www.nicnas.gov.au</a>

**Director  
NICNAS**

## **TABLE OF CONTENTS**

FULL PUBLIC REPORT .....	3
1. APPLICANT AND NOTIFICATION DETAILS .....	3
2. IDENTITY OF CHEMICAL .....	3
3. PLC CRITERIA JUSTIFICATION .....	3
4. PHYSICAL AND CHEMICAL PROPERTIES .....	4
5. INTRODUCTION AND USE INFORMATION .....	4
6. HUMAN HEALTH IMPLICATIONS .....	4
7. ENVIRONMENTAL IMPLICATIONS .....	4
8. CONCLUSIONS AND RECOMMENDATIONS .....	5
Human health risk assessment .....	5
Environmental risk assessment .....	5
Recommendations .....	5
Regulatory Obligations .....	5

**FULL PUBLIC REPORT****Polymer in R9915 Polyester Resin****1. APPLICANT AND NOTIFICATION DETAILS**

## APPLICANT(S)

The Valspar (Australia) Corporation Pty Limited (ABN: 82 000 039 396)  
203 Power Street  
Glendenning NSW 2761

## NOTIFICATION CATEGORY

Polymer of Low Concern

## EXEMPT INFORMATION (SECTION 75 OF THE ACT)

Data items and details claimed exempt from publication:

Chemical Name, CAS Number, Molecular and Structural Formulae, Molecular Weight, Polymer Constituents, Residual Monomers/Impurities, Use Details, Manufacture Volume.

## VARIATION OF DATA REQUIREMENTS (SECTION 24 OF THE ACT)

No variation to the schedule of data requirements is claimed.

## PREVIOUS NOTIFICATION IN AUSTRALIA BY APPLICANT(S)

None

## NOTIFICATION IN OTHER COUNTRIES

None

**2. IDENTITY OF CHEMICAL**

## MARKETING NAME(S)

Polymer in R9915 Polyester Resin

## MOLECULAR WEIGHT (MW)

Number Average Molecular Weight (Mn) >1000 Da

## REACTIVE FUNCTIONAL GROUPS

The notified polymer contains only low concern functional groups.

**3. PLC CRITERIA JUSTIFICATION***Criterion*

Molecular Weight Requirements  
Functional Group Equivalent Weight (FGEW) Requirements  
Low Charge Density  
Approved Elements Only  
Stable Under Normal Conditions of Use  
Not Water Absorbing  
Not a Hazard Substance or Dangerous Good

*Criterion met*

Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes

The notified polymer meets the PLC criteria.

#### 4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa:	Clear solid
Glass Transition Temp	Approximately 50°C
Density	1300 kg/m <sup>3</sup> at 25°C
Water Solubility	1.4 g/L. Tested gravimetrically after filtration of the notified polymer/water mixture. The water solubility is expected to be low based on the largely hydrophobic structure of the notified polymer.
Dissociation Constant	Not determined. No dissociable functional groups are present in the notified polymer.
Reactivity	Stable under normal environmental conditions
Degradation Products	None under normal conditions of use. Hydrolysis is not expected to occur in the environmental pH range of 4 – 9 despite the presence of hydrolysable functional groups in the notified polymer.

#### 5. INTRODUCTION AND USE INFORMATION

##### MAXIMUM INTRODUCTION VOLUME OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

<i>Year</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>
<i>Tonnes</i>	10-30	30-100	100-300	100-300	< 500

##### Use

The notified polymer will be used in industrial coating formulations. It will be applied to surfaces of metal and later fabricated into articles.

##### Mode of Introduction and Disposal

The notified polymer will be manufactured within Australia as a resin solution (60 - 90%) and then formulated into paints.

#### 6. HUMAN HEALTH IMPLICATIONS

##### Hazard Characterisation

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be considered to be of low hazard.

##### Occupational Health and Safety Risk Assessment

Dermal and ocular exposure to the notified polymer may occur during manufacturing and formulation processes, for example during filling drums, transfer of resin and mixing with other ingredients. Exposure to significant amounts of the notified polymer will be limited because of the engineering controls (closed vessel, use of drum handling equipment, etc) and personal protective equipment (coveralls, eye protection, gloves).

Worker exposure during paint application to metal surfaces is unlikely due to the automated nature of the external roller coating process that will be used.

Overall, the OHS risk presented by the notified polymer is expected to be low, based on the minimal exposure to workers and the expected low hazard of the polymer.

##### Public Health Risk Assessment

Products containing the notified polymer will not be available to the public. The public may come into contact with substrates coated in paint containing the notified polymer, however, it is expected to be encapsulated in the coating and not bioavailable. Given that the notified polymer is of low hazard and is bound within a matrix, the risk to public health is expected to be negligible.

#### 7. ENVIRONMENTAL IMPLICATIONS

##### Hazard Characterisation

No ecotoxicological data were submitted. PLCs without significant ionic functionality are of low concern to the aquatic environment.

##### Environmental Risk Assessment

The notified polymer will most likely end up in landfill to undergo slow processes of biotic and abiotic degradation. Release of the notified polymer to the aquatic environment is not expected at any point in manufacture, formulation, use or ultimate disposal. Therefore, the notified polymer is not expected to pose an unacceptable risk to the environment based on the reported use pattern.

## 8. CONCLUSIONS AND RECOMMENDATIONS

### Hazard Characterisation

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be considered to be of low hazard.

### Human health risk assessment

Under the conditions of the occupational settings described, the notified polymer is not considered to pose an unacceptable risk to the health of workers.

When used in the proposed manner, the notified polymer is not considered to pose an unacceptable risk to public health.

### Environmental risk assessment

Based on the reported use pattern, the notified polymer is not considered to pose a risk to the environment.

### Recommendations

#### CONTROL MEASURES

##### Occupational Health and Safety

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself, however, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the MSDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Approved Criteria for Classifying Hazardous Substances* [NOHSC:1008(2004)], workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

##### Disposal

- The notified polymer should be disposed of to landfill or be incinerated during container or metal substrate recycling processes.

##### Emergency procedures

- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

### Regulatory Obligations

#### *Secondary Notification*

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory

obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
  - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
  - the function or use of the notified polymer has changed from a component of industrial coating formulations, or is likely to change significantly;
  - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
  - the method of manufacture of the notified polymer in Australia has changed, or is likely to change, in a way that may result in an increased risk of an adverse effect of the notified polymer on occupational health and safety, public health, or the environment;
  - additional information has become available to the person as to an adverse effect of the chemical on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

*Material Safety Data Sheet*

The MSDS of the R9915 Polyester Resin containing the notified polymer provided by the notifier was reviewed by NICNAS. The accuracy of the information on the MSDS remains the responsibility of the applicant.