NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in Synolac 1001

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health and Ageing, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of Sustainability, Environment, Water, Population and Communities.

For the purposes of subsection 78(1) of the Act, this Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

CITAMADV

December 2011

Table of Contents

	IIVIAIX I	
CON	ICLUSIONS AND REGULATORY OBLIGATIONS	2
ASS]	ESSMENT DETAILS	3
1.	APPLICANT AND NOTIFICATION DETAILS	3
2.	IDENTITY OF POLYMER	3
3.	PLC CRITERIA JUSTIFICATION	4
4.	PHYSICAL AND CHEMICAL PROPERTIES	4
5.	INTRODUCTION AND USE INFORMATION	4
6.	HUMAN HEALTH RISK ASSESSMENT	4
	ENVIRONMENTAL RISK ASSESSMENT	

SUMMARY

The following details will be published in the NICNAS Chemical Gazette:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1027	PPG Industries	Polymer in Synolac	No	< 1 tonne per	Component of coatings
	Australia Pty Ltd	1001		annum	

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

No specific engineering controls, work practices or personal protective equipment are required
for the safe use of the notified polymer itself, however, these should be selected on the basis
of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the MSDS should be easily accessible to employees.
- Spray application should be carried out in accordance with the Safe Work Australia *National Guidance Material for Spray Painting* [NOHSC (1999)].
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Approved Criteria for Classifying Hazardous Substances* [NOHSC:1008(2004)], workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

Disposal

• The notified polymer should be disposed to landfill.

Emergency Procedures

- Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.
- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and*

Assessment) Act (1989) the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from component of coatings, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

Material Safety Data Sheet

The MSDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the MSDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

PPG Industries Australia Pty Ltd (ABN 82 055 500 939) McNaughton Rd CLAYTON VIC 3168

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume

2. IDENTITY OF POLYMER

Marketing Name(s)

Polymer in Synolac 1001

Molecular Weight

Number Average Molecular Weight (Mn) is > 1,000 Da

Reactive Functional Groups

The notified polymer contains only low concern functional groups.

3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa Viscous liquid (formulation)

Melting Point/Glass Transition Temp Not determined

Density 1320 kg/m³ (temperature unknown) for the formulation Water Solubility Not determined. Expected to have low solubility based on

structural considerations.

Particle Size Liquid (formulation)

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	< 1	< 1	< 1	< 1	< 1

Use

The notified polymer will not be manufactured or reformulated in Australia.

The notified polymer will be imported at < 1% to use as part of a two pack coating for aircraft and metal structures at a concentration of < 1%. The paint is typically applied by airless spray equipment or air-assisted high-volume low-pressure spray equipment.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Polymers without significant ionic functionality are generally of low concern to the environment. The notified polymer is not manufactured or reformulated in Australia; therefore, there is no release due to these activities. Most of the notified polymer will be irreversibly incorporated within an inert polymer matrix adhering to aircraft and metal structures following application of coating. The notified polymer is expected to share the fate of articles to which it has been applied and be either disposed of to landfill or recycled at the end of the articles useful life. During industrial use of the notified polymer it is estimated that up to 1% of the notified polymer may be spilt, 1% may remain as residues in import containers and, with an application efficiency of 40-60% by spray, up to 60% may be released as overspray which is expected to be captured on tarpaulins or plastic coverings. Residues in import containers, spills and overspray are expected to be collected and disposed of to landfill. Up to 1% of the import volume of notified polymer is estimated to be released to sewers during use as residues in application equipment washings. However, due to its expected low water solubility the majority of the notified polymer is expected to sorb to sludge during sewage treatment and be disposed of to landfill. The notified polymer is not expected to be readily biodegradable but due to its high molecular weight is not expected to cross biological membranes and it is therefore not expected to bioaccumulate. The notified polymer is expected to eventually degrade in landfill, or be thermally decomposed during metals reclamation, to form water and oxides of carbon. Therefore, based on its assumed low hazard and assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.