NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN FULL PUBLIC REPORT

Polymer in SURPASS ELITE W Series

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (Cwlth) (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health and Ageing, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of Sustainability, Environment, Water, Population and Communities.

For the purposes of subsection 78(1) of the Act, this Full Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Full Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

April 2011

Table of Contents

| 1. | APPLICANT AND NOTIFICATION DETAILS | . 2 |
|----|------------------------------------|-----|
| 2. | IDENTITY OF POLYMER | . 2 |
| | PLC CRITERIA JUSTIFICATION | |
| | PHYSICAL AND CHEMICAL PROPERTIES | |
| | INTRODUCTION AND USE INFORMATION | |
| | HUMAN HEALTH RISK ASSESSMENT | |
| | ENVIRONMENTAL RISK ASSESSMENT | |
| | RECOMMENDATIONS | |

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

Akzo Nobel Car Refinishes Australia Pty Ltd (ABN 26 087 571 882) 269 Williamstown Road PORT MELBOURNE VIC 3207

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)

SURPASS ELITE W Series

Molecular Weight

Number Average Molecular Weight (Mn) is > 1,000 Da

Reactive Functional Groups

The notified polymer contains only low concern functional groups.

3. PLC CRITERIA JUSTIFICATION

| Criterion | Criterion met |
|--|---------------|
| Molecular Weight Requirements | Yes |
| Functional Group Equivalent Weight (FGEW) Requirements | Yes |
| Low Charge Density | Yes |
| Approved Elements Only | Yes |
| Stable Under Normal Conditions of Use | Yes |
| Not Water Absorbing | Yes |
| Not a Hazard Substance or Dangerous Good | Yes |

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa: Imported as a component of a solid mixture Melting Point/Glass Transition Temp Density Imported as a component of a solid mixture Imported as a component of a solid mixture

Water Solubility < 800 g/L at 20°C. Expected to be water dispersible based

on the presence of polar functionality and the use pattern in

water containing solvent systems.

Dissociation Constant $pKa \sim 4$. The notified polymer contains functionality that is

expected to dissociate in the environmental pH range (4–9).

Particle Size Not determined, however the notified polymer is expected

to be water dispersible.

Reactivity Stable under normal environmental conditions. Hydrolysis

is not expected to occur in the environmental pH range 4–9.

Degradation Products None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

| Year | 1 | 2 | 3 | 4 | 5 |
|--------|------|------|------|------|------|
| Tonnes | < 25 | < 25 | < 25 | < 25 | < 25 |

Use

The notified polymer will not be manufactured in Australia.

The notified polymer will be imported into Australia as a component of a pigment dispersant in solid form at a concentration of < 10%.

The imported pigment products will be incorporated into automotive refinish paints and industrial coatings resulting in the finished paint/coating products containing up to 1% notified polymer.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unacceptable given the assumed low hazard.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Anionic polymers are known to be moderately toxic to algae. The mode of toxic action is over-chelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone. This may apply to the notified polymer, however, the toxicity to algae is likely to be reduced due to the presence of calcium ions in the aquatic compartment which will bind to the acid functional groups.

Notified polymer in reformulation wastes, container residues and fully cured solid wastes are expected to be collected and sent to a licensed waste facility for disposal in accordance with state/territory waste standards. The main release as overspray during use will typically entail landfill disposal, after interception by spray booth filters. If residues are washed to sewer from cleaning of reformulation and application equipment, the notified polymer is expected to partition to sludge during sewage treatment.

Once cured, the coatings containing the notified polymer will form an inert polymer matrix, and the incorporated notified polymer will not be bioavailable. Discarded coated articles will be either sent to landfill or thermally decomposed during the recycling of the coated substrates at the end of their useful lives. In landfill, the notified polymer contained in solid waste or on coated surfaces is expected to be immobile due to its incorporation into an inert matrix of cured coatings and will eventually degrade via abiotic or biotic processes into water and oxides of carbon and nitrogen. The notified polymer is not expected to be readily biodegradable, but bioaccumulation is not likely based on its high molecular weight.

Therefore, the notified polymer is not expected to pose an unacceptable risk to the aquatic environment based on the reported use pattern and its characteristics as a PLC.

8. RECOMMENDATIONS

Human Health Risk Assessment

When used in the proposed manner, the notified polymer is not considered to pose an unacceptable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the reported use pattern, the notified polymer is not expected to pose a risk to the environment.

Health and Safety Recommendations

No specific engineering controls, work practices or personal protective equipment are required
for the safe use of the notified polymer itself, however, these should be selected on the basis of
all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the MSDS should be easily accessible to employees.
- Spray application should be carried out in accordance with the Safe Work Australia *National Guidance Material for Spray Painting* [NOHSC (1999)].
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Approved Criteria for Classifying Hazardous Substances* [NOHSC:1008(2004)], workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

Disposal

• The notified polymer should be disposed of to landfill.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from a component of surface coatings, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;

- the notified polymer has begun to be manufactured in Australia;
- additional information has become available to the person as to an adverse effect of the chemical on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

Material Safety Data Sheet

The MSDS of products containing the notified polymer were provided by the applicant. The accuracy of the information on the MSDS remains the responsibility of the applicant.