# NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

# POLYMER OF LOW CONCERN PUBLIC REPORT

#### Z-130

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health and Ageing, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of Sustainability, Environment, Water, Population and Communities.

For the purposes of subsection 78(1) of the Act, this Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

April 2012

## **Table of Contents**

SUM	1MARY	. 2
CON	ICLUSIONS AND REGULATORY OBLIGATIONS	. 2
ASS	ESSMENT DETAILS	. 3
	APPLICANT AND NOTIFICATION DETAILS	
	IDENTITY OF POLYMER	
	PLC CRITERIA JUSTIFICATION	
	PHYSICAL AND CHEMICAL PROPERTIES	
	INTRODUCTION AND USE INFORMATION	
	HUMAN HEALTH RISK ASSESSMENT	
	HUMAN HEALTH RISK ASSESSMENT	
	FNVIRONMENTAL RISK ASSESSMENT	

# **SUMMARY**

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1053	LUBRIZOL INTERNATIONAL INC	Z-130	No	≤ 20 tonnes per annum	Used as a component of surface coatings

# **CONCLUSIONS AND REGULATORY OBLIGATIONS**

## **Human Health Risk Assessment**

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

## **Environmental Risk Assessment**

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

## **Health and Safety Recommendations**

No specific engineering controls, work practices or personal protective equipment are required
for the safe use of the notified polymer itself. However, these should be selected on the basis of
all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the MSDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Approved Criteria for Classifying Hazardous Substances* [NOHSC:1008(2004)], workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

## **Environmental Recommendations**

 No specific control measures are required to minimise release of the notified polymer to the environment.

## **Disposal**

• The notified polymer should be disposed of to landfill.

## Storage

- The following precautions should be taken by workers regarding storage of the notified polymer:
  - Store in a segregated and approved area.
  - Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (oxidising substances, strong acids, strong bases).

# **Emergency Procedures**

- Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.
- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

## **Secondary Notification**

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
  - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
  - the function or use of the notified polymer has changed from a component of surface coatings, or is likely to change significantly;
  - the amount of notified polymer being introduced has increased per annum, or is likely to increase, significantly;
  - the notified polymer has begun to be manufactured in Australia;
  - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

## **Material Safety Data Sheet**

The MSDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the MSDS remains the responsibility of the applicant.

## ASSESSMENT DETAILS

## 1. APPLICANT AND NOTIFICATION DETAILS

# **Applicants**

Lubrizol International Inc. (ABN 52 073 495 603) 28 River Street SILVERWATER NSW 2128

# **Exempt Information (Section 75 of the Act)**

Data items and details claimed exempt from publication: chemical name, CAS number, structural formulae, molecular weight, polymer constituents, residual monomers/impurities and import volume.

## 2. IDENTITY OF POLYMER

# Marketing Name(s)

Turboset Ultra Pro (contains the notified polymer at  $\leq 37$  %).

## Other Name(s)

Z - 130

# **Reactive Functional Groups**

The notified polymer contains amine functional groups. As the functional group equivalent weight (FGEW) is greater than 5000, the polymer can be classified as a PLC.

## 3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Not applicable
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

## 4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa Milky white liquid

Melting Point/Glass Transition Temp > 250 °C

Density  $1000 \text{ kg/m}^3 \text{ at } 25 \text{ }^{\circ}\text{C*}$ 

Water Solubility Not determined. The notified polymer is expected to be

water dispersible based on the presence of polar

functionality and the use pattern in water containing solvent

systems.

Dissociation Constant Not determined. The notified polymer is a salt and will be

ionised under environmental conditions.

Particle Size Imported as an aqueous solution

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

#### 5. INTRODUCTION AND USE INFORMATION

## Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	≤ 20	≤ 20	≤ 20	≤ 20	≤ 20

#### Use

The notified polymer will not be manufactured in Australia. The notified polymer will be imported into Australia as a component of finished surface coatings in an aqueous solution at a concentration of  $\leq 37$  %.

<sup>\*</sup>For imported product containing the notified polymer in an aqueous solution at  $\leq$  37 %.

# 6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

## 7. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be considered to be of low hazard.

## 8. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Anionic polymers are known to be moderately toxic to algae. The mode of toxic action is over-chelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone. This is unlikely to apply to the notified polymer and it is therefore not considered to be an over-chelation hazard to algae. The notified polymer also contains potentially cationic functionality, however the cationic charge density is low and the notified polymer is therefore not expected to be of concern to the aquatic environment.

There will be no local manufacture or re-formulation of the notified polymer, and therefore, no release of the notified polymer to the environment is expected from these processes. Maximum release of up to 1.6% of the total import volume of notified polymer to the environment may occur from spills (<0.54%), residues in empty containers (<0.54%) and cleaning of equipment (<0.54%) during use. Excess coating is not expected during its use. Accidental spills are expected to be contained, collected and disposed of to landfill or washed to sewer. In the case that coating residues are washed to sewer from cleaning of spills and application equipment, the notified polymer is not expected to be released at ecotoxicologically significant concentrations.

Once cured, the coatings containing the notified polymer will form an inert polymer matrix, and the incorporated notified polymer will not be bioavailable. Discarded coated articles are expected to be disposed of to landfill at the end of their useful lives. In landfill, the notified polymer contained in solid waste or on coated surfaces is expected to be immobile due to its incorporation into an inert matrix and will eventually degrade via abiotic or biotic processes into water and oxides of carbon and nitrogen. The notified polymer is not expected to be readily biodegradable and bioaccumulation is not likely based on its very high molecular weight. Therefore, the notified polymer is not considered to pose an unreasonable risk to the aquatic environment based on the assessed use pattern.