2

NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in 80207 ALKYD

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals* (Notification and Assessment) Act 1989 (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

May 2019

SHMMARY

Table of Contents

D C 14.	11/11/11/11/11	_
CON	ICLUSIONS AND REGULATORY OBLIGATIONS	2
ASS	ESSMENT DETAILS	4
1.	APPLICANT AND NOTIFICATION DETAILS	4
2.	IDENTITY OF POLYMER	4
3.	PLC CRITERIA JUSTIFICATION	4
4.	PHYSICAL AND CHEMICAL PROPERTIES	4
5.	INTRODUCTION AND USE INFORMATION	4
6.	HUMAN HEALTH RISK ASSESSMENT	5
7.	ENVIRONMENTAL RISK ASSESSMENT	5
BIBI	LIOGRAPHY	5

SUMMARY

The following details will be published in the NICNAS Chemical Gazette:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1537	Cintox Australia	Polymer in 80207	No	< 1 tonne per	A component of paints
	Pty Ltd	ALKYD		annum	

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

• No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2015) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and*

Assessment) Act (1989) the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from a component of paints, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

Safety Data Sheet

The SDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

Cintox Australia Pty Ltd (ABN: 63 122 874 613) Suite 1, Level 2, 38-40 George Street PARRAMATTA NSW 2150

Exempt Information (Section 75 of the Act)

Data items and details exempt from publication include: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)

80207 ALKYD (containing the notified polymer at < 10% concentration)

Molecular Weight

Number Average Molecular Weight (Mn) is > 1,000 g/mol

3. PLC CRITERIA JUSTIFICATION

4	Yes
Molecular Weight Requirements	1 03
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa Viscous liquid
Melting Point/Glass Transition Temperature <-17 °C
Density 1.01 – 1.06
Water Solubility Insoluble

Particle Size The notified polymer will be introduced in solution.
Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	< 1	< 1	< 1	< 1	< 1

Use

The notified polymer will be imported into Australia in finished architectural paints at a concentration of < 10%. The notified polymer will not be manufactured or reformulated within Australia. The paint products containing the notified polymer will be sold to both the commercial and do-it-yourself (DIY) sectors and applied by brush, roller or spray.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Polymers without significant ionic functionality are generally of low concern to the environment.

The notified polymer will be imported in finished architectural paints and will not be reformulated or repackaged in Australia. Accidental spills of the products containing the notified polymer during import, transport, storage and use are expected to be absorbed on suitable materials and disposed of to landfill in accordance with local government regulations.

The paints will be used by professional workers and the public, and may be applied by brush, roller or spray. Paint excess to requirements, is expected to be collected and cured before disposal to landfill. The liquid waste from cleaning of professional application equipment is expected to be collected by an approved waste contractor for disposal in accordance with local government regulations. As the worst case scenario, it is assumed that up to 5% of the total annual import volume of notified polymer used by do-it-yourself (DIY) users may be incorrectly disposed of to the sewer, drains, or ground from waste and washing of application equipment. Assuming the worst-case where DIY users are the vast majority of users and the releases occur nationwide over the entire year with no removal of the notified polymer during wastewater treatment, the predicted environmental concentration (PEC) is estimated to be 0.03 μ g/L [0.05 × 1,000 kg/year \div 365 days/year \div (24.386 million persons × 200 L/person/day)]. As the notified polymer is expected to be generally of low concern to the aquatic environment, the release of the notified polymer is not expected to lead to ecotoxicologically significant concentrations in the aquatic environment.

Most of the notified polymer is expected to share the fate of the articles to which it has been applied, to be disposed of to landfill at the end of their useful lives. Residual notified polymer in empty containers is expected to be cured before disposal to landfill. In landfill, the notified polymer will be present as cured solids and will be neither bioavailable nor mobile. The notified polymer is not expected to bioaccumulate due to its high molecular weight. The notified polymer in landfill and water is expected to eventually degrade via biotic and abiotic processes to form water and oxides of carbon.

Therefore, based on its assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

BIBLIOGRAPHY

Safe Work Australia (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, https://www.safeworkaustralia.gov.au/doc/model-code-practice-spray-painting-and-powder-coating.