

File No PLC/646

19 June 2006

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME
(NICNAS)**

FULL PUBLIC REPORT

DP3001

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. This legislation is an Act of the Commonwealth of Australia. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Department of Health and Ageing, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Department of the Environment and Heritage.

For the purposes of subsection 78(1) of the Act, this Full Public Report may be inspected at:

Library
Australian Safety and Compensation Council
25 Constitution Avenue
CANBERRA ACT 2600
AUSTRALIA

To arrange an appointment contact the Librarian on TEL + 61 2 6279 1162 or email ascc.library@dewr.gov.au

This Full Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	334 - 336 Illawarra Road MARRICKVILLE NSW 2204, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX	+ 61 2 8577 8888.
Website:	www.nicnas.gov.au

**Director
NICNAS**

TABLE OF CONTENTS

FULL PUBLIC REPORT	3
1. APPLICANT AND NOTIFICATION DETAILS	3
2. IDENTITY OF CHEMICAL	3
3. PLC CRITERIA JUSTIFICATION	3
4. PHYSICAL AND CHEMICAL PROPERTIES	4
5. INTRODUCTION AND USE INFORMATION	4
6. HUMAN HEALTH IMPLICATIONS	5
6.1. Exposure Assessment	5
6.2. Toxicological Hazard Characterisation	5
6.3. Human Health Risk Assessment	5
7. ENVIRONMENTAL IMPLICATIONS	5
7.1. Exposure Assessment	5
7.2. Environmental Hazard Characterisation	6
7.3. Environmental Risk Assessment	6
8. CONCLUSIONS	6
8.1. Level of Concern for Occupational Health and Safety	6
8.2. Level of Concern for Public Health	6
8.3. Level of Concern for the Environment	6
9. MATERIAL SAFETY DATA SHEET	6
9.1. Material Safety Data Sheet	6
10. RECOMMENDATIONS	6
10.1. Secondary Notification	7

FULL PUBLIC REPORT**DP3001****1. APPLICANT AND NOTIFICATION DETAILS**

APPLICANT(S)

DuPont (Australia) Ltd (ABN 59 000 716 469)
168 Walker St
North Sydney NSW 2060

Canon Australia Pty. Ltd (ABN 66 005 002 951)
1 Thomas Holt Drive
North Ryde NSW 2113

NOTIFICATION CATEGORY

Polymer of Low Concern

EXEMPT INFORMATION (SECTION 75 OF THE ACT)

Data items and details claimed exempt from publication:

Chemical Name, Other Names, CAS Number, Molecular and Structural Formulae, Spectral data,
Molecular Weight, Polymer Constituents, Residual Monomers/Impurities, Use Details, and
Manufacture/Import Volume.

VARIATION OF DATA REQUIREMENTS (SECTION 24 OF THE ACT)

No variation to the schedule of data requirements is claimed.

PREVIOUS NOTIFICATION IN AUSTRALIA BY APPLICANT(S)

Expired Permits for the notified polymer held by DuPont (permit No. 529) under LVC/540, jointly
notified with Canon Australia (permit No. 528), permits issued April 2003.

NOTIFICATION IN OTHER COUNTRIES

USA 1992; Canada 1996.

2. IDENTITY OF CHEMICAL

MARKETING NAME(S)

DP3001

MOLECULAR WEIGHT (MW)

Number Average Molecular Weight (Mn) >1000

REACTIVE FUNCTIONAL GROUPS

The notified polymer contains only low concern functional groups.

3. PLC CRITERIA JUSTIFICATION

<i>Criterion</i>	<i>Criterion met (yes/no/not applicable)</i>
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa

Expected to be a solid. Introduced as a dispersion in water.

Melting Point/Glass Transition Temp

Not measured as polymer is introduced in solution.

Density

50% w/w solution in THF is 1140 kg/m³ (temperature not supplied)
Estimated density of solid 1100–1200 kg/m³.

Water Solubility

Not determined. A related polymer has a water solubility of 188 mg/L, based on the average of the highest values for dissolved carbon content of water in a polymer stability test. Based on the polymer structure, the notified polymer is expected to have a water solubility < 188 mg/L.

Dissociation Constant

The notified polymer contains an anionic functionality expected to have typical acidity.

Particle Size

Not measured as polymer only used in solution.

Reactivity

Stable under normal environmental conditions.

Degradation Products

None under normal conditions of use.

5. INTRODUCTION AND USE INFORMATION

MAXIMUM INTRODUCTION VOLUME OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

<i>Year</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>
<i>Tonnes</i>	< 1	< 1	< 1	< 1	< 1

USE AND MODE OF INTRODUCTION AND DISPOSAL

Mode of Introduction

Imported as a component (<10%) in printing ink in sealed ink cartridges.

Reformulation/manufacture processes

No reformulation or manufacturing processes will occur in Australia.

Use

The printing ink cartridges containing the notified polymer are used in office and consumer printing.

6. HUMAN HEALTH IMPLICATIONS

6.1. Exposure Assessment

OCCUPATIONAL EXPOSURE

Dermal and inhalation exposure to the notified polymer may occur when refilling/replacing spent cartridges. However, the concentration of the notified polymer in the ink is low, and the design of the cartridges is such that exposure to the notified polymer should be low. Once the ink dries, the chemical would be trapped in the printed paper, and therefore dermal exposure to the notified chemical from contact with the dried ink is not expected.

PUBLIC EXPOSURE

The scenarios by which the public may be exposed to the notified chemical would involve home use of printers, and are similar to those for office workers. However, it is expected that the public will be using the printer less often than workers.

6.2. Toxicological Hazard Characterisation

The notified polymer meets the PLC criteria and can therefore be considered to be of low hazard.

6.3. Human Health Risk Assessment

OCCUPATIONAL HEALTH AND SAFETY

The OHS risk presented by the notified polymer is expected to be low, based on the minimal exposure to workers and the low intrinsic hazard of the polymer.

PUBLIC HEALTH

The risk to public health presented by the notified polymer is expected to be low due to its intrinsic low toxicity, low concentration in the ink and low potential for exposure.

7. ENVIRONMENTAL IMPLICATIONS

7.1. Exposure Assessment

ENVIRONMENTAL RELEASE

Environmental release of the notified polymer is summarised in the following table.

<i>Source of release</i>	<i>% Volume</i>	<i>Released to / Fate</i>
Residual notified polymer in cartridges	≤5%	Landfill
Notified polymer on printed paper	≤43%	Paper Recycling Facilities
Notified polymer on printed paper	≥52%	Landfill

ENVIRONMENTAL FATE

Notified polymer that is disposed of to landfill is expected to associate with soil and organic material and should be immobile within the landfill environment. Over time, the notified polymer is expected to degrade by biotic and abiotic means to form simple organic compounds.

Notified polymer on printed paper sent for recycling is expected to be destroyed by the bleaching oxidation step or be removed as a suspension in the waste water where it is coagulated, dried and burnt in the mill boiler.

7.2. Environmental Hazard Characterisation

No ecotoxicological data were submitted. Anionic polymers are known to be moderately toxic to algae. The mode of toxic action is overchelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone. This could apply to the notified polymer. However, the toxicity to algae is likely to be further reduced due to the presence of calcium ions, which will bind to the functional groups.

7.3. Environmental Risk Assessment

The notified polymer is imported into Australia in non-refillable print cartridges. Following its use, it is assumed that up to 43% will be destroyed during recycling of printed paper. The remainder is expected to be disposed of to landfill, either as residual within print cartridges or associated with printed paper. Release to the aquatic environment is not anticipated, and therefore, the overall environmental risk is expected to be acceptable.

8. CONCLUSIONS**8.1. Level of Concern for Occupational Health and Safety**

There is Low Concern to occupational health and safety under the conditions of the occupational settings described.

8.2. Level of Concern for Public Health

There is No Significant Concern to public health when used in the proposed manner.

8.3. Level of Concern for the Environment

The polymer is not considered to pose a risk to the environment based on its reported use pattern.

9. MATERIAL SAFETY DATA SHEET**9.1. Material Safety Data Sheet**

The notifier has provided MSDS as part of the notification statement. The accuracy of the information on the MSDS remains the responsibility of the applicant.

10. RECOMMENDATIONS**CONTROL MEASURES****Occupational Health and Safety**

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself, however, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- Service personnel should wear cotton or disposable gloves and ensure adequate ventilation is present when removing spent printer cartridges containing the notified polymer and during routine maintenance and repairs.
- A copy of the MSDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the NOHSC *Approved Criteria for Classifying Hazardous Substances*, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

Disposal

- The notified polymer should be disposed of to landfill.

Emergency procedures

- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

10.1. Secondary Notification

The Director of Chemicals Notification and Assessment must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under subsection 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.
- or
- (2) Under subsection 64(2) of the Act:
 - if any of the circumstances listed in the subsection arise.

The Director will then decide whether secondary notification is required.