NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME (NICNAS)

POLYMER OF LOW CONCERN PUBLIC REPORT

Lewatit A 8071

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment.

For the purposes of subsection 78(1) of the Act, this Public Report may be inspected at our NICNAS office by appointment only at Level 7, 260 Elizabeth Street, Surry Hills NSW 2010.

This Public Report is also available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.

Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.

TEL: + 61 2 8577 8800 FAX: + 61 2 8577 8888 Website: www.nicnas.gov.au

Director NICNAS

September 2014

Table of Contents

SUMMARY		. 2
CONCLUSIONS A	ND REGULATORY OBLIGATIONS	. 2
	ETAILS	
	AND NOTIFICATION DETAILS	
	F POLYMER	
	IA JUSTIFICATION	
	AND CHEMICAL PROPERTIES	
	TION AND USE INFORMATION	
	ALTH RISK ASSESSMENT	
	ENTAL RISK ASSESSMENT	

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1226	Lanxess Pty Ltd	Lewatit A 8071	No	≤ 20 tonnes per annum	Ion exchange resin for industrial water purification

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

No specific engineering controls, work practices or personal protective equipment are required
for the safe use of the notified polymer itself. However, these should be selected on the basis of
all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the (M)SDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System for the Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

• The notified polymer should be disposed of to landfill.

Emergency Procedures

• Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these

circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from an ion exchange resin in industrial water purification, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

(Material) Safety Data Sheet

The (M)SDS of the notified polymer was provided by the applicant. The accuracy of the information on the (M)SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

LANXESS Pty Ltd. (ABN: 58 071 919 116)

Unit 1/31 Hill Road

HOMEBUSH BAY NSW 2127

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, use details and import volume.

2. IDENTITY OF POLYMER

Marketing Name(s)

Lewatit A 8071

Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 Da

3. PLC CRITERIA JUSTIFICATION

Criterion	Criterion met
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Not applicable
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa Solid/gel like white/translucent resin beads

Melting Point/Glass Transition Temp > 200 °C

Density $660-730 \text{ kg/m}^3 \text{ at } 23 \text{ }^{\circ}\text{C}$

Water Solubility The notified polymer is not expected to be soluble in water

as it is a highly crosslinked ion exchange resin with a very

high molecular weight.

Dissociation Constant The notified polymer is a salt. Therefore, it is expected to be

ionised in the environmental pH range (4 - 9). However, this is not considered to be a concern as the notified polymer is

insoluble in water.

Particle Size 0.4-1.6mm diameter beads

Reactivity Stable under normal environmental conditions

Degradation Products None under normal conditions of use. Hydrolysis is not

expected to occur.

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

Year	1	2	3	4	5
Tonnes	5-10	5-20	5-20	5-20	5-20

Use

The notified polymer will be introduced into Australia at 100% concentration and will be filled into columns as an ion exchange resin where it will serve as the stationary phase for purification of industrial recycled water.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. The notified polymer will be used as an ion exchange resin, in the form of solid beads, for industrial water purification.

Insoluble polymers are not expected to be toxic unless the material is in the form of finely divided particles. Most often, the toxicity of these polymer particles does not depend on a specific reactive structural feature, but occurs from occlusion of respiratory organs such as gills. These polymers exert low toxicity, toxicity typically occurs only at high concentration; acute toxicity values are generally >100 mg/L and chronic toxicity values are generally >10 mg/L.

The notified polymer will be imported as final product, ion exchange resin, and will be repackaged locally into columns. Wastes from spills (up to 1% of the total import volume) are expected to be collected and placed in sealed containers for disposal to landfill. Empty import containers are also expected to be disposed of to landfill. At the end of the useful life of the resin, the columns will be emptied and the spent resins are expected to be drummed and disposed of to landfill. The columns will be cleaned and reused.

In conclusion, most of the notified polymer is expected to end up in landfill in the forms of residues, collected spills or spent resin. The notified polymer is not expected to be readily biodegradable. It is also not expected to cross biological membranes as the notified polymer has high molecular weight. Therefore, it is not expected to be bioaccumulative. In landfill, the notified polymer is expected to eventually degrade via abiotic and biotic pathways to form water and oxides of carbon and nitrogen. Therefore, based on its assumed low hazard and assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.