In [ ]:

```
Program-2:
For a given set of training data examples stored in a .CSV file, implement
and demonstrate the Candidate-Elimination algorithm to output a description
of the set of all hypotheses consistent with the training examples.
```

In [21]:

```
import numpy as np
import pandas as pd
```

In [22]:

```
# Loading Data from a CSV File
data = pd.DataFrame(data=pd.read_csv('trainingdata.csv'))
print(data)
```

```
     sky airTemp humidity    wind water forecast enjoySport
0  Sunny    Warm   Normal  Strong  Warm     Same        Yes
1  Sunny    Warm     High  Strong  Warm     Same        Yes
2  Rainy    Cold     High  Strong  Warm   Change         No
3  Sunny    Warm     High  Strong  Cool   Change        Yes
```

In [23]:

```
# Separating concept features from Target
concepts = np.array(data.iloc[:,0:-1])
print(concepts)
```

```
[['Sunny' 'Warm' 'Normal' 'Strong' 'Warm' 'Same']
 ['Sunny' 'Warm' 'High' 'Strong' 'Warm' 'Same']
 ['Rainy' 'Cold' 'High' 'Strong' 'Warm' 'Change']
 ['Sunny' 'Warm' 'High' 'Strong' 'Cool' 'Change']]
```

In [24]:

```
# Isolating target into a separate DataFrame
# copying last column to target array
target = np.array(data.iloc[:,-1])
print(target)
```

```
['Yes' 'Yes' 'No' 'Yes']
```

In [31]:

```
def learn(concepts,target):
    specific_h=concepts[0].copy()
    general_h=[["?" for i in range(len(specific_h))]
                    for i in range(len(specific_h))]
    for i, h in enumerate(concepts):


        # Checking if the hypothesis has a positive target
        if target[i] == "Yes":
            for x in range(len(specific_h)):

                # Change values in S & G only if values change
                if h[x] != specific_h[x]:
                    specific_h[x] = '?'
                    general_h[x][x] = '?'

        # Checking if the hypothesis has a negative target
        if target[i] == "No":
            for x in range(len(specific_h)):
                # For negative hyposthesis change values only  in G
                if h[x] != specific_h[x]:
                    general_h[x][x] = specific_h[x]
                else:
                    general_h[x][x] = '?'

        print("\nSteps of Candidate Elimination Algorithm",i+1)
        print(specific_h)
        print(general_h)

    # find indices where we have empty rows, meaning those that are unchanged
    indices = [i for i, val in enumerate(general_h)
               if val == ['?', '?', '?', '?', '?', '?']]
    for i in indices:
        # remove those rows from general_h
        general_h.remove(['?', '?', '?', '?', '?', '?'])
    # Return final values
    return specific_h, general_h
```

In [32]:

```
s_final, g_final = learn(concepts, target)
print("\nFinal specific hypothesis:", s_final, sep="\n")
print("\nFinal general hypothesis:", g_final, sep="\n")
```

```

Steps of Candidate Elimination Algorithm 1
['Sunny' 'Warm' 'Normal' 'Strong' 'Warm' 'Same']
[['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?',
'?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?',
'?', '?'], ['?', '?', '?', '?', '?', '?']]

Steps of Candidate Elimination Algorithm 2
['Sunny' 'Warm' '?' 'Strong' 'Warm' 'Same']
[['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?',
'?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?',
'?', '?'], ['?', '?', '?', '?', '?', '?']]

Steps of Candidate Elimination Algorithm 3
['Sunny' 'Warm' '?' 'Strong' 'Warm' 'Same']
[['Sunny', '?', '?', '?', '?', '?'], ['?', 'Warm', '?', '?', '?', '?'],
['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?',
'?', '?', '?', '?'], ['?', '?', '?', '?', '?', 'Same']]

Steps of Candidate Elimination Algorithm 4
['Sunny' 'Warm' '?' 'Strong' '?' '?']
[['Sunny', '?', '?', '?', '?', '?'], ['?', 'Warm', '?', '?', '?', '?'],
['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?',
'?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Final specific hypothesis:
['Sunny' 'Warm' '?' 'Strong' '?' '?']

Final general hypothesis:
[['Sunny', '?', '?', '?', '?', '?'], ['?', 'Warm', '?', '?', '?', '?']]
```

In [ ]:

```

```