SmartOrders API Documentation

This document outlines the API endpoints, request/response formats, and authentication mechanisms for the SmartOrders application **as implemented in the current codebase**.

1. General Information

- **Base URL**: `https://api.smartorders.com/v1` (placeholder)
- **Default Format**: All requests and responses are in `application/json`.
- **Authentication**: Most endpoints require a Bearer Token (stored under `auth_token` in `SharedPreferences`).
- **Date Format**: ISO 8601 (e.g., `2025-12-11T13:49:14Z`).
- **Current implementation note**: The app is currently wired to a **mock API service** (`MockApiService`) that simulates these endpoints locally. A `Dio` client (`ApiClient`) exists but is not yet wired to a production backend.

---

2. Authentication & Session

Base Response Structure

Every response follows this structure:

Field	Type	Description
`success`	`boolean`	Indicates if the request was successful.
`data`	`object | array`	The response payload (if successful).
`message`	`string?`	Success message or useful information.
`error`	`string?`	Description of the error (if `success` is false).

List Response Structure (Paginated)

List endpoints return the following structure inside `data`:

Field	Type	Description
`items`	`array`	Page items.
`total`	`int`	Total number of matching records.
`page`	`int`	Current page (1-based).
`limit`	`int`	Page size.

Login

Authenticates a user and returns a token.

- **URL**: `/login`
- **Method**: `POST`
- **Auth Required**: No

Request Body:

```
{
  "email": "user@example.com",
  "password": "your_password"
}
```

Success Response:

```
{
  "success": true,
  "data": {
    "user": {
      "id": "U10001",
      "name": "Abdullah Al Nahian",
      "email": "user@example.com",
      "status": "Active"
    },
    "userId": "U10001",
    "token": "mock_token_1710000000000",
    "accounts": ["10002345@nsa", "10002345@psa", "10002345@usa",
"10002345@cpl"]
  },
  "message": "Login successful."
}
```

Failure Response:

```
{
  "success": false,
  "error": "Invalid email or password"
}
```

Mock behavior: Login succeeds when `password == "password"`.

Register

Requests a new account registration.

- **URL**: `/register`

- **Method**: `POST`
- **Auth Required**: No

Request Body:

```
{
  "branch": "Main Branch",
  "account": "ACC123",
  "name": "Full Name",
  "email": "user@example.com",
  "phone": "0123456789"
}
```

Success Response:

```
{
  "success": true,
  "data": { "message": "Registration request submitted successfully" },
  "message": "Please wait for administrator approval"
}
```

Forgot Password

Initiates a password reset process.

- **URL**: `/forgot-password`
- **Method**: `POST`
- **Auth Required**: No

Request Body:

```
{
  "email": "user@example.com"
}
```

Success Response:

```
{
  "success": true,
  "message": "Password reset request submitted. An administrator will contact
you."
}
```

Check Session

Validates the current authentication token.

- **URL**: `/check-session`
- **Method**: `GET`
- **Auth Required**: Yes

Success Response:

```
{
  "success": true,
  "data": {
    "user": {
      "id": "U10001",
      "name": "Abdullah Al Nahian",
      "email": "user@email.com",
      "status": "Active",
      "accounts": ["10002345@nsa", "10002345@psa", "10002345@usa",
"10002345@cpl"]
    }
  }
}
```

Logout

Invalidates the current session token.

- **URL**: `/logout`
- **Method**: `POST`
- **Auth Required**: Yes

Change Password

Updates the user's password.

- **URL**: `/change-password`
- **Method**: `POST`
- **Auth Required**: Yes

Request Body:

```
{
  "oldPassword": "current_password",
  "newPassword": "new_password"
}
```

Success Response:

```
{
```

```
  "success": true,
  "message": "Password changed successfully"
}
```

Failure Response:

```
{
  "success": false,
  "error": "Current password is incorrect"
}
```

Mock behavior: Change password succeeds when `oldPassword == "password"`.

---

3. Products

List Products

Retrieves a paginated list of products.

- **URL**: `/products`
- **Method**: `GET`
- **Auth Required**: Yes
- **Query Parameters**:
  - `page` (int, default: 1)
  - `limit` (int, default: 20)
  - `search` (string) - Search by name, SKU, or generic name.
  - `promotionsOnly` (boolean)
  - `inStockOnly` (boolean)
  - `sortBy` (string) *(currently ignored by mock; mock always sorts by `rate` descending)*

Product Model:

Field	Type	Description
`id`	`string`	Unique identifier.
`name`	`string`	Product name.
`sku`	`string`	Stock Keeping Unit.
`genericId`	`string?`	Generic group ID (used to expand search results).
`genericName`	`string`	Generic version of the medicine.
`dose`	`string`	Dosage information (e.g., 500mg).
`price`	`double`	Current unit price.
`supplier`	`string`	Manufacturer/Supplier.

`stockQuantity`	`int`	Current stock count.
`stockNumber`	`int`	Duplicate of stock count (present in mock payload).
`inStock`	`boolean`	Availability flag.
`hasPromo`	`boolean`	Promotion availability flag.
`promoStatus`	`boolean`	Duplicate of promo flag (present in mock payload).
`rate`	`int`	Ranking score used for default sorting (descending).

Get Product Details

Retrieves full details for a specific product.

- **URL**: `/products/{productId}`
- **Method**: `GET`
- **Auth Required**: Yes

Get Product Purchase History

Retrieves the last 6 months of purchase history for a product.

- **URL**: `/products/{productId}/history`
- **Method**: `GET`
- **Auth Required**: Yes

Success Response Data Example:

```
[
  { "month": "Oct", "year": "25", "quantity": 3 },
  { "month": "Nov", "year": "25", "quantity": 1 }
]
```

Get Monthly Offers

Retrieves a list of special monthly promotions and deals.

- **URL**: `/products/monthly-offers`
- **Method**: `GET`
- **Auth Required**: Yes

Success Response Data Example:

```
[
```

```
  {
    "productId": "OFFER001",
    "description": "Amoxicillin 500mg Caps - Box of 20",
    "subDescription": "Wholesale Carton (x20 units)",
    "normalPrice": 14500.00,
    "offerPrice": 12450.00,
    "currency": "ZAR",
    "isClaimed": false
  }
]
```

---

4. Orders

Create Order

Places a new order.

- **URL**: `/orders`
- **Method**: `POST`
- **Auth Required**: Yes

Request Body:

```
{
  "customerCategory": "Pharmacy",
  "customerRoute": "North-West",
  "items": [
    {
      "productId": "p01",
      "quantity": 10,
      "price": 2.00,
      "totalExcl": 20.00,
      "vat": 3.00,
      "totalIncl": 23.00,
      "saving": 0.00
    }
  ],
  "accountId": "10002345@nsa"
}
```

Success Response Data:

```
{
  "orderId": "ORD-123456789",
  "orderNumber": "102238_998877",
  "status": "Pending"
}
```

List Orders

Retrieves user's order history.

- **URL**: `/orders`
- **Method**: `GET`
- **Auth Required**: Yes
- **Query Parameters**: `page`, `limit`, `accountId`.

Order Summary Model:

Field	Type	Description
`id`	`string`	Unique ID.
`orderId`	`string`	Duplicate of ID (present in some mock rows).
`company`	`string`	Company identifier.
`customer`	`string?`	Customer/company label (present in mock rows for account-specific data).
`account`	`string`	Account number.
`orderNumber`	`string`	Display order number.
`orderDate`	`string`	Formatted date (DD/MM/YYYY).
`invoice`	`string`	Invoice reference (if available).
`invoiceDate`	`string?`	Invoice date (or -).
`orderTotalIncl`	`double`	Total inclusive amount.
`status`	`string`	Status values in mock include: Pending, Processing, Completed, Cancelled.

Get Order Details

Retrieves details for a specific order (used by the Order Details screen and PDF export).

- **URL**: `/orders/{orderId}`
- **Method**: `GET`
- **Auth Required**: Yes

Success Response Data (Shape)


```
{
  "id": "ORD-NSA-001",
  "orderNumber": "102238_121125134914",
  "company": "CITY-PTA",
  "account": "102238",
  "accountName": "MARSHALLS TRAD HEALTHCARE",
  "orderDate": "11/12/2025 1:49:14 PM",
  "invoiceDate": "11/12/2025",
  "invoice": "INV-9921",
  "status": "Cancelled",
```

```
  "items": [
    {
      "description": "SURGICAL FACE MASK 3-PLY",
      "ordQty": 2,
      "ordFree": 0,
      "ordPrice": 3.85,
      "invQty": 0,
      "invFree": 0,
      "invPrice": 0.0,
      "saving": 0.0,
      "invoice": "-",
      "mainAcc": "Yes",
      "result": "Cancelled"
    }
  ],
  "totalInclusive": 1240.5,
  "totalVat": 59.6,
  "totalSaving": 104.2
}
```

---

5. Reports

Sales Report

Generates a product sales report.

- **URL**: `/reports/products`
- **Method**: `GET`
- **Auth Required**: Yes
- **Query Parameters**:
  - `fromDate` (ISO Date)
  - `toDate` (ISO Date)
  - `productFilter` (string?)
  - `accountId` (string?)

Success Response Data (Shape)

```
{
  "account": "10002345@nsa",
  "totalOrders": 24,
  "completedOrders": 18,
  "pendingOrders": 6,
  "monthlyRevenue": 18500,
  "reportData": [
    { "product": "P001", "name": "Panadol 500mg Tablets" }
  ]
}
```

If `accountId` is not one of the known mock accounts, the response is: `{ "reportData": [...], "generatedAt": "<ISO8601>" }`

Age Analysis

Retrieves the aging analysis for the account balance.

- **URL**: `/reports/age-analysis`
- **Method**: `GET`
- **Auth Required**: Yes
- **Query Parameters**: `accountId` (string?)

Success Response Data Example:


```
{
  "account": "10002345@nsa",
  "accountName": "Alpha Diagnostics",
  "current": 1250.0,
  "days30": 450.0,
  "days60": 780.0,
  "days90": 0.0,
  "days120": 0.0,
  "days150": 0.0,
  "days180": 0.0,
  "total": 2480.0
}
```

Age Analysis (All Accounts)

Retrieves age analysis rows for all accounts (used by age analysis table).

- **URL**: `/reports/age-analysis/all`
- **Method**: `GET`
- **Auth Required**: Yes

Success Response Data (Shape)


```
[
  {
    "account": "10002345@nsa",
    "accountName": "Alpha Diagnostics",
    "current": 1250.0,
    "days30": 450.0,
    "days60": 780.0,
    "days90": 0.0,
    "days120": 0.0,
    "days150": 0.0,
    "days180": 0.0,
    "total": 2480.0
  }
]
```

---

6. System

Check for Updates

Checks if a new version of the app is available.

- **URL**: `/check-for-updates`
- **Method**: `GET`
- **Auth Required**: No

Response:

```
{
  "success": true,
  "data": {
    "hasUpdate": false,
    "currentVersion": "1.0.0",
    "latestVersion": "1.0.0"
  }
}
```