BreakBite

Smart Food, Smart Time

Complete Project Documentation and Rebuild Guide (Version 2)

Team BreakByte
Gono Bishwabidyalay - CSE Software Development Contest 2026
Category 1: Semester 1st to 4th
Document date: 12 November 2026 (version 2; version 1 was dated 20 October 2026)
Live site: https://raito-del.github.io/BreakBite/
Repository: github.com/raito-del/BreakBite

Confidential team document. Contains no passwords or private keys.

What changed in version 2

This version brings the document in line with the current repository. The main changes are:

- **Splash page added.** `index.html` is now an animated splash page with the BreakBite cookie logo. The Bite button opens `home.html`.
- **Home page moved.** The Student and Staff home page (earlier `index.html`) is now `home.html`.
- **Logo files added.** `logo.css` and `logo.js` are new files in the project root.
- **Theme changed.** The Spice Kitchen colours are now live in `style.css`. The Mint theme is no longer in use.
- **File inventory corrected.** Section 6 now lists the files in the repository. Three preview files from version 1 are not in the repository copy and are marked for checking.
- **Open items recorded.** Section 13 lists the two logo linking tasks that are still open.

1. Team and roles

Team name: BreakByte. Project name: BreakBite. Each member owns a set of files so that work does not clash on GitHub.

Name	Student ID	Responsibility	Owned files
Nahar Mim (Team Lead)	26251037	Lead, documentation, home page	home.html, README.md, this document
Sadnan Ahmed	26251038	Student ordering pages	student.html
Wasika Jahan	26251026	UI design and styling	style.css, visual design
Mirza Muin Labbaik	26251021	Staff page and database setup	staff.html, firebase.js
Habiba Jannat Taiyaba	26251011	Break Planner and testing	planner.html
Logo and splash page	-	Animated logo and splash page	index.html, logo.css, logo.js (owner to be confirmed by the team)

Shared files (style.css, firebase.js) are changed carefully: one person edits, others pull first. The team uses GitHub Desktop: Fetch origin, Pull origin, work, Commit, Push.

2. Project overview and idea

University students usually have a short break between classes, often 15 to 45 minutes, and limited money. The canteen has long queues, so students waste part of the break waiting, and often cannot decide what to eat in time. BreakBite solves this with three ideas:

- **Pre-order:** choose food from a live menu, get a token, and collect it when it is ready.
- **Rush radar:** show how busy the canteen is, so students know when to come.
- **Break Planner:** enter break time and money, and get a suggested set of items that fits both.

The staff side runs the canteen from one page: live order board, menu and price control, food waste discounts, planner settings, and an end-of-day report.

Target user: a first-year university student who has 30 minutes and some money, and wants a fast, clear decision.

3. Thinking process and design decisions

3.1 Why plain HTML, CSS and JavaScript?

A build tool or framework adds setup steps that can break for teammates. Plain files open directly in Live Server or GitHub Pages, and every member can read them. Firebase is added through its CDN modules, so there is no npm step.

3.2 Why Firebase?

Orders must be shared between many devices in real time: a student's phone and the staff tablet. Firestore gives live updates (onSnapshot) on the free Spark plan. Firebase Authentication gives staff a real login without storing passwords in code.

3.3 Why one stylesheet?

All colours and shapes are CSS variables in one style.css file. Changing the colours in `:root` re-themes every page, so no HTML needs editing. Version 2 used this to switch the site to the Spice Kitchen theme.

3.4 Why a shared order counter?

Token numbers must be unique even when two students press the button at the same moment. A Firestore transaction reads counters/orders, adds one, and writes the new order in one safe step.

3.5 Why a daily report and reset?

A canteen runs one day at a time. End-of-day saves a summary first, then clears orders and restarts tokens at 1. The report is saved before anything is deleted, so no sales data is lost if the process fails.

3.6 Why a knapsack-style planner?

The planner solves a small version of the unbounded knapsack problem: items have time and price, and the budget has time and money limits. A dynamic programming table gives the best answer quickly for small menus, without a server.

3.7 Why a splash page first?

New in v2 The splash page gives the site a clear entry point with the BreakBite logo. One click on Bite leads to the home page, where students and staff choose their role. The logo is a visual

identity for the project, and the splash page keeps the home page separate from the entry animation.

3.8 Trade-offs we accepted (honest view)

- Firestore rules are open for the contest demo. This is not secure for real money or private data (see section 10).
- The planner maximises item count, so it can repeat one cheap item many times. A variety rule is planned.
- Token lookup lets anyone read an order by token number. The data is low sensitivity, but it is public.
- The site has no build step, so code is simple but not split into modules.

4. Features (complete list)

Area	Feature	Where	Status
Entry	Animated BreakBite logo and splash page (cookie, Bite button, hint)	index.html, logo.css	Done (v2)
Entry	Logo click animation (chomp and crumbs) then open ordering page	logo.js	Written, not linked yet
Student	Live menu with prices, discounts and availability	student.html	Done
Student	+ / - quantity steppers and sticky cart bar	student.html	Done
Student	Place pre-order with a transactional token	student.html	Done
Student	Multiple active orders kept per browser	student.html	Done
Student	Token status steps (Received, Preparing, Ready)	student.html	Done
Student	Token lookup by number	student.html	Done
Student	Rush radar (orders waiting)	student.html	Done
Student	Break Planner with time and money input	planner.html	Done
Staff	Email and password login (Firebase Auth)	staff.html	Done
Staff	Live order board with advance buttons	staff.html	Done
Staff	Completed list (latest 10)	staff.html	Done
Staff	Menu: add, edit, sold out, delete	staff.html	Done
Staff	Food Waste Saver discounts (5 to 90 percent)	staff.html	Done
Staff	Break Planner settings (min, max, step, default eat time)	staff.html	Done
Staff	End of day: report, delete orders, reset tokens	staff.html	Done
Staff	Past daily reports (last 7)	staff.html	Done
Home	Student and Staff role switch	home.html	Done
Design	Spice Kitchen theme, mobile layout, animations, theme variables	style.css	Done

Future	Green Token and student-side Food Waste Saver	-	Planned
Future	Planner variety rule, stricter security rules	-	Planned

5. Architecture and technology

Layer	Technology	Notes
Pages	HTML5, CSS3, vanilla JavaScript (ES modules)	No framework, no build step
Styling	style.css with :root variables, plus logo.css for the splash logo	Spice Kitchen theme live
Animation	logo.js (click animation), logo.css (keyframes)	Every logo class starts with bb-
Database	Cloud Firestore (asia-south1, Mumbai)	Live listeners with onSnapshot
Login	Firebase Authentication, Email/Password	Staff accounts created in console
SDK	Firebase Web SDK 10.12.2 from gstatic CDN	Version pinned on purpose
Hosting	GitHub Pages from branch main, root folder	https://raito-del.github.io/BreakBite/
Editor	VS Code with Live Server	Test pages on localhost
Version control	Git and GitHub Desktop	.gitattributes sets text=auto (LF in repo)

Flow: a student page reads menu and writes orders. The staff page reads orders and changes status. Both pages connect to Firestore through the same firebase.js, and Firestore pushes updates to every open page.

6. File inventory (every file)

All files sit in the project root folder, because pages link to each other with relative paths (for example `href="student.html"`). The table below lists the files in the repository copy checked for version 2 (11 files).

File	Purpose	Key contents	Status
index.html	Splash page	Animated cookie logo, the word Break, red Bite button, hint "Click Bite to order food". Bite opens home.html through a small inline script.	Changed in v2
home.html	Home page	Header tabs, Student and Staff role links, hero text, two cards (Order food, Break Planner)	Moved in v2
logo.css	Logo styles	Layout, Bite button, hint pill, animations. Class names start with bb-	New in v2
logo.js	Logo click script	Chomp animation, nine flying crumbs, opens student.html after 0.8 seconds	New in v2, not linked yet
student.html	Ordering page	Rush radar, menu list, cart bar, place order transaction, token tracking, your orders, token lookup	Unchanged
planner.html	Break Planner	Loads settings/planner and menu once, best-combination search, result list	Unchanged
staff.html	Staff dashboard	Login screen, Orders board, Completed list, End of day, reports, Menu, Food Waste Saver, Settings	Unchanged
style.css	Shared stylesheet	Spice Kitchen theme variables, buttons, cards, tickets, steps, tables, login, responsive rules, animations, doodle background	Theme switched in v2
firebase.js	Firebase connection	Config object, initializeApp, exports db (Firestore) and auth (Authentication)	Unchanged
README.md	Project information	Name, description, features, team table, folder structure, workflow, dates	Folder list needs update (see section 13)
.gitattributes	Line endings	Single rule: * text=auto	Unchanged

Not in the repository copy: yellow-preview.html, spice-kitchen-preview.html, spice-kitchen-animated-preview.html and BreakBite_Break_Planner_Presentation.pdf were listed in version 1 as preview and showcase files. They are not in the uploaded repository copy. The team should confirm whether they are kept elsewhere or removed from this list.

6.1 What lives inside each page (quick map)

- **index.html:** no database. Animated splash only. Bite opens home.html.
- **home.html:** no database. Links and role icons. Staff link opens staff.html, which asks for Firebase login.
- **logo.js and logo.css:** no database. Animation only.
- **student.html:** listeners on menu, orders with status Received or Preparing (rush radar), and each saved order id. Writes new orders and the counter.
- **planner.html:** one read of settings/planner and one read of menu; no live listener. Pure client-side calculation.
- **staff.html:** login gate, listeners on orders (latest 50) and menu, status changes, menu edits, discounts, settings, daily reports and counter reset.
- **style.css:** no JavaScript. Shared by all pages.
- **firebase.js:** no UI. Imported by every page that uses the database or login.

7. Data model (Firestore)

Collection / document	Fields	Written by	Read by
menu/{id}	name, price (Tk), minutes (eat time), available (bool), discount (0-90), order (sort key)	Staff	Student, Planner, Staff
orders/{id}	token, items [{name, qty, price}], count, total, status, createdAt	Student (create), Staff (status)	Student (own), Staff, Rush radar
counters/orders	last (number)	Student (transaction), Staff (reset)	Student (transaction)
settings/planner	minBreak, maxBreak, step, defaultEat	Staff	Planner, Staff
daily_reports/{id}	date, totalOrders, totalSales, items {name: qty}, activeAtClose, createdAt	Staff (End of day)	Staff (last 7)

Status values used everywhere: Received, Preparing, Ready, Done. The order board shows the first three. Done orders leave the board and appear in Completed.

8. How the main features work

8.1 Placing an order (student.html)

- Student changes quantities; each + or - updates a local object. The cart bar shows the count and total.
- On Place pre-order, a Firestore transaction reads counters/orders, sets last = last + 1, and writes the order with status Received.
- The new order id is saved in localStorage (key breakbite_orders), so the student can see it after a refresh.
- The student page listens to that order and shows steps and a message. When status becomes Done, the order leaves the list.

8.2 Staff order flow (staff.html)

- Orders listener loads the latest 50 orders by createdAt. Active orders fill three columns.
- Each button moves an order one step: Received to Preparing, Preparing to Ready, Ready to Done.
- Queue and waiting time: queue = count of Received and Preparing; estimated wait = 3 + queue x 2 minutes.

8.3 Rush radar

Count below 5 shows Low rush, 5 to 9 shows Medium rush, 10 or more shows High rush.

8.4 Break Planner (planner.html)

The planner reads settings and menu once. It checks that the break time is between minBreak and maxBreak, then runs a dynamic programming table over time (minutes) and spend (Tk). It picks the state with the most items, then the largest spend, and walks back to list the items. Discounted prices are used. Items with no minutes use defaultEat.

8.5 End of day (staff.html)

- Staff press End of day. Two confirmation questions appear. The second warns that it cannot be undone.
- The app builds the summary (count, total sales, quantity per item). Nothing is deleted yet.
- It writes one daily_reports document. If this write fails, the process stops and no order is deleted.
- Orders are deleted in batches of up to 400. Then counters/orders is set to last = 0, so the next token is 1.

8.6 Login and logout

Staff enter email and password. The dashboard shows only when onAuthStateChanged reports a signed-in user. Logout calls signOut. No password is stored in code or in the browser.

8.7 Discounts (Food Waste Saver)

Staff choose a food and a percent from 5 to 90. The menu document gets discount = percent. Student, planner and staff pages all show the discounted price. Stop discount sets discount back to 0.

8.8 Splash and logo flow New in v2

- The splash page shows the cookie, the word Break and a red Bite button. A yellow hint pill says "Click Bite to order food".
- The cookie floats, the three pixel squares twinkle, and the Bite button bobs gently. Hover lifts the button; press pushes it down.
- Clicking Bite in index.html opens home.html.
- logo.js holds the longer version: Bite squashes, the cookie chomps, nine crumbs fly out, and after 0.8 seconds student.html opens. This version is not linked yet (see section 13).
- All logo animation is switched off for users who set reduced motion.

9. Design system and theme

All colours are variables in `:root` of style.css. A theme change means editing only these values.

Variable	Spice Kitchen (live in v2)	Mint theme (v1, no longer used)	Used for
--bg	#fff3dc	#d9f6e4	Page background
--ink	#3b2314	#0d3326	Text, borders, shadows
--accent	#d9482b	#1f9d6b	Hover, highlights, numbers
--card	#ffffff	#ffffff	Cards and header
--danger	#b02a1a	#c0392b	Delete, errors
--turmeric	#f2b33d	not used	Tabs, badges, cart button
--t-yellow / --t-blue / --t-mint	#ffe08a / #ffd0a8 / #cfeab0	#ffe7a0 / #d4e6f7 / #c5ecd5	Received / Preparing / Ready

9.1 Animations

- Button hover: small wiggle and lift. Press: pushes down.
- Menu row: lifts on hover with a soft shadow.
- Cart bar: slides up on page open.
- Current order step: soft red glow. Ready token: gentle pulse (Chrome and Edge, through :has()).
- Splash logo: floating cookie, twinkling squares, bobbing Bite button, chomp on click (v2).
- All animation is switched off for users who set reduced motion.

9.2 Food doodle background

A small inline SVG pattern (burger, pizza, tea cup, samosa, fries, drumstick) sits behind the page at low opacity. It needs no image file.

10. Security status and known limitations

Topic	Current state	Risk	Planned fix
Firestore rules	Open for read and write until 1 Dec 2026	Anyone can edit menu or orders	Rules that require auth for menu, settings, reports, counters
Staff login	Firebase Email/Password. Accounts added by admin	Low	Keep Email/Password only; disable sign-up
Staff gate on home page	Staff icon opens the login page	Low	Keep; login page is the real gate
Token lookup	Anyone can read an order by token	Low (only status and items)	Accept, or restrict with a per-order code
Planner variety	Can repeat one item many times	Quality, not security	Cap repeats per item
Token numbers	Keep counting until End of day	Low	Daily reset is manual, by design
Web config in code	apiKey is public by design	Low	Secure with rules, not by hiding the key

Recommended rules for the final showcase: students may read menu and settings, create orders and read their own order; only signed-in staff may update orders, change menu and settings, write daily reports, and reset counters. Appendix A includes the target rules.

11. Rebuild guide (step by step)

Follow these steps to recreate BreakBite from nothing. Replace the placeholder values with your own Firebase settings. Never write a real password into code or into this document.

1. Create a GitHub repository, for example BreakBite. Add a README.md.
2. Create the files listed in section 6 in one folder. Copy the code from Appendix A and from the team repository. Include logo.css and logo.js.
3. Open console.firebase.google.com. Create a project. Turn Google Analytics off.
4. Add a Web app (the </> icon). Copy the six values from firebaseConfig into firebase.js.
5. Build > Firestore Database > Create database. Choose Standard, location asia-south1 (Mumbai), start in test mode.

6. Firestore > Rules: paste the rules from Appendix A (temporary open rules for demo) and Publish.
7. Build > Authentication > Get started > Sign-in method > Email/Password > Enable > Save.
8. Authentication > Users > Add user: add each staff email and a password of at least 6 characters.
9. Authentication > Settings > Authorized domains: add raito-del.github.io (or your GitHub Pages domain).
10. In Firestore, create collection counters, document orders with field last = 0 (number).
11. Open the repo on GitHub > Settings > Pages > Source: Deploy from a branch > main > / (root) > Save.
12. Wait 1 to 2 minutes. Open https://<your-user>.github.io/BreakBite/ and test every page, starting with the splash page.
13. Open staff.html, log in, add menu items with name, price and eat time, then save planner settings.
14. Place a test order from student.html. Advance it on staff.html. Check the status on student.html.
15. Press End of day once to test the report, then check Past daily reports.

12. Work log and timeline

Date (2026)	Milestone
18 October	Repository created, first pages, Firebase guide written for the team
19 October	Firebase project and Firestore set up; firebase.js; first student and staff pages connected
19 to 20 October	Break Planner built; staff login with Firebase Auth; style.css unified; mobile fixes
20 October	GitHub Pages live; home page with Student and Staff icons; token lookup; End of day and reports; theme previews and animations; presentation PDF. Document version 1.
22 October	Animated logo, splash page (index.html), logo.css and logo.js added. Update 1 written.
Date not recorded in repo	Home page separated into home.html. Spice Kitchen theme applied to style.css.
12 November	Document version 2 written, bringing the documentation in line with the repository. Final project submission (deadline).
16 November	Showcase and poster

13. Future work and open items

13.1 Open items from version 2

- **Link the logo click animation.** index.html does not load logo.js yet. To use the chomp and crumbs, add `<script src="logo.js"></script>` before the closing body tag, remove the inline script, and set TARGET in logo.js to the page that should open.
- **Fix the Home tab links.** The Home tab in student.html and planner.html still points to index.html, which is now the splash page. It should point to home.html.
- **Update README.md.** The folder structure in README.md still lists index.html as the home page. It should list index.html (splash), home.html, logo.css and logo.js, and planner.html is already listed.
- **Confirm preview files.** Check where the preview files and the showcase PDF from version 1 are kept.

13.2 Planned work

- Tighten Firestore rules as in Appendix A, and test with a second staff account.
- Add a variety rule to the Break Planner (for example, one item at most twice).
- Green Token: a student-side feature for reusable containers.
- Student-side Food Waste Saver: show discount items on the order page with a clear badge.
- Optional: daily automatic reset with a scheduled Cloud Function (needs the Blaze plan).

Appendix A. Key source code

The full, current source of every page is in the GitHub repository. The excerpts below carry the important logic. Placeholder values replace the real Firebase keys.

A.1 Placing an order with a safe token (student.html)

```
const counterRef = doc(db, "counters", "orders");
const orderRef = doc(collection(db, "orders"));
await runTransaction(db, async function (tx) {
  const cs = await tx.get(counterRef);
  const next = (cs.exists() ? cs.data().last : 0) + 1; // next token number
  tx.set(counterRef, { last: next });
  tx.set(orderRef, {
    token: next, items: items, count: count, total: total,
    status: "Received", createdAt: serverTimestamp()
  });
});
addId(orderRef.id); // remember this order in this browser
```

A.2 End of day: report first, delete second (staff.html)

```
await addDoc(collection(db, "daily_reports"), { // 1. save report first
  date: todayKey(), totalOrders: all.size, totalSales: totalSales,
  items: itemCount, activeAtClose: activeCount, createdAt: serverTimestamp()
});
const docs = all.docs; // 2. delete in batches of 400
for (let i = 0; i < docs.length; i += 400) {
  const batch = writeBatch(db);
  docs.slice(i, i + 400).forEach(function (d) { batch.delete(d.ref); });
  await batch.commit();
}
await setDoc(doc(db, "counters", "orders"), { last: 0 }); // 3. restart tokens
```

A.3 Planner: best combination (planner.html)

Full function is in the repository file planner.html. The core is a dynamic programming table over time and spend. For each state it keeps the largest item count and the food added last, then walks back to list the items.

A.4 Splash page script (index.html) and logo script (logo.js)

```
// index.html (current): Bite opens the home page
document.getElementById('bbBite').addEventListener('click', function () {
  window.location.href = 'home.html';
});

// logo.js (written, not linked yet): chomp, crumbs, then open the order page
var TARGET = "student.html";
bite.addEventListener("click", function () {
  if (busy) return;
  busy = true;
  cookie.classList.add("bb-chomp");
  crumbs(r.left + r.width / 2, r.top + r.height / 2);
  setTimeout(function () { window.location.href = TARGET; }, 800);
});
```

A.5 Current rules (open, demo only)

```
rules_version = '2';
service cloud.firestore {
  match /databases/{database}/documents {
    match /{document=**} {
      allow read, write: if request.time < timestamp.date(2026, 12, 1);
    }
  }
}
```

A.6 Target rules for the showcase (recommended)

```
rules_version = '2';
service cloud.firestore {
  match /databases/{database}/documents {
    function isStaff() { return request.auth != null; }
    match /menu/{id} { allow read: if true; allow write: if isStaff(); }
    match /settings/{id} { allow read: if true; allow write: if isStaff(); }
    match /counters/{id} { allow read: if true; allow write: if true; }
    match /orders/{id} {
      allow read: if true;
      allow create: if true;
      allow update, delete: if isStaff();
    }
    match /daily_reports/{id} { allow read: if isStaff(); allow create: if
isStaff(); }
  }
}
```

Note: counters must allow create and update from students for token numbers to work. Test every page after changing rules.

Appendix B. Complete source of every file

The complete text of each file is in the repository. Version 2 changes these files:

Order	File	Version 2 status
B.1	index.html	Splash page (version 1 Appendix B.9). Bite opens home.html.
B.2	home.html	Home page (the earlier index.html content, version 1 Appendix B.1). Only the file name changed.
B.3	logo.css	Logo styles (version 1 Appendix B.10)
B.4	logo.js	Logo script (version 1 Appendix B.11). Not linked yet.
B.5	style.css	Theme switched to Spice Kitchen. Version 1 Appendix B.6 shows the same theme.
B.6	student.html, planner.html, staff.html, firebase.js, README.md, .gitattributes	No code change in v2. Version 1 Appendix B.2 to B.8 apply. Update the Home tab link and README as noted in section 13.1.

Update 1. Animated logo and splash page (22 October 2026)

This update added the BreakBite logo and a new splash page. The logo is a cookie with a bite taken out, three small pixel squares that stand for bytes, and the wordmark with Bite as a red button. It uses the Spice Kitchen colours. Firebase, the data model and the other pages were not changed by this update.

- **Cookie:** the break. The bite taken out of it is the Bite in the name.
- **Pixel squares:** red, leaf green and turmeric, standing for bytes. The fourth square of a 2 × 2 grid is missing, as if bitten off.
- **Colours:** cookie #f2b33d, outline and shadow #3b2314, Bite button #d9482b with text #fff5e6, pixel square #cfeab0.

- **Style:** thick brown outline and a hard offset shadow, matching the cards and buttons of the site.

Appendix C. New code files (version 2)

The four files added or changed for the splash page and logo are listed below in full, so the project can be rebuilt from this document.

C.1 index.html (splash page)

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>BreakBite</title>
  <link rel="stylesheet" href="style.css">
  <link rel="stylesheet" href="logo.css">
  <style>
    .splash-main {
      min-height: 100vh;
      display: flex;
      align-items: center;
      justify-content: center;
      padding: 24px;
    }
  </style>
</head>
<body>

<main class="splash-main">
  <div class="bb-logo-wrap">
    <div class="bb-logo">
      <svg class="bb-cookie" id="bbCookie" viewBox="0 0 220 220" aria-hidden="true">
        <defs>
          <mask id="bbBiteMask">
            <rect width="220" height="220" fill="#fff"/>
            <circle class="bb-bite-cut" cx="176" cy="60" r="34" fill="#000"/>
          </mask>
        </defs>
        <circle cx="116" cy="118" r="88" fill="#3b2314"/>
        <g mask="url(#bbBiteMask)">
          <circle cx="106" cy="108" r="88" fill="#f2b33d" stroke="#3b2314" stroke-
width="7"/>
          <circle cx="70" cy="90" r="8" fill="#3b2314"/>
          <circle cx="112" cy="70" r="8" fill="#3b2314"/>
          <circle cx="96" cy="140" r="8" fill="#3b2314"/>
          <circle cx="140" cy="122" r="8" fill="#3b2314"/>
          <circle cx="66" cy="150" r="8" fill="#3b2314"/>
        </g>
        <circle class="bb-bite-cut" cx="176" cy="60" r="34" fill="none"
stroke="#3b2314" stroke-width="7"/>
        <g class="bb-crumbs">
          <rect x="150" y="18" width="24" height="24" rx="6" fill="#d9482b"
stroke="#3b2314" stroke-width="5"/>
          <rect x="182" y="18" width="24" height="24" rx="6" fill="#cfeab0"
stroke="#3b2314" stroke-width="5"/>
          <rect x="182" y="50" width="24" height="24" rx="6" fill="#f2b33d"
stroke="#3b2314" stroke-width="5"/>
```

```
        </g>
      </svg>
      <div class="bb-word">
        <span class="bb-break">Break</span>
        <button class="bb-bite" id="bbBite" type="button" aria-label="Bite: enter
the site">Bite</button>
      </div>
    </div>
    <div class="bb-hint" id="bbHint">Click <b>Bite</b> to order food <span
class="bb-arrow">&uarr;</span></div>
  </div>
</main>

<script>
  document.getElementById('bbBite').addEventListener('click', function () {
    window.location.href = 'home.html';
  });
</script>
</body>
</html>
```

C.2 home.html (home page)

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>BreakBite</title>
  <link rel="stylesheet" href="style.css">
  <style>
    .role-switch { display: flex; gap: 10px; flex-wrap: wrap; margin-bottom: 20px; }
    .role-btn {
      display: flex; align-items: center; gap: 10px;
      background: var(--card); color: var(--ink);
      border: 2px solid var(--ink); border-radius: 12px;
      padding: 12px 18px; box-shadow: var(--shadow-small);
      font-weight: 800; font-size: 16px; cursor: pointer; text-decoration: none;
    }
    .role-btn .ico {
      display: inline-grid; place-items: center;
      width: 34px; height: 34px; border-radius: 9px;
      background: var(--ink); color: var(--card); font-size: 18px;
    }
    .role-btn.on { background: var(--t-mint); }
    .role-btn:hover { background: var(--accent); color: #fff; }
    .role-btn:hover .ico { background: #fff; color: var(--ink); }
  </style>
</head>
<body>

<header class="top">
  <div class="brand">BreakBite</div>
  <nav class="tabs" aria-label="Main sections">
    <a class="tab" href="student.html">Order</a>
    <a class="tab" href="planner.html">Break Planner</a>
    <a class="tab active" href="home.html">Home</a>
  </nav>
</header>

<main class="wide">
  <div class="role-switch">
    <a class="role-btn on" href="home.html">
      <span class="ico">S</span> Student
    </a>
    <a class="role-btn" href="staff.html">
      <span class="ico">T</span> Staff
    </a>
  </div>

  <section class="hero">
    <h1>Less waiting, more break.</h1>
```

```
    <p>Pre-order your canteen food, skip the queue, and plan your break with the
time you have.</p>
  </section>

  <div class="grid">
    <a class="card" href="student.html">
      <h2>Order food</h2>
      <p>See today's menu, pick your items, and track your token until it is ready.
</p>
      <span class="go">Open ordering &rarr;</span>
    </a>
    <a class="card" href="planner.html">
      <h2>Break Planner</h2>
      <p>Enter your break time and money. We suggest what you can eat in that time.
</p>
      <span class="go">Plan my break &rarr;</span>
    </a>
  </div>
</main>

</body>
</html>
```

C.3 logo.css (logo styles)

```
/* BreakBite animated logo */
.bb-logo-wrap{display:flex;flex-direction:column;align-items:center;text-
align:center;margin:0 0 28px}
.bb-logo{display:flex;align-items:center;gap:clamp(10px,2.4vw,22px);flex-
wrap:wrap;justify-content:center}

.bb-cookie{width:clamp(96px,14vw,150px);height:auto;overflow:visible;animation:bb-
float 3.2s ease-in-out infinite;transform-origin:50% 60%}
.bb-cookie .bb-crumbs{transform-box:fill-box;transform-origin:center;animation:bb-
twinkle 2.4s ease-in-out infinite}
.bb-cookie .bb-bite-cut{transform-box:fill-box;transform-
origin:center;transition:transform .5s ease}
.bb-cookie.bb-chomp{animation:bb-chomp .7s cubic-bezier(.3,.7,.3,1) both}
.bb-cookie.bb-chomp .bb-bite-cut{transform:translate(10px,-6px) scale(1.25)}

.bb-word{display:flex;align-items:center;gap:10px;flex-wrap:wrap;justify-
content:center}
.bb-break{font-size:clamp(38px,6vw,64px);font-weight:900;letter-
spacing:-2px;color:var(--ink,#3b2314);animation:bb-slide .8s .1s cubic-
bezier(.2,.9,.3,1.2) both}

.bb-bite{position:relative;font:inherit;font-size:clamp(38px,6vw,64px);font-
weight:900;letter-spacing:-2px;color:#fff5e6;background:var(--
accent,#d9482b);border:4px solid var(--ink,#3b2314);border-radius:20px;padding:2px
18px 8px;box-shadow:7px 7px 0 var(--ink,#3b2314);cursor:pointer;animation:bb-slide
.8s .25s cubic-bezier(.2,.9,.3,1.2) both,bb-bob 2.6s 1.2s ease-in-out
infinite;transition:transform .15s,box-shadow .15s,background .15s}
.bb-bite:hover{background:#c23b1f;transform:translate(-3px,-3px) rotate(-2deg);box-
shadow:10px 10px 0 var(--ink,#3b2314);animation-play-state:paused}
.bb-bite:active{transform:translate(4px,4px);box-shadow:3px 3px 0 var(--
ink,#3b2314)}
.bb-bite:focus-visible{outline:4px solid var(--gold,#f2b33d);outline-offset:6px}
.bb-bite.bb-pressed{animation:bb-squash .45s ease both}

.bb-hint{margin-top:22px;display:inline-flex;align-
items:center;gap:10px;background:var(--gold,#f2b33d);border:3px solid var(--
ink,#3b2314);border-radius:999px;padding:9px 18px;font-weight:800;font-
size:clamp(14px,2vw,17px);color:var(--ink,#3b2314);box-shadow:4px 4px 0 var(--
ink,#3b2314);animation:bb-hintPulse 1.8s ease-in-out infinite}
.bb-hint .bb-arrow{display:inline-block;animation:bb-up 1s ease-in-out infinite}
.bb-hint.bb-hide{opacity:0;transition:opacity .3s}

.bb-crumb{position:fixed;width:12px;height:12px;border-radius:50%;background:var(--
gold,#f2b33d);border:2px solid var(--ink,#3b2314);pointer-events:none;animation:bb-
fly .8s ease-out forwards;z-index:50}

@keyframes bb-float{0%,100%{transform:translateY(0) rotate(0)}50%
{transform:translateY(-8px) rotate(3deg)}}
@keyframes bb-twinkle{0%,100%{transform:scale(1) rotate(0)}50%{transform:scale(1.15)
```

```
rotate(8deg)}}
@keyframes bb-slide{from{opacity:0;transform:translateY(24px)
scale(.9)}to{opacity:1;transform:none}}
@keyframes bb-bob{0%,100%{transform:translateY(0)}50%{transform:translateY(-6px)}}
@keyframes bb-chomp{0%{transform:scale(1) rotate(0)}30%{transform:scale(1.12,.9)
rotate(-6deg)}60%{transform:scale(.96,1.04) rotate(3deg)}100%{transform:scale(1)
rotate(0)}}
@keyframes bb-squash{0%{transform:scale(1)}35%{transform:scale(1.12,.86)}70%
{transform:scale(.94,1.06)}100%{transform:scale(1)}}
@keyframes bb-hintPulse{0%,100%{box-shadow:4px 4px 0 var(--ink,#3b2314)}50%{box-
shadow:6px 6px 0 var(--ink,#3b2314);transform:translateY(-2px)}}
@keyframes bb-up{0%,100%{transform:translateY(0)}50%{transform:translateY(-4px)}}
@keyframes bb-fly{0%{opacity:1;transform:translate(0,0) scale(1)}100%
{opacity:0;transform:translate(var(--dx),var(--dy)) scale(.4) rotate(200deg)}}

@media (prefers-reduced-motion:reduce){.bb-logo-wrap *,.bb-
crumb{animation:none!important;transition:none!important}}
```

C.4 logo.js (logo script)

```
/* BreakBite logo: clicking "Bite" chomps the cookie, then opens the order page */
(function () {
  var bite = document.getElementById("bbBite");
  var cookie = document.getElementById("bbCookie");
  var hint = document.getElementById("bbHint");
  if (!bite || !cookie) return;
  var TARGET = "student.html";
  var busy = false;

  function crumbs(x, y) {
    for (var i = 0; i < 9; i++) {
      var c = document.createElement("span");
      c.className = "bb-crumb";
      var angle = (Math.PI * 2 / 9) * i + Math.random() * 0.4;
      var dist = 60 + Math.random() * 60;
      c.style.left = x + "px";
      c.style.top = y + "px";
      c.style.setProperty("--dx", Math.cos(angle) * dist + "px");
      c.style.setProperty("--dy", Math.sin(angle) * dist + "px");
      document.body.appendChild(c);
      setTimeout(function (el) { el.remove(); }.bind(null, c), 900);
    }
  }

  bite.addEventListener("click", function () {
    if (busy) return;
    busy = true;
    if (hint) hint.classList.add("bb-hide");
    bite.classList.add("bb-pressed");
    cookie.classList.add("bb-chomp");
    var r = bite.getBoundingClientRect();
    crumbs(r.left + r.width / 2, r.top + r.height / 2);
    setTimeout(function () { window.location.href = TARGET; }, 800);
  });
})();
```