

CENTRE FOR RAILWAY INFORMATION SYSTEMS (CRIS)

Ministry of Railways, Government of India

INTERNSHIP TRAINING REPORT

ON

Finding the Maximum Freight Paths Between Any Given Origin–Destination Pair Using Alternate Routes Without Disturbing Scheduled Trains

Submitted By

Raiyan Wasim

Bachelor of Technology (B.Tech), Galgotias University

Department of Computer Science and Engineering

Internship Conducted At

Centre for Railway Information Systems (CRIS)

Chanakyapuri, New Delhi

Under the Guidance of

Mr. Merajus Salekin

Assistant General Manager (AGM)

Advanced Data Science and Operations Research (ADAOR) Group

Centre for Railway Information Systems (CRIS)

Internship Duration

01 January 2026 – 30 June 2026

ACKNOWLEDGEMENT

I would like to express my sincere gratitude to the Centre for Railway Information Systems (CRIS), New Delhi, for providing me with the opportunity to undertake my internship training and gain practical exposure to real-world railway data analytics and operations research applications.

I am especially thankful to my mentor, **Mr. Merajus Salekin, Assistant General Manager (AGM), Advanced Data Science and Operations Research (ADAOR) Group**, for his constant guidance, encouragement, and valuable suggestions throughout the internship period. His technical insights and support played a crucial role in the successful completion of this project.

I would also like to extend my gratitude to all the officers and staff members of the ADAOR Group for their cooperation and for providing a professional and learning-oriented environment during my training.

The internship enabled me to apply my academic knowledge to a practical railway problem and helped me develop skills in graph theory, network optimization, data analysis, algorithm design, and software development.

Finally, I would like to thank my college faculty members, friends, and family for their continuous support and encouragement throughout the duration of this internship.

Raiyan Wasim

B.Tech, Computer Science and Engineering

Date: 30.06.2026

ABSTRACT

Indian Railways handles a significant volume of freight transportation across an extensive rail network. Efficient utilization of available rail infrastructure is essential for maximizing freight movement while ensuring that scheduled passenger and freight train operations remain unaffected. The identification of alternate freight routes between Origin-Destination (O-D) station pairs is therefore an important operational requirement.

This project presents a network-based approach for determining the maximum possible freight flow between any given O-D pair through alternate routes while considering route distance constraints. The railway network was modeled as a graph, where stations are represented as nodes and rail links are represented as edges with associated distance and capacity attributes.

The developed system utilizes Dijkstra's Shortest Path Algorithm to determine the minimum-distance route between stations and employs a modified Ford-Fulkerson Maximum Flow Algorithm to identify feasible freight paths within a user-defined distance limit. The application also provides an interactive Geographic Information System (GIS) based visualization of the railway network, enabling route analysis, freight flow analysis, station search, and dynamic path highlighting.

The solution was implemented using Python, NetworkX, Pandas, Folium, HTML, CSS, and JavaScript. The final system successfully identifies multiple valid freight paths, computes maximum freight capacity under operational constraints, and visualizes results through an interactive railway network map. The project demonstrates the practical application of graph theory and network optimization techniques in railway transportation planning and decision support systems.

1. INTRODUCTION

Indian Railways is one of the largest railway networks in the world and serves as the backbone of transportation in India. It plays a vital role in both passenger movement and freight transportation, connecting thousands of stations across the country through an extensive network of railway lines. Freight transportation is particularly important for the movement of commodities such as coal, steel, cement, food grains, petroleum products, and other industrial goods that contribute significantly to the nation's economy.

As the demand for freight transportation continues to grow, efficient utilization of railway infrastructure becomes increasingly important. Freight trains often share railway tracks with passenger services, making capacity management a challenging task. Any disruption, congestion, or capacity limitation on a particular route can significantly affect freight movement and overall network efficiency. Therefore, the identification of alternate routes and the assessment of available freight carrying capacity are essential for effective railway operations and planning.

Traditional route planning approaches primarily focus on identifying the shortest path between two stations. However, in practical railway operations, multiple alternate routes may exist between an Origin-Destination (O-D) pair. These alternate routes can be utilized when the primary route becomes congested, unavailable, or reaches its capacity limits.

Evaluating these alternate paths and determining the maximum possible freight movement through the network requires the application of graph theory and network optimization techniques.

In this project, the Indian Railways network is modeled as a graph where railway stations are represented as nodes and railway sections are represented as edges. Each edge contains operational attributes such as route length and freight carrying capacity. Using this network representation, various graph algorithms are applied to perform route analysis and freight flow assessment.

The developed system provides an interactive Geographic Information System (GIS) based platform for railway network visualization and analysis. The application enables users to search stations, explore railway infrastructure, generate multiple alternate routes between stations, and estimate freight carrying capacity under distance constraints. Dijkstra's Shortest Path Algorithm is used to identify the shortest route between stations, while Yen's Algorithm is employed to generate multiple feasible alternate routes. For freight flow analysis, a modified Ford-Fulkerson approach is utilized to determine the maximum freight movement possible between an Origin-Destination pair while considering route distance limitations.

The project combines railway domain knowledge, geospatial visualization, graph theory, and optimization techniques into a unified analytical platform. The developed solution demonstrates how modern data science and operations research methodologies can be applied to support railway planning, infrastructure utilization, and freight transportation decision-making processes.

2. OBJECTIVES AND PROBLEM STATEMENT

2.1 Problem Statement

Indian Railways operates one of the largest rail transportation networks in the world, consisting of thousands of stations and railway sections with varying infrastructure characteristics such as route length, line capacity, traction type, gauge, and operational constraints. Freight movement across this network must be planned efficiently while ensuring that scheduled train operations are not adversely affected.

Conventional route planning methods primarily focus on identifying the shortest path between an Origin-Destination (O-D) pair. However, in real-world railway operations, multiple alternate routes may exist between the same O-D pair. During congestion, maintenance activities, capacity limitations, or operational disruptions, freight traffic may need to be diverted through alternate paths. Therefore, it becomes necessary to identify

feasible alternate routes and estimate the maximum freight carrying capability of the railway network under defined operational constraints.

The problem addressed in this project is the development of a railway network analysis system capable of:

- Modeling the Indian Railways network as a graph using station and route data.
- Identifying multiple alternate routes between any Origin-Destination pair.
- Estimating the maximum freight flow that can be transported through the network.
- Restricting freight movement within a user-defined distance threshold relative to the shortest route.
- Providing an interactive visualization platform for route and freight flow analysis.

2.2 Objectives

The primary objectives of this project are:

1. To construct a graph-based representation of the railway network using station connectivity, route length, and line capacity data.
2. To develop an interactive GIS-based visualization platform for exploring railway infrastructure and network connectivity.
3. To implement station search functionality using both station names and station codes.
4. To identify the shortest route between any Origin-Destination pair using Dijkstra's Shortest Path Algorithm.
5. To generate multiple alternate routes between stations using Yen's K-Shortest Paths Algorithm.
6. To estimate the maximum freight carrying capability between an Origin-Destination pair using a modified Ford-Fulkerson maximum flow approach.
7. To evaluate freight movement under distance constraints by limiting path selection to a user-defined multiple of the shortest route distance.
8. To provide visual representation of route analysis and freight flow results for improved decision support and network understanding.
9. To create a scalable analytical framework that can be extended in the future for real-time railway operations, capacity planning, and freight optimization studies.

3. TECHNOLOGIES USED

The development of the Railway Network Visualization and Freight Flow Analysis System required the integration of multiple technologies for data processing, graph modeling, geospatial visualization, algorithm implementation, and user interaction. The technologies used in the project are described below.

3.1 Python

Python was used as the primary programming language for the development of the project. It was utilized for data processing, graph construction, algorithm implementation, and generation of the interactive railway network visualization.

3.2 Pandas

Pandas was used for reading, cleaning, transforming, and managing railway network data obtained from Excel files. It facilitated efficient preprocessing and manipulation of large datasets.

3.3 NetworkX

NetworkX was employed to model the railway network as a graph structure. It was also used to implement graph-based algorithms such as Dijkstra's Shortest Path Algorithm, Yen's K-Shortest Paths Algorithm, and Ford-Fulkerson Maximum Flow Algorithm.

3.4 GeoPandas

GeoPandas was used to create and manage geospatial railway line geometries through GeoDataFrames, enabling integration of spatial information with the visualization layer.

3.5 Folium

Folium was used to create the interactive web-based map interface. It enabled visualization of railway stations, network connectivity, route analysis results, and freight flow paths.

3.6 HTML

HTML was used to design the structure of various user interface components, including the station search panel, route analysis panel, freight flow panel, and interactive controls.

3.7 CSS

CSS was used to enhance the appearance and usability of the application by providing styling for panels, buttons, inputs, route displays, and map overlays.

3.8 JavaScript

JavaScript was used to implement client-side interactivity, including station search functionality, route highlighting, freight path visualization, panel management, and dynamic user interactions.

3.9 Jupyter Notebook

Jupyter Notebook served as the primary development environment for algorithm testing, data analysis, debugging, and generation of the final visualization system.

3.10 Microsoft Excel

Microsoft Excel was used for storing and managing railway network data before preprocessing and graph construction.

3.11 Railway Network Dataset

The railway network dataset used in this project was cleaned and processed prior to graph construction. The dataset contained railway infrastructure and operational attributes necessary for route analysis and freight flow computation.

The major fields used in the project are listed below:

- Railway
- Division
- Source Station Name (SrcName)
- Source Station Code (SrcCode)
- Source Latitude (SrcLat)
- Source Longitude (SrcLong)
- Destination Station Name (DstnName)
- Destination Station Code (DstnCode)
- Destination Latitude (DstnLat)
- Destination Longitude (DstnLong)
- Group Route
- High Density Network (HDN Route)
- Highly Utilized Network (HUN Route)
- Gauge
- Route Length
- Line Type
- Traction
- System of Working
- Line Capacity

These attributes were utilized to construct a graph-based representation of the railway network, perform route analysis, estimate freight carrying capacity, and generate interactive visualizations.

4. SYSTEM DESIGN

The Railway Network Visualization and Freight Flow Analysis System was designed as a graph-based analytical platform that integrates railway infrastructure data, graph algorithms, and geospatial visualization techniques. The system converts railway network data into a graph representation and provides interactive tools for route discovery and freight capacity analysis.

4.1 System Architecture

The overall system consists of four major components:

1. Data Processing Layer
2. Graph Construction Layer
3. Analysis Engine
4. Visualization and User Interface Layer

The workflow of the system is illustrated below:

Railway Dataset → Data Cleaning → Graph Construction → Route Analysis / Freight Analysis
→ Interactive Visualization

4.2 Data Processing Layer

The railway network dataset was first cleaned and preprocessed using Python and Pandas. Missing values, duplicate records, and inconsistent station information were removed or corrected before graph creation.

The cleaned dataset contained:

- Station Names
- Station Codes
- Geographic Coordinates
- Route Lengths
- Line Capacity
- Gauge Information
- Traction Type
- Operational Attributes

These attributes were subsequently used for graph construction and analysis.

4.3 Graph Construction Layer

The railway network was modeled as an undirected weighted graph using the NetworkX library.

In the graph model:

- Stations are represented as Nodes.
- Railway Sections are represented as Edges.
- Route Length is stored as the edge weight.
- Line Capacity is stored as an edge attribute.
- Geographic coordinates are stored as node attributes.

This graph representation enables efficient application of shortest path and network flow algorithms.

4.4 Route Analysis Module

The Route Analysis Module is responsible for identifying feasible routes between a selected Origin-Destination (O-D) pair.

The module performs the following operations:

1. Accepts source and destination station inputs.
2. Searches the railway graph for available paths.
3. Applies Dijkstra's Algorithm to identify the shortest route.
4. Applies Yen's K-Shortest Paths Algorithm to generate alternate routes.
5. Displays route distance and station sequence information.
6. Highlights selected routes on the interactive railway map.

This module assists users in understanding network connectivity and alternate routing possibilities.

4.5 Freight Flow Analysis Module

The Freight Flow Analysis Module estimates the maximum freight movement possible between an Origin-Destination pair while respecting route distance constraints.

The module performs the following operations:

1. Computes the shortest route distance using Dijkstra's Algorithm.
2. Calculates the maximum allowable distance based on a user-defined multiplier.
3. Constructs a residual graph using available line capacities.
4. Applies a modified Ford-Fulkerson Maximum Flow Algorithm.
5. Filters paths that exceed the allowable distance threshold.
6. Calculates total freight carrying capacity.

7. Identifies bottleneck sections limiting freight movement.
8. Displays valid freight paths and corresponding capacities.

This approach enables evaluation of freight movement without relying exclusively on the shortest route.

4.6 Visualization Layer

The visualization layer was implemented using Folium, HTML, CSS, and JavaScript.

The interactive interface provides:

- Railway network visualization.
- Station search functionality.
- Route analysis panel.
- Freight flow analysis panel.
- Dynamic route highlighting.
- Freight path highlighting.
- Interactive map navigation.

The visualization layer improves usability and enables users to interpret analytical results directly on the railway network map.

5. IMPLEMENTATION

5.1 Data Preparation and Network Construction

The project began with the preprocessing of railway network data obtained in spreadsheet format. The dataset contained station information, railway divisions, geographical coordinates, route lengths, and line capacities.

Using the Pandas library, the dataset was cleaned and transformed into a format suitable for graph construction. Source and destination station codes were used to establish connectivity between stations. The processed data was then converted into a graph structure using the NetworkX library.

In the constructed graph:

- Each railway station was represented as a node.
- Each railway section was represented as an edge.
- Route length was stored as an edge weight.
- Line capacity was stored as an edge attribute.
- Station coordinates were stored for visualization purposes.

This graph served as the foundation for all route and freight flow analyses performed in the system.

5.2 Interactive Railway Network Visualization

An interactive railway network map was developed using Folium to provide a visual representation of the Indian Railways network.


The map supports:

- Zooming and panning.
- Railway zone visualization using different colors.
- Station labeling.
- Layer controls.
- Dynamic route highlighting.
- Freight path visualization.

HTML, CSS, and JavaScript were integrated with Folium to create a user-friendly interface and enhance interactivity.

Features Implemented

- Search Station Panel
- Route Analysis Panel
- Freight Flow Analysis Panel
- Menu Controls
- Label Toggle Functionality
- Interactive Route Highlighting



5.3 Route Analysis Module

The Route Analysis Module was developed to identify feasible routes between any selected Origin-Destination (O-D) pair.


Users can enter source and destination stations and specify the number of routes to be generated. The system then computes:

- Shortest route
- Alternate routes
- Route distances
- Station sequences

Generated routes are displayed within the Route Analysis panel and can be highlighted directly on the railway map for visual inspection.

Route Analysis Workflow

1. User selects source station.
2. User selects destination station.
3. User specifies the number of routes.
4. System generates shortest and alternate routes.
5. Selected routes are highlighted on the map.



5.4 Freight Flow Analysis Module

The Freight Flow Analysis Module was developed to estimate the maximum freight carrying capability between an Origin-Destination pair.

Users provide:

- Source station
- Destination station
- Distance multiplier

The system first determines the shortest route distance and then calculates a maximum allowable distance threshold. Freight paths exceeding this threshold are discarded.

Valid paths are processed using a modified maximum flow approach to determine:


- Total freight flow
- Number of valid paths
- Individual path capacities
- Bottleneck sections limiting flow

Results are displayed within the Freight Flow panel and selected freight paths can be highlighted on the railway map.

Freight Analysis Workflow

1. User selects source station.
2. User selects destination station.
3. User selects distance multiplier.

4. System computes shortest path distance.
5. Maximum allowable distance is calculated.
6. Freight paths are evaluated.
7. Total freight flow is computed.
8. Results are displayed and visualized.




5.5 Station Search Functionality

A station search feature was implemented to improve navigation within the railway network map.

The search system supports:

- Station name search.
- Station code search.
- Auto-complete suggestions.
- Map centering on selected stations.
- Station highlighting.

This functionality enables quick identification and exploration of stations within the railway network.



6. CHALLENGES FACED AND SOLUTIONS

During the development of the Railway Network Visualization and Freight Flow Analysis System, several practical challenges were encountered. Most of these challenges were related to data quality, data standardization, and integration of multiple technologies into a unified platform. The major challenges and their corresponding solutions are discussed below.

6.1 Railway Data Cleaning and Standardization

The primary challenge encountered during the project was the preprocessing and cleaning of railway network data. The original dataset was distributed across multiple worksheets and contained inconsistencies in station naming conventions, formatting, and coding standards.

Several stations appeared in different formats across the dataset. For example, some records contained full station names while others used station codes. In addition, suffixes such as “JN”, “JN.”, “JUNCTION”, “ROAD”, “CANTT”, and other naming variations created duplicate representations of the same station.

Solution

A systematic data cleaning process was performed using Python and Pandas. Station names were standardized, duplicate representations were identified, and consistent station codes were adopted as unique identifiers throughout the network. This ensured that each station was represented only once within the graph model.

6.2 Handling Multiple Data Sources

The railway network information was spread across multiple sheets containing different operational and infrastructure attributes. Integrating these datasets into a single network representation required careful validation and mapping of common fields.

Solution

Relevant attributes such as source station, destination station, geographical coordinates, route length, and line capacity were extracted and consolidated into a unified dataset. The cleaned dataset served as the primary source for graph construction and analysis.

6.3 Graph Construction Challenges

The railway network consists of thousands of interconnected stations and railway sections. Incorrect node creation or duplicate station entries could result in disconnected components and inaccurate route calculations.

Solution

Station codes were used as unique node identifiers during graph construction. Validation checks were performed to ensure that all edges correctly connected their corresponding source and destination stations.

6.4 Freight Flow Modeling

Traditional shortest-path approaches are insufficient for evaluating freight movement because multiple alternate routes may contribute to overall freight carrying capacity. Designing a system capable of identifying valid alternate paths while respecting distance constraints was a significant challenge.

Solution

A modified Ford-Fulkerson Maximum Flow approach was implemented. The algorithm was integrated with a distance threshold based on the shortest route distance, ensuring that unrealistic detours were excluded from freight flow calculations.

6.5 User Interface Development

Developing an interactive interface within a Folium-generated map required combining Python-generated content with custom HTML, CSS, and JavaScript components. Managing panel layouts, route highlighting, freight visualization, and user interactions presented several implementation challenges.

Solution

Custom user interface panels were developed using HTML, CSS, and JavaScript. Additional controls were implemented for route analysis, freight flow analysis, station search, path highlighting, and dynamic result visualization, resulting in a user-friendly analytical platform.

6.6 Performance and Visualization

Displaying a large railway network while maintaining responsiveness and readability was another challenge. Excessive labels and overlapping routes could reduce usability and affect performance.

Solution

Interactive controls such as label toggling, route highlighting, layer management, and selective visualization were implemented. These features improved map clarity and allowed users to focus on specific network components when performing analysis.

7. ALGORITHMS USED

The Railway Network Visualization and Freight Flow Analysis System relies on graph theory and network optimization algorithms for route discovery and freight capacity estimation. The railway network is represented as a weighted graph where stations are modeled as nodes and railway sections are modeled as edges.

The major algorithms used in the project are discussed below.

7.1 Dijkstra's Shortest Path Algorithm

Dijkstra's Algorithm is a graph traversal algorithm used to determine the shortest path between two nodes in a weighted graph. In this project, it is used to identify the minimum-distance railway route between a selected Origin-Destination (O-D) pair.

The algorithm starts from the source station and repeatedly selects the node with the minimum tentative distance. The process continues until the destination station is reached.

Application in the Project

The algorithm is used to:

- Determine the shortest route between two stations.
- Calculate the minimum route distance.
- Establish the baseline distance used in freight flow analysis.
- Generate the reference route for alternate path evaluation.

Time Complexity

$$O((V + E) \log V)$$

where:

- V = Number of Stations (Vertices)
- E = Number of Railway Sections (Edges)

7.2 Yen's K-Shortest Paths Algorithm

Yen's Algorithm is an extension of shortest path analysis that generates multiple loopless shortest paths between a source and destination node.

Unlike Dijkstra's Algorithm, which returns only one shortest path, Yen's Algorithm produces several alternate routes ordered by increasing distance.

Application in the Project

The algorithm is used in the Route Analysis Module to:

- Generate alternate routes between stations.
- Provide multiple routing options to users.
- Support route comparison and network exploration.
- Visualize different feasible railway paths.

The algorithm repeatedly removes portions of previously discovered routes and computes alternative paths until the desired number of routes is obtained.

Time Complexity

$$O(K \times N \times (E + V \log V))$$

where:

- K = Number of routes requested
- N = Number of stations
- E = Number of railway sections

7.3 Ford-Fulkerson Maximum Flow Algorithm

The Ford-Fulkerson Algorithm is a network optimization technique used to determine the maximum possible flow between a source node and a destination node in a capacity-constrained network.

The algorithm repeatedly identifies augmenting paths between the source and destination and increases flow until no additional feasible path exists.

Application in the Project

The Freight Flow Analysis Module utilizes a modified Ford-Fulkerson approach to:

- Estimate maximum freight movement.
- Identify valid freight routes.
- Evaluate freight carrying capacity.
- Determine bottleneck sections limiting flow.

Each railway section is assigned a capacity value derived from the railway dataset. These capacities are used during flow computation.

Residual Graph

A residual graph is constructed to track the remaining capacity available on each railway section after flow assignment.

The residual capacity is calculated as:

Residual Capacity = Original Capacity – Assigned Flow

The algorithm continues until no augmenting path with available capacity exists.

Time Complexity

$O(E \times \text{MaxFlow})$

where:

- E = Number of railway sections
- MaxFlow = Total freight flow value

7.4 Distance-Constrained Freight Flow Enhancement

A standard Ford-Fulkerson implementation may identify excessively long freight routes that are operationally impractical.

To address this limitation, a distance constraint was introduced in the project.

The procedure consists of:

1. Computing the shortest route distance using Dijkstra's Algorithm.
2. Applying a user-defined multiplier.
3. Calculating the maximum allowable distance.
4. Rejecting freight paths exceeding this threshold.
5. Evaluating only feasible freight routes.

Example

If:

Shortest Distance = 100 km

Multiplier = 2

Then:

Maximum Allowed Distance = 200 km

Only freight paths whose total distance is less than or equal to 200 km are considered during maximum flow computation.

This enhancement ensures that freight movement remains operationally realistic while still utilizing alternate routes to maximize carrying capacity.

8. RESULTS AND DISCUSSION

The developed Railway Network Visualization and Freight Flow Analysis System was successfully implemented and tested on the processed Indian Railways network dataset. The system was capable of performing route analysis, freight flow estimation, station search, and interactive visualization of railway infrastructure.

The following results demonstrate the major functionalities of the developed system.

8.1 Railway Network Visualization

The complete railway network was successfully visualized on an interactive GIS-based map. Railway stations were represented as nodes and railway sections were represented as edges connecting the stations.


The visualization supports zooming, panning, filtering, and dynamic interaction with the railway network.



8.2 Station Search Functionality

The station search module successfully enabled users to locate stations using either station names or station codes. Auto-suggestion functionality was implemented to improve usability and assist users in identifying valid stations within the network.


The search feature automatically navigates to the selected station and highlights its location on the map.



8.3 Route Analysis Module

The Route Analysis Module successfully generated shortest and alternate routes between selected Origin-Destination station pairs.

The system provided route distance information, route sequences, and interactive route highlighting. Multiple routes generated through Yen's K-Shortest Paths Algorithm enabled comparison of alternate railway corridors.




8.4 Freight Flow Analysis Module

The Freight Flow Analysis Module successfully estimated the maximum freight carrying capability between selected Origin-Destination station pairs.

The module identified valid freight paths, calculated path-wise freight flow, and determined total network flow while respecting user-defined distance constraints.

The results also identified bottleneck sections responsible for limiting freight movement across the network.






8.5 Network Filtering and Interactive Controls

The implemented filtering mechanisms enabled users to visualize specific portions of the railway network based on operational attributes such as:

- Railway Zone
- Gauge Type
- Line Type
- Traction
- HDN Route
- HUN Route
- Group Route
- System of Working

These filters improved network readability and enabled focused analysis of selected railway corridors.





8.6 Overall System Performance

The developed system successfully integrated graph theory, network optimization, and geospatial visualization into a single analytical platform.

The implementation demonstrated the ability to:

- Construct a graph representation of the railway network.
- Generate multiple alternate routes between stations.
- Estimate freight carrying capacity under operational constraints.
- Identify bottleneck railway sections.

- Visualize analytical results through an interactive GIS interface.

The system provides a practical framework for railway route analysis, freight planning, and network exploration.

9. CONCLUSION AND FUTURE SCOPE

9.1 Conclusion

The objective of this project was to develop an interactive Railway Network Visualization and Freight Flow Analysis System capable of supporting route analysis and freight capacity assessment on the Indian Railways network. The railway infrastructure data was successfully processed, cleaned, and transformed into a graph-based network representation using modern data science and network analysis techniques.

The developed system integrates graph theory, network optimization, and geospatial visualization into a unified analytical platform. Dijkstra's Algorithm was utilized for shortest path computation, Yen's K-Shortest Paths Algorithm was implemented for alternate route generation, and a modified Ford-Fulkerson based approach was employed for freight flow analysis under distance constraints.

The system provides an interactive GIS-based environment where users can search stations, analyze routes, estimate freight carrying capacity, identify bottleneck sections, and visualize results directly on the railway network map. The implementation demonstrates the practical applicability of graph algorithms in solving real-world railway planning and operational problems.

Overall, the project successfully achieved its objectives and provides a scalable framework for railway network analysis, route planning, and freight transportation studies.

9.2 Future Scope

The developed system successfully models the railway network as a graph and provides route analysis as well as freight flow estimation between selected Origin–Destination (O-D) pairs. However, several enhancements can further improve the accuracy, usability, and operational value of the system.

At present, the network primarily utilizes major stations and junctions for route computation. In future versions, additional intermediate stations, block sections, and operational nodes can be incorporated to create a more detailed representation of the railway network. This would improve route accuracy and provide a finer level of analysis.

The current freight flow module determines the maximum feasible flow between an O-D pair based on available capacities and distance constraints. Future enhancements may include section-wise capacity utilization analysis, where the contribution and limitation of each intermediate section are explicitly identified. For example, if a particular section acts as the bottleneck that restricts overall freight movement, the system can highlight that section and quantify its impact on total network capacity. Such analysis can assist planners in identifying critical capacity constraints and prioritizing infrastructure upgrades.

A centralized network management module can also be incorporated to support Create, Read, Update, and Delete (CRUD) operations on network data. This would allow authorized users to add new stations, modify coordinates, update section capacities, edit route information, and manage railway network records without requiring changes to the underlying source code.

Another potential enhancement is the integration of operational parameters such as scheduled train paths, maintenance blocks, temporary speed restrictions, and line occupancy information. Incorporating these factors would enable more realistic capacity assessment and route planning.

The system can also be deployed as a centralized web application within the railway network, providing controlled access to planners, analysts, and operational staff. User authentication and role-based access mechanisms can be implemented to support secure access and collaborative usage across different departments.

In addition, advanced visualization dashboards may be developed to provide zone-wise, division-wise, and corridor-wise capacity analysis, helping decision-makers evaluate network performance and identify potential bottlenecks more effectively.

These enhancements would transform the current prototype into a comprehensive decision-support tool for railway network planning, capacity assessment, and freight movement analysis.

REFERENCES

1. NetworkX Developers. *NetworkX Documentation*. Available at: <https://networkx.org/documentation/>
2. GeoPandas Developers. *GeoPandas Documentation*. Available at: <https://geopandas.org/>
3. Folium Developers. *Folium Documentation*. Available at: <https://python-visualization.github.io/folium/>

4. Pandas Developers. *Pandas Documentation*. Available at:
<https://pandas.pydata.org/docs/>
5. OpenStreetMap Contributors. *OpenStreetMap Geographic Data*. Available at:
<https://www.openstreetmap.org/>
6. Cormen, T. H., Leiserson, C. E., Rivest, R. L., and Stein, C. *Introduction to Algorithms*, 4th Edition. MIT Press, 2022.
7. Ford, L. R., and Fulkerson, D. R. *Maximal Flow Through a Network*. Canadian Journal of Mathematics, 1956.
8. Dijkstra, E. W. *A Note on Two Problems in Connexion with Graphs*. Numerische Mathematik, 1959.
9. Yen, J. Y. *Finding the K Shortest Loopless Paths in a Network*. Management Science, 1971.
10. Center for Railway Information Systems (CRIS), Indian Railways. Internal railway network data and operational information provided during internship training.
11. Railway Board, Ministry of Railways, Government of India. Publicly available railway infrastructure and route classification information.
12. Google Colaboratory Documentation. Available at:
<https://colab.research.google.com/>